



- 1 PINS: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL. STACKING CLIPS; NICKEL PLATED ONLY.
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5 ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6 RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF THE HOUSING
- 7 MATERIAL: HOUSING & ORGANIZER; LCP; COLOR, BLACK
PIN; BRASS & PHOSPHOR BRONZE
STACKING CLIP; PHOSPHOR BRONZE

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

5	1,17,34	ALL	36,67	5146046-1
	35,51,68	OTHER PINS		
VOLTAGE KEYING	5.0 [0.197]	4.25 [0.167]	3.5 [0.138]	PART NUMBER
"L" (PIN LENGTH) AND LOCATION				
THIS DRAWING IS A CONTROLLED DOCUMENT.				
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN G. ATTADIA - DOCK5 03-23-05 CHK D.L. GORENC 03-23-05 APVD M. WALSMLEY 03-23-05 NAME PRODUCT SPEC APPLICATION SPEC SIZE CAE CODE DRAWING NO RESTRICTED TO
0 PLC	±	±	±	
1 PLC	±	±	±	
2 PLC	± 0.13 [005]	±	±	
3 PLC	±	±	±	
4 PLC	±	±	±	
ANGLES	±	±	±	
MATERIAL	FINISH	WEIGHT	SCALE	REV
		18.5 GRAMS	A1 00779	0
CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1		

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

[View 5146046-1 on WIN SOURCE](#)

[TE Connectivity Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management