TDK

February 2024

RoHS REACH Halogen Free Lead Free

Product Portal Search Simulation Model Selection Guide Tech Library Tech Note

Chip varistors

ESD/Voltage protection devices

AVR/SGNE series

AVRM/AVR-M	**: Standard Type**
AVRL	**: Low Capacitance Type**
AVRH	**: High reliability Type**
SGNE	**: Low Clamp Type**

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

REMINDERS

○Please pay careful attention to the precautions and follow safe designing practices when using these products.

○Please observe the following precautions in order to avoid problems with chip varistors such as characteristic degradation and element destruction

Please store these products in an environment with a temperature of 5 to 40°C and humidity level of 20 to 70%RH, and use them within six months.
Poor storage conditions may lead to the deterioration of the solderability of the edge electrodes, so please be careful to avoid contact with humidity, dew condensation, dust, toxic gas (hydrogen, hydrogen sulfide, sulfurous acid, chlorine, ammonia, etc.), direct sunlight, and so on.
Please do not use products that have been dropped or detached when mounting.
Please solder with the reflow soldering method, and not the flow (dip) soldering method.

○Please observe the following precautions to avoid problems with varistors such as characteristic degradation and element destruction, which ultimately lead to the generation of heat and smoke with the elements.

Do not use in locations where the temperatures exceed the operating temperature range such as under direct sunlight or near sources of heat.
Do not use in locations where there are high levels of humidity such as under direct exposure to weather and areas where steam is released.
Do not use in locations such as dusty areas, high-saline environments, places where the atmosphere is contaminated with corrosive gas, etc.
Avoid powerful vibrations, impact (such as by dropping), pressure, etc. that may lead to splitting in the products.
Do not use with a voltage that exceeds the maximum allowable circuit voltage.
When resin coating (including modular) a varistor, do not use a resin that will cause deterioration of the varistor. Be sure never to use resin that generates hydrogen as palladium is used for the inner electrode.
Avoid attachment near combustible materials.

○Please contact our sales offices when considering the use of the products listed on this catalog for applications, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property (\qspecific uses\q such as automobiles, airplanes,medical instruments, nuclear devices, etc.) as well as when considering the use for applications that exceed the range and conditions of this catalog.

○As range of catalog, conditions are transcended, or for damage that generated by was used in application specific, etc, accept no the responsibility, wish.

○Please take appropriate measures such as acquiring protective circuits and devices that meet the uses, applications, and conditions of the instruments and keeping backup circuits.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Overview of the AVR/SGNE series

CHARACTERISTICS OF CHIP VARISTOR

Varistors are voltage dependent nonlinear resistive elements with a resistance that decreases rapidly when the voltage is over the constant value.
Varistors become zener diode of 2 serial connection and equivalent, and does not have polarity.

current vs. voltage characteristics



the effect of the varistor

Without varistor

A malfunction and failure of electronic equipment



With Varistor

Suppress abnormal voltage by inserting varistor in a circuit



EQUIVALENT CIRCUIT OF CHIP VARISTORS



CHIP VARISTORS FEATURE

- IEC61000-4-2 LEVEL4 compliant.
- Reliability characteristics evaluated based on AEC-Q200 condition. (Automotive products)
- High ESD withstanding voltage
- Small-sized products are available
- 85℃,125℃,150℃ Supported

Fig.1 Internal structure of multilayer chip varistors



No.	Name	
(1)	Semiconductor ceramics	
(2)	Internal electrode(Pd)	
(3)	Terminal electrode	Ag
(4)		Ni
(5)		Sn

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Overview of the AVR/SGNE series

PART NUMBER CONSTRUCTION

AVRM series

AVRM	1608	C	390	K	T	271	N
Series name	L x W dimensions (mm)	Structure code	Varistor voltage (V)	Varistor voltage tolerance (%)	Packaging style	Capacitance (pF)	Capacitance tolerance (%)

Series name	L x W dimensions (mm)		Structure code		Varistor voltage (V)		Varistor voltage tolerance (%)		Packaging style		Capacitance (pF)		Capacitance tolerance (%)	
AVRM series	0402	0.4x0.2	C	General structure	390=39x10^0		K	±10	T	Taping	271=27x10^1		K	±10
	0603	0.6x0.3			6R8	6.8	M	±20			221	220	M	±20
	1005	1.0x0.5			270	27	N	±30			271	270	N	±30
	1608	1.6x0.8			390	39								
	2012	2.0x1.2												

AVR-M series

AVR-M	1608	C	270	M	T	AAB
Series name	L x W dimensions (mm)	Structure code	Varistor voltage (V)	Varistor voltage tolerance (%)	Packaging style	Company special symbol

Series name	L x W dimensions (mm)		Structure code		Varistor voltage (V)		Varistor voltage tolerance (%)		Packaging style		Company special symbol
AVR-M series	0603	0.6x0.3	C	General structure	270=27x10^0		K	±10	T	Taping	
	1005	1.0x0.5	G	Conductive paste compatible	080	8	M	±20			
	1608	1.6x0.8			120	12	N	±30			
	2012	2.0x1.2			270	27					

AVRL series

AVRL	10	1D	3R3	F	T	A
Series name	L x W dimensions (mm)	Maximum continuous voltage (V)	Capacitance (pF)	Capacitance tolerance (pF)	Packaging style	Company special symbol

Series name	L x W dimensions (mm)		Maximum continuous voltage (V)		Capacitance (pF)		Capacitance tolerance (pF)		Packaging style		Company special symbol
AVRL series	04	0.4x0.2	1A	10	R50	0.5	F	±1	T	Taping	
L=Low cap	06	0.6x0.3	1D	20	1R1	1.1	G	±2			
	10	1.0x0.5	1E	25	3R3	3.3	N	±0.3			
	16	1.6x0.8			6R8	6.8					

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Overview of the AVR/SGNE series

PART NUMBER CONSTRUCTION

SGNE series

SGNE	04	C	080	M	T
Series name	L x W dimensions (mm)	Structure code	Varistor voltage (V)	Varistor voltage tolerance (%)	Packaging style
Low Clamp series	04 0.4x0.2	C General structure	080=8x10^0	M ±20	T Taping
	06 0.6x0.3		080 8		
	10 1.0x0.5		270 27		

150	N	25
Capacitance (pF)	Capacitance tolerance	ESD clamping voltageAverage voltage(IEC61000-4-2, 8kV)
150=15x10^0	N ±30%	
6R8 6.8	G ±2.0pF	
150 15		

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Overview of the AVR/SGNE series

PART NUMBER CONSTRUCTION

AVRH series

AVRH	10	C	270	K	T
Series name	L x W dimensions (mm)	Structure code	Varistor voltage (V)	Varistor voltage tolerance (%)	Packaging style
AVRH series	10 | 1.0x0.5	C | General structure	270=27x10^0	K | ±10	T | Taping
H=High Reliability			270 | 27	Y | Special	
			390 | 39		
			101 | 100		

150	N	A	8
Capacitance (pF)	Capacitance tolerance	ESD voltage tolerance IEC61000-4-2 (kV)	Operating temperature limit (°C)
150=15x10^0	K | ±10%	A | 25	8 | 150
4R7 | 4.7	M | ±20%	E | 8	
150 | 15	N | ±30%		
500 | 50	Y | Special		

AVRH series(array)

AVRH	16	A2	C	270	K	T
Series name	L x W dimensions (mm)	Type	Structure code	Varistor voltage (V)	Varistor voltage tolerance (%)	Packaging style
AVRH series	16 | 1.6x0.8	A2 | 2in1 Array	C | General structure	270=27x10^0	K | ±10	T | Taping
H=High Reliability				270 | 27		

200	N	A	8
Capacitance (pF)	Capacitance tolerance	ESD voltage tolerance IEC61000-4-2 (kV)	Operating temperature limit (°C)
200=20x10^0	N | ±30%	A | 25	8 | 150
200 | 20			

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Overview of the AVR/SGNE series

TERMINOLOGY

Item	Unit	Description
Varistor voltage(Breakdown voltage)	V1mA(V)	Chip varistor-terminal voltage when DC1mA was flowed
Maximum continuous voltage	Vdc(V)	DC voltage that is continuously applied between chip varistor terminalsTerminal chip varistors leakage current-value: 50μA max.Voltage appearing across the varistor when a pulse current (8/20μs*1) of specified peak value is applied.
Clamping voltage	Vcl(V)	Voltage between terminal chip varistors of the Specified peak current value of the impulse current (8/20μs*1) is applied
Maximum energy	E(Joule)	When applied specified peak impulse current-value current (10/1000μs*2) once, maximum energy that electrical property of chip varistors be not deteriorated
Maximum peak current	Ip(A)	When applied impulse current (8/20μs*1) once, maximum current that electrical property of chip varistors be not deteriorated
Capacitance	C(pF)	Oscillator frequency 1kHz or 1MHz, capacitance between chip varistor-terminal in oscillator voltage 1Vrms
Capacitance Difference	ΔC(pF)	Measure the capacitance of each Ch at an oscillator frequency of 1 MHz and an oscillator voltage of 1 V, The absolute value of the difference of the capacitance values obtained

*1 8/20μs test waveform



*2 10/1000μs test waveform



⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR/SGNE series 0402 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA	C	Vdc	Vcl	E	Ip	Operating temperature range	ESD voltage tolerance	AEC-Q200
	(V)	1kHz/1MHz* (pF)	DC (V)	8/20µs (V)	10/1000µs (J)	8/20µs (A)	(°C)	IEC61000-4-2 (kV)	
AVRM0402C6R8NT101N	6.8(4.76 to 8.84)	100(70 to 130)	3.5	15(1A)	0.01	4	-40 to 85	8	
AVRM0402C120MT330N	12(9.6 to 14.4)	33(23.1 to 43.9)	5.5	20(1A)	0.005	1	-40 to 85	8	
AVRL041E1R1NTA	39(31.2 to 46.8)	1.1(0.8 to 1.4)*	25	-	-	-	-40 to 85	4	
SGNE04C080MT150N25	8(6.4 to 9.6)	15(10.5 to 19.5)*	5.5	20(1A)	0.005	1	-40 to 85	8	

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR/SGNE series 0603 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA (V)	C 1kHz/1MHz* (pF)	Vdc DC (V)	Vcl 8/20µs (V)	E 10/1000µs (J)	Ip 8/20µs (A)	Operating temperature range (°C)	ESD voltage tolerance IEC61000-4-2 (kV)	AEC-Q200
AVRM0603C6R8NT101N	6.8(4.76 to 8.84)	100(70 to 130)	3.5	14(1A)	0.01	10	-40 to 85	8	
AVRM0603C6R8NT331N	6.8(4.76 to 8.84)	330(231 to 429)	3.5	14(1A)	0.02	16	-40 to 85	8	
AVRM0603C080MT101N	8(6.4 to 9.6)	100(70 to 130)	5.5	17(1A)	0.01	4	-40 to 85	8	
AVRM0603C120MT150N	12(10 to 15.6)	15(10.5 to 19.5)	5.5	35(1A)	0.003	1	-40 to 85	8	
AVR-M0603C120MTAAB	12(9.6 to 14.4)	33(25 to 41)	7.5	23(1A)	0.01	1	-40 to 85	8	
AVRM0603C120MT101N	12(10 to 15.6)	100(70 to 130)	5.5	20(1A)	0.01	5	-40 to 85	8	
AVRM0603C200MT150N	20(16 to 24)	15(10.5 to 19.5)	12	40(1A)	0.01	1	-40 to 85	8	
AVRL061FR50ETA	140(112 to 168)	0.5(0.3 to 0.7)*	30	-	-	-	-40 to 85	4	
AVRL061E1R1NTA	39(31.2 to 46.8)	1.1(0.8 to 1.4)*	25	-	-	-	-40 to 85	4	
SGNE06C080MT150N25	8(6.4 to 9.6)	15(10.5 to 19.5)*	5.5	21(1A)	0.005	1	-40 to 85	8	
SGNE06C270MT6R8G60	27(21.6 to 32.4)	6.8(4.8 to 8.8)	15	54(1A)	0.005	1	-40 to 85	8	

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR/SGNE series 1005 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA	C	Vdc	Vcl	E	Ip	Operating temperature range	ESD voltage tolerance	AEC-Q200
	(V)	1kHz/1MHz* (pF)	DC (V)	8/20μs (V)	10/1000μs (J)	8/20μs (A)	(°C)	IEC61000-4-2 (kV)	
AVRM1005C6R8NT101N	6.8(4.76 to 8.84)	100(70 to 130)	3.5	14(1A)	0.02	10	-40 to 85	8	
AVRM1005C6R8NT331N	6.8(4.76 to 8.84)	330(231 to 429)	3.5	15(1A)	0.008	24	-40 to 85	8	
AVR-M1005C080MTAAB	8(6.4 to 9.6)	650(520 to 780)	5.5	14(1A)	0.04	25	-40 to 85	8	
AVR-M1005C080MTABB	8(6.4 to 9.6)	100(55 to 145)	5.5	15(1A)	0.02	3	-40 to 85	8	
AVR-M1005C080MTACB	8(6.4 to 9.6)	33(14 to 52)	5.5	19(1A)	0.01	1	-40 to 85	8	
AVR-M1005C080MTADB	8(6.4 to 9.6)	480(384 to 576)	5.5	14(1A)	0.04	25	-40 to 85	8	
AVR-M1005C120MTAAB	12(9.6 to 14.4)	130(104 to 156)	7.5	20(1A)	0.05	10	-40 to 85	8	
AVR-M1005C120MTACC	12(9.6 to 14.4)	460(276 to 644)*	7.5	21(1A)	0.01	24	-40 to 85	8	
AVR-M1005C180MTAAB	18(14.4 to 21.6)	120(72 to 168)*	11	30(1A)	0.06	16	-40 to 85	8	
AVRM1005C270KT101N	27(24 to 30)	100(70 to 130)	19	44(1A)	0.06	4	-40 to 85	8	
AVR-M1005C270MTAAB	27(21.6 to 32.4)	40(24 to 42)	15	47(1A)	0.06	4	-40 to 85	8	
AVR-M1005C270MTABB	27(21.6 to 32.4)	15(10.5 to 19.5)	15	49(1A)	0.05	1	-40 to 85	8	
AVRL101A1R1NTA	90(79.6 to 110.4)	1.1(0.8 to 1.4)*	10	-	-	-	-40 to 85	8	
AVRL101E1R1NTB	39(31.2 to 46.8)	1.1(0.8 to 1.4)*	25	-	-	-	-40 to 85	4	
AVRL101D3R3FTA	27(21.6 to 32.4)	3.3(2.3 to 4.3)*	20	62(0.5A)	0.01	0.5	-40 to 125	8	✓
AVRL101D6R8GTA	27(21.6 to 32.4)	6.8(4.8 to 8.8)*	20	58(1A)	0.01	1	-40 to 125	8	✓
SGNE10C080MT150N28	8(6.4 to 9.6)	15(10.5 to 19.5)	5.5	21(1A)	0.01	19	-40 to 85	8	

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVRH series 1005 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA	C	Vdc	Vcl	E	Ip	Operating temperature range	ESD voltage tolerance	AEC-Q200
	(V)	1kHz/1MHz* (pF)	DC (V)	8/20μs (V)	10/1000μs (J)	8/20μs (A)	(°C)	IEC61000-4-2 (kV)	
AVRH10C220YT201MA8	22(19 to 26)	200(160 to 240)	16	40(2A)	0.07	40	-55 to 150	25	✓
AVRH10C270KT150NA8	27(24 to 30)	15(10.5 to 19.5)	19	52(2A)	0.02	2	-55 to 150	25	✓
AVRH10C270KT350NA8	27(24 to 30)	35(24.5 to 45.5)	19	52(2A)	0.02	8	-55 to 150	25	✓
AVRH10C390KT500NA8	39(35 to 43)	50(35 to 65)	28	72(2A)	0.06	15	-55 to 150	25	✓
AVRH10C101KT4R7FA8	100(90 to 110)	4.7(3.7 to 5.7)	70	190(1A)	0.03	1	-55 to 150	25	✓
AVRH10C101KT4R7YA8	115(103.5 to 126.5)	4.7(4.13 to 5.27)*	70	212(1A)	0.03	1	-55 to 150	25	✓
AVRH10C101KT1R1NE8	110(100 to 120)	1.1(0.8 to 1.4)*	70	187(0.3A)	0.007	0.3	-55 to 150	8	✓
AVRH10C101KT1R2YE8	110(100 to 120)	1.23(1.10 to 1.36)*	70	187(0.3A)	0.007	0.3	-55 to 150	8	✓
AVRH10C221KT1R5YA8	220(198 to 242)	1.5(1.37 to 1.63)*	70	400(0.5A)	0.007	0.5	-55 to 150	25	✓

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR series 1608 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd, Pd/Ag
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA (V)	C 1kHz/1MHz* (pF)	Vdc DC (V)	Vcl 8/20μs (V)	E 10/1000μs (J)	Ip 8/20μs (A)	Operating temperature range (°C)	ESD voltage tolerance IEC61000-4-2 (kV)	AEC-Q200
AVR-M1608C080MTAAB	8(6.4 to 9.6)	650(520 to 780)	5.5	15(2A)	0.09	30	-40 to 85	8	
AVR-M1608C120MT2AB	12(9.6 to 14.4)	400(320 to 480)	7.5	20(2A)	0.06	15	-40 to 85	8	
AVR-M1608C120MT6AB	12(9.6 to 14.4)	1050(840 to 1260)	7.5	20(2A)	0.09	50	-40 to 125	8	
AVR-M1608C180MT6AB	18(14.4 to 21.6)	600(480 to 720)	11	30(2A)	0.1	30	-40 to 85	8	
AVR-M1608C220KT2AB	22(19.8 to 24.2)	210(168 to 252)	16	37(2A)	0.03	10	-40 to 125	25	✓
AVR-M1608C220KT6AB	22(19.8 to 24.2)	560(448 to 672)	16	34(2A)	0.1	30	-40 to 125	25	✓
AVR-M1608C270MTABB	27(21.6 to 32.4)	15(11 to 20)	17	52(2A)	0.05	2	-55 to 150	25	✓
AVR-M1608C270MTAAB	27(21.6 to 32.4)	30(21 to 39)	17	52(2A)	0.05	2	-55 to 150	25	✓
AVR-M1608C270KTACB	27(24 to 30)	60(42 to 78)	19	54(2A)	0.05	10	-55 to 150	25	✓
AVRM1608C270KT800M	27(24 to 30)	80(64 to 96)	19	53(2A)	0.02	28	-55 to 150	25	✓
AVR-M1608C270KT2AB	27(24 to 30)	160(128 to 192)	19	42(2A)	0.1	20	-55 to 150	25	✓
AVRM1608C270KT221M	27(24 to 30)	220(176 to 264)	19	52(2A)	0.1	56	-55 to 150	25	✓
AVR-M1608C270KT6AB	27(24 to 30)	430(344 to 516)	19	42(2A)	0.1	48	-55 to 150	25	✓
AVR-M1608G270KT6AB	27(24 to 30)	430(344 to 516)	19	42(2A)	0.1	48	-55 to 150	25	✓
AVRM1608C390KT271N	39(35 to 43)	270(216 to 324)	28	69(2A)	0.1	78	-55 to 150	25	✓
AVRM1608C560KT101M	56(50.4 to 61.6)	100(80 to 120)	40	113(2A)	0.3	60	-55 to 150	25	✓
AVRM1608C720KT750M	72(64.8 to 79.2)	75(60 to 90)	53	135(2A)	0.1	40	-55 to 150	25	✓
AVRL161A1R1NTA	90(79.6 to 110.4)	1.1(0.8 to 1.4)*	10	-	-	-	-40 to 85	8	
AVRL161A1R1NTB	39(31.2 to 46.8)	1.1(0.8 to 1.4)*	10	-	-	-	-40 to 85	4	
AVRL161D3R3FTA	27(21.6 to 32.4)	3.3(2.3 to 4.3)*	20	62(0.5A)	0.01	0.5	-40 to 125	8	✓
AVRL161D6R8GTA	27(21.6 to 32.4)	6.8(4.8 to 8.8)*	20	58(1A)	0.01	1	-40 to 125	8	✓

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVRH series(array) 1608 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

PRODUCT CHARACTERISTICS LIST

Item	V1mA	C	Vdc	Vcl	E	Ip	ΔC	Operating temperature range	ESD voltage tolerance	AEC-Q200
	(V)	1kHz/1MHz* (pF)	DC (V)	8/20μs (V)	10/1000μs (J)	8/20μs (A)	1MHz (pF)	(°C)	IEC61000-4-2 (kV)	
AVRH16A2C270KT200NA8	27(24 to 30)	20(14 to 26)	19	60(2A)	0.04	4	1.0	-55 to 150	25	✓

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR series 2012 type

SHAPE & DIMENSIONS



Electrode material
Internal:Pd
External:Ag/Ni/Sn

Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm



PRODUCT CHARACTERISTICS LIST

Item	V1mA	C	Vdc	Vcl	E	Ip	Operating temperature range	ESD voltage tolerance	AEC-Q200
	(V)	1kHz/1MHz* (pF)	DC (V)	8/20μs (V)	10/1000μs (J)	8/20μs (A)	(°C)	IEC61000-4-2 (kV)	
AVR-M2012C120MT6AB	12(9.6 to 14.4)	1000(550 to 1450)	7.5	20(5A)	0.2	60	-40 to 85	8	
AVR-M2012C220KT6AB	22(19.8 to 24.2)	800(560 to 1040)	16	38(5A)	0.3	100	-40 to 125	25	✓
AVRM2012C330KT801N	33(30 to 36)	800(560 to 1040)	24	59(5A)	0.5	240	-55 to 150	25	✓
AVR-M2012C390KT6AB	39(35 to 43)	430(301 to 559)	28	62(5A)	0.3	100	-55 to 150	25	✓
AVRM2012C560KT251M	56(50.4 to 61.6)	250(200 to 300)	40	113(5A)	0.3	150	-55 to 150	25	✓
AVRM2012C720KT201M	72(64.8 to 79.2)	200(160 to 240)	53	142(5A)	0.3	100	-55 to 150	25	✓

V1mA: Varistor voltage, C:Capacitance, Vdc:Maximum allowable circuit voltage, Vcl:Clamping voltage, E:Energy capacity, Ip:Surge current

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

AVR/SGNE series Electrostatic absorption characteristics

discharge voltage waveform (example)

WITHOUT VARISTOR, WAVEFORM AT VARISTOR INSTALLATION



WAVEFORM AT VARISTOR INSTALLATION



Test conditions

150pF/330Ω (IEC61000-4-2)
Contact discharge, Charged voltage 8kV

TEST CIRCUIT DIAGRAM



⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Attention on a circuit board design

Board design

When attached to chip varistors, amount of silver used (fillet size) has direct impact on chip varistors after mounting. Thus, sufficient consideration is necessary.

Set of land dimensions

(1) As the stress rises in the chip varistors owing to the increase in silver, breakage and cracks will occur. Cause including crack, as caution on board land design, configure the shape and dimensions so that the amount of silver is appropriate. If you installed 2 or more parts in the Common Land, separated by a solder resist and special land of each component.

(2) When peak levels panning-at soldering is excessive, by solder contraction stress, mechanical-thermal stress causes a Yasuku chip crack. In addition, when the peak level is underestimated, terminal electrode fixed strength is insufficient. This causes chip dropouts and may affect circuit reliability. Representative example of the panning of peak levels is shown in the following.

Recommended silver dose

Solder volume overload		Solder stress is increased, and it is easy for a crack to form.
Decent solder volume		
Solder volume deficit		Fixed strength is weak, and there is connection a problem and risk of loss.

Recommended silver dose

Example	Cases to avoid	Improvement example (land division)
Lead wire and land of part discrete doubles up		
Arrangements in the vicinity		
Arrangements of chip component\qs companion		

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Attention on a circuit board design

Arrangements of components

(1) I was based on camber of substrate and suggested protocol of chip varistors arrangement, as stress does not join to the utmost is shown in following.

	Substrate for flexural stressAdverse events	**Substrate for flexural stress Good example**
Direction of surface solder		
	Solder the mountain fold as a top.	Solder the mountain fold as a bottom. [Please review the italicized portion, as I am unsure what you mean to convey here.]
Chip arrangements (direction)		
	Mounted vertically to the perforation and slit.	Mounted horizontally to the perforation and slit.
Distance from perforation and slit portion		
	Close location is disadvantageous of perforation and slit.	It is an advantage so distant location away places the perforation and slit.

(2) In payment near by board, depending on mount position of chip varistors, as mechanical stress varies, please refer to the following diagram.



The order of A > B = C > D > E eases the stress.

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Local precautions

Application to board

Mounting head pressure

Under suction nozzle if dead point too, during implementation, excessive force joins of chip varistors low, as cause causes of crack, please use with reference to something about following.

1) Being set to top surface of substrate so that under suction nozzle as for dead center, substrate does not bend back, and adjust, please.
2) Nozzle pressure at implementation is 1N to 3N in static load, please.
3) Substrate fixes up back surface of substrate with support pin in impact of suction nozzle to wely deflection to the utmost, and substrate hold deflection, please. A representative example is shown in the following.

Cases to avoid	Recommended case
Single-sided mounting 	
Double-sided mounting 	

Mechanical shock that, if positioning your nail to wear, ragged edge of positionings, participates in chip varistors are locally, and chip varistors, as there is possibility of crack generated, cut the closed positioning, and maintenance and inspection, and, exchange of manage dimensions and position nail periodically, please.

Soldering

Significant impact is possible on the performance of chip varistors, flux checks something about follow, please use.

(1) Flux uses one with 0.1wt % (Cl conversion)or less halide substance contains amounts, please. In addition, do not do this with strongly acidic objects.
(2) When soldering the chip varistor to the circuit board, please apply the flux in the minimum necessary amount.
(3) If Used soluble flux, perform thorough wash particularly, please.

Reflow temperature profile



Item	Specification	
	For eutectic mixture solder	Use of lead-free solder
Preheating temperature	160 to 180°C	150 to 180°C
Solder melting temperature	200°C	230°C
Maximum temperature	240°C max.	260°C max.
Preheating time	100s max.	120s max.
Time to reach higher than the solder melting temperature	30s max.	40s max.
number of possible reflow cycles	2 max.	2 max.

Soldering iron

(1) The tip temperature of the soldering iron will vary depending on the type of soldering iron, the size of the circuit board, and the shape and dimensions of the land pattern. While a higher temperature at the tip of the soldering iron can speed up the soldering work, it can also cause cracks due to thermal shock. Therefore, please carry out the work within the following conditions.

Temperature of iron tips (°C)	Wattage (W)	Pallet point shape (mm)	Soldering time (Second)	Frequency
350max.	30max.	ø3.0max.	5 max.	Within each terminal once(Within total of twice)

(2) Direct contact between the soldering iron tip and the body of the chip varistor can cause particularly large strains due to thermal shock, and may result in cracks. Therefore, please ensure that you do not touch any part other than the terminal electrodes directly.

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Local precautions

Cleaning

(1) If cleaning liquid is inappropriate, residues and other foreign body of fluxes builds up on chip varistors, and can degrade the performance of chip varistors (particularly the insulation resistance).
(2) Wash conditions may compromise performance of chip varistors if they are improper (wash due, wash excess).

2-1) For wash due

(a) By substance of a system in flux residue halide, metal including terminal electrodes may experience corrosion.
(b) Substance of a system in flux residue halide builds up on chip varistors, and reduces the insulation resistance.
(c) Soluble flux makes comparisons of colophony series flux, and there is event with trends of significant (1)and(2).

2-2) For excess wash

(1) Owing to lavage, chip varistors deteriorates, and reduces performance of chip varistors.
(2) In ultrasonography, when output is passed, substrate resonates size, and crack occurs in body and sprang of chip varistors in vibration of substrate. Since this may reduce the strength of the terminal electrode, please note the following conditions. [Please review the italicized portion, as I am unsure what you mean to convey here.]

Ultrasound output： 20W/liter or less
Ultrasound frequency： 40kHz or less
Cleaning time： 5minutes or less

2-3) Concentration including halogen that when cleaning liquid to pollution, when you released is higher, and may cause similar of results into wash due.

Substrate handling after component mounting

(1) When substrate is divided, a flexible so that show in following diagram to substrate, and is given by stress including twist, as there is possibility that crack occurs of chip varistors, please check that stress is within acceptable limits.



(2) During each substrate operational check, push pressure with contact failure of check pin of boards checkers of check pin may be toned up to be prevented. As substrate is bent under loading, chip varistors is broken owing to stress. There is also the possibility that solder on the terminal electrode will peel off. Follow the diagram for reference, and check that the substrate bends, please.

Item	Cases to avoid	Recommended case
Substrate sags		

Single-part component handling

(1) Chip varistors can be damaged or cracked due to impact from falling. Therefore, please do not use chip varistors that have been dropped.



(2) At stacking storage after implementation and treatment of substrate, corner of boards is regarded as chip varistors. Please be careful, as there is the possibility that breakage and cracks will occur on impact.



⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Chip varistors

RoHS Directive Compliant Product
Compatible with lead-free solders

Packaging style

reel dimensions



Dimensions in mm

tape dimensions



Dimensions in mm



Dimensions in mm

Type	A	B	P1	T
AVRM0402/AVRL04/SGNE04	0.26±0.04	0.46±0.04	2.0±0.05	0.40max.
AVRM0603/AVR-M0603/AVRL06/SGNE06	0.38±0.05	0.68±0.05	2.0±0.05	0.45max.
AVRM1005/AVR-M1005/AVRL10/AVRH10	0.65+0.05/−0.1	1.15+0.05/−0.1	2.0±0.05	0.65max.
AVRM1608/AVR-M1608/AVRL16	1.1±0.2	1.9±0.2	4.0±0.1	1.1max.
AVRH16A2	1.1±0.2	1.9±0.2	4.0±0.1	0.8max.
AVRM2012/AVR-M2012	1.5±0.2	2.3±0.2	4.0±0.1	1.7max.

Package quantity / Individual weight

Type	Package quantity (pieces/reel)	Individual weight (mg)
AVRM0402/AVRL04/SGNE04	20,000	0.1
AVRM0603/AVR-M0603/AVRL06/SGNE06	15,000	0.2
AVRM1005/AVR-M1005/AVRL10/AVRH10	10,000	1.2
AVRM1608/AVR-M1608/AVRL16	4,000	5.3
AVRH16A2	4,000	4.0
AVRM2012/AVR-M2012	2,000	13

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View AVRL061E1R1NTA on WIN SOURCE
- TDK Corporation Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management