



**THE DATASHEET OF
HLS-06-SL**



Fuseholders for Indicating Fuses

GMT Type



CATALOG SYMBOL: HLS, HLT, PCT
FUSEHOLDERS FOR GMT TYPE INDICATING FUSES
ELECTRICAL RATING—60V DC, 125V AC
UL RECOGNIZED (GUIDE # IZLT2, FILE E14853)
15AMP (60V DC)


Materials:

Body: Thermosplastic, UL 94V0 flammability rating

Terminals: Tin-plated bifurcated copper

For use with GMT Type Indicating Fuses


Multiple Fuseholders with bus bars
Ordering Information—Catalog No.






* Angle Bar mounts on common or center terminals only.
† Minimum of 4 Poles Required.
** SL Version is not available with bus bars.

Dimensional Data

Printed Circuit Board Application
Shown With GMT Fuse Installed





Note: Similar Body Dimensions
of All Holders Are Identical.



The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View HLS-06-SL on WIN SOURCE](#)
-  [Eaton Bussmann Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management