


PCV

Chip Type, High Voltage / Long Life



- High voltage (to 125V), Low ESR, High ripple current.
- Load life of 3000 hours at 105°C.
- SMD type : Lead free reflow soldering condition at 260°C peak correspondence.
- Compliant to the RoHS directive (2011/65/EU,(EU)2015/863).
- AEC-Q200 Qualified. Please contact us for details.




■ Specifications


| Item | Performance Characteristics | | | | | | | | | |
|---|--|---|--------------------|--|-------|---|-----------|---|-----------------------|---|
| Category Temperature Range | -55 to +105°C | | | | | | | | | |
| Rated Voltage Range | 16 to 125V | | | | | | | | | |
| Rated Capacitance Range | 5.6 to 680μF | | | | | | | | | |
| Capacitance Tolerance | ±20% at 120Hz, 20°C | | | | | | | | | |
| Tangent of loss angle (tan δ) | Less than or equal to the specified value at 120Hz, 20°C | | | | | | | | | |
| ESR (※ 1) | Less than or equal to the specified value at 100kHz, 20°C | | | | | | | | | |
| Leakage Current (※ 2) | Less than or equal to the specified value . After 2 minutes' application of rated voltage at 20°C | | | | | | | | | |
| Temperature Characteristics (Max.Impedance Ratio) | $Z(+105^{\circ}\text{C}) / Z(+20^{\circ}\text{C}) \leq 1.25$ (100kHz) $Z(-55^{\circ}\text{C}) / Z(+20^{\circ}\text{C}) \leq 1.25$ | | | | | | | | | |
| Endurance | The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 3000 hours at 105°C. | <table border="1"> <tr><td>Capacitance change</td><td>Within ± 20% of the initial capacitance value (※3)</td></tr> <tr><td>tan δ</td><td>150% or less than the initial specified value</td></tr> <tr><td>ESR (※ 1)</td><td>150% or less than the initial specified value</td></tr> <tr><td>Leakage current (※ 2)</td><td>Less than or equal to the initial specified value</td></tr> </table> | Capacitance change | Within ± 20% of the initial capacitance value (※3) | tan δ | 150% or less than the initial specified value | ESR (※ 1) | 150% or less than the initial specified value | Leakage current (※ 2) | Less than or equal to the initial specified value |
| Capacitance change | Within ± 20% of the initial capacitance value (※3) | | | | | | | | | |
| tan δ | 150% or less than the initial specified value | | | | | | | | | |
| ESR (※ 1) | 150% or less than the initial specified value | | | | | | | | | |
| Leakage current (※ 2) | Less than or equal to the initial specified value | | | | | | | | | |
| Damp Heat (Steady State) | The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 60°C, 90% RH. | <table border="1"> <tr><td>Capacitance change</td><td>Within ± 20% of the initial capacitance value (※3)</td></tr> <tr><td>tan δ</td><td>150% or less than the initial specified value</td></tr> <tr><td>ESR (※ 1)</td><td>150% or less than the initial specified value</td></tr> <tr><td>Leakage current (※ 2)</td><td>Less than or equal to the initial specified value</td></tr> </table> | Capacitance change | Within ± 20% of the initial capacitance value (※3) | tan δ | 150% or less than the initial specified value | ESR (※ 1) | 150% or less than the initial specified value | Leakage current (※ 2) | Less than or equal to the initial specified value |
| Capacitance change | Within ± 20% of the initial capacitance value (※3) | | | | | | | | | |
| tan δ | 150% or less than the initial specified value | | | | | | | | | |
| ESR (※ 1) | 150% or less than the initial specified value | | | | | | | | | |
| Leakage current (※ 2) | Less than or equal to the initial specified value | | | | | | | | | |
| Resistance to Soldering Heat | After soldering the capacitor under the soldering conditions prescribed here, the capacitor shall meet the specifications listed at right. Pre-heating shall be done at 150 to 200°C and for 60 to 180 sec. The duration for over +230°C temperature at capacitor surface shall not exceed 60 seconds. In case peak temperature is 250°C or less, reflow soldering shall be two times maximum. In case peak temperature is 260°C or less, reflow soldering shall be once. Measurement for solder temperature profile shall be made at the capacitor top. | <table border="1"> <tr><td>Capacitance change</td><td>Within ± 10% of the initial capacitance value (※3)</td></tr> <tr><td>tan δ</td><td>130% or less than the initial specified value</td></tr> <tr><td>ESR (※ 1)</td><td>130% or less than the initial specified value</td></tr> <tr><td>Leakage current (※ 2)</td><td>Less than or equal to the initial specified value</td></tr> </table> | Capacitance change | Within ± 10% of the initial capacitance value (※3) | tan δ | 130% or less than the initial specified value | ESR (※ 1) | 130% or less than the initial specified value | Leakage current (※ 2) | Less than or equal to the initial specified value |
| Capacitance change | Within ± 10% of the initial capacitance value (※3) | | | | | | | | | |
| tan δ | 130% or less than the initial specified value | | | | | | | | | |
| ESR (※ 1) | 130% or less than the initial specified value | | | | | | | | | |
| Leakage current (※ 2) | Less than or equal to the initial specified value | | | | | | | | | |
| Marking | Navy blue print on the case top | | | | | | | | | |

- ※ 1 ESR should be measured at both of the terminal ends closest where the terminals protrude through the plastic platform.
- ※ 2 Conditioning : If any doubt arises, measure the leakage current after the voltage treatment of applying DC rated voltage continuously to the capacitor for 120 minutes at 105°C.
- ※ 3 Initial value : The value before test of examination of resistance to soldering.

■ Dimensions



Type numbering system (Example : 35V 82μF)



| Size | φ6.3 x 6L | φ8 x 7L | φ8 x 10L | φ8 x 12L | φ10 x 8L | φ10 x 10L | φ10 x 12.7L |
|------|------------|------------|------------|------------|------------|------------|-------------|
| φD | 6.3 | 8.0 | 8.0 | 8.0 | 10.0 | 10.0 | 10.0 |
| L | 5.9 | 6.9 | 9.9 | 11.9 | 7.9 | 9.9 | 12.6 |
| A | 7.3 | 9.0 | 9.0 | 9.0 | 11.0 | 11.0 | 11.0 |
| B | 6.6 | 8.3 | 8.3 | 8.3 | 10.3 | 10.3 | 10.3 |
| C | 6.6 | 8.3 | 8.3 | 8.3 | 10.3 | 10.3 | 10.3 |
| E | 2.1 | 3.2 | 3.2 | 3.2 | 4.6 | 4.6 | 4.6 |
| H | 0.5 to 0.8 | 0.8 to 1.1 | 0.8 to 1.1 | 0.8 to 1.1 | 0.8 to 1.1 | 0.8 to 1.1 | 0.8 to 1.1 |

| Voltage | V | 16 | 20 | 25 | 35 | 50 | 63 | 80 | 100 | 125 |
|---------|---|----|----|----|----|----|----|----|-----|-----|
| Code | C | D | E | V | H | J | K | 2A | 2B | |

● Frequency coefficient of rated ripple current

| Frequency | 120Hz | 1kHz | 10kHz | 100kHz or more |
|-------------|-------|------|-------|----------------|
| Coefficient | 0.05 | 0.30 | 0.70 | 1.00 |

PCV

■ Dimensions

| Rated Voltage (V) (code) | Surge Voltage (V) | Rated Capacitance (μF) | Case Size φD × L (mm) | tan δ | Leakage Current (μA) (at 20°C after 2 minutes) | ESR (mΩ) (20°C/100kHz) | Rated Ripple (mAmps) (105°C/100kHz) | Part Number |
|-----------------------------|-------------------|------------------------|-----------------------|-------|---|---------------------------|--|----------------|
| 16 (1C) | 18.4 | 56 | 6.3 × 6 | 0.12 | 179 | 50 | 1000 | PCV1C560MCL1GS |
| | | 82 | △ 6.3 × 6 | 0.12 | 262 | 47 | 1300 | PCV1C820MCL2GS |
| | | 100 | 8 × 7 | 0.12 | 320 | 36 | 1500 | PCV1C101MCL1GS |
| | | 150 | △ 8 × 7 | 0.12 | 480 | 34 | 1700 | PCV1C151MCL2GS |
| | | 220 | ▲ 8 × 10 | 0.12 | 704 | 27 | 2000 | PCV1C221MCL6GS |
| | | 220 | 10 × 8 | 0.12 | 704 | 31 | 2000 | PCV1C221MCL1GS |
| | | 270 | □ 8 × 10 | 0.12 | 864 | 21 | 3800 | PCV1C271MCL7GS |
| | | 270 | 8 × 12 | 0.12 | 864 | 26 | 2300 | PCV1C271MCL1GS |
| | | 270 | △ 10 × 8 | 0.12 | 864 | 24 | 3200 | PCV1C271MCL2GS |
| | | 330 | 10 × 10 | 0.12 | 1056 | 26 | 2400 | PCV1C331MCL1GS |
| | | 390 | △ 8 × 12 | 0.12 | 1248 | 20 | 4100 | PCV1C391MCL2GS |
| | | 470 | △ 10 × 10 | 0.12 | 1504 | 21 | 3900 | PCV1C471MCL2GS |
| | | 470 | 10 × 12.7 | 0.12 | 1504 | 25 | 2800 | PCV1C471MCL1GS |
| 680 | △ 10 × 12.7 | 0.12 | 2176 | 19 | 4400 | PCV1C681MCL2GS | | |
| 20 (1D) | 23.0 | 47 | 6.3 × 6 | 0.12 | 188 | 55 | 1000 | PCV1D470MCL1GS |
| | | 56 | △ 6.3 × 6 | 0.12 | 224 | 48 | 1300 | PCV1D560MCL2GS |
| | | 68 | 8 × 7 | 0.12 | 272 | 45 | 1300 | PCV1D680MCL1GS |
| | | 100 | △ 8 × 7 | 0.12 | 400 | 42 | 1400 | PCV1D101MCL2GS |
| | | 150 | ▲ 8 × 10 | 0.12 | 600 | 28 | 2000 | PCV1D151MCL6GS |
| | | 150 | 10 × 8 | 0.12 | 600 | 33 | 1900 | PCV1D151MCL1GS |
| | | 180 | △ 10 × 8 | 0.12 | 720 | 25 | 3100 | PCV1D181MCL2GS |
| | | 220 | □ 8 × 10 | 0.12 | 880 | 22 | 3700 | PCV1D221MCL7GS |
| | | 220 | 8 × 12 | 0.12 | 880 | 27 | 2300 | PCV1D221MCL1GS |
| | | 270 | △ 8 × 12 | 0.12 | 1080 | 21 | 4000 | PCV1D271MCL2GS |
| | | 270 | 10 × 10 | 0.12 | 1080 | 27 | 2300 | PCV1D271MCL1GS |
| | | 330 | △ 10 × 10 | 0.12 | 1320 | 22 | 3800 | PCV1D331MCL2GS |
| | | 330 | 10 × 12.7 | 0.12 | 1320 | 26 | 2700 | PCV1D331MCL1GS |
| 470 | △ 10 × 12.7 | 0.12 | 1880 | 20 | 4300 | PCV1D471MCL2GS | | |
| 25 (1E) | 28.7 | 33 | 6.3 × 6 | 0.12 | 165 | 60 | 1000 | PCV1E330MCL1GS |
| | | 47 | △ 6.3 × 6 | 0.12 | 235 | 49 | 1300 | PCV1E470MCL2GS |
| | | 56 | 8 × 7 | 0.12 | 280 | 50 | 1300 | PCV1E560MCL1GS |
| | | 82 | △ 8 × 7 | 0.12 | 410 | 47 | 1400 | PCV1E820MCL2GS |
| | | 120 | ▲ 8 × 10 | 0.12 | 600 | 29 | 1900 | PCV1E121MCL6GS |
| | | 120 | 10 × 8 | 0.12 | 600 | 35 | 1800 | PCV1E121MCL1GS |
| | | 150 | □ 8 × 10 | 0.12 | 750 | 23 | 3600 | PCV1E151MCL7GS |
| | | 150 | 8 × 12 | 0.12 | 750 | 28 | 2200 | PCV1E151MCL1GS |
| | | 150 | △ 10 × 8 | 0.12 | 750 | 26 | 3000 | PCV1E151MCL2GS |
| | | 180 | 10 × 10 | 0.12 | 900 | 28 | 2300 | PCV1E181MCL1GS |
| | | 220 | △ 8 × 12 | 0.12 | 1100 | 22 | 3800 | PCV1E221MCL2GS |
| | | 270 | △ 10 × 10 | 0.12 | 1350 | 23 | 3700 | PCV1E271MCL2GS |
| | | 270 | 10 × 12.7 | 0.12 | 1350 | 27 | 2700 | PCV1E271MCL1GS |
| 390 | △ 10 × 12.7 | 0.12 | 1950 | 21 | 4200 | PCV1E391MCL2GS | | |
| 35 (1V) | 40.2 | 18 | 6.3 × 6 | 0.12 | 126 | 64 | 900 | PCV1V180MCL1GS |
| | | 22 | △ 6.3 × 6 | 0.12 | 154 | 50 | 1300 | PCV1V220MCL2GS |
| | | 27 | 8 × 7 | 0.12 | 189 | 55 | 1200 | PCV1V270MCL1GS |
| | | 39 | △ 8 × 7 | 0.12 | 273 | 52 | 1400 | PCV1V390MCL2GS |
| | | 56 | 8 × 10 | 0.12 | 392 | 31 | 1900 | PCV1V560MCL1GS |
| | | 68 | 10 × 8 | 0.12 | 476 | 37 | 1800 | PCV1V680MCL1GS |
| | | 82 | □ 8 × 10 | 0.12 | 574 | 24 | 3600 | PCV1V820MCL7GS |
| | | 82 | 8 × 12 | 0.12 | 574 | 29 | 2200 | PCV1V820MCL1GS |
| | | 82 | △ 10 × 8 | 0.12 | 574 | 27 | 3000 | PCV1V820MCL2GS |
| | | 100 | 10 × 10 | 0.12 | 700 | 29 | 2200 | PCV1V101MCL1GS |
| | | 120 | □ 8 × 12 | 0.12 | 840 | 23 | 3800 | PCV1V121MCL7GS |
| | | 120 | △ 10 × 10 | 0.12 | 840 | 24 | 3700 | PCV1V121MCL2GS |
| | | 150 | 10 × 12.7 | 0.12 | 1050 | 28 | 2600 | PCV1V151MCL1GS |
| 180 | △ 10 × 12.7 | 0.12 | 1260 | 22 | 4100 | PCV1V181MCL2GS | | |



■ Dimensions



| Rated Voltage (V) (code) | Surge Voltage (V) | Rated Capacitance (μF) | Case Size φD × L (mm) | tan δ | Leakage Current (μA) (at 20°C after 2 minutes) | ESR (mΩ) (20°C/100kHz) | Rated Ripple (mA Arms) (105°C/100kHz) | Part Number |
|--------------------------|-------------------|------------------------|-----------------------|-------|--|------------------------|---------------------------------------|----------------|
| 50 (1H) | 57.5 | 8.2 | 6.3×6 | 0.12 | 82 | 81 | 800 | PCV1H8R2MCL1GS |
| | | 12 | △ 6.3×6 | 0.12 | 120 | 55 | 1200 | PCV1H120MCL2GS |
| | | 15 | 8×7 | 0.12 | 150 | 63 | 1100 | PCV1H150MCL1GS |
| | | 22 | △ 8×7 | 0.12 | 220 | 60 | 1300 | PCV1H220MCL2GS |
| | | 33 | ▲ 8×10 | 0.12 | 330 | 36 | 1700 | PCV1H330MCL6GS |
| | | 33 | 10×8 | 0.12 | 330 | 49 | 1500 | PCV1H330MCL1GS |
| | | 39 | 8×12 | 0.12 | 390 | 34 | 2000 | PCV1H390MCL1GS |
| | | 47 | □ 8×10 | 0.12 | 470 | 29 | 3300 | PCV1H470MCL7GS |
| | | 47 | △ 10×8 | 0.12 | 470 | 37 | 2600 | PCV1H470MCL2GS |
| | | 47 | 10×10 | 0.12 | 470 | 30 | 2200 | PCV1H470MCL1GS |
| | | 56 | △ 8×12 | 0.12 | 560 | 28 | 3400 | PCV1H560MCL2GS |
| | | 68 | △ 10×10 | 0.12 | 680 | 29 | 3400 | PCV1H680MCL2GS |
| | | 68 | 10×12.7 | 0.12 | 680 | 29 | 2600 | PCV1H680MCL1GS |
| 100 | △ 10×12.7 | 0.12 | 1000 | 27 | 3600 | PCV1H101MCL2GS | | |
| 63 (1J) | 72.4 | 5.6 | 6.3×6 | 0.12 | 71 | 105 | 700 | PCV1J5R6MCL1GS |
| | | 8.2 | △ 6.3×6 | 0.12 | 103 | 56 | 1200 | PCV1J8R2MCL2GS |
| | | 10 | 8×7 | 0.12 | 126 | 75 | 1000 | PCV1J100MCL1GS |
| | | 12 | △ 8×7 | 0.12 | 151 | 70 | 1100 | PCV1J120MCL2GS |
| | | 22 | ▲ 8×10 | 0.12 | 277 | 37 | 1700 | PCV1J220MCL6GS |
| | | 22 | 10×8 | 0.12 | 277 | 56 | 1400 | PCV1J220MCL1GS |
| | | 27 | □ 8×10 | 0.12 | 340 | 30 | 3200 | PCV1J270MCL7GS |
| | | 27 | 8×12 | 0.12 | 340 | 35 | 2000 | PCV1J270MCL1GS |
| | | 27 | △ 10×8 | 0.12 | 340 | 38 | 2500 | PCV1J270MCL2GS |
| | | 33 | 10×10 | 0.12 | 416 | 31 | 2200 | PCV1J330MCL1GS |
| | | 39 | △ 8×12 | 0.12 | 491 | 29 | 3400 | PCV1J390MCL2GS |
| | | 47 | △ 10×10 | 0.12 | 592 | 30 | 3300 | PCV1J470MCL2GS |
| | | 47 | 10×12.7 | 0.12 | 592 | 30 | 2500 | PCV1J470MCL1GS |
| 56 | △ 10×12.7 | 0.12 | 706 | 28 | 3400 | PCV1J560MCL2GS | | |
| 80 (1K) | 92.0 | 10 | 8×10 | 0.12 | 160 | 43 | 1600 | PCV1K100MCL1GS |
| | | 12 | 8×12 | 0.12 | 192 | 41 | 1800 | PCV1K120MCL1GS |
| | | 15 | 10×10 | 0.12 | 240 | 39 | 1900 | PCV1K150MCL1GS |
| | | 22 | 10×12.7 | 0.12 | 352 | 38 | 2200 | PCV1K220MCL1GS |
| 100 (2A) | 115 | 6.8 | 8×10 | 0.12 | 136 | 48 | 1500 | PCV2A6R8MCL1GS |
| | | 10 | 8×12 | 0.12 | 200 | 45 | 1700 | PCV2A100MCL1GS |
| | | 12 | 10×10 | 0.12 | 240 | 42 | 1900 | PCV2A120MCL1GS |
| | | 18 | 10×12.7 | 0.12 | 360 | 41 | 2100 | PCV2A180MCL1GS |
| 125 (2B) | 143 | 6.8 | 8×10 | 0.12 | 170 | 93 | 1100 | PCV2B6R8MCL1GS |
| | | 8.2 | 8×12 | 0.12 | 205 | 84 | 1300 | PCV2B8R2MCL1GS |
| | | 12 | 10×10 | 0.12 | 300 | 69 | 1400 | PCV2B120MCL1GS |
| | | 15 | 10×12.7 | 0.12 | 375 | 48 | 2000 | PCV2B150MCL1GS |

No marked, [1] will be put at 12th digit of type numbering system.
 △ : In this case, [2] will be put at 12th digit of type numbering system.
 ▲ : In this case, [6] will be put at 12th digit of type numbering system.
 □ : In this case, [7] will be put at 12th digit of type numbering system.


• For taping specifications, recommended land size/soldering by reflow and minimum order quantity, please refer to the Guidelines for Aluminum Electrolytic Capacitors.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View PCV1C471MCL2GS on WIN SOURCE](#)
-  [Nichicon Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management