

Product Overview


Qorvo’s QPM2239 is a packaged, high-power Ku-band amplifier module, fabricated on Qorvo’s production 0.15 um GaN on SiC process (QGaN15). Covering 13–15.5 GHz, the QPM2239 provides 80 W of saturated output power and 29 dB of small-signal gain while achieving > 25% power-added efficiency.

The QPM2239 is packaged in a 10-lead 19.05 x 19.05 mm bolt-down package with a Cu base for superior thermal management. It can support a variety of operating conditions to best support system requirements. With good thermal properties, it can support a range of bias voltages and will perform well under CW operation.

The QPM2239 has DC blocking capacitors on both RF ports, which are matched to 50 ohms.

The QPM2239 is ideal for supporting communications and radar applications in both commercial and military markets

RoHS compliant




Key Features

- Frequency Range: 13 – 15.5 GHz
- P_{SAT} ($P_{IN} = 25$ dBm): 49 dBm
- PAE ($P_{IN} = 25$ dBm): > 25 %
- IM3 ($P_{OUT}/Tone = 38$ dBm): -22 dBc
- Small Signal Gain: 29 dB
- Bias: CW, $V_D = +28$ V, $I_{DQ} = 800$ mA, $V_G = -2.5$ V typ.
- Package Dimensions: 19.05 x 19.05 x 4.5 mm

Performance is typical across frequency. Please reference electrical specification table and data plots for more details.

Functional Block Diagram



Applications

- Commercial VSAT
- Military Satcom
- Datalinks
- Radar

Ordering Information

Part No.	Description
QPM2239	13-15.5GHz 80W GaN Power Amplifier Module
QPM2239S2	Samples (2 pcs. pack)
QPM2239EVB1	Evaluation Board for QPM2239

Absolute Maximum Ratings

Parameter	Value / Range
Drain Voltage (V_D)	+29.5 V
Gate Voltage Range (V_G)	-6 to 0 V
Drain Current (I_D)	12.5 A
Gate Current (I_G)	See chart page 13
Power Dissipation (P_{DISS}), 85 °C	234 W
Input Power (P_{IN}), CW, 50 Ω , $V_D=28$ V, $I_{DQ}=800$ mA, $T_{BASE} = 85$ °C	28 dBm
Input Power (P_{IN}), CW, 3:1 VSWR, $V_D=28$ V, $I_{DQ}=800$ mA, $T_{BASE} = 85$ °C	27 dBm
Mounting Temperature	Refer to Assembly Notes, page 17
Storage Temperature	-55 to +150 °C

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

Recommended Operating Conditions

Parameter	Min	Typ	Max	Units
Drain Voltage (V_D)		+28		V
Drain Current, Quiescent (I_{DQ})		800	900	mA
Drain Current, RF (I_{D_Drive})	See chart page 3, 4, 6			mA
Gate Voltage Typ. Range (V_G)	-2 to -2.9			V
Gate Current, RF (I_{G_Drive})	See chart page 6			mA
T_{BASE} Range	-40		+85	°C

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

Electrical Specifications







Parameter	Conditions ⁽¹⁾ ⁽²⁾	Min	Typ	Max	Units
Operational Frequency Range		13		15.5	GHz
Output Power at Saturation, P_{SAT}	$P_{IN} = +25$ dBm		49		dBm
Power Added Efficiency, PAE	$P_{IN} = +25$ dBm		25		%
3 RD Intermodulation Products, IM3	$P_{OUT}/Tone = +38$ dBm; $\Delta f = 10$ MHz		-22		dBc
5 TH Intermodulation Products, IM5	$P_{OUT}/Tone = +38$ dBm; $\Delta f = 10$ MHz		-30		dBc
Small Signal Gain, S_{21}			29		dB
Input Return Loss, IRL			15		dB
Output Return Loss, ORL			15		dB
P_{SAT} Temperature Coefficient	$T_{DIFF} = -40$ °C to +85 °C ; $P_{IN} = +25$ dBm		-0.01		dBm/°C
S_{21} Temperature Coefficient	$T_{DIFF} = -40$ °C to +85 °C		-0.11		dB/°C

Notes:

1. Test conditions unless otherwise noted: CW, $V_D = 28$ V, $I_{DQ} = 800$ mA, $V_G = -2.5$ V +/- typical, $T_{BASE} = +25$ °C, $Z_0 = 50$ Ω
2. T_{BASE} is back side of package







Performance Plots – Large Signal

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ °C}$









Performance Plots – Large Signal

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$







Performance Plots – Large Signal

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$









Performance Plots – Large Signal

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$









Performance Plots – Linearity

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, Tone Spacing = 10 MHz, $T_{BASE} = +25\text{ °C}$









Performance Plots – Linearity

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, Tone Spacing = 10 MHz, $T_{BASE} = +25\text{ }^\circ\text{C}$









Performance Plots – Linearity

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, Tone Spacing = 10 MHz, $T_{BASE} = +25\text{ }^\circ\text{C}$









Performance Plots – Linearity

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$









Performance Plots – Harmonic

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$



Performance Plots – Small Signal

Test conditions unless otherwise noted: CW, $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, $T_{BASE} = +25\text{ }^\circ\text{C}$





Thermal and Reliability Information


Parameter	Test Conditions	Value	Units
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85\text{ }^{\circ}\text{C}$ $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$	0.49	$^{\circ}\text{C/W}$
Channel Temperature, T_{CH} (Quiescent) ⁽²⁾	$P_{DISS} = 22.4\text{ W}$	96	$^{\circ}\text{C}$
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85\text{ }^{\circ}\text{C}$, CW $V_D = 28\text{ V}$, $I_{DQ} = 800\text{ mA}$, Freq = 14.5 GHz, $I_{D_DRIVE} = 9.9\text{ A}$, $P_{IN} = 25\text{ dBm}$, $P_{OUT} = 48.5\text{ dBm}$	0.49	$^{\circ}\text{C/W}$
Channel Temperature, T_{CH} (Under RF) ⁽²⁾	$P_{DISS} = 207\text{ W}$	186	$^{\circ}\text{C}$

Notes:

- Thermal resistance determined to the back of package (85 $^{\circ}\text{C}$)
- Channel temperature indicated is an IR scan equivalent temperature. Thermal resistance is calculated using this value. Additional information can be found in the Qorvo Applications Note "GaN Device TCHMAX Theta-JC and Reliability Estimates," located here <https://www.qorvo.com/products/d/da006480>



Applications Circuit



Notes:

1. V_{G1} and V_{G2} can be tied together at the harness level to form V_G as shown (the same with V_{D1} and V_{D2})
2. Each gate (V_{G1} , V_{G2}) and each drain (V_{D1} , V_{D2}) must be biased


Bias-Up Procedure

1. Set I_D limit to 12.5 A (or each I_{D1} , I_{D2} to 6.25 A),
Set I_G limit to 100 mA (or each I_{G1} , I_{G2} to 50 mA)
2. Set V_G to -5.0 V (or each V_{G1} , V_{G2} to -5 V).
Ensure $I_{DQ} \sim 0$ mA
3. Set V_D +28 V (or each $V_{D1} = V_{D2} = +28$ V)
4. Adjust V_G more positive until $I_{DQ} = 800$ mA
(or adjust V_{G1} until $I_{D1} = 400$ mA, V_{G2} until $I_{D2} = 400$ mA)
Each $V_G \sim -2.5$ V +/- 0.7 V typical range
5. Apply RF signal

Bias-Down Procedure

1. Turn off RF signal
2. Reduce V_G (or V_{G1} , V_{G2}) to -5.0 V. Ensure $I_{DQ} \sim 0$ mA
3. Set V_D (or V_{D1} , V_{D2}) to 0 V
4. Turn off V_D supply
5. Turn off V_G supply

Application Evaluation Board (EVB)




Data sheet = EVB @ T_{BASE} – Thru Loss

Bill of Materials

Reference Des.	Value	Description	Manuf.	Part Number
U1	-	QPM2239-SM	Qorvo	
C2, C5, C8, C11	0.1 uF	CAP, 0.1uF, 10%, 50V, X7R, 0805	Various	
C3, C6, C9, C12	10 uF	CAP, 10uF, 20%, 50V, X5R, 1206	Various	
H1, H2, H3, H4	-	Header, connector 2x2, SMD	Various	
S1 – S7	-	Screw, Cap, socket head, 2-56x1/8"	Various	
S9 – S12	-	Screw, Cap, socket head, 0-80x3/32'	Various	
J1, J2	SMA	Female End Launch Connector	Southwest Microwave	292-04A-5
PCB	-	Rogers 6035HTC, 10 mil dielectric, 0.5 oz. copper (gold plated), 2 layers	Rogers Corp.	
Carrier	-	T-Carrier, Copper C110, 1.744 x 2.201 x 0.275"		Custom, Qorvo
Solder	-	Paste, solder, SAC305		
Epoxy	-	Epoxy, Ablebond 84-1LMI 3cc	Henkel Corporation	84-1LMI
Thermal Compound	-	Chem, thermal compound, Silver GR	Arctic Silver	Artic Silver 5 AS5-3.5G

Mechanical Information


NOTES:
1. MATERIALS

PACKAGE BASE: COPPER

LEADS: ALLOY 194

LID: PLASTIC

FINISH: GOLD

2. PART IS EPOXY SEALED
3. UNITS: INCHES
4. TOLERANCES (UNLESS NOTED):

.XX = ± .01

.XXX = ± .005

5. MARKINGS

PART NUMBER: QPM2239

WORK YEAR: YY

WORK WEEK: WW

SERIAL NUMBER: ZZZ

BATCH ID: MXXX

Pin Description

Pin No.	Symbol	Description
1	V _{G1}	Gate voltage Amp 1. Bias network is required; see recommended Application Circuit on page 14
2, 4, 7, 9	Ground	Must be grounded to PCB
3	RF _{IN}	RF Input; matched to 50 Ω, DC blocked
5	V _{G2}	Gate voltage Amp 2. Bias network is required; see recommended Application Circuit on page 14
6	V _{D2}	Drain voltage Amp 2. Bias network is required; see recommended Application Circuit on page 14
8	RF _{OUT}	RF Output; matched to 50 Ω, DC blocked
10	V _{D1}	Drain voltage Amp 1. Bias network is required; see recommended Application Circuit on page 14

Assembly Notes

1. Carefully clean the PC board, base plate, and package leads with alcohol. Allow it to dry fully.
2. To improve the thermal and RF performance, Qorvo recommends attaching a heat sink to the bottom of the package and apply either a thermal compound (Arctic Silver 5 recommended) or a .004 inch (maximum thickness) Indium shim between the heat sink and the package. Refer to the applications note [Application of Arctic Silver 5 Thermal Compound and Indium Shims for Qorvo CP-style Packaged Components](#) for more information.
3. The component leads should be manually soldered. Apply a low residue solder alloy meeting J-STD-001 (ROL0, ROL1 or equivalent) with a liquidus temperature below 220 °C to each pin of the TGA/QPA/QPMxxxx. The use of low residue/no-clean flux (ROL0, ROL1) is recommended. The package lead temperature should not exceed 260 deg C. Each solder connection should be completed within 2 to 5 seconds. Adding flux during hand soldering of the component leads with localized spot cleaning is acceptable. Soldering irons meeting the requirements of J-STD-001, Appendix A are acceptable.
4. The leads should be soldered in a staggered or star pattern from side to side, and never solder two adjacent leads. This allows the heat to dissipate on each lead, and not cause the adjacent leads to become de-soldered and damaged or displaced.



5. The packaged part should not be subjected to conventional SMT automated solder reflow processes.
6. (The following is for information only. There are many variables in a second level assembly that Qorvo does not control, so Qorvo does not recommend an absolute torque value.) Use screws to attach the component to the heat sink. A suggested final torque value is 16 in-oz. for a 0-80 screw. Start with screws finger tight, then torque to 8 in-oz., then torque to final value. Use the following tightening pattern:



Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	0B	ANSI/ESD/JEDEC JS-001
ESD – Charged Device Model (CDM)	C2A	ANSI/ESD/JEDEC JS-002
MSL – Moisture Sensitivity Level	N/A	Blank, null, no content



Caution!
ESD-Sensitive Device

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Product uses RoHS Exemption 7c-I to meet RoHS Compliance requirements.
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2024 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View QPM2239 on WIN SOURCE](#)

 [Qorvo US Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management