




# Midi Spring<sup>®</sup> Air Core Inductors



- Air core inductors feature high Q and current handling
- Acrylic top provides a flat surface for pick and place
- Solder coated leads ensure reliable soldering

**Terminations** RoHS compliant tin-silver over copper. Other terminations available at additional cost.

**Weight** 0.10– 0.16 g

**Ambient temperature** –40°C to +125°C with Irms current

**Maximum part temperature** +140°C (ambient + temp rise)

**Storage temperature** Component: –40°C to +140°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +5 to +70 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Packaging** 500/7" reel; 2000/13" reel Plastic tape: 12 mm wide, 0.3 mm thick, 8 mm pocket spacing, 4.33 mm pocket depth  
Recommended pick and place nozzle: OD: 0.110"; ID: 0.091"

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>(nH) | Percent tolerance <sup>3</sup> | Q <sup>4</sup> |     | Test freq.<br>(MHz) | SRF min <sup>5</sup><br>(GHz) | DCR max <sup>6</sup><br>(mOhm) | Irms <sup>7</sup><br>(A) |
|--------------------------|---------------------------------|--------------------------------|----------------|-----|---------------------|-------------------------------|--------------------------------|--------------------------|
|                          |                                 |                                | typ            | min |                     |                               |                                |                          |
| 1812SMS-22N_L_           | 22                              | <b>5,2</b>                     | 135            | 100 | 150                 | 3.2                           | 4.2                            | 3.0                      |
| 1812SMS-27N_L_           | 27                              | <b>5,2</b>                     | 135            | 100 | 150                 | 2.7                           | 4.0                            | 3.5                      |
| 1812SMS-33N_L_           | 33                              | <b>5,2</b>                     | 130            | 100 | 150                 | 2.5                           | 4.8                            | 3.0                      |
| 1812SMS-39N_L_           | 39                              | <b>5,2</b>                     | 135            | 100 | 150                 | 2.1                           | 4.4                            | 3.0                      |
| 1812SMS-47N_L_           | 47                              | <b>5,2</b>                     | 135            | 100 | 150                 | 2.1                           | 5.6                            | 3.0                      |
| 1812SMS-56N_L_           | 56                              | <b>5,2</b>                     | 125            | 100 | 150                 | 1.5                           | 6.2                            | 3.0                      |
| 1812SMS-68N_L_           | 68                              | <b>5,2</b>                     | 120            | 100 | 150                 | 1.5                           | 8.2                            | 2.5                      |
| 1812SMS-82N_L_           | 82                              | <b>5,2</b>                     | 120            | 100 | 150                 | 1.3                           | 9.4                            | 2.5                      |
| 1812SMS-R10_L_           | 100                             | <b>5,2</b>                     | 115            | 100 | 150                 | 1.2                           | 12.3                           | 1.7                      |
| 1812SMS-R12_L_           | 120                             | <b>5,2</b>                     | 125            | 100 | 150                 | 1.1                           | 17.3                           | 1.5                      |
| 1812SMS-R15_L_           | 150                             | <b>5,2</b>                     | 145            | 100 | 150                 | 0.75                          | 33.0                           | 1.2                      |

1. When ordering, specify **tolerance, termination and packaging** codes:

1812SMS-R15GLC

**Tolerance:** G = 2% J = 5%

**Termination:** L = RoHS compliant tin-silver (96.5/3.5) over copper. Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or S = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape, 500 parts per full reel. Quantities less than full reel available: in tape (not machine ready) or with leader and trailer (\$25 charge).

B = Less than full reel. In an effort to simplify our part numbering system, Coilcraft is eliminating the need for multiple packaging codes. When ordering, simply change the last letter of your part number from B to C.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked, 2000 parts per full reel.

2. Inductance tested at 150 MHz on an Agilent/HP 4286A LCR meter or equivalent with a Coilcraft SMD-A test fixture and correlation.

3. Tolerances in bold are stocked for immediate shipment.

4. Q tested at 150 MHz on an Agilent/HP 4291A Impedance Analyzer with an Agilent/HP 16193 test fixture or equivalents.

5. SRF tested on the Agilent/HP 8753D Network Analyzer or equivalent and a Coilcraft CCF1248 test fixture.

6. DCR tested on the Cambridge Technology Model 510 Micro-ohmmeter or equivalent.

7. Current that causes a 15°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

8. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

For part marking data see [www.coilcraft.com/colrcode.cfm](http://www.coilcraft.com/colrcode.cfm).



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)

**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)

**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)

**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)

**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 184-1 Revised 12/02/21

© Coilcraft Inc. 2021


This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Designer's Kit C318 contains 12 each of all 5% values.  
 Designer's Kit C318-2 contains 12 each of all 2% values.





# Midi Spring® Air Core Inductors


## Typical L vs Frequency




## Typical Q vs Frequency



| A max | B max | C max | D            | E            | F max |
|-------|-------|-------|--------------|--------------|-------|
| 0.195 | 0.250 | 0.165 | 0.140 ±0.010 | 0.170 ±0.015 | 0.030 |
| 4,95  | 6,35  | 4,20  | 3,56 ±0,25   | 4,32 ±0,38   | 0,76  |



### Recommended Land Pattern



Dimensions are in  $\frac{\text{inches}}{\text{mm}}$

**S-Parameter files**  
ON OUR WEB SITE  
**SPICE models**  
ON OUR WEB SITE



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 184-2 Revised 12/02/21  
 © Coilcraft Inc. 2021  
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 1812SMS-R15GLC on WIN SOURCE](#)

 [Coilcraft Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management