



THE DATASHEET OF LMK042B7102KC-FW

Notice for TAIYO YUDEN products

Please read this notice before using the TAIYO YUDEN products.

REMINDERS

- Product information in this catalog is as of October 2009. All of the contents specified herein are subject to change without notice due to technical improvements, etc. Therefore, please check for the latest information carefully before practical application or usage of the Products.

Please note that Taiyo Yuden Co., Ltd. shall not be responsible for any defects in products or equipment incorporating such products, which are caused under the conditions other than those specified in this catalog or individual specification.

- Please contact Taiyo Yuden Co., Ltd. for further details of product specifications as the individual specification is available.

- Please conduct validation and verification of products in actual condition of mounting and operating environment before commercial shipment of the equipment.

- All electronic components or functional modules listed in this catalog are developed, designed and intended for use in general electronics equipment.(for AV, office automation, household, office supply, information service, telecommunications, (such as mobile phone or PC) etc.). Before incorporating the components or devices into any equipment in the field such as transportation,(automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network (telephone exchange, base station) etc. which may have direct influence to harm or injure a human body, please contact Taiyo Yuden Co., Ltd. for more detail in advance. Do not incorporate the products into any equipment in fields such as aerospace, aviation, nuclear control, submarine system, military, etc. where higher safety and reliability are especially required.

In addition, even electronic components or functional modules that are used for the general electronic equipment, if the equipment or the electric circuit require high safety or reliability function or performances, a sufficient reliability evaluation check for safety shall be performed before commercial shipment and moreover, due consideration to install a protective circuit is strongly recommended at customer's design stage.

- The contents of this catalog are applicable to the products which are purchased from our sales offices or distributors (so called "TAIYO YUDEN's official sales channel").

It is only applicable to the products purchased from any of TAIYO YUDEN's official sales channel.

- Please note that Taiyo Yuden Co., Ltd. shall have no responsibility for any controversies or disputes that may occur in connection with a third party's intellectual property rights and other related rights arising from your usage of products in this catalog. Taiyo Yuden Co., Ltd. grants no license for such rights.

- Caution for export

Certain items in this catalog may require specific procedures for export according to "Foreign Exchange and Foreign Trade Control Law" of Japan, "U.S. Export Administration Regulations", and other applicable regulations. Should you have any question or inquiry on this matter, please contact our sales staff.

Should you have any question or inquiry on this matter, please contact our sales staff.

HIGH VALUE MULTILAYER CERAMIC CAPACITORS



WAVE

REFLOW

FEATURES

- The use of nickel as electrode material and plating processing improve the solderability and heat resistance characteristics. It also prevents migration and raises the level of reliability.
- Low equivalent series resistance(ESR) provides superior noise absorption characteristics.
- Compared to tantalum or aluminum electrolytic capacitors, multilayer ceramic capacitors offer a number of superior features, including:
Higher permissible ripple current values
Smaller case sizes with high rated voltage
Improved reliability due to higher insulation resistance and breakdown voltage.


APPLICATIONS

- General digital circuit
- Power supply bypass capacitors
Liquid crystal modules
Liquid crystal drive voltage lines
LSI, IC, converters(both for input and output)
- Smoothing capacitors
DC-DC converters (for both input and output)
Switching power supplies (secondary side)

ORDERING CODE

J	M	K	3	1	6	B	J	1	0	6	M	L	-	T	△			
1	2	3	4	5			6	7		8	9	10			11			
1 Rated voltage (VDC)		2 Series name		4 Dimensions (EIA) L×W (mm)			5 Temperature characteristics code		6 Nominal capacitance (pF)		7 Capacitance tolerance		8 Thickness (mm)		9 Special code		11 Internal code	
A 4		M Multilayer ceramic capacitor		107 (0603) 1.6×0.8			BJ B		example		K ±10%		K 0.45		- Standard product		△ Standard product	
J 6.3				212 (0805) 2.0×1.25			X5R		473 47,000		M ±20%		A 0.8					
L 10				316 (1206) 3.2×1.6			B7 X7R		105 1,000,000		Z +80 -20 %		D 0.85					
E 16		3 End termination		325 (1210) 3.2×2.5			△F F						G 1.25					
T 25		K Plated					Y5V						L 1.6					
G 35							△=Blank space						N 1.9					
U 50													Y 2.0max					
													M 2.5					
															10 Packaging			
															T φ178mm Taping (4mm pitch) All types			
															P φ178mm Taping (4mm pitch, 1000pcs/reel) 1210Type Thickness : M			

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Note:

- *1. Including dimension tolerance ± 0.15mm (±0.006 inch).
- *2. Including dimension tolerance ± 0.3mm (±0.012 inch).
- *3. Including dimension tolerance ± 0.2mm (±0.008 inch).
- *4. Including dimension tolerance + 0.15/-0.1mm (+0.006/-0.004 inch).

Type(EIA)	L	W	T	e	Standard quantity [pcs]	
					Paper tape	Embossed tape
□MK107 (0603)	1.6±0.10 ^{*3,4} (0.063±0.004)	0.8±0.10 ^{*3,4} (0.031±0.004)	0.45±0.05(0.018±0.002) 0.8±0.10 ^{*3,4} (0.031±0.004)	K 0.35±0.25 (0.014±0.010) A	4000	—
□MK212 (0805)	2.0±0.10 ^{*1,3} (0.079±0.004)	1.25±0.10 ^{*1,3} (0.049±0.004)	0.45±0.05(0.018±0.002) 0.85±0.10(0.033±0.004) 1.25±0.10 ^{*1,3} (0.049±0.004)	K 0.5±0.25 (0.020±0.010) D G	4000	—
□MK316 (1206)	3.2±0.15 ^{*3} (0.126±0.006)	1.6±0.15 ^{*3} (0.063±0.006)	0.85±0.10(0.033±0.004) 1.25±0.10(0.049±0.004) 1.6±0.20(0.063±0.008)	D 0.5±0.25 (0.020±0.010) G L	4000	3000
□MK325 (1210)	3.2±0.30 (0.126±0.012)	2.5±0.20 ^{*2} (0.098±0.008)	0.85±0.10(0.033±0.004) 1.9±0.20(0.075±0.008) 1.9±0.1 ^{+0.1} -0.2 (0.075±0.004) 2.5±0.20 ^{*2} (0.098±0.008)	D 0.6±0.3 (0.024±0.012) N Y M	—	2000

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Type	107																212																316																325																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
	TC	X7R	B/X5R				X5R	F/Y5V				X7R	B/X5R				X5R	F/Y5V				X7R	B/X5R				X5R	F/Y5V				X7R	B/X5R				X5R	F/Y5V																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
Cap [μF]	VDC	16	10	6.3	3.5	2.5	1.6	1.0	0.63	0.50	0.25	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0.025	0.16	0.10	0.063	0.050	0

Note : Letters in the table indicate thickness.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

● Low Profile Multilayer Ceramic Capacitors

Cap [μF]	Type TC VDC [3digits]	107						212						316						325											
		B/X5R			X5R			X7R			B/X5R			X5R			F/Y5V			B/X5R			X5R			F/Y5V			B/X5R		
		10	6.3	25	16	10	6.3	16	10	25	16	10	25	16	10	6.3	50	10	6.3	50	25	16	10	6.3	50	35	10	6.3	25	16	10
0.1	104																														
0.22	224																	D													
0.33	334																														
0.47	474									D		D																			
0.68	684																														
1	105	K	K	K	K			D	D	D	D	D							D	D											
2.2	225					K	K	D	D	D	D	D					D		D	D	D					G					
3.3	335																														D
4.7	475					K	K			D	D	D				K	D-K		D		D	D				G	D				D
6.8	685																														
10	106												D	D	D-K						D	D	D					D	D	D	D
22	226															D													D	D	
47	476																												D		

Note : Letters in the table indicate thickness.

Temp. char. Code	Temperature characteristics				Capacitance tolerance (%)
	Applicable standard	Temperature range [°C]	Ref. Temp. [°C]	Capacitance change (%)	
BJ	JIS B	-25~+85	20	±10	±10 (K) ±20 (M)
	EIA X5R	-55~+85	25	±15	
B7	EIA X7R	-55~+125	25	±15	
F	JIS F	-25~+85	20	+30/-80	+80 (Z) -20
	EIA Y5V	-30~+85	25	+22/-82	

■ PART NUMBERS

● 107TYPE

[Temp.char. B: B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm)	
50V	UMK107 BJ105□A ¹		RoHS	1	X5R	10	R	±10% ±20%	0.8±0.1	
35V	GMK107 BJ105□A ¹		RoHS	1	B/X5R	5			0.8±0.1	
	TMK107 BJ105□K ¹		RoHS	1	X5R	10			0.45±0.05	
25V	TMK107 BJ224□A		RoHS	0.22	B/X5R	3.5	R/W		0.8±0.1	
	TMK107 BJ474□A ¹		RoHS	0.47	B/X5R	3.5	R		0.8±0.1	
	TMK107 BJ105□A ¹		RoHS	1	B/X5R	5			0.8±0.1	
16V	EMK107 BJ105□K ¹		RoHS	1	X5R	10			R/W	0.45±0.05
	EMK107 BJ224□A		RoHS	0.22	B/X5R ²	3.5	0.8±0.1			
	EMK107 BJ474□A		RoHS	0.47	B/X5R ²	3.5	0.8±0.1			
		EMK107 BJ105□A ¹		RoHS	1	B/X5R ²	5		0.8±0.1	
		EMK107 BJ225□A ¹		RoHS	2.2	B/X5R	10		R	0.8±0.1
10V	LMK107 BJ105□K ¹		RoHS	1	B/X5R	10	R			0.45±0.05
	LMK107 BJ225□K ¹		RoHS	2.2	X5R	10				0.45±0.05
	LMK107 BJ475MK ^{1,4}		RoHS	4.7	X5R	10		±20%	0.45±0.05	
		LMK107 BJ224□A		RoHS	0.22	B/X5R ²	3.5	R/W	0.8±0.1	
		LMK107 BJ474□A		RoHS	0.47	B/X5R ²	3.5		0.8±0.1	
		LMK107 BJ105□A ¹		RoHS	1	B/X5R ²	5		0.8±0.1	
		LMK107 BJ225□A ¹		RoHS	2.2	B/X5R	10	±10% ±20%	0.8±0.1	
	LMK107 BJ475□A ¹		RoHS	4.7	X5R	10	0.8±0.1			
	LMK107 BJ106MA ^{1,4}		RoHS	10	X5R	10	±20%		0.8±0.2	
6.3V	JMK107 BJ105□K ¹		RoHS	1	B/X5R	10	R	±10%	0.45±0.05	
	JMK107 BJ225□K ¹		RoHS	2.2	X5R	10		±20%	0.45±0.05	
	JMK107 BJ475MK ¹		RoHS	4.7	X5R	10		±20%	0.45±0.05	
	JMK107 BJ225□A ¹		RoHS	2.2	B/X5R	10		±10%	0.8±0.1	
	JMK107 BJ475□A ¹		RoHS	4.7	X5R	10		±20%	0.8±0.1	
	JMK107 BJ106MA ¹		RoHS	10	X5R	10		±20%	0.8+0.15/-0.1	
4V	AMK107 BJ106MA ¹		RoHS	10	X5R	10	0.8±0.1			
	AMK107 BJ226MA ^{1,3}		RoHS	22	X5R	10	0.8±0.2			

[Temp.char. B7:X7R]

Rated Voltage	Ordering code	EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm)
16V	EMK107 B7 224□A ^{*1}	RoHS	0.22	X7R	3.5	R/W	±10% ±20%	0.8±0.1
	EMK107 B7 474□A ^{*1}	RoHS	0.47	X7R	3.5	R		0.8±0.1
	EMK107 B7 105□A ^{*1}	RoHS	1	X7R	5			0.8±0.1
10V	LMK107 B7 224□A	RoHS	0.22	X7R	3.5	R/W		0.8±0.1
	LMK107 B7 474□A	RoHS	0.47	X7R	3.5	R		0.8±0.1
	LMK107 B7 105□A ^{*1}	RoHS	1	X7R	5			0.8±0.1
6.3V	JMK107 B7 224□A	RoHS	0.22	X7R	3.5	R/W		0.8±0.1
	JMK107 B7 474□A	RoHS	0.47	X7R	3.5	R		0.8±0.1
	JMK107 B7 105□A ^{*1}	RoHS	1	X7R	5			0.8±0.1
		JMK107 B7 225□A ^{*1}	RoHS	2.2	X7R	10		0.8±0.1
	JMK107 B7 475□A ^{*1}	RoHS	4.7	X7R	10		0.8±0.1	

[Temp.char. F:F/Y5V]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm)
50V	UMK107 F104ZA		RoHS	0.1	F/Y5V	7	R/W	+80% -20%	0.8 $\pm$ 0.1
25V	TMK107 F474ZA		RoHS	0.47	F/Y5V	7			0.8 $\pm$ 0.1
16V	EMK107 F224ZA		RoHS	0.22	F/Y5V	7			0.8 $\pm$ 0.1
	EMK107 F474ZA		RoHS	0.47	F/Y5V	7			0.8 $\pm$ 0.1
	EMK107 F105ZA		RoHS	1	F/Y5V	16			0.8 $\pm$ 0.1
	EMK107 F225ZA		RoHS	2.2	F/Y5V	16	0.8 $\pm$ 0.1		
10V	LMK107 F105ZA		RoHS	1	F/Y5V	16	R		0.8 $\pm$ 0.1
	LMK107 F225ZA		RoHS	2.2	F/Y5V	16			0.8 $\pm$ 0.1

□ Please specify the capacitance tolerance code. *1 1.5 times the rated voltage is applied to the chip during the high temperature loading test. *2 We may provide X7R for some items according to the individual specification. *3 The exchange of individual specification is necessary depending on the application and circuit condition. Please contact Taiyo Yuden sales channels. *4 "D" is used for the internal code.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

● 212TYPE

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm]
50V	UMK212 BJ104□G		RoHS	0.1	B/X5R ⁺²	3.5	R/W		1.25±0.1
	UMK212 BJ224□G ⁺¹		RoHS	0.22	B/X5R ⁺²	3.5			1.25±0.1
	UMK212 BJ474□G ⁺¹		RoHS	0.47	B/X5R ⁺²	3.5			1.25±0.1
	UMK212 BJ105□G ⁺¹		RoHS	1	X5R	5			1.25±0.1
25V	TMK212 BJ474□D		RoHS	0.47	B/X5R	3.5	R	±10% ±20%	0.85±0.1
	TMK212 BJ105□D		RoHS	1	B/X5R	5			0.85±0.1
	TMK212 BJ225□D ⁺¹		RoHS	2.2	B/X5R	5			0.85±0.1
	TMK212 BJ475□D ⁺¹⁺⁴		RoHS	4.7	X5R	10			0.85±0.1
	TMK212 BJ225□G ⁺¹		RoHS	2.2	B/X5R	5			1.25±0.1
	TMK212 BJ475□G ⁺¹		RoHS	4.7	X5R	10			1.25±0.15
	EMK212 BJ105□D		RoHS	1	B/X5R ⁺²	5			0.85±0.1
16V	EMK212 BJ225□D		RoHS	2.2	B/X5R ⁺²	5			0.85±0.1
	EMK212 BJ475□D ⁺¹		RoHS	4.7	B/X5R	10			0.85±0.1
	EMK212 BJ106□D ⁺¹⁺⁴		RoHS	10	X5R	10			0.85±0.1
	EMK212 BJ225□G		RoHS	2.2	B/X5R ⁺²	5			1.25±0.1
	EMK212 BJ475□G ⁺¹		RoHS	4.7	B/X5R ⁺²	5			1.25±0.15
	EMK212 BJ106□G ⁺¹		RoHS	10	X5R	10			1.25±0.15
10V	LMK212 BJ475□K ⁺¹		RoHS	4.7	X5R	10			0.45±0.05
	LMK212 BJ105□D		RoHS	1	B/X5R ⁺²	3.5			0.85±0.1
	LMK212 BJ225□D		RoHS	2.2	B/X5R ⁺²	5			0.85±0.1
	LMK212 BJ475□D		RoHS	4.7	B/X5R	10			0.85±0.1
	LMK212 BJ106□D ⁺¹		RoHS	10	X5R	10			0.85±0.1
	LMK212 BJ225□G		RoHS	2.2	B/X5R ⁺²	5			1.25±0.1
	LMK212 BJ475□G		RoHS	4.7	B/X5R ⁺²	5			1.25±0.15
	LMK212 BJ106□G		RoHS	10	X5R	10			1.25±0.15
6.3V	LMK212 BJ226MG ⁺¹		RoHS	22	X5R	10			±20% 1.25±0.2
	JMK212 BJ475□K ⁺¹		RoHS	4.7	X5R	10		±10% ±20%	0.45±0.05
	JMK212 BJ106MK ⁺¹		RoHS	10	X5R	10			0.45±0.05
	JMK212 BJ475□D		RoHS	4.7	X5R	10			0.85±0.1
	JMK212 BJ106□D		RoHS	10	X5R	10			0.85±0.1
	JMK212 BJ226MD ⁺¹		RoHS	22	X5R	10			0.85±0.1
	JMK212 BJ475□G		RoHS	4.7	B/X5R	5			±10% 1.25±0.15
	JMK212 BJ106□G		RoHS	10	X5R ⁺²	10			±10% 1.25±0.15
	JMK212 BJ226MG ⁺¹		RoHS	22	X5R	10			±20% 1.25±0.15
	JMK212 BJ476MG ⁺¹		RoHS	47	X5R	10		±20% 1.25±0.2	

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm]
50V	UMK212 B7 104□G		RoHS	0.1	X7R	3.5	R/W		1.25±0.1
	UMK212 B7 224□G ⁺¹		RoHS	0.22	X7R	3.5			1.25±0.1
	UMK212 B7 474□G ⁺¹		RoHS	0.47	X7R	3.5			1.25±0.1
35V	GMK212 B7 105□G ⁺¹		RoHS	1	X7R	3.5			1.25±0.1
25V	TMK212 B7 105□G ⁺¹		RoHS	1	X7R	5	R		1.25±0.1
16V	EMK212 B7 474□D		RoHS	0.47	X7R	3.5	R/W	±10% ±20%	0.85±0.1
	EMK212 B7 105□D		RoHS	1	X7R	5			0.85±0.1
	EMK212 B7 225□D ⁺¹		RoHS	2.2	X7R	5	R		0.85±0.1
	EMK212 B7 105□G		RoHS	1	X7R	3.5	R/W		1.25±0.1
	EMK212 B7 225□G ⁺¹		RoHS	2.2	X7R	10			1.25±0.1
	EMK212 B7 475□G ⁺¹		RoHS	4.7	X7R	10			1.25±0.1
10V	LMK212 B7 105□D		RoHS	1	X7R	3.5	R		0.85±0.1
	LMK212 B7 225□D		RoHS	2.2	X7R	5			0.85±0.1
	LMK212 B7 105□G		RoHS	1	X7R	3.5			1.25±0.1
	LMK212 B7 225□G		RoHS	2.2	X7R	5			1.25±0.1
6.3V	LMK212 B7 475□G ⁺¹		RoHS	4.7	X7R	10	R/W		1.25±0.1
	JMK212 B7 106□G ⁺¹		RoHS	10	X7R	10	R		1.25±0.15

[Temp.char. F:F/Y5V]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm)
50V	UMK212 F224ZD		RoHS	0.22	F/Y5V	7	R/W	+80% −20%	0.85±0.1
	UMK212 F474ZG		RoHS	0.47	F/Y5V	7			1.25±0.1
	UMK212 F105ZG		RoHS	1	F/Y5V	7			1.25±0.1
16V	EMK212 F225ZG		RoHS	2.2	F/Y5V	7	R		1.25±0.1
10V	LMK212 F225ZD		RoHS	2.2	F/Y5V	9			0.85±0.1
	LMK212 F475ZG		RoHS	4.7	F/Y5V	9			1.25±0.1
	LMK212 F106ZG		RoHS	10	F/Y5V	16			1.25±0.1
6.3V	JMK212 F475ZD		RoHS	4.7	F/Y5V	16			0.85±0.1
	JMK212 F106ZG		RoHS	10	F/Y5V	16			1.25±0.1

□ Please specify the capacitance tolerance code. *1 1.5 times the rated voltage is applied to the chip during the high temperature loading test. *2 We may provide X7R for some items according to the individual specification. *4 "D" is used for the internal code.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

316TYPE

[Temp.char. B: B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance 〔μF〕	Temperature characteristics	Dissipation factor 〔%〕Max.	Soldering method R: Reflow soldering W: Wave soldering	Capacitance tolerance	Thickness 〔mm〕
50V	UMK316 BJ105□D ^{*1}		RoHS	1	B/X5R	3.5	R	±10% ±20%	0.85±0.1
	UMK316 BJ225□D ^{*1}		RoHS	2.2	B/X5R	3.5			0.85±0.1
	UMK316 BJ105□L		RoHS	1	B/X5R ^{*2}	3.5			1.6±0.2
	UMK316 BJ475□L ^{*1}		RoHS	4.7	X5R	10			1.6±0.2
25V	TMK316 BJ105□D		RoHS	1	B/X5R	3.5			0.85±0.1
	TMK316 BJ225□D ^{*1}		RoHS	2.2	B/X5R	3.5			0.85±0.1
	TMK316 BJ475□D ^{*1}		RoHS	4.7	X5R	5			0.85±0.1
	TMK316 BJ106□D ^{*1}		RoHS	10	X5R	10			0.85±0.1
	TMK316 BJ225□L		RoHS	2.2	B/X5R ^{*2}	3.5			1.6±0.2
	TMK316 BJ475□L ^{*1}		RoHS	4.7	B/X5R	5			1.6±0.2
	TMK316 BJ106□L ^{*1}		RoHS	10	X5R ^{*2}	5			1.6±0.2
	TMK316 BJ226ML ^{*1}		RoHS	22	B/X5R	10			1.6±0.2
16V	EMK316 BJ225□D		RoHS	2.2	B/X5R	3.5	R/W	±20%	0.85±0.1
	EMK316 BJ475□D		RoHS	4.7	X5R	5			0.85±0.1
	EMK316 BJ106□D ^{*1}		RoHS	10	X5R	10			0.85±0.1
	EMK316 BJ225□L		RoHS	2.2	B/X5R ^{*2}	3.5			1.6±0.2
	EMK316 BJ475□L		RoHS	4.7	B/X5R	5	R	±10% ±20%	1.6±0.2
	EMK316 BJ106□L ^{*1}		RoHS	10	B/X5R ^{*2}	5			1.6±0.2
	EMK316 BJ226ML ^{*1}		RoHS	22	B/X5R	10			1.6±0.2
	EMK316 BJ476ML ^{*1}		RoHS	47	X5R	10			1.6±0.2
10V	LMK316 BJ475□D		RoHS	4.7	B/X5R	5			0.85±0.1
	LMK316 BJ106□D		RoHS	10	B/X5R	10			0.85±0.1
	LMK316 BJ226MD ^{*1}		RoHS	22	X5R	10			0.85±0.1
	LMK316 BJ106□L		RoHS	10	B/X5R ^{*2}	5			1.6±0.2
	LMK316 BJ226ML ^{*1}		RoHS	22	B/X5R	10			1.6±0.2
	LMK316 BJ476ML ^{*1}		RoHS	47	X5R	10			1.6±0.2
	JMK316 BJ106□D		RoHS	10	B/X5R	10			0.85±0.1
	JMK316 BJ226MD ^{*1}		RoHS	22	X5R	10			0.85±0.1
6.3V	JMK316 BJ476MD ^{*1}		RoHS	47	X5R	10	R	±10% ±20%	1.6±0.2
	JMK316 BJ106□L		RoHS	10	B/X5R ^{*2}	5			1.6±0.2
	JMK316 BJ226□L		RoHS	22	B/X5R	10			1.6±0.2
	JMK316 BJ476ML		RoHS	47	X5R	10			1.6±0.2
	JMK316 BJ107ML ^{*1,*3}		RoHS	100	X5R	10			1.6±0.2
	JMK316 BJ107ML ^{*1}		RoHS	100	X5R	10			1.6±0.2
4V	AMK316 BJ107ML ^{*1}		RoHS	100	X5R	10			1.6±0.2

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

*3 The exchange of individual specification is necessary depending on the application and circuit condition. Please contact Taiyo Yuden sales channels.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm)
50V	UMK316 B7 224□L		RoHS	0.22	X7R	2.5	R/W	±10% ±20%	1.6±0.2
	UMK316 B7 474□L		RoHS	0.47	X7R	3.5			1.6±0.2
	UMK316 B7 105□L		RoHS	1	X7R	3.5			1.6±0.2
25V	TMK316 B7 105□L		RoHS	1	X7R	3.5	R		1.6±0.2
	TMK316 B7 225□L		RoHS	2.2	X7R	3.5			1.6±0.2
	TMK316 B7 106□L*1,*4		RoHS	10	X7R	10			1.6±0.2
16V	EMK316 B7 225□L		RoHS	2.2	X7R	3.5	R/W		1.6±0.2
	EMK316 B7 106□L*4		RoHS	10	X7R	10	R		1.6±0.2
10V	LMK316 B7 225□L		RoHS	2.2	X7R	3.5	R/W		1.6±0.2
	LMK316 B7 475□L		RoHS	4.7	X7R	5	R		1.6±0.2
	LMK316 B7 106□L*1,*4		RoHS	10	X7R	10			1.6±0.2
6.3V	JMK316 B7 106□L		RoHS	10	X7R	5			1.6±0.2

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*4 "D" is used for the internal code.

[Temp.char. F:F/Y5V]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm]
50V	UMK316 F225ZG		RoHS	2.2	F/Y5V	7	R/W	+80% -20%	1.25±0.1
35V	GMK316 F475ZG		RoHS	4.7	F/Y5V	7	R		1.25±0.1
	GMK316 F106ZL		RoHS	10	F/Y5V	9			1.6±0.2
25V	TMK316 F106ZL		RoHS	10	F/Y5V	9			1.6±0.2
16V	EMK316 F106ZL		RoHS	10	F/Y5V	9			1.6±0.2
10V	LMK316 F475ZD		RoHS	4.7	F/Y5V	9			0.85±0.1
	LMK316 F226ZL		RoHS	22	F/Y5V	16			1.6±0.2
6.3V	JMK316 F106ZD		RoHS	10	F/Y5V	16			0.85±0.1

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

325TYPE

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance 〔μF〕	Temperature characteristics	Dissipation factor 〔%〕Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness 〔mm〕
50V	UMK325 BJ475MM ^{*1}		RoHS	4.7	X5R	5	R	±20%	2.5±0.2
	UMK325 BJ106MM ^{*1}		RoHS	10	X5R	5			2.5±0.2
35V	GMK325 BJ225MN		RoHS	2.2	B/X5R	3.5			1.9±0.2
	GMK325 BJ475MN ^{*1}		RoHS	4.7	X5R	10			1.9±0.2
	GMK325 BJ106MN ^{*1}		RoHS	10	B/X5R	5			1.9±0.2
25V	TMK325 BJ106MD ^{*1}		RoHS	10	B/X5R	5			0.85±0.1
	TMK325 BJ335MN		RoHS	3.3	B/X5R ^{*2}	3.5			1.9±0.2
	TMK325 BJ475MN		RoHS	4.7	B/X5R ^{*2}	3.5			1.9±0.2
	TMK325 BJ106MN		RoHS	10	B/X5R	5			1.9±0.2
	TMK325 BJ106MM ^{*1}		RoHS	10	B/X5R ^{*2}	3.5			2.5±0.2
16V	EMK325 BJ106MD ^{*1}		RoHS	10	B/X5R	5			0.85±0.1
	EMK325 BJ226MD ^{*1}		RoHS	22	B/X5R	10			0.85±0.1
	EMK325 BJ475MN		RoHS	4.7	B/X5R ^{*2}	3.5			1.9±0.2
	EMK325 BJ106MN		RoHS	10	B/X5R	3.5			1.9±0.2
	EMK325 BJ226MM ^{*1}		RoHS	22	B/X5R	5			2.5±0.2
10V	EMK325 BJ476MM ^{*1}		RoHS	47	X5R	10			2.5±0.2
	LMK325 BJ335MD		RoHS	3.3	B/X5R	3.5			0.85±0.1
	LMK325 BJ475MD		RoHS	4.7	B/X5R	5			0.85±0.1
	LMK325 BJ106MD ^{*1}		RoHS	10	B/X5R	5			0.85±0.1
	LMK325 BJ226MY ^{*1}		RoHS	22	B/X5R	5			1.9+0.1/-0.2
	LMK325 BJ106MN		RoHS	10	B/X5R ^{*2}	3.5			1.9±0.2
	LMK325 BJ226MM		RoHS	22	B/X5R	5			2.5±0.2
6.3V	LMK325 BJ476MM ^{*1}		RoHS	47	X5R	10			2.5±0.2
	LMK325 BJ107MM ^{*1}		RoHS	100	X5R	10			2.5±0.3
	JMK325 BJ226MY		RoHS	22	B/X5R	5			1.9+0.1/-0.2
	JMK325 BJ107MY ^{*1}		RoHS	100	X5R	10			1.9+0.1/-0.2
	JMK325 BJ476MN ^{*1}		RoHS	47	X5R	10			1.9±0.2
	JMK325 BJ476MM ^{*1}		RoHS	47	X5R	10			2.5±0.2
	JMK325 BJ107MM ^{*1}		RoHS	100	X5R	10			2.5±0.3

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance 〔μF〕	Temperature characteristics	Dissipation factor 〔%〕Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness 〔mm〕
25V	TMK325 B7 335MN		RoHS	3.3	X7R	3.5	R	±20%	1.9±0.2
	TMK325 B7 475MN ^{*1}		RoHS	4.7	X7R	3.5			1.9±0.2
16V	EMK325 B7 475MN		RoHS	4.7	X7R	3.5			1.9±0.2
10V	LMK325 B7 106MN		RoHS	10	X7R	3.5			1.9±0.2

□ Please specify the capacitance tolerance code.


*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

[Temp.char. F:F/Y5V]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance 〔μF〕	Temperature characteristics	Dissipation factor 〔%〕Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness 〔mm〕
16V	EMK325 F226ZN		RoHS	22	F/Y5V	16	R	+80% -20%	1.9±0.2
10V	LMK325 F226ZN		RoHS	22	F/Y5V	16			1.9±0.2
6.3V	JMK325 F476ZN		RoHS	47	F/Y5V	16			1.9±0.2

● Example of Impedance ESR vs. Frequency characteristics

■ Taiyo Yuden multilayer ceramic capacitor



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

STANDARD MULTILAYER CERAMIC CAPACITORS (CLASS1:TEMPERATURE COMPENSATING TYPE)



REFLOW

FEATURES

- Improved higher density mounting.
- Monolithic structure provides higher reliability.
- A wide range of capacitance values available in standard case sizes.

APPLICATIONS

- General electronic equipment
- Communication equipment
(cellular phone, wireless applications, etc.)

ORDERING CODE

U M K 1 0 5 C H 1 0 1 J V — F △

1 2 3 4 5 6 7 8 9 10 11

1 Rated voltage (VDC)

E	16
T	25
U	50

2 Series name

M	Multilayer ceramic capacitor
---	------------------------------

3 End termination

K	Plated
---	--------

**4 Dimensions (EIA)
L×W (mm)**

042 (01005)	0.4×0.2
063 (0201)	0.6×0.3
105 (0402)	1.0×0.5

5 Temperature characteristics (ppm/°C)

C□ : 0	CH, CJ, CK	Tolerance H : ±60 J : ±120 K : ±250
R□ : -220	RH	
S□ : -330	SH, SJ, SK	
T□ : -470	TJ, TK	
U□ : -750	UJ, UK	
SL : +350~-1000		

□=Tolerance

6 Nominal capacitance (pF)

example	
0R5	0.5
010	1
100	10

※R=decimal point

7 Capacitance tolerance

C	±0.25pF
D	±0.5pF
F	±1pF
J	±5%
K	±10%

8 Thickness (mm)

C	0.2
P, T	0.3
V	0.5
W	0.5

9 Special code

—	Standard Product
---	------------------

10 Packaging


F	φ178mm Taping (2mm pitch)
---	---------------------------

11 Internal code

△	Standard Product
---	------------------

△=Blank space

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	T		e	Standard quantity [pcs]	
						Paper tape	Embossed tape
□MK042 (01005)	0.4±0.02 (0.016±0.001)	0.2±0.02 (0.008±0.001)	0.2±0.02 (0.008±0.001)	C	0.1±0.03 (0.004±0.001)	20000	—
□MK063 (0201)	0.6±0.03 (0.024±0.001)	0.3±0.03 (0.012±0.001)	0.3±0.03 (0.012±0.001)	P, T	0.15±0.05 (0.006±0.002)	15000	—
□MK105 (0402)	1.0±0.05 (0.039±0.002)	0.5±0.05 (0.020±0.002)	0.5±0.05 (0.020±0.002)	W,V	0.25±0.10 (0.010±0.004)	10000	—

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Cap [pF]	Type	042			063			105					
	Temp.char.	C□	C□	U□	C□	U□	SL	R□	S□	T□			
	VDC	16V	50V	25V	50V								
	[pF : 3digits]												
0.5	0R5	C	P	T	W	W			W	W	W		
1	010												
1.5	1R5												
2	020												
3	030												
4	040												
5	050												
6	060												
7	070												
8	080												
9	090												
10	100							W					
12	120												
15	150												
18	180												
22	220												
27	270		T										
33	330												
39	390												
47	470				V								
56	560												
68	680												
82	820					V							
100	101												
120	121												
150	151												
180	181												
220	221												
270	271												
330	331												
390	391												
470	471												
560	561												
680	681												
820	821												
1000	102												

Note: Letters in the table indicate thickness.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

042TYPE

Class 1

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)	
16V	EMK042 CK0R5CC		RoHS	0.5	CK	410	R	±0.25pF	0.2±0.02 (0.008±0.001)	
	EMK042 CK010CC		RoHS	1		420				
	EMK042 CK1R5CC		RoHS	1.5		430				
	EMK042 CK020CC		RoHS	2		440				
	EMK042 CJ030CC		RoHS	3	CJ	460				±0.5pF
	EMK042 CH040CC		RoHS	4	CH	480				
	EMK042 CH050CC		RoHS	5		500				
	EMK042 CH060DC		RoHS	6		520				
	EMK042 CH070DC		RoHS	7		540				
	EMK042 CH080DC		RoHS	8		560				
	EMK042 CH090DC		RoHS	9		580				
	EMK042 CH100DC		RoHS	10		600				
	EMK042 CH120JC		RoHS	12		640		±5%		
	EMK042 CH150JC		RoHS	15		700				
	EMK042 CH180JC		RoHS	18		760				
	EMK042 CH220JC		RoHS	22		840				
	EMK042 CH270JC		RoHS	27		940				
	EMK042 CH330JC		RoHS	33		1000				
	EMK042 CH390JC		RoHS	39		1000				
	EMK042 CH470JC		RoHS	47		1000				
	EMK042 CH560JC		RoHS	56		1000				
	EMK042 CH680JC		RoHS	68		1000				
	EMK042 CH820JC		RoHS	82		1000				
	EMK042 CH101JC		RoHS	100	1000					

Note: "W" is used for the internal code.

Note: Please contact Taiyo Yuden sales channels about items (capacitance, tolerance, and temperature characteristics) other than listed above.

063TYPE

Class1 [C△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)	
50V	UMK063 CK0R5CP		RoHS	0.5	CK	410	R	±0.25pF	0.3±0.03 (0.012±0.001)	
	UMK063 CK010CP		RoHS	1		420				
	UMK063 CK1R5CP		RoHS	1.5		430				
	UMK063 CK020CP		RoHS	2		440				
	UMK063 CJ030CP		RoHS	3	CJ	460				±0.5pF
	UMK063 CH040CP		RoHS	4		480				
	UMK063 CH050CP		RoHS	5	CH	500		±5%		
	UMK063 CH060DP		RoHS	6		520				
	UMK063 CH070DP		RoHS	7		540				
	UMK063 CH080DT		RoHS	8		560				
	UMK063 CH090DT		RoHS	9		580				
	UMK063 CH100DT		RoHS	10		600				
	UMK063 CH120JT		RoHS	12		640				
	UMK063 CH150JT		RoHS	15		700				
	UMK063 CH180JT		RoHS	18		760				
	UMK063 CH220JT		RoHS	22		840				
	UMK063 CH270JT		RoHS	27		940				
	UMK063 CH330JT		RoHS	33		1000				
	UMK063 CH390JT		RoHS	39		1000				
	UMK063 CH470JT		RoHS	47		1000				
	UMK063 CH560JT		RoHS	56		1000				
	UMK063 CH680JT		RoHS	68		1000				
	UMK063 CH820JT		RoHS	82		1000				
	UMK063 CH101JT		RoHS	100		1000				

Note: "G" is used for the special code when the capacitance is less than 8pF.

Note: Please contact Taiyo Yuden sales channels about items (capacitance, tolerance, and temperature characteristics) other than listed above.

Class1 [U△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)	
25V	TMK063 UK0R5CT		RoHS	0.5	UK	410	R	±0.25pF	0.3±0.03 (0.012±0.001)	
	TMK063 UK010CT		RoHS	1		420				
	TMK063 UK1R5CT		RoHS	1.5		430				
	TMK063 UK020CT		RoHS	2		440				
	TMK063 UK030CT		RoHS	3		460				
	TMK063 UJ040CT		RoHS	4		480				
	TMK063 UJ050CT		RoHS	5	UJ	500		±0.5pF		
	TMK063 UJ060DT		RoHS	6		520				
	TMK063 UJ070DT		RoHS	7		540				
	TMK063 UJ080DT		RoHS	8		560				
	TMK063 UJ090DT		RoHS	9		580				
	TMK063 UJ100DT		RoHS	10		600				
	TMK063 UJ120JT		RoHS	12		640				±5%
	TMK063 UJ150JT		RoHS	15		700				

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

105TYPE

Class1 [C△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 CK0R5CW		RoHS	0.5	CK	410	R	±0.25pF	0.5±0.05 (0.020±0.002)
	UMK105 CK010CW		RoHS	1		420			
	UMK105 CK1R5CW		RoHS	1.5		430			
	UMK105 CK020CW		RoHS	2		440			
	UMK105 CJ030CW		RoHS	3	CJ	460			
	UMK105 CH040CW		RoHS	4	480				
	UMK105 CH050CW		RoHS	5	500				
	UMK105 CH060DW		RoHS	6	520				
	UMK105 CH070DW		RoHS	7	540				
	UMK105 CH080DV		RoHS	8	560	±5%			
	UMK105 CH090DV		RoHS	9	580				
	UMK105 CH100DV		RoHS	10	600				
	UMK105 CH120JV		RoHS	12	640				
	UMK105 CH150JV		RoHS	15	700				
	UMK105 CH180JV		RoHS	18	760				
	UMK105 CH220JV		RoHS	22	840				
	UMK105 CH270JV		RoHS	27	940				
	UMK105 CH330JV		RoHS	33	1000				
	UMK105 CH390JV		RoHS	39	1000				
	UMK105 CH470JV		RoHS	47	1000				
	UMK105 CH560JV		RoHS	56	1000				
	UMK105 CH680JV		RoHS	68	1000				
	UMK105 CH820JV		RoHS	82	1000				
	UMK105 CH101JV		RoHS	100	1000				
	UMK105 CH121JV		RoHS	120	1000				
	UMK105 CH151JV		RoHS	150	1000				
	UMK105 CH181JV		RoHS	180	1000				
	UMK105 CH221JV		RoHS	220	1000				
	UMK105 CH271JV		RoHS	270	1000				
	UMK105 CH331JV		RoHS	330	1000				

Note: Please contact Taiyo Yuden sales channels about items (capacitance, tolerance, and characteristics) other than listed above.

Class1 [U△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 UK0R5CW		RoHS	0.5	UK	410	R	±0.25pF	0.5±0.05 (0.020±0.002)
	UMK105 UK010CW		RoHS	1		420			
	UMK105 UK1R5CW		RoHS	1.5		430			
	UMK105 UK020CW		RoHS	2		440			
	UMK105 UK030CW		RoHS	3		460			
	UMK105 UJ040CW		RoHS	4	UJ	480		±0.5pF	
	UMK105 UJ050CW		RoHS	5		500			
	UMK105 UJ060DW		RoHS	6		520			
	UMK105 UJ070DW		RoHS	7		540			
	UMK105 UJ080DW		RoHS	8		560			
	UMK105 UJ090DW		RoHS	9		580			
	UMK105 UJ100DW		RoHS	10		600		±5%	
	UMK105 UJ120JW		RoHS	12		640			
	UMK105 UJ150JW		RoHS	15		700			
	UMK105 UJ180JW		RoHS	18		760			
	UMK105 UJ220JV		RoHS	22		840			
	UMK105 UJ270JV		RoHS	27		940			
	UMK105 UJ330JV		RoHS	33		1000			
	UMK105 UJ390JV		RoHS	39		1000			
	UMK105 UJ470JV		RoHS	47		1000			
	UMK105 UJ560JV		RoHS	56		1000			
	UMK105 UJ680JV		RoHS	68		1000			
	UMK105 UJ820JV		RoHS	82		1000			
	UMK105 UJ101JV		RoHS	100		1000			
	UMK105 UJ121JV		RoHS	120		1000			
	UMK105 UJ151JV		RoHS	150		1000			
	UMK105 UJ181JV		RoHS	180		1000			
	UMK105 UJ221JV		RoHS	220		1000			
	UMK105 UJ271JV		RoHS	270		1000			
	UMK105 UJ331JV		RoHS	330		1000			

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

Class1 [SL characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 SL121JV		RoHS	120	SL	1000	R	±5%	0.5±0.05 (0.020±0.002)
	UMK105 SL151JV		RoHS	150		1000			
	UMK105 SL181JV		RoHS	180		1000			
	UMK105 SL221JV		RoHS	220		1000			
	UMK105 SL271JV		RoHS	270		1000			
	UMK105 SL331JV		RoHS	330		1000			

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

Class1 [RH characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 RH5R6JW		RoHS	5.6	RH	512	R	±5%	0.5±0.05 (0.020±0.002)
	UMK105 RH6R8JW		RoHS	6.8		536			
	UMK105 RH8R2JW		RoHS	8.2		564			
	UMK105 RH100JW		RoHS	10		600			
	UMK105 RH120JW		RoHS	12		640			
	UMK105 RH150JW		RoHS	15		700			
	UMK105 RH180JW		RoHS	18		760			
	UMK105 RH200JW		RoHS	20		800			

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

Class1 [S△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 SK0R5BW		RoHS	0.5	SK	410	R	±0.1pF	0.5±0.05 (0.020±0.002)
	UMK105 SK010BW		RoHS	1		420			
	UMK105 SK1R2BW		RoHS	1.2		424			
	UMK105 SK1R5BW		RoHS	1.5		430			
	UMK105 SK1R8BW		RoHS	1.8		436			
	UMK105 SK2R2JW		RoHS	2.2		444			
	UMK105 SK2R7JW		RoHS	2.7	SJ	454		±5%	
	UMK105 SJ3R3JW		RoHS	3.3		466			
	UMK105 SJ3R9JW		RoHS	3.9		478			
	UMK105 SH4R7JW		RoHS	4.7		494			
	UMK105 SH5R6JW		RoHS	5.6	SH	512			
	UMK105 SH6R8JW		RoHS	6.8		536			
	UMK105 SH8R2JW		RoHS	8.2		564			
	UMK105 SH100JW		RoHS	10		600			
	UMK105 SH120JW		RoHS	12		640			
	UMK105 SH150JW		RoHS	15		700			
	UMK105 SH180JW		RoHS	18		760			
	UMK105 SH200JW		RoHS	20		800			

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

Class1 [T△ characteristic]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics (EIA)	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 TK0R5BW		RoHS	0.5	TK	410	R	±0.1pF	0.5±0.05 (0.020±0.002)
	UMK105 TK010BW		RoHS	1		420			
	UMK105 TK1R2BW		RoHS	1.2		424			
	UMK105 TK1R5BW		RoHS	1.5		430			
	UMK105 TK1R8BW		RoHS	1.8		436			
	UMK105 TK2R2JW		RoHS	2.2		444			
	UMK105 TK2R7JW		RoHS	2.7		454			
	UMK105 TK3R3JW		RoHS	3.3		466			
	UMK105 TK3R9JW		RoHS	3.9		478			
	UMK105 TJ4R7JW		RoHS	4.7	TJ	494		±5%	
	UMK105 TJ5R6JW		RoHS	5.6		512			
	UMK105 TJ6R8JW		RoHS	6.8		536			
	UMK105 TJ8R2JW		RoHS	8.2		564			
	UMK105 TJ100JW		RoHS	10		600			
	UMK105 TJ120JW		RoHS	12		640			
	UMK105 TJ150JW		RoHS	15		700			
	UMK105 TJ180JW		RoHS	18		760			
	UMK105 TJ200JW		RoHS	20		800			

Note: Please contact Taiyo Yuden sales channels about items (capacitance and tolerance) other than listed above.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

STANDARD MULTILAYER CERAMIC CAPACITORS (CLASS2 :HIGH DIELECTRIC CONSTANT TYPE)



REFLOW

FEATURES

- Improved higher density mounting.
- Monolithic structure provides higher reliability.
- A wide range of capacitance values available in standard case sizes.


APPLICATIONS

- General electronic equipment
- Communication equipment
(cellular phone, wireless applications, etc.)

ORDERING CODE

L	M	K	1	0	5	B	J	1	0	4	K	V	—	F	△	
1	2	3	4	5	6	7	8	9	10	11						
1 Rated voltage [VDC]		3 End termination		5 Temperature characteristics code		6 Nominal capacitance [pF]		7 Capacitance tolerance		9 Special code		10 Packaging				
A	4	K	Plated	BJ		B	example	102	1000	K	±10%	—	Standard Product			
J	6.3			B7		X5R	223	22000	M	±20%	F					
L	10			△F		F			Z	+80 -20 %	φ178mm Taping (2mm pitch)					
E	16					Y5V										
T	25															
G	35															
U	50															
2 Series name								8 Thickness [mm]				11 Internal code				
M	Multilayer ceramic capacitor							C		0.2			△			
								P		0.3			Standard Product			
								V		0.5			△=Blank space			

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	T		e	Standard quantity [pcs]	
						Paper tape	Embossed tape
□MK042 (01005)	0.4±0.02 (0.016±0.001)	0.2±0.02 (0.008±0.001)	0.2±0.02 (0.008±0.001)	C	0.1±0.03 (0.004±0.001)	20000	—
□MK063 (0201)	0.6±0.03 (0.024±0.001)	0.3±0.03 (0.012±0.001)	0.3±0.03 (0.012±0.001)	P	0.15±0.05 (0.006±0.002)	15000	—
□MK105 (0402)	1.0±0.05*1 (0.039±0.002)	0.5±0.05*1 (0.020±0.002)	0.5±0.05*1 (0.020±0.002)	V	0.25±0.10 (0.010±0.004)	10000	—

Note:*1. Including dimension tolerance±0.1mm

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Cap [pF]	Type	042			063			105												F/Y5V			
		Temp.char.			Temp.char.			Temp.char.												Temp.char.			
		X7R	B/X5R	X5R	X7R	B/X5R	X5R	X7R	B/X5R	X5R	X7R	B/X5R	X5R	X7R	B/X5R	X5R	X7R	B/X5R	X5R	50V	25V	16V	10V
100	101																						
150	151																						
220	221																						
330	331	C	C		P																		
470	471																						
680	681																						
1000	102																						
1500	152																						
2200	222																						
3300	332																						
4700	472																						
6800	682																						
10000	103																						
15000	153																						
22000	223																						
33000	333																						
47000	473																						
68000	683																						
100000	104																						
220000	224																						
330000	334																						
470000	474																						
1000000	105																						
2200000	225																						
3300000	335																						
4700000	475																						

Note : Letters in the table indicate thickness.

Temp.char.Code	Temperature characteristics					Capacitance tolerance [%]
	Applicable standard		Temperature range [°C]	Ref. Temp. [°C]	Capacitance change [%]	
B/BJ	JIS	B	-25~+85	20	±10	±10 (K) ±20 (M)
	EIA	X5R	-55~+85	25	±15	
B7	EIA	X7R	-55~+125	25	±15	
F	JIS	F	-25~+85	20	+30/-80	+80 (Z)
	EIA	Y5V	-30~+85	25	+22/-82	-20

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

042TYPE(01005 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)							
10V	LMK042 BJ101□C		RoHS	100	B/X5R ⁺²	5	R	±10% ±20%	0.2±0.02 (0.008±0.001)							
	LMK042 BJ151□C		RoHS	150												
	LMK042 BJ221□C		RoHS	220												
	LMK042 BJ331□C		RoHS	330												
	LMK042 BJ471□C		RoHS	470												
	LMK042 BJ681□C		RoHS	680												
	LMK042 BJ102□C		RoHS	1000	X5R	10										
	LMK042 BJ152□C ⁺¹		RoHS	1500												
	LMK042 BJ222□C ⁺¹		RoHS	2200												
	LMK042 BJ332□C ⁺¹		RoHS	3300												
	LMK042 BJ472□C ⁺¹		RoHS	4700												
LMK042 BJ682□C ⁺¹		RoHS	6800	B/X5R ⁺²												
LMK042 BJ103□C ⁺¹		RoHS	10000													
6.3V	JMK042 BJ152□C ⁺¹		RoHS							1500						
	JMK042 BJ222□C ⁺¹		RoHS							2200						
	JMK042 BJ332□C ⁺¹		RoHS							3300						
	JMK042 BJ472□C ⁺¹		RoHS							4700						
	JMK042 BJ682□C ⁺¹		RoHS							6800						
	JMK042 BJ103□C ⁺¹		RoHS							10000						

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R/X7S for some items according to the individual specification.

Note: "W" is used for the internal code.

[Temp.char. B7 : X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
10V	LMK042 B7 101 □ C		RoHS	100	X7R	5	R	±10% ±20%	0.2±0.02 (0.008±0.001)
	LMK042 B7 151 □ C		RoHS	150					
	LMK042 B7 221 □ C		RoHS	220					
	LMK042 B7 331 □ C		RoHS	330					
	LMK042 B7 471 □ C		RoHS	470					
	LMK042 B7 681 □ C		RoHS	680					
	LMK042 B7 102 □ C		RoHS	1000					

□ Please specify the capacitance tolerance code.

Note: "W" is used for the internal code.

063TYPE(0201 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)												
25V	TMK063 BJ101□P		RoHS	100	B/X5R ^{*2}	3.5	R	±10% ±20%	0.3±0.03 (0.012±0.001)												
	TMK063 BJ151□P		RoHS	150																	
	TMK063 BJ221□P		RoHS	220																	
	TMK063 BJ331□P		RoHS	330																	
	TMK063 BJ471□P		RoHS	470																	
	TMK063 BJ681□P		RoHS	680	B/X5R	5															
	TMK063 BJ102□P		RoHS	1000																	
	TMK063 BJ152□P		RoHS	1500																	
	TMK063 BJ222□P		RoHS	2200																	
	TMK063 BJ332□P		RoHS	3300																	
TMK063 BJ472□P		RoHS	4700	B/X5R ^{*2}																	
TMK063 BJ682□P		RoHS	6800																		
TMK063 BJ103□P		RoHS	10000																		
16V	EMK063 BJ152□P		RoHS							1500	B/X5R ^{*2}	7.5		±10% ±20%							
	EMK063 BJ222□P		RoHS							2200											
	EMK063 BJ332□P		RoHS	3300																	
	EMK063 BJ472□P		RoHS	4700																	
	EMK063 BJ682□P		RoHS	6800																	
EMK063 BJ103□P		RoHS	10000	B/X5R																	
10V	LMK063 BJ223□P ^{*1}		RoHS							22000	X5R	10				±20%					
	LMK063 BJ333□P ^{*1}		RoHS							33000											
	LMK063 BJ473□P ^{*1}		RoHS							47000											
	LMK063 BJ683□P ^{*1}		RoHS							68000											
	LMK063 BJ104□P ^{*1}		RoHS	100000																	
LMK063 BJ224MP ^{*1}		RoHS	220000	B/X5R																	
6.3V	JMK063 BJ223□P ^{*1}		RoHS							22000	X5R	7.5		±10% ±20%							
	JMK063 BJ333□P ^{*1}		RoHS							33000											
	JMK063 BJ473□P ^{*1}		RoHS							47000											
	JMK063 BJ683□P ^{*1}		RoHS							68000											
	JMK063 BJ104□P ^{*1}		RoHS	100000																	
JMK063 BJ224MP ^{*1}		RoHS	220000	10																	
											±20%										

To next page

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
4V	AMK063 BJ224MP*1		RoHS	220000	X5R	10	R	±20%	0.3±0.03 (0.012±0.001)
	AMK063 BJ334MP*1,*3		RoHS	330000					
	AMK063 BJ474MP*1,*3		RoHS	470000					

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

*3 The exchange of individual specification is necessary depending on the application and circuit condition. Please contact Taiyo Yuden sales channels.

[Temp.char. B7 : X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
25V	TMK063 B7 101□P		RoHS	100	X7R	3.5	R	±10% ±20%	0.3±0.03 (0.012±0.001)
	TMK063 B7 151□P		RoHS	150					
	TMK063 B7 221□P		RoHS	220					
	TMK063 B7 331□P		RoHS	330					
	TMK063 B7 471□P		RoHS	470					
	TMK063 B7 681□P		RoHS	680					
16V	TMK063 B7 102□P		RoHS	1000		5			
	EMK063 B7 152□P		RoHS	1500					
	EMK063 B7 222□P		RoHS	2200					
	EMK063 B7 332□P		RoHS	3300					
	EMK063 B7 472□P		RoHS	4700					
	EMK063 B7 682□P		RoHS	6800					
	EMK063 B7 103□P		RoHS	10000					

□ Please specify the capacitance tolerance code.

● 105TYPE(0402 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (pF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
50V	UMK105 BJ 221□V		RoHS	220	B/X5R*2	2.5	R	±10% ±20%	0.5±0.05 (0.02±0.002)
	UMK105 BJ 331□V		RoHS	330					
	UMK105 BJ 471□V		RoHS	470					
	UMK105 BJ 681□V		RoHS	680					
	UMK105 BJ 102□V		RoHS	1000					
	UMK105 BJ 152□V		RoHS	1500					
	UMK105 BJ 222□V		RoHS	2200					
	UMK105 BJ 332□V		RoHS	3300					
	UMK105 BJ 472□V		RoHS	4700					
	UMK105 BJ 682□V*1		RoHS	6800					
	UMK105 BJ 103□V		RoHS	10000	3.5				
35V	GMK105 BJ 104□V*1		RoHS	100000	B/X5R	5			
25V	TMK105 BJ 153□V		RoHS	15000	B/X5R*2	3.5			
	TMK105 BJ 223□V		RoHS	22000					
	TMK105 BJ 333□V*1		RoHS	33000					
	TMK105 BJ 473□V*1		RoHS	47000					
		TMK105 BJ 104□V*1		RoHS	100000	B/X5R			
16V	EMK105 BJ 153□V		RoHS	15000	B/X5R*2	3.5			
	EMK105 BJ 223□V		RoHS	22000					
	EMK105 BJ 333□V		RoHS	33000					
	EMK105 BJ 473□V		RoHS	47000					
	EMK105 BJ 683□V		RoHS	68000	B/X5R	5			
	EMK105 BJ 104□V*1		RoHS	100000	B/X5R*2				
	EMK105 BJ 224□V*1		RoHS	220000	B/X5R				
	EMK105 BJ 105□V*1		RoHS	1000000	X5R				
10V	LMK105 BJ 104□V		RoHS	100000	B/X5R	5			
	LMK105 BJ 224□V*1		RoHS	220000					
	LMK105 BJ 474□V*1		RoHS	470000	X5R	10			
	LMK105 BJ 105□V*1		RoHS	1000000					
6.3V	JMK105 BJ 224□V*1		RoHS	220000	X5R	10			
	JMK105 BJ 474□V*1		RoHS	470000					
	JMK105 BJ 105□V*1		RoHS	1000000					
	JMK105 BJ 225MV*1		RoHS	2200000					
4V	AMK105 BJ 335MV*1,*3		RoHS	3300000	X5R	10		±20%	0.5±0.1 (0.02±0.004)
	AMK105 BJ 475MV*1		RoHS	4700000					

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

*3 The exchange of individual specification is necessary depending on the application and circuit condition. Please contact Taiyo Yuden sales channels.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	UMK105 B7 221□V		RoHS	220	X7R	2.5	R	±10% ±20%	0.5±0.05 (0.02±0.002)
	UMK105 B7 331□V		RoHS	330					
	UMK105 B7 471□V		RoHS	470					
	UMK105 B7 681□V		RoHS	680					
	UMK105 B7 102□V		RoHS	1000					
	UMK105 B7 152□V		RoHS	1500					
	UMK105 B7 222□V		RoHS	2200					
	UMK105 B7 332□V		RoHS	3300					
	UMK105 B7 472□V* ¹		RoHS	4700					
	UMK105 B7 682□V* ¹		RoHS	6800					
UMK105 B7 103□V* ¹		RoHS	10000						
25V	TMK105 B7 152□V		RoHS	1500		2.5			
	TMK105 B7 222□V		RoHS	2200					
	TMK105 B7 332□V		RoHS	3300					
	TMK105 B7 472□V		RoHS	4700					
	TMK105 B7 682□V		RoHS	6800					
	TMK105 B7 103□V		RoHS	10000					
	16V	EMK105 B7 223□V		RoHS					
EMK105 B7 473□V			RoHS	47000					
EMK105 B7 104□V* ¹			RoHS	100000		5			
10V	LMK105 B7 223□V		RoHS	22000		3.5			
	LMK105 B7 473□V		RoHS	47000					
	LMK105 B7 104□V* ¹		RoHS	100000					
6.3V	JMK105 B7 224□V* ¹		RoHS	220000					

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

[Temp.char. F:Y5V]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	UMK105 F103ZV		RoHS	10000	F/Y5V	5	R	+80% -20%	0.5±0.05 (0.02 ± 0.002)
25V	TMK105 F223ZV		RoHS	22000		7			
16V	EMK105 F473ZV		RoHS	47000		9			
	EMK105 F104ZV		RoHS	100000		11			
10V	LMK105 F224ZV		RoHS	220000		12.5			
6.3V	JMK105 F474ZV		RoHS	470000		20			
	JMK105 F105ZV* ¹		RoHS	1000000					

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

MULTILAYER CERAMIC CAPACITORS FOR HIGH FREQUENCY APPLICATIONS(1GHz+)



REFLOW

FEATURES

- Q value in the high frequency range (1 GHz+) is superior compared to other types of multilayer capacitors.
- The 1005(0402) case size is designed for high density mounting and weight reduction in various applications.


APPLICATIONS

- Suitable for those high frequency applications in which a capacitor with both a high Q-value and small size is required such as portable communications and other wireless applications. VCO, TCXO etc.
- Adjustment of characteristics in high frequency circuit

ORDERING CODE

U	V	K	1	0	5	R	H	4	R	3	J	W	—	F
1	2	3	4	5	6	7	8	9	10					
1 Rated voltage [VDC]		3 End termination		5 Temperature characteristics [ppm/°C]		6 Nominal capacitance [pF]		7 Capacitance tolerance		9 Special code		10 Packaging		
E	16	K	Plated	CH	0±60	example	020	B	±0.1pF	—	Standard Product	F	φ178mm Taping (2mm pitch)	
U	50			RH	-220±60	4R3	4.3	J	±5%					
2 Series name		4 Dimensions (EIA) (L×W) [mm]		8 Thickness [mm]		※R=Decimal point								
V	Multilayer ceramic capacitor for high frequency	105(0402)	1.0×0.5	W	0.5									

EXTERNAL DIMENSIONS/STANDARD QUANTITY




Type(EIA)	L	W	T	e	Standard quantity [pcs]	
					Paper tape	Embossed tape
□VK105 (0402)	1.0±0.05 (0.039±0.002)	0.5±0.05 (0.020±0.002)	0.5±0.05 (0.020±0.002)	0.25±0.1 (0.010±0.004)	10000	—

Unit : mm (inch)

SPECIFICATIONS

Temperature Characteristics	Operating Temperature range	Temperature Coefficient range [ppm/°C]	Capacitance Tolerance
CH	-55~+125°C	0±60	±0.1pF (~2.0pF)
RH		-220±60	±5% (2.2pF~)

Capacitance vs Q value (Typical for CH characteristic)



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

Rated Voltage (DC)	Ordering code		EHS (Environmental Hazardous Substances)	Temperature characteristics		Capacitance [pF]	Capacitance tolerance	Q (at 1GHz) (min.)	Thickness [mm]	Typical Q
				CH	RH					
E: 16V U: 50V	☐ VK105 CH0R3BW		RoHS	●		0.3	±0.1pF	300	0.5±0.05	1200
	☐ VK105 CH0R4BW		RoHS	●		0.4		300		1200
	☐ VK105 CH0R5BW		RoHS	●		0.5		300		1200
	☐ VK105 CH0R6BW		RoHS	●		0.6		300		1100
	☐ VK105 CH0R7BW		RoHS	●		0.7		300		1100
	☐ VK105 CH0R8BW		RoHS	●		0.8		300		1000
	☐ VK105 CH0R9BW		RoHS	●		0.9		300		950
	☐ VK105 CH010BW		RoHS	●		1.0		300		950
	☐ VK105 CH1R1BW		RoHS	●		1.1		280		930
	☐ VK105 CH1R2BW		RoHS	●		1.2		270		850
	☐ VK105 CH1R3BW		RoHS	●		1.3		260		740
	☐ VK105 CH1R5BW		RoHS	●		1.5		240		710
	☐ VK105 CH1R6BW		RoHS	●		1.6		230		670
	☐ VK105 CH1R8BW		RoHS	●		1.8		210		650
	☐ VK105 CH020BW		RoHS	●		2.0	±5%	190		610
	☐ VK105 CH2R2JW		RoHS	●		2.2		180		530
	☐ VK105 CH2R4JW		RoHS	●		2.4		170		510
	☐ VK105 CH2R7JW		RoHS	●		2.7		150		460
	☐ VK105 CH030JW		RoHS	●		3.0		130		390
	☐ VK105 CH3R3JW		RoHS	●		3.3		120		370
	☐ VK105 CH3R6JW		RoHS	●		3.6		110		360
	☐ VK105 CH3R9JW		RoHS	●		3.9		99		360
	☐ VK105 CH4R3JW		RoHS	●		4.3		84		360
	☐ VK105 CH4R7JW		RoHS	●		4.7		84		340
	☐ VK105 CH5R1JW		RoHS	●		5.1		84		320
	☐ VK105 RH0R5BW		RoHS		●	0.5	±0.1pF	300		1100
	☐ VK105 RH0R6BW		RoHS		●	0.6		300		1000
	☐ VK105 RH0R7BW		RoHS		●	0.7		300		1000
	☐ VK105 RH0R8BW		RoHS		●	0.8		300		970
	☐ VK105 RH0R9BW		RoHS		●	0.9		300		950
	☐ VK105 RH010BW		RoHS		●	1.0		300		900
	☐ VK105 RH1R1BW		RoHS		●	1.1		280		900
	☐ VK105 RH1R2BW		RoHS		●	1.2		270		740
	☐ VK105 RH1R3BW		RoHS		●	1.3		260		700
	☐ VK105 RH1R5BW		RoHS		●	1.5		240		680
	☐ VK105 RH1R6BW		RoHS		●	1.6		230		640
	☐ VK105 RH1R8BW		RoHS		●	1.8		210		620
	☐ VK105 RH020BW		RoHS		●	2.0	±5%	190		570
	☐ VK105 RH2R2JW		RoHS		●	2.2		180		480
	☐ VK105 RH2R4JW		RoHS		●	2.4		170		470
	☐ VK105 RH2R7JW		RoHS		●	2.7		150		420
	☐ VK105 RH030JW		RoHS		●	3.0		130		360
	☐ VK105 RH3R3JW		RoHS		●	3.3		120		350
	☐ VK105 RH3R6JW		RoHS		●	3.6		110		340
	☐ VK105 RH3R9JW		RoHS		●	3.9		99		340
	☐ VK105 RH4R3JW		RoHS		●	4.3		84		340
	☐ VK105 RH4R7JW		RoHS		●	4.7		84		320
	☐ VK105 RH5R1JW		RoHS		●	5.1		84		310

☐Please specify the Rated Voltage code.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

SUPER LOW DISTORTION MULTILAYER CERAMIC CAPACITORS(CFCAP™)



REFLOW

FEATURES

- Newly developed dielectric material and the use of nickel for internal electrodes provide superior temperature characteristics with high capacitance, small case size and low cost.
- Low distortion and low shock noise make these capacitors appropriate for use in analog or digital mobile devices.
- Superior heat-resistance, high breakdown voltage, and mechanical strength make these capacitors appropriate for replacing film capacitors.

APPLICATIONS

- Signal line for AV products
- Analog signal coupling applications
- PLL circuit of mobile phones
- Good temperature characteristics for time constant circuits, oscillation circuits and filters

ORDERING CODE

T

M

K

3

1

6

S

D

1

0

4

K

L

—

T

△

1

Rated voltage [VDC]

U50

G35

T25

E16

L10

J6.3

2

Series name

M

Multilayer ceramic capacitor

3

End termination

K

Plated

4

Dimensions (EIA) (L×W) (mm)

105 (0402)1.0×0.5

107 (0603)1.6×0.8

212 (0805)2.0×1.25

316 (1206)3.2×1.6

5

Series symbol

SD

Standard

6

Nominal capacitance (μF)

example

2230.022

1040.1

7

Capacitance tolerance

K

±10%

8

Thickness (mm)

P0.3

V0.5

A0.8

D0.85

F1.15

G1.25

L1.6

9

Special code

—

Standard Product

10

Packaging

T

φ178mm Taping (4mm pitch)
107, 212, 316 Type

F

φ178mm Taping (2mm pitch)
105 Type

11

Internal code


△

Standard Product

△=Blank space

EXTERNAL DIMENSIONS/STANDARD QUANTITY

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	T		e	Standard quantity [pcs]	
						Paper tape	Embossed tape
□MK105 (0402)	1.0±0.05 (0.039±0.002)	0.5±0.05 (0.020±0.002)	0.3±0.03 (0.012±0.001)	P	0.25±0.10 (0.010±0.004)	10000	—
			0.5±0.05 (0.020±0.002)	V			
□MK107 (0603)	1.6±0.10 (0.063±0.004)	0.8±0.10 (0.031±0.004)	0.8±0.10 (0.031±0.004)	A	0.35±0.25 (0.014±0.010)	4000	—
□MK212 (0805)	2.0±0.10 (0.079±0.004)	1.25±0.10 (0.049±0.004)	0.85±0.10 (0.033±0.004)	D	0.5±0.25 (0.020±0.010)	4000	—
			1.25±0.10 (0.049±0.004)	G		—	3000
□MK316 (1206)	3.2±0.15 (0.126±0.006)	1.6±0.15 (0.063±0.006)	1.15±0.10 (0.045±0.004)	F	0.5 ^{+0.35 -0.25} (0.020 ^{+0.014 -0.010})	—	3000
			1.6±0.20 (0.063±0.008)	L			2000

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Cap [μF]	Type	105					107				212				316	
	Temp.Char	SD					SD				SD				SD	
	VDC	50V	25V	16V	10V	6.3V	50V	25V	16V	10V	50V	35V	16V	10V	35V	25V
0.00039	391	V														
0.00047	471	V														
0.00056	561	V														
0.00068	681		V													
0.00082	821		V													
0.001	102		V				A									
0.0012	122		V				A									
0.0015	152			V	P		A									
0.0018	182			V			A									
0.0022	222			V			A									
0.0027	272			V		P	A									
0.0033	332				V		A									
0.0039	392				V			A			D					
0.0047	472				V			A			D					
0.0056	562								A		D					
0.0068	682										D					
0.0082	822										D					
0.01	103										D					
0.012	123											D				
0.015	153											D				
0.018	183											G				
0.022	223											G				
0.027	273											G				
0.033	333												D		F	
0.039	393														F	
0.047	473															F
0.056	563															F
0.068	683															F
0.082	823													G		L
0.1	104													G		L

※Letters in the table indicate thickness.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

105TYPE (0402 case size)

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	UMK105 SD391KV		RoHS	0.00039	Standard type	0.1	R	±10%*	0.5±0.05 (0.020±0.002)
	UMK105 SD471KV		RoHS	0.00047					
	UMK105 SD561KV		RoHS	0.00056					
25V	TMK105 SD681KV		RoHS	0.00068					
	TMK105 SD821KV		RoHS	0.00082					
	TMK105 SD102KV		RoHS	0.0010					
	TMK105 SD122KV		RoHS	0.0012					
16V	EMK105 SD152KV		RoHS	0.0015					
	EMK105 SD182KV		RoHS	0.0018					
	EMK105 SD222KV		RoHS	0.0022					
	EMK105 SD272KV		RoHS	0.0027					
10V	LMK105 SD152KP		RoHS	0.0015					0.3±0.03 (0.012±0.001)
	LMK105 SD332KV		RoHS	0.0033					0.5±0.05 (0.020±0.002)
	LMK105 SD392KV		RoHS	0.0039					
	LMK105 SD472KV		RoHS	0.0047					
6.3V	JMK105 SD272KP		RoHS	0.0027					0.3±0.03 (0.012±0.001)

*: Capacitance tolerance J (±5%) is also available. Please contact Taiyo Yuden sales channels.

107TYPE (0603 case size)

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	UMK107 SD102KA		RoHS	0.0010	Standard type	0.1	R	±10%*	0.8±0.1 (0.031±0.004)
	UMK107 SD122KA		RoHS	0.0012					
	UMK107 SD152KA		RoHS	0.0015					
	UMK107 SD182KA		RoHS	0.0018					
	UMK107 SD222KA		RoHS	0.0022					
	UMK107 SD272KA		RoHS	0.0027					
25V	UMK107 SD332KA		RoHS	0.0033					
	TMK107 SD392KA		RoHS	0.0039					
	TMK107 SD472KA		RoHS	0.0047					
16V	EMK107 SD562KA		RoHS	0.0056					
	EMK107 SD682KA		RoHS	0.0068					
	EMK107 SD822KA		RoHS	0.0082					
	EMK107 SD103KA		RoHS	0.010					
10V	LMK107 SD123KA		RoHS	0.012					
	LMK107 SD153KA		RoHS	0.015					
	LMK107 SD183KA		RoHS	0.018					
	LMK107 SD223KA		RoHS	0.022					

*: Capacitance tolerance J (±5%) is also available. Please contact Taiyo Yuden sales channels.

212TYPE (0805 case size)

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	UMK212 SD392KD		RoHS	0.0039	Standard type	0.1	R	±10%*	0.85±0.1 (0.033±0.004)
	UMK212 SD472KD		RoHS	0.0047					
	UMK212 SD562KD		RoHS	0.0056					
	UMK212 SD682KD		RoHS	0.0068					
	UMK212 SD822KD		RoHS	0.0082					
	UMK212 SD103KD		RoHS	0.01					
35V	GМК212 SD123KD		RoHS	0.012					1.25±0.1 (0.049±0.004)
	GМК212 SD153KD		RoHS	0.015					
	GМК212 SD183KG		RoHS	0.018					
	GМК212 SD223KG		RoHS	0.022					
	GМК212 SD273KG		RoHS	0.027					
16V	EMK212 SD333KD		RoHS	0.033					0.85±0.1 (0.033±0.004)
10V	LMK212 SD473KD		RoHS	0.047					1.25±0.1 (0.049±0.004)
	LMK212 SD683KG		RoHS	0.068					
	LMK212 SD823KG		RoHS	0.082					
	LMK212 SD104KG		RoHS	0.1					

*: Capacitance tolerance J (±5%) is also available. Please contact Taiyo Yuden sales channels.


316TYPE (1206 case size)

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
35V	GМК316 SD333KF		RoHS	0.033	Standard type	0.1	R	±10%*	1.15±0.1 (0.045±0.004)
	GМК316 SD393KF		RoHS	0.039					
	TMK316 SD473KF		RoHS	0.047					
25V	TMK316 SD563KF		RoHS	0.056					
	TMK316 SD683KF		RoHS	0.068					
	TMK316 SD823KL		RoHS	0.082					
	TMK316 SD104KL		RoHS	0.1					1.6±0.2 (0.063±0.008)

*: Capacitance tolerance J (±5%) is also available. Please contact Taiyo Yuden sales channels.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.



Capacitance-temperature characteristics



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

Multilayer Ceramic Capacitors and Medium-High Voltage Multilayer Ceramic Capacitors are noted separately.

Super Low Distortion Multilayer Ceramic Capacitors (CFCAP)

1. Operating Temperature Range												
Specified Value	−55 to +125°C											
2. Storage Temperature Range												
Specified Value	−55 to +125°C											
3. Rated Voltage												
Specified Value	6.3VDC, 10VDC, 16VDC, 25VDC, 35VDC, 50VDC											
4. Withstanding Voltage (Between terminals)												
Specified Value	No breakdown or damage											
[Test Methods and Remarks] Applied voltage: Rated voltage×3 Duration: 1 to 5 sec. Charge/discharge current: 50mA max.												
5. Insulation Resistance												
Specified Value	10000 MΩ or 500MΩ μF, whichever is smaller											
[Test Methods and Remarks] Applied voltage: Rated voltage Duration: 60±5 sec. Charge/discharge current: 50mA max.												
6. Capacitance (Tolerance)												
Specified Value	±10%											
[Test Methods and Remarks] Measuring frequency : 1kHz±10% Measuring voltage : 1±0.2Vrms Bias application: None												
7. Dissipation Factor												
Specified Value	0.1%max											
[Test Methods and Remarks] Measuring frequency : 1kHz±10% Measuring voltage : 1±0.2Vrms Bias application: None												
8. Deflection												
Specified Value	Appearance: No abnormality Capacitance change: ±5%											
[Test Methods and Remarks] Warp: 1mm Speed: 0.5mm/second Duration:10 seconds Test board: glass epoxy resin substrate Thickness: 1.6mm Capacitance measurement shall be conducted with the board bent.												
												
(Unit: mm)												
9. Adhesive Strength of Terminal Electrodes												
Specified Value	No terminal separation or its indication.											
[Test Methods and Remarks] Applied force: 5N Duration: 30 ±5 seconds												
												
10. Solderability												
Specified Value	At least 95% of terminal electrode is covered by new solder.											
[Test Methods and Remarks]												
	<table><tr><td></td><td>Solder type</td><td>Solder temperature</td><td>Duration</td></tr><tr><td>Eutectic solder</td><td>H60A or H63A</td><td>230±5°C</td><td rowspan="2">4±1 sec.</td></tr><tr><td>Lead-free solder</td><td>Sn—3.0Ag—0.5Cu</td><td>245±3°C</td></tr></table>		Solder type	Solder temperature	Duration	Eutectic solder	H60A or H63A	230±5°C	4±1 sec.	Lead-free solder	Sn—3.0Ag—0.5Cu	245±3°C
	Solder type	Solder temperature	Duration									
Eutectic solder	H60A or H63A	230±5°C	4±1 sec.									
Lead-free solder	Sn—3.0Ag—0.5Cu	245±3°C										
11. Resistance to Soldering												
Specified Value	Appearance: No abnormality Capacitance change: ±2.5% max. Dissipation factor : Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality											
[Test Methods and Remarks] Solder temp.: 270 ±5°C Duration: 3 ±0.5 sec. Preheating conditions : 80 to 100°C, 2 to 5 min. or 5 to 10 min. 150 to 200°C, 2 to 5 min. or 5 to 10 min. Recovery : 24±2hrs under the standard condition Note1												

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

1

Note1

1

MEDIUM-HIGH VOLTAGE MULTILAYER CERAMIC CAPACITORS



REFLOW

FEATURES

- The use of nickel as electrode material prevents migration and provides high reliability.
- Small case sizes with high rated voltage.


APPLICATIONS

- General telephone exchange
- Inverter
- Wireless and Telecommunication base
- For DC/DC Converter

ORDERING CODE

H	M	K	3	1	6	B	J	1	0	4	K	L	—	T	△
1	2	3	4	5	6	7	8	9	10	11					
1 Rated voltage (VDC)		3 End termination		4 Dimensions (EIA) L×W (mm)		5 Temperature characteristics code		7 Capacitance tolerance		9 Thickness (mm)		9 Special code		11 Internal code	
H 100 Q 250 S 630		K Plated		107 (0603) 1.6×0.8 212 (0805) 2.0×1.25 316 (1206) 3.2×1.6 325 (1210) 3.2×2.5 432 (1812) 4.5×3.2		BJ B B7 X5R C7 X7R X7S		K ±10% M ±20%		A 0.8 D 0.85 G 1.25 F 1.15 L 1.6 N 1.9 M 2.5		— Standard Product		△ Standard Product △=Blank space	
2 Series name		10 Packaging													
M Multilayer ceramic capacitor		T φ178mm Taping (4mm pitch)													

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	T		e	Standard quantity [pcs]	
						Paper tape	Embossed tape
□MK107 (0603)	1.6±0.10 (0.063±0.004)	0.8±0.10 (0.031±0.004)	0.8±0.10 (0.031±0.004)	A	0.35±0.25 (0.014±0.010)	4000	—
□MK212 (0805)	2.0±0.10 (0.079±0.004)	1.25±0.10 (0.049±0.004)	0.85±0.10 (0.033±0.004)	D	0.5±0.25 (0.020±0.010)	4000	—
			1.25±0.10 (0.049±0.004)	G		—	3000
□MK316 (1206)	3.2±0.15 (0.126±0.006)	1.6±0.15 (0.063±0.006)	1.15±0.10 (0.045±0.004)	F	0.5 ^{+0.35} _{-0.25} (0.020 ^{+0.014} _{-0.010})	—	3000
			1.6±0.20 (0.063±0.008)	L			2000
□MK325 (1210)	3.2±0.3 (0.126±0.012)	2.5±0.20 (0.098±0.008)	1.15±0.10 (0.045±0.004)	F	0.6±0.3 (0.024±0.012)	—	2000
			1.9±0.20 (0.075±0.008)	N			
□MK432 (1812)	4.5±0.4 (0.177±0.016)	3.2±0.30 (0.126±0.012)	2.5±0.20 (0.098±0.008)	M	0.9±0.6 (0.035±0.024)	—	500

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Cap [μF]	Type Temp. Char VDC	107			212			316			325			432		
		X7R	X7S	B/X5R	X7R	B/X5R		X7R	B/X5R		X7R	B/X5R		X7R	B/X5R	
		100V	100V	100V	100V	250V		100V	250V	630V	100V	250V	630V	100V	250V	630V
0.001	102	A		A		D				F						
0.0015	152	A		A		D				F						
0.0022	222	A		A		D				F						
0.0033	332	A		A		D				F						
0.0047	472	A		A		G				F						
0.0068	682	A		A		G				F						
0.01	103	A		A	G	G	G			F						
0.015	153	A		A	G	G	G			L						
0.022	223	A		A	G	G	G			L						
0.033	333	A		A	G	G	G			L						
0.047	473				G	G		L	L				N	N		M
0.068	683				G	G		L	L						M	M
0.1	104		A	A	G	G		L	L		F	N		F	N	M
0.15	154							L			N	N		N	N	
0.22	224				G		G	L			N	N		N	N	
0.33	334							L			N			N		M
0.47	474							L			N			N		M
0.68	684										N			N		M
1.0	105							L			N			N		M
1.5	155													M		M
2.2	225										N			N		M

※Letters in the table indicate thickness.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

AVAILABLE CAPACITANCE RANGE

Temp.char.Code	Temperature characteristics					Capacitance tolerance [%]
	Applicable standard		Temperature range [°C]	Ref. Temp. [°C]	Capacitance change [%]	
BJ	JIS	B	-25~+85	20	±10	±10 (K) ±20 (M)
	EIA	X5R	-55~+85	25	±15	
B7	EIA	X7R	-55~+125	25	±15	
C7	EIA	X7S	-55~+125	25	±22	

PART NUMBERS

107TYPE(0603 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
100V	HMK107 BJ102□A		RoHS	0.001	B/X5R*2	3.5	R	±10% ±20%	0.8±0.1 (0.031±0.0041)
	HMK107 BJ152□A		RoHS	0.0015					
	HMK107 BJ222□A		RoHS	0.0022					
	HMK107 BJ332□A		RoHS	0.0033					
	HMK107 BJ472□A		RoHS	0.0047					
	HMK107 BJ682□A		RoHS	0.0068					
	HMK107 BJ103□A		RoHS	0.01					
	HMK107 BJ153□A		RoHS	0.015					
	HMK107 BJ223□A		RoHS	0.022					
	HMK107 BJ333□A		RoHS	0.033					
	HMK107 BJ104□A		RoHS	0.1					

□ Please specify the capacitance tolerance code.

*2 : We may provide X7R/X7S for some items according to the individual specification.

[Temp.char. B7:X7R C7:X7S]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
100V	HMK107 B7 102□A		RoHS	0.001	X7R	3.5	R	±10% ±20%	0.8±0.1 (0.031±0.0041)
	HMK107 B7 152□A		RoHS	0.0015					
	HMK107 B7 222□A		RoHS	0.0022					
	HMK107 B7 332□A		RoHS	0.0033					
	HMK107 B7 472□A		RoHS	0.0047					
	HMK107 B7 682□A		RoHS	0.0068					
	HMK107 B7 103□A		RoHS	0.01					
	HMK107 B7 153□A		RoHS	0.015					
	HMK107 B7 223□A		RoHS	0.022					
	HMK107 B7 333□A		RoHS	0.033					
	HMK107 C7 104□A		RoHS	0.1	X7S				

□ Please specify the capacitance tolerance code.

212TYPE(0805 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)	
100V	HMK212 BJ103□G		RoHS	0.01	B/X5R ⁺²	3.5	R	±10% ±20%	1.25±0.1 (0.049±0.004)	
	HMK212 BJ153□G		RoHS	0.015						
	HMK212 BJ223□G		RoHS	0.022						
	HMK212 BJ333□G		RoHS	0.033						
	HMK212 BJ473□G		RoHS	0.047						
	HMK212 BJ683□G		RoHS	0.068						
	HMK212 BJ104□G		RoHS	0.1						
HMK212 BJ224□G		RoHS	0.22	250V		2.5				0.85±0.1 (0.033±0.004)
QMK212 BJ102□D		RoHS	0.001							
QMK212 BJ152□D		RoHS	0.0015							
QMK212 BJ222□D		RoHS	0.0022							
QMK212 BJ332□D		RoHS	0.0033							
QMK212 BJ472□G		RoHS	0.0047							1.25±0.1 (0.049±0.004)
QMK212 BJ682□G		RoHS	0.0068							
QMK212 BJ103□G		RoHS	0.01							
	QMK212 BJ153□G		RoHS	0.015						
	QMK212 BJ223□G		RoHS	0.022						

□ Please specify the capacitance tolerance code.

*2 : We may provide X7R for some items according to the individual specification.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
100V	HMK212 B7 103□G		RoHS	0.01	X7R	3.5	R	±10% ±20%	1.25±0.1 (0.049±0.004)
	HMK212 B7 153□G		RoHS	0.015					
	HMK212 B7 223□G		RoHS	0.022					
	HMK212 B7 333□G		RoHS	0.033					
	HMK212 B7 473□G		RoHS	0.047					
	HMK212 B7 683□G		RoHS	0.068					
	HMK212 B7 104□G		RoHS	0.1					
HMK212 B7 224□G		RoHS	0.22	2.5		0.85±0.1 (0.033±0.004)			
250V	QMK212 B7 102□D		RoHS					0.001	
	QMK212 B7 152□D		RoHS					0.0015	
	QMK212 B7 222□D		RoHS					0.0022	
	QMK212 B7 332□D		RoHS					0.0033	
	QMK212 B7 472□G		RoHS					0.0047	
	QMK212 B7 682□G		RoHS					0.0068	
	QMK212 B7 103□G		RoHS					0.01	
	QMK212 B7 153□G		RoHS					0.015	
	QMK212 B7 223□G		RoHS	0.022		1.25±0.1 (0.049±0.004)			

□ Please specify the capacitance tolerance code.

316TYPE(1206 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)		
100V	HMK316 BJ473□L		RoHS	0.047	B/X5R*2	3.5	R	±10% ±20%	1.6±0.2 (0.063±0.008)		
	HMK316 BJ683□L		RoHS	0.068							
	HMK316 BJ104□L		RoHS	0.1							
	HMK316 BJ154□L		RoHS	0.15							
	HMK316 BJ224□L		RoHS	0.22							
	HMK316 BJ334□L		RoHS	0.33							
	HMK316 BJ474□L		RoHS	0.47							
HMK316 BJ105□L		RoHS	1	250V		QMK316 BJ333□L				RoHS	0.033
QMK316 BJ473□L		RoHS	0.047								
QMK316 BJ683□L		RoHS	0.068								
QMK316 BJ104□L		RoHS	0.1								
630V	SMK316 BJ102□F		RoHS	0.001		2.5					1.15±0.1 (0.045±0.004)
	SMK316 BJ152□F		RoHS	0.0015							
	SMK316 BJ222□F		RoHS	0.0022							
	SMK316 BJ332□F		RoHS	0.0033							
	SMK316 BJ472□F		RoHS	0.0047							
	SMK316 BJ682□F		RoHS	0.0068							
	SMK316 BJ103□F		RoHS	0.01							
	SMK316 BJ153□L		RoHS	0.015	1.6±0.2 (0.063±0.008)						
SMK316 BJ223□L		RoHS	0.022								

□ Please specify the capacitance tolerance code.

*2 : We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)			
100V	HMK316 B7 473□L		RoHS	0.047	X7R	3.5	R	±10% ±20%	1.6±0.2 (0.063±0.008)			
	HMK316 B7 683□L		RoHS	0.068								
	HMK316 B7 104□L		RoHS	0.1								
	HMK316 B7 154□L		RoHS	0.15								
	HMK316 B7 224□L		RoHS	0.22								
	HMK316 B7 334□L		RoHS	0.33								
	HMK316 B7 474□L		RoHS	0.47								
HMK316 B7 105□L		RoHS	1	250V		QMK316 B7 333□L				RoHS	0.033	
QMK316 B7 473□L		RoHS	0.047									
QMK316 B7 683□L		RoHS	0.068									
QMK316 B7 104□L		RoHS	0.1									
630V	SMK316 B7 102□F		RoHS	0.001		2.5						1.15±0.1 (0.045±0.004)
	SMK316 B7 152□F		RoHS	0.0015								
	SMK316 B7 222□F		RoHS	0.0022								
	SMK316 B7 332□F		RoHS	0.0033								
	SMK316 B7 472□F		RoHS	0.0047								
	SMK316 B7 682□F		RoHS	0.0068								
	SMK316 B7 103□F		RoHS	0.01								
	SMK316 B7 153□L		RoHS	0.015	1.6±0.2 (0.063±0.008)							
SMK316 B7 223□L		RoHS	0.022									

□ Please specify the capacitance tolerance code.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

● 325TYPE(1210 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)	
100V	HMK325 BJ104□F		RoHS	0.1	B/X5R*2	3.5	R	±10% ±20%	1.15±0.1 (0.045±0.004)	
	HMK325 BJ154□N		RoHS	0.15						
	HMK325 BJ224□N		RoHS	0.22						
	HMK325 BJ334□N		RoHS	0.33						
	HMK325 BJ474□N		RoHS	0.47						
	HMK325 BJ684□N		RoHS	0.68						
	HMK325 BJ105□N		RoHS	1						
250V	HMK325 BJ225□N		RoHS	2.2		2.5				
	QMK325 BJ473□N		RoHS	0.047						
	QMK325 BJ104□N		RoHS	0.1						
	QMK325 BJ154□N		RoHS	0.15						
630V	QMK325 BJ224□N		RoHS	0.22						
	SMK325 BJ223□N		RoHS	0.022						
	SMK325 BJ333□N		RoHS	0.033						
	SMK325 BJ473□N		RoHS	0.047						

□ Please specify the capacitance tolerance code.

*2 : We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
100V	HMK325 B7 104□F		RoHS	0.1	X7R	3.5	R	±10% ±20%	1.15±0.1 (0.045±0.004)
	HMK325 B7 154□N		RoHS	0.15					1.9±0.2 (0.075±0.008)
	HMK325 B7 224□N		RoHS	0.22					
	HMK325 B7 334□N		RoHS	0.33					
	HMK325 B7 474□N		RoHS	0.47					
	HMK325 B7 684□N		RoHS	0.68					
	HMK325 B7 105□N		RoHS	1					
250V	HMK325 B7 225□N		RoHS	2.2		2.5			
	QMK325 B7 473□N		RoHS	0.047					
	QMK325 B7 104□N		RoHS	0.1					
	QMK325 B7 154□N		RoHS	0.15					
630V	QMK325 B7 224□N		RoHS	0.22					
	SMK325 B7 223□N		RoHS	0.022					
	SMK325 B7 333□N		RoHS	0.033					
	SMK325 B7 473□N		RoHS	0.047					

□ Please specify the capacitance tolerance code.

● 432TYPE(1812 case size)

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	tan δ Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
100V	HMK432 BJ474□M		RoHS	0.47	B/X5R ^{a2}	3.5	R	±10% ±20%	2.5±0.2 (0.098±0.008)
	HMK432 BJ105□M		RoHS	1					
	HMK432 BJ155□M		RoHS	1.5					
	HMK432 BJ225□M		RoHS	2.2					
250V	QMK432 BJ104□M		RoHS	0.1		2.5			
	QMK432 BJ224□M		RoHS	0.22					
	QMK432 BJ334□M		RoHS	0.33					
	QMK432 BJ474□M		RoHS	0.47					
630V	SMK432 BJ473□M		RoHS	0.047					
	SMK432 BJ683□M		RoHS	0.068					
	SMK432 BJ104□M		RoHS	0.1					

□ Please specify the capacitance tolerance code.

*2 : We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]



Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
100V	HMK432 B7 474□M		RoHS	0.47	X7R	3.5	R	±10% ±20%	2.5±0.2 (0.098±0.008)
	HMK432 B7 105□M		RoHS	1					
	HMK432 B7 155□M		RoHS	1.5					
	HMK432 B7 225□M		RoHS	2.2					
250V	QMK432 B7 104□M		RoHS	0.1		2.5			
	QMK432 B7 224□M		RoHS	0.22					
	QMK432 B7 334□M		RoHS	0.33					
	QMK432 B7 474□M		RoHS	0.47					
630V	SMK432 B7 473□M		RoHS	0.047					
	SMK432 B7 683□M		RoHS	0.068					
	SMK432 B7 104□M		RoHS	0.1					

□ Please specify the capacitance tolerance code.


* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

● Example of Impedance ESR vs. Frequency characteristics

■ Taiyo Yuden medium-high voltage ceramic capacitor





● Temperature characteristics



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

Multilayer Ceramic Capacitors and Super Low Distortion Multilayer Ceramic Capacitors are noted separately.

Medium—High Voltage Multilayer Ceramic Capacitor

1. Operating Temperature Range													
Specified Value	X7R, X7S : -55~+125℃ X5R : -55~+85℃ B : -25~+85℃												
2. Storage Temperature Range													
Specified Value	X7R, X7S : -55~+125℃ X5R : -55~+85℃ B : -25~+85℃												
3. Rated Voltage													
Specified Value	100VDC, 250VDC, 630VDC												
4. Withstanding Voltage (Between terminals)													
Specified Value	No breakdown or damage												
[Test Methods and Remarks] Applied voltage:Rated voltage×2.5 (HMK) , Rated voltage×2 (QMK) , Rated voltage×1.2 (SMK) Duration : 1 to 5sec. Charge/discharge current : 50mA max.													
5. Insulation Resistance													
Specified Value	100MΩμF or 10GΩ, whichever is smaller.												
[Test Methods and Remarks] Applied voltage:Rated voltage (HMK, QMK) , 500V (SMK) Duration : 60±5sec. Charge/discharge current : 50mA max.													
6. Capacitance (Tolerance)													
Specified Value	±10%、±20%												
[Test Methods and Remarks] Measuring frequency:1kHz±10% Measuring voltage:1±0.2Vrms Bias application:None													
7. Dissipation Factor													
Specified Value	3.5%max (HMK) 2.5%max (QMK, SMK)												
[Test Methods and Remarks] Measuring frequency:1kHz±10% Measuring voltage:1±0.2Vrms Bias application:None													
8. Temperature Characteristic of Capacitance													
Specified Value	B: ±10% (-25~+85℃) X5R: ±15% (-55~+85℃) X7R: ±15% (-55~+125℃) X7S: ±22% (-55~+125℃)												
[Test Methods and Remarks] Capacitance value at each step shall be measured in thermal equilibrium, and the temperature characteristic shall be calculated from the following equation.													
<table><tr><td>Step</td><td>B</td><td>X5R、X7R、X7S</td></tr><tr><td>1</td><td colspan="2">Minimum operating temperature</td></tr><tr><td>2</td><td>20℃</td><td>25℃</td></tr><tr><td>3</td><td colspan="2">Maximum operating temperature</td></tr></table>	Step	B	X5R、X7R、X7S	1	Minimum operating temperature		2	20℃	25℃	3	Maximum operating temperature		$\frac{(C-C_2)}{C_2} \times 100 (\%)$ C : Capacitance value in Step 1 or Step 3 C₂ : Capacitance value in Step 2
Step	B	X5R、X7R、X7S											
1	Minimum operating temperature												
2	20℃	25℃											
3	Maximum operating temperature												
9. Deflection													
Specified Value	Appearance:No abnormality Capacitance change:Within±10%												
[Test Methods and Remarks] Warp:1mm Duration:10sec. Test board:glass epoxy-resin substrate Thickness:1.6mm Capacitance measurement shall be conducted with the board bent.													
													
(Unit: mm)													
10. Adhesive Strength of Terminal Electrodes													
Specified Value	No terminal separation or its indication.												
[Test Methods and Remarks] Applied force:5N Duration:30±5sec.													
													
11. Solderability													
Specified Value	At least 95% of terminal electrode is covered by new solder												
[Test Methods and Remarks]													
<table><tr><td></td><td>Solder type</td><td>Solder temperature</td><td>Duration</td></tr><tr><td>Eutectic solder</td><td>H60A or H63A</td><td>230±5℃</td><td rowspan="2">4±1 sec.</td></tr><tr><td>Lead-free solder</td><td>Sn-3.0Ag-0.5Cu</td><td>245±3℃</td></tr></table>		Solder type	Solder temperature	Duration	Eutectic solder	H60A or H63A	230±5℃	4±1 sec.	Lead-free solder	Sn-3.0Ag-0.5Cu	245±3℃		
	Solder type	Solder temperature	Duration										
Eutectic solder	H60A or H63A	230±5℃	4±1 sec.										
Lead-free solder	Sn-3.0Ag-0.5Cu	245±3℃											

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
 For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

12. Resistance to Soldering

Specified Value	Appearance: No abnormality Capacitance change: Within±15% (HMK), ±10% (QMK, SMK) Dissipation factor: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality
【Test Methods and Remarks】 Preconditioning: Thermal treatment (at 150°C for 1hr) Note1 Solder temperature: 270±5°C Duration: 3±0.5sec. Preheating conditions: 80 to 100°C, 2 to 5 min. 150 to 200°C, 2 to 5 min. Recovery: 24±2hrs under the standard condition Note3	

13. Temperature Cycle (Thermal Shock)

Specified Value	Appearance: No abnormality Capacitance change: Within±15% (HMK), ±7.5% (QMK, SMK) Dissipation factor: Initial value Insulation resistance: Initial value
【Test Methods and Remarks】 Preconditioning: Thermal treatment (at 150°C for 1hr) Note1 Conditions for 1 cycle / Step 1: Minimum operating temperature $\pm 9^{\circ}\text{C}$ 30±3min. Step 2: Room temperature 2 to 3min. Step 3: Maximum operating temperature $\pm 9^{\circ}\text{C}$ 30±3min. Step 4: Room temperature 2 to 3min. Number of cycles: 5 times Recovery: 24±2hrs under the standard condition Note3	

14. Humidity (Steady state)

Specified Value	Appearance: No abnormality Capacitance change: Within±15% Dissipation factor: 7%max (HMK), 5%max (QMK, SMK). Insulation resistance: 25MΩμF or 1000MΩ, whichever is smaller.
【Test Methods and Remarks】 Preconditioning: Thermal treatment (at 150°C for 1hr) Note1 Temperature: 40±2°C Humidity: 90 to 95%RH Duration: 500 ± 24 hrs Recovery: 24±2hrs under the standard condition Note3	

15. Humidity Loading

Specified Value	Appearance: No abnormality Capacitance change: Within±15% Dissipation factor: 7%max (HMK), 5%max (QMK, SMK). Insulation resistance: 10MΩμF or 500MΩ, whichever is smaller.
【Test Methods and Remarks】 According to JIS 5102 clause 9.9. Preconditioning: Voltage treatment Note2 Temperature: 40±2°C Humidity: 90 to 95%RH Applied voltage: Rated voltage Charge/discharge current: 50mA max. Duration: 500 ± 24 hrs Recovery: 24±2hrs under the standard condition Note3	

16. High Temperature Loading

Specified Value	Appearance: No abnormality Capacitance change: Within±15% Dissipation factor: 7%max (HMK), 5%max (QMK, SMK). Insulation resistance: 50MΩμF or 1000MΩ, whichever is smaller.
【Test Methods and Remarks】 According to JIS 5102 clause 9.10. Preconditioning: Voltage treatment Note2 Temperature: 125±3°C (B7), 85±2°C (BJ) Applied voltage: Rated voltage×2 (HMK) Rated voltage×1.5 (QMK) Rated voltage×1.2 (SMK) Charge/discharge current: 50mA max. Duration: 1000 ± 24 hrs Recovery: 24±2hrs under the standard condition Note3	

Note1 Thermal treatment: Initial value shall be measured after test sample is heat-treated at 150+0/−10°C for an hour and kept at room temperature for 24±2hours.

Note2 Voltage treatment: Initial value shall be measured after test sample is voltage-treated for an hour at both the temperature and voltage specified in the test conditions, and kept at room temperature for 24±2hours.

Note3 Standard condition: Temperature: 5 to 35°C, Relative humidity: 45 to 85 % RH, Air pressure: 86 to 106kPa
When there are questions concerning measurement results, in order to provide correlation data, the test shall be conducted under the following condition.
Temperature: 20±2°C, Relative humidity: 60 to 70 % RH, Air pressure: 86 to 106kPa
Unless otherwise specified, all the tests are conducted under the "standard condition".

LW REVERSAL DECOUPLING CAPACITORS (LWDC™)



REFLOW

FEATURES

- Low equivalent series resistance (ESR).
- Low equivalent series inductor (ESL).
- The effect of noise removal in the high frequency.
- Decreased ripple voltage.
- Small size with high capacitance.


APPLICATIONS

- Decoupling capacitors
- Filtering capacitors

ORDERING CODE

1	2	3	4	5	6	7	8	9	10	11
J	W	K	2 1 2	B	J	1 0 6	M	D	—	T △
1 Rated voltage (VDC)	2 Series name	3 End termination	4 Dimensions (EIA) L×W (mm)	5 Temperature characteristics code	6 Nominal capacitance (μF)	7 Capacitance tolerance	8 Thickness (mm)	9 Special code	10 Packaging	11 Internal code
A 4 J 6.3 L 10 E 16 T 25	W LW Reverse Type	K Plated	105 (0204) 0.52×1.0 107 (0306) 0.8×1.6 212 (0508) 1.25×2.0	BJ B X5R B7 X7R C6 X6S C7 X7S	example 105 1.0 106 10.0	K ±10% M ±20%	P 0.3 V 0.5 A 0.8 D 0.85	— Standard Product	F φ178mm Taping (2mm pitch) 0204 Type T φ178mm Taping (4mm pitch) 0306, 0508 Type	△ Standard Product △=Blank space

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	T	Standard quantity [pcs]	
				Paper tape	Embossed tape
□WK105 (0204)	0.52±0.05 (0.020±0.002)	1.00±0.05 (0.039±0.002)	0.30±0.05 (0.012±0.002) 0.50±0.05 (0.020±0.002)	P V	10000 —
□WK107 (0306)	0.80±0.10 (0.031±0.004)	1.60±0.10 (0.063±0.004)	0.50±0.05 (0.020±0.002)	V	—
□WK212 (0508)	1.25±0.15 (0.049±0.006)	2.00±0.15 (0.079±0.006)	0.85±0.10 (0.033±0.004)	D	4000 —

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

Cap [μF]	Type	105				107								212	
	Temp.Char	X7S	X6S	X5R		X7R	X7S	X6S	X5R					X6S	X5R
	VDC	6.3	4	6.3	4	25	16	6.3	4	4	25	16	10	6.3	
0.10	104	P		P		V					V				
0.22	224		P	P	P		V					V			
0.47	474		P	P			V					V			
1.0	105		V	V				V					V	V	
2.2	225								V					V	
4.7	475									V				V	D
10.0	106													D	D

※ Letters in the table indicate thickness.

Temp.char.Code	Temperature characteristics					Capacitance tolerance [%]
	Applicable standard		Temperature range(°C)	Ref. Temp.(°C)	Capacitance change(%)	
BJ	JIS	B	−25~+85	20	±10	±10 (K) ±20 (M)
	EIA	X5R	−55~+85	25	±15	
B7	EIA	X7R	−55~+125	25	±15	
C6	EIA	X6S	−55~+105	25	±22	
C7	EIA	X7S	−55~+125	25	±22	

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

105TYPE (0204 case size)

[Temp.char. BJ:X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
6.3V	JWK105 BJ104MP ^{*1}		RoHS	0.1	X5R ^{*2}	5	R	±20% (M)	0.3±0.05 (0.012±0.002)
	JWK105 BJ474MP ^{*1}		RoHS	0.47		10			0.5±0.05 (0.020±0.002)
	JWK105 BJ105MV ^{*1}		RoHS	1					0.3±0.05 (0.012±0.002)
4V	AWK105 BJ224MP ^{*1}		RoHS	0.22					

^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test. ^{*2} We may provide X6S/X7S for some items according to the individual specification.

[Temp.char. C6:X6S C7:X7S]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μF)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
6.3V	JWK105 C7 104MP ^{*1}		RoHS	0.1	X7S	5	R	±20% (M)	0.3±0.05 (0.012±0.002)
4V	AWK105 C6 224MP ^{*1}		RoHS	0.22	X6S	10			
	AWK105 C6 474MP ^{*1}		RoHS	0.47					
		AWK105 C6 105MV ^{*1}		RoHS					1

^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

107TYPE (0306 case size)

[Temp.char. BJ:X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
25V	TWK107 BJ 104MV		RoHS	0.1	X5R	5	R	$\pm 20\%$ (M)	0.5 $\pm$ 0.05 (0.020 $\pm$ 0.002)
16V	EWK107 BJ 224MV		RoHS	0.22					
	EWK107 BJ 474MV		RoHS	0.47					
10V	LWK107 BJ 105MV ^{*1}		RoHS	1	X5R	10			
6.3V	JWK107 BJ 105MV ^{*1}		RoHS	1	X5R ^{*2}				
	JWK107 BJ 225MV ^{*1}		RoHS	2.2	X5R				
	JWK107 BJ 475MV ^{*1}		RoHS	4.7					

^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test. ^{*2} We may provide X7R/X7S for some items according to the individual specification.

[Temp.char. B7:X7R C7:X7S C6:X6S]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance 〔μF〕	Temperature characteristics	Dissipation factor 〔%〕Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness 〔mm〕 〔inch〕
25V	TWK107 B7 104MV ^{*1}		RoHS	0.1	X7R	5	R	±20%〔M〕	0.5±0.05 (0.020±0.002)
16V	EWK107 B7 224MV ^{*1}		RoHS	0.22					
	EWK107 B7 474MV ^{*1}		RoHS	0.47					
6.3	JWK107 C7 105MV ^{*1}		RoHS	1	X7S	10			
4V	AWK107 C7 225MV ^{*1}		RoHS	2.2					
	AWK107 C6 475MV ^{*1}		RoHS	4.7					

^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

212TYPE (0508 case size)

[Temp.char. BJ:X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
10V	LWK212 BJ475□D ^{*1}		RoHS	4.7	X5R	10	R	$\pm 10\%$ (K) $\pm 20\%$ (M)	0.85 $\pm$ 0.1 (0.033 $\pm$ 0.004)
	LWK212 BJ106MD ^{*1}		RoHS	10				$\pm 20\%$ (M)	

□ Please specify the capacitance tolerance code. ^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

[Temp.char. C6:X6S]



Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance (μ F)	Temperature characteristics	Dissipation factor (%) Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness (mm) (inch)
6.3V	JWK212 C6 475□D ^{*1}		RoHS	4.7	X6S	10	R	$\pm 10\%$ (K) $\pm 20\%$ (M)	0.85 $\pm$ 0.1 (0.033 $\pm$ 0.004)
	JWK212 C6 106MD ^{*1}		RoHS	10				$\pm 20\%$ (M)	

□ Please specify the capacitance tolerance code. ^{*1} 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

ELECTRICAL CHARACTERISTICS

Example of Impedance ESR vs. Frequency characteristics

Taiyo Yuden multilayer ceramic capacitor



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

ARRAY TYPE MULTILAYER CERAMIC CAPACITORS



REFLOW

FEATURES

- High density and high efficiency mounting.
- Internal electrodes are composed of nickel for improved cost performance and reliability.


APPLICATIONS

- General electronic equipment
- Communication equipment (cellular phone, wireless applications, etc.)

ORDERING CODE

E	4	K	2	1	2	B	J	1	0	4	M	D	—	T	△
1	2	3	4	5	6	7	8	9	10	11					
1 Rated voltage (VDC)		3 End termination		4 Dimensions (EIA) L×W (mm)		5 Temperature characteristics code		7 Capacitance tolerance		8 Thickness (mm)		9 Special code		11 Internal code	
J	6.3	K	Plated	096 (0302)	0.9×0.6	BJ	B	F	±1pF	P	0.3	—	Standard Product	△	Standard Product
L	10			110 (0504)	1.4×1.0	B7	X5R	K	±10%	K	0.45				△=Blank space
E	16			212 (0805)	2.0×1.25	CH	X7R	M	±20%	V	0.5				
T	25	2 Series name				C0H		6 Nominal capacitance (pF)		B	0.6	10 Packaging			
U	50	2	2 circuits multilayer capacitor					example		A	0.8	T	φ178mm Taping (4mm pitch) 0504, 0805 Type		
		4	4 circuits multilayer capacitor					104 100,000		D	0.85	F	φ178mm Taping (2mm pitch) 0302 Type		
								105 1,000,000							

EXTERNAL DIMENSIONS/STANDARD QUANTITY



Type (EIA)	L	W	E1	E2	P	T	Standard quantity [pcs]	
							Paper tape	Embossed tape
□2K096 (0302)	0.9±0.05 (0.035±0.002)	0.6±0.05 (0.024±0.002)	0.23±0.10 (0.009±0.004)	0.125±0.075 (0.005±0.003)	0.45±0.05 (0.018±0.002)	P	0.30±0.03 (0.012±0.001)	10000
						K	0.45±0.05 (0.018±0.002)	
						V	0.5±0.05 (0.020±0.002)	
□2K110 (0504)	1.37±0.07 (0.054±0.003)	1.00±0.08 (0.039±0.003)	0.36±0.10 (0.014±0.004)	0.2±0.10 (0.008±0.004)	0.64±0.10 (0.025±0.004)	B	0.60±0.06 (0.024±0.003)	4000
						A	0.80±0.08 (0.031±0.003)	
						D	0.85±0.10 (0.033±0.004)	
□2K212 (0805)	2.00±0.10 (0.079±0.004)	1.25±0.10 (0.049±0.004)	0.50±0.20 (0.020±0.008)	0.25±0.15 (0.010±0.006)	1.00±0.10 (0.039±0.004)	D	0.85±0.10 (0.033±0.004)	4000
□4K212 (0805)	2.00±0.10 (0.079±0.004)	1.25±0.10 (0.049±0.004)	0.25±0.10 (0.010±0.004)	0.25±0.15 (0.010±0.006)	0.50±0.10 (0.020±0.004)	D	0.85±0.10 (0.033±0.004)	4000

Unit : mm (inch)

AVAILABLE CAPACITANCE RANGE

BJ/B7

Cap [μF]	Type	096 2 circuits □2K096		110 2 circuits □2K110										212 2 circuits □2K212		212 4 circuits □4K212					
		Temp. Char	B/X5R	X5R	X7R			B/X5R				X5R			B/X5R	X5R	X7R	B/X5R			X5R
		VDC	10V	6.3V	50V	25V	16V	50V	25V	16V	10V	16V	10V	6.3V	25V	10V	16V	25V	16V	10V	10V
		[pF:3digits]																			
0.001	102			B			B														
0.0022	222			B			B														
0.0047	472			B			B														
0.01	103	P			B			B													
0.022	223				B			B													
0.047	473		K			B			B												
0.1	104		K			B		B	B								D	D	D		
0.22	224		K																	D	
0.47	474										A									D	
1.0	105											A	A,V	V	D					D	
2.2	225													A		D					

※ Letters in the table indicate thickness.

CH

Cap [pF]	Type	096 2 circuits □2K096	110 2 circuits □2K110
	Temp.Char	CH	CH
	VDC	25V	50V
	[pF:3digits]		
10	100	P	B
12	120	P	B
15	150	P	B
18	180	P	B
22	220	P	B
27	270	P	B
33	330	P	B
39	390	P	B
47	470	P	B
56	560	P	B
68	680	P	B
82	820	P	B
100	101	P	B

※ Letters in the table indicate thickness.

Temp.char.Code	Temperature characteristics					Capacitance tolerance [%]
	Applicable standard		Temperature range [°C]	Ref. Temp. [°C]	Capacitance change	
BJ	JIS	B	−25~+85	20	±10 [%]	±10 (K) ±20 (M)
	EIA	X5R	−55~+85	25	±15 [%]	
B7	EIA	X7R	−55~+125	25	±15 [%]	
CH	JIS	CH	−55~+125	20	±60 [ppm/°C]	±10 (K)
	EIA	C0H	−55~+125	25	±60 [ppm/°C]	

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

PART NUMBERS

● 096TYPE (0302 case size) 2 circuits type

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
10V	L2K096 BJ103□P		RoHS	0.01	B/X5R	5	R	±10% [K] ±20% [M]	0.3±0.03 (0.012±0.001)
6.3V	J2K096 BJ473□K*1		RoHS	0.047	X5R				10
	J2K096 BJ104□K*1		RoHS	0.1					
	J2K096 BJ224MK*1		RoHS	0.22					

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

[Temp.char. CH:CH/C0H]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)		
25V	T2K096 CH100FP		RoHS	10	CH/C0H	400+20・C	R	±1pF [F]	0.3±0.03 (0.012±0.001)		
	T2K096 CH120KP		RoHS	12				±10% [K]			
	T2K096 CH150KP		RoHS	15							
	T2K096 CH180KP		RoHS	18							
	T2K096 CH220KP		RoHS	22							
	T2K096 CH270KP		RoHS	27							
	T2K096 CH330KP		RoHS	33		1000		±10% [K]			
	T2K096 CH390KP		RoHS	39							
	T2K096 CH470KP		RoHS	47							
	T2K096 CH560KP		RoHS	56							
	T2K096 CH680KP		RoHS	68							
	T2K096 CH820KP		RoHS	82							
T2K096 CH101KP		RoHS	100								

Note: Please contact Taiyo Yuden sales channels about temperature characteristics other than listed above.

● 110TYPE (0504 case size) 2 circuits type

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%]Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)				
50V	U2K110 BJ102□B		RoHS	0.001	B/X5R*2	3.5	R	±10% [K] ±20% [M]	0.6±0.06 (0.024±0.002)				
	U2K110 BJ222□B		RoHS	0.0022									
	U2K110 BJ472□B		RoHS	0.0047									
25V	T2K110 BJ103□B		RoHS	0.01	B/X5R	5				±10% [K] ±20% [M]	0.8±0.08 (0.031±0.003)		
	T2K110 BJ223□B		RoHS	0.022									
	T2K110 BJ104□B		RoHS	0.1									
16V	E2K110 BJ473□B		RoHS	0.047	B/X5R*2	3.5 5						±10% [K] ±20% [M]	0.6±0.06 (0.024±0.002)
	E2K110 BJ104□B		RoHS	0.1									
	E2K110 BJ105□A ⁻¹		RoHS	1.0									
10V	L2K110 BJ224□B		RoHS	0.22	B/X5R	5		±20% [M]	0.5±0.05 (0.02±0.002)				
	L2K110 BJ474□A		RoHS	0.47									
	L2K110 BJ105□A ⁻¹		RoHS	1.0									
	L2K110 BJ105MV ⁻¹		RoHS	1.0									
6.3V	J2K110 BJ105□V ⁻¹		RoHS	1.0	X5R	10				±10% [K] ±20% [M]	0.8±0.08 (0.031±0.003)		
	J2K110 BJ225□A ⁻¹		RoHS	2.2									

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%]Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
50V	U2K110 B7 102□B		RoHS	0.001	X7R	3.5	R	±10% [K] ±20% [M]	0.6±0.06 (0.024±0.002)
	U2K110 B7 222□B		RoHS	0.0022					
	U2K110 B7 472□B		RoHS	0.0047					
25V	T2K110 B7 103□B		RoHS	0.01					
	T2K110 B7 223□B		RoHS	0.022					
16V	E2K110 B7 473□B		RoHS	0.047		5			
	E2K110 B7 104□B		RoHS	0.1					

□ Please specify the capacitance tolerance code.

PART NUMBERS

[Temp.char. CH:CH/C0H]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [pF]	Temperature characteristics	Q	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)				
50V	U2K110 CH100FB		RoHS	10	CH/C0H	400+20・C	R	±1pF [F]	0.6±0.06 (0.024±0.002)				
	U2K110 CH120KB		RoHS	12				±10% [K]					
	U2K110 CH150KB		RoHS	15									
	U2K110 CH180KB		RoHS	18									
	U2K110 CH220KB		RoHS	22									
	U2K110 CH270KB		RoHS	27									
	U2K110 CH330KB		RoHS	33		1000							
	U2K110 CH390KB		RoHS	39									
	U2K110 CH470KB		RoHS	47									
	U2K110 CH560KB		RoHS	56									
	U2K110 CH680KB		RoHS	68									
	U2K110 CH820KB		RoHS	82									
U2K110 CH101KB		RoHS	100										

Note: Please contact Taiyo Yuden sales channels about temperature characteristics other than listed above.

● 212TYPE (0805 case size) 2 circuits type

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
25V	T2K212 BJ105□D		RoHS	1.0	B/X5R	5	R	±10% [K] ±20% [M]	0.85±0.1 (0.033±0.004)
10V	L2K212 BJ225MD* ¹		RoHS	2.2	X5R	10		±20% [M]	

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

● 212TYPE (0805 case size) 4 circuits type

[Temp.char. BJ:B/X5R]

Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
25V	T4K212 BJ104□D		RoHS	0.1	B/X5R	5	R	±10% [K] ±20% [M]	0.85±0.1 (0.033±0.004)
16V	E4K212 BJ104□D		RoHS	0.1	B/X5R ^{*2}				
10V	L4K212 BJ224□D		RoHS	0.22	B/X5R				
	L4K212 BJ474□D		RoHS	0.47					
		L4K212 BJ105□D ^{*1}		RoHS	1	X5R			

□ Please specify the capacitance tolerance code.

*1 1.5 times the rated voltage is applied to the chip during the high temperature loading test.

*2 We may provide X7R for some items according to the individual specification.

[Temp.char. B7:X7R]


Rated Voltage	Ordering code		EHS (Environmental Hazardous Substances)	Capacitance [μF]	Temperature characteristics	Dissipation factor [%] Max.	Soldering method R:Reflow soldering W:Wave soldering	Capacitance tolerance	Thickness [mm] (inch)
16V	E4K212 B7 104□D		RoHS	0.1	X7R	5	R	±10% [K] ±20% [M]	0.85±0.1 (0.033±0.004)

□ Please specify the capacitance tolerance code.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

● Example of Impedance ESR vs. Frequency characteristics

■ Taiyo Yuden multilayer ceramic capacitor



* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

① Minimum Quantity


● Taped packaging

Type (EIA)	Thickness		Standard quantity [pcs]	
	mm (inch)	code	Paper tape	Embossed tape
□MK042(01005)	0.2(0.008)	C	20000	—
□MK063(0201)	0.3(0.012)	P,T	15000	
□2K096(0302)	0.3(0.012)	P	10000	
	0.45(0.018)	K		
□WK105(0204)	0.3(0.012)	P		
	0.5(0.020)	V		
□MK105(0402)	0.5(0.020)	V, W		
□VK105(0402)	0.5(0.020)	W	4000	4000
□MK107(0603)	0.45(0.018)	K		
□WK107(0306)	0.5(0.020)	V	—	4000
	0.8(0.031)	A	4000	—
□2K110(0504)	0.5(0.020)	V		
	0.6(0.024)	B		
	0.8(0.031)	A		
	0.45(0.018)	K		
□MK212(0805)	0.85(0.033)	D	—	3000
□WK212(0508)	1.25(0.049)	G		
□4K212(0805)	0.85(0.033)	D	4000	—
□2K212(0805)	0.85(0.033)	D		
	0.85(0.033)	D		
□MK316(1206)	1.15(0.045)	F	—	3000
	1.25(0.049)	G		
	1.6(0.063)	L		
	0.85(0.033)	D	—	2000
□MK325(1210)	1.15(0.045)	F		
	1.9(0.075)	N		
	2.0max(0.079)	Y		
	2.5(0.098)	M		
□MK432(1812)	2.5(0.098)	M	—	500(T), 1000(P)
			—	500


② Taping material

※ No bottom tape for pressed carrier tape



● Paper tape



● Embossed tape




● Chip filled



③ Taping dimensions

● Paper Tape (0.315 inches wide)


● Pressed carrier tape (2mm pitch)



Type (EIA)	Chip Cavity		Insertion Pitch F	Tape Thickness	
	A	B		T	T1
□MK042(01005)	0.25 (0.010)	0.45 (0.018)	2.0 ± 0.05 (0.079 ± 0.002)	0.36max. (0.014)	0.27max. (0.011)
□MK063(0201)	0.37 (0.016)	0.67 (0.027)		0.45max. (0.018)	0.42max. (0.017)
□WK105(0204)	0.65 (0.026)	1.15 (0.045)		0.45max. (0.018max.)	0.42max. (0.017max.)

Unit : mm (inch)


● Punched carrier tape (2mm pitch)



Type (EIA)	Chip Cavity		Insertion Pitch F	Tape Thickness	
	A	B		T	
□2K096(0302)	0.72 (0.028)	1.02 (0.040)	2.0 ± 0.05 (0.079 ± 0.002)	0.45max.(0.018max.) 0.6max.(0.024max.)	
□MK105(0402)	0.65 (0.026)	1.15 (0.045)		0.8max. (0.031max.)	
□VK105(0402)	0.65 (0.026)	1.15 (0.045)		0.8max. (0.031max.)	

Unit : mm (inch)

● Punched carrier tape (4mm pitch)




Type (EIA)	Chip Cavity		Insertion Pitch F	Tape Thickness	
	A	B		T	
□MK107(0603)	1.0 (0.039)	1.8 (0.071)	4.0 ± 0.1 (0.157 ± 0.004)	1.1max. (0.043max.)	
□WK107(0306)	1.0 (0.039)	1.8 (0.071)		1.1max. (0.043max.)	
□2K110(0504)	1.15 (0.045)	1.55 (0.061)		1.0max. (0.039max.)	
□MK212(0805)	1.65 (0.065)	2.4 (0.094)		1.1max. (0.043max.)	
□WK212(0508)	1.65 (0.065)	2.4 (0.094)		1.1max. (0.043max.)	
□4K212(0805)	1.65 (0.065)	2.4 (0.094)	4.0 ± 0.1 (0.157 ± 0.004)	1.1max. (0.043max.)	
□2K212(0805)	1.65 (0.065)	2.4 (0.094)		1.1max. (0.043max.)	
□MK316(1206)	2.0 (0.079)	3.6 (0.142)	4.0 ± 0.1 (0.157 ± 0.004)	1.1max. (0.043max.)	

Unit : mm (inch)

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.


● Embossed tape (0.315 inches wide)



Type(EIA)	Chip Cavity		Insertion Pitch F	Tape Thickness	
	A	B		K	T
□WK107(0306)	1.0 (0.039)	1.8 (0.071)	4.0 ± 0.1 (0.157 ± 0.004)	1.3max. (0.051max.)	0.25 ± 0.1 (0.01 ± 0.004)
□MK212(0805)	1.65 (0.065)	2.4 (0.094)		3.4max. (0.134max.)	0.6max. (0.024max.)
□MK316(1206)	2.0 (0.079)	3.6 (0.142)			
□MK325(1210)	2.8 (0.110)	3.6 (0.142)			

Unit : mm (inch)


● Embossed tape (0.472 inches wide)




Type(EIA)	Chip Cavity		Insertion Pitch F	Tape Thickness	
	A	B		K	T
□MK432(1812)	3.7 (0.146)	4.9 (0.193)	8.0 ± 0.1 (0.315 ± 0.004)	4.0max. (0.157max.)	0.6max. (0.024max.)

Unit : mm (inch)

④ Leader and Blank portion




⑤ Reel size





⑥ Top Tape Strength

The top tape requires a peel-off force of 0.1 to 0.7N in the direction of the arrow as illustrated below.



⑦ Bulk Cassette



Unit : mm (inch)

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

Multilayer Ceramic Capacitors

1. Operating Temperature Range

Specified Value	Temperature Compensating (Class 1)	Standard	-55 to +125°C	
		High Frequency Type		
High Permittivity (Class 2)			BJ	Specification
				Temperature Range
			B	-25 to +85°C
			X5R	-55 to +85°C
			B7	X7R
			C6	X6S
			C7	X7S
F			F	-25 to +85°C
			Y5V	-30 to +85°C

2. Storage Temperature Range

Specified Value	Temperature Compensating (Class 1)	Standard	-55 to +125°C	
		High Frequency Type		
High Permittivity (Class 2)			BJ	Specification
				Temperature Range
			B	-25 to +85°C
			X5R	-55 to +85°C
			B7	X7R
			C6	X6S
			C7	X7S
F			F	-25 to +85°C
			Y5V	-30 to +85°C

3. Rated Voltage

Specified Value	Temperature Compensating (Class 1)	Standard	50VDC, 25VDC, 16VDC
		High Frequency Type	50VDC, 16VDC
	High Permittivity (Class 2)		50VDC, 35VDC, 25VDC, 16VDC, 10VDC, 6.3VDC, 4VDC

4. Withstanding Voltage (Between terminals)

Specified Value	Temperature Compensating (Class 1)	Standard	No breakdown or damage
		High Frequency Type	
	High Permittivity (Class 2)		

【Test Methods and Remarks】

	Class 1	Class 2
Applied voltage	Rated voltage×3	Rated voltage×2.5
Duration	1 to 5 sec.	
Charge/discharge current	50mA max.	

5. Insulation Resistance

Specified Value	Temperature Compensating (Class 1)	Standard	10000 MΩ min.
		High Frequency Type	
	High Permittivity (Class 2) Note 1		C≤0.047μF : 10000 MΩ min. C>0.047μF : 500MΩ·μF

【Test Methods and Remarks】

Applied voltage: Rated voltage
Duration: 60±5 sec.
Charge/discharge current: 50mA max.

6. Capacitance (Tolerance)

Specified Value	Temperature Compensating (Class 1)	Standard	C△	0.5pF≤C≤5pF : ±0.25pF	RH	0.5pF≤C≤2pF : ±0.1pF
			U△	0.5pF<C≤10pF : ±0.5pF		
			C>10pF : ±5%	T△	C>2pF : ±5%	
	High Frequency Type	CH	0.5pF≤C≤2pF : ±0.1pF			
		RH	C>2pF : ±5%			
	High Permittivity (Class 2)	BJ, B7, C6, C7 : ±10% or ±20%, F : -20%/+80%				

【Test Methods and Remarks】

	Class 1		Class 2	
	Standard	High Frequency Type	C≤10μF	C>10μF
Preconditioning	None		Thermal treatment (at 150°C for 1hr) Note 2	
Measuring frequency	1MHz±10%		1kHz±10%	120±10Hz
Measuring voltage Note 1	0.5 to 5Vrms		1±0.2Vrms	0.5±0.1Vrms
Bias application	None			

7. Q or Dissipation Factor

Specified Value	Temperature Compensating (Class 1)	Standard	C<30 pF : Q≥400+20C、C≥30 pF : Q≥1000 (C : Nominal capacitance)
		High Frequency Type	Refer to detailed specification
	High Permittivity (Class 2) Note 1		BJ, B7, C6, C7 : 2.5% max., F : 7% max.

【Test Methods and Remarks】

	Class 1		Class 2	
	Standard	High Frequency Type	C≤10μF	C>10μF
Preconditioning	None		Thermal treatment (at 150°C for 1hr) Note 2	
Measuring frequency	1MHz±10%		1kHz±10%	120±10Hz
Measuring voltage Note 1	0.5 to 5Vrms		1±0.2Vrms	0.5±0.1Vrms
Bias application	None			

High Frequency Type
Measuring equipment: HP4291A
Measuring jig: HP16192A

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

RELIABILITY DATA

8. Temperature Characteristic of Capacitance (Without voltage application)

Specified Value	Temperature Compensating (Class 1)	Standard	Temperature Characteristic [ppm/°C]		Tolerance	
			C□ : 0	CH, CJ, CK	H±60 J±120 K±250	
			R□ : -220	RH		
		S□ : -330	SH, SJ, SK			
		T□ : -470	TJ, TK			
		High Frequency Type	U□ : -750	UJ, UK		
	SL : +350 to -1000					
	High Permittivity (Class 2)					

[Test Methods and Remarks]

Class 1

Capacitance at 20°C and 85°C shall be measured in thermal equilibrium, and the temperature characteristic shall be calculated from the following equation.

$$\frac{(C_{85}-C_{20})}{C_{20} \times \Delta T} \times 10^6 \text{ (ppm/°C)} \quad \Delta T=65$$

Class 2

Capacitance at each step shall be measured in thermal equilibrium, and the temperature characteristic shall be calculated from the following equation.

Step	B, F	5R, X7R, X6S, X7S, Y5V	$\frac{(C-C_2)}{C_2} \times 100 (\%)$
1	Minimum operating temperature		
2	20°C	25°C	
3	Maximum operating temperature		

C : Capacitance in Step 1 or Step 3
C₂ : Capacitance in Step 2

9. Deflection

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance : No abnormality Capacitance change : Within ±5% or ±0.5 pF, whichever is larger.
		High Frequency Type	Appearance : No abnormality Capacitance change : Within ±0.5 pF
Specified Value	High Permittivity (Class 2)		Appearance : No abnormality Capacitance change : Within ±12.5% (BJ, B7, C6, C7), Within ±30% (F)


[Test Methods and Remarks]

Multilayer Ceramic Capacitors

	Board	Thickness	Warp	Duration
042, 063 Type	glass epoxy-resin substrate	0.8mm	1mm	10 sec.
105 Type or more		1.6mm		

Array Type

	Board	Thickness	Warp	Duration
096, 110, 212 Type	glass epoxy-resin substrate	1.6mm	1mm	10 sec.



Capacitance measurement shall be conducted with the board bent (Unit: mm)

10. Body Strength


Specified Value	Temperature Compensating (Class 1)	Standard	—
		High Frequency Type	No mechanical damage.
Specified Value	High Permittivity (Class 2)		—

[Test Methods and Remarks]

High Frequency Type

Applied force: 5N

Duration: 10 sec.



11. Adhesive Strength of Terminal Electrodes

Specified Value	Temperature Compensating (Class 1)	Standard	—
		High Frequency Type	No terminal separation or its indication.
Specified Value	High Permittivity (Class 2)		—


[Test Methods and Remarks]

Multilayer Ceramic Capacitors

	Applied force	Duration
042, 063 Type	2N	30±5 sec.
105 Type or more	5N	

Array Type

	Applied force	Duration
096 Type	2N	30±5 sec.
110, 212 Type	5N	



12. Solderability

Specified Value	Temperature Compensating (Class 1)	Standard	—
		High Frequency Type	At least 95% of terminal electrode is covered by new solder.
Specified Value	High Permittivity (Class 2)		—

[Test Methods and Remarks]

	Solder type	Solder temperature	Duration
Eutectic solder	H60A or H63A	230±5°C	4±1 sec.
Lead-free solder	Sn-3.0Ag-0.5Cu	245±3°C	

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

13. Resistance to Soldering

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance: No abnormality Capacitance change: Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, whichever is larger. Q: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality
		High Frequency Type	Appearance: No abnormality Capacitance change: Within $\pm 2.5\%$ Q: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality
	High Permittivity (Class 2) Note 1		Appearance: No abnormality Capacitance change: Within $\pm 7.5\%$ (BJ, B7, C6, C7) Within $\pm 20\%$ (F) Dissipation factor: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality

【Test Methods and Remarks】

Class 1

	042, 063 Type	105 Type Array (096, 110 Type)
Preconditioning	None	
Preheating	150°C, 1 to 2 min.	80 to 100°C, 2 to 5 min. 150 to 200°C, 2 to 5 min.
Solder temperature	270 $\pm$ 5°C	
Duration	3 $\pm$ 0.5 sec.	
Recovery	6 to 24 hrs (Standard condition) Note 5	

Class 2

	042, 063 Type	105, 107, 212 Type Array (096, 110, 212 Type)	316, 325 Type
Preconditioning	Thermal treatment (at 150°C for 1 hr) Note 2		
Preheating	150°C, 1 to 2 min.	80 to 100°C, 2 to 5 min. 150 to 200°C, 2 to 5 min.	80 to 100°C, 5 to 10 min. 150 to 200°C, 5 to 10 min.
Solder temperature	270 $\pm$ 5°C		
Duration	3 $\pm$ 0.5 sec.		
Recovery	24 $\pm$ 2 hrs (Standard condition) Note 5		

14. Temperature Cycle (Thermal Shock)

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance: No abnormality Capacitance change: Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, whichever is larger. Q: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality
		High Frequency Type	Appearance: No abnormality Capacitance change: Within $\pm 0.25\text{pF}$ Q: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality
	High Permittivity (Class 2) Note 1		Appearance: No abnormality Capacitance change: Within $\pm 7.5\%$ (BJ, B7, C6, C7) Within $\pm 20\%$ (F) Dissipation factor: Initial value Insulation resistance: Initial value Withstanding voltage (between terminals): No abnormality

【Test Methods and Remarks】

	Class 1	Class 2
Preconditioning	None	Thermal treatment (at 150°C for 1 hr) Note 2
1 cycle	Step	Temperature (°C)
	1	Minimum operating temperature +0/−3
	2	Room temperature
	3	Maximum operating temperature +0/−3
	4	Room temperature
Number of cycles	5 times	
Recovery	6 to 24 hrs (Standard condition) Note 5	24 $\pm$ 2 hrs (Standard condition) Note 5

15. Humidity (Steady State)

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance: No abnormality Capacitance change: Within $\pm 5\%$ or $\pm 0.5\text{pF}$, whichever is larger. Q: $C < 10\text{pF}$: $Q \geq 200 + 10C$ $10 \leq C < 30\text{pF}$: $Q \geq 275 + 2.5C$ $C \geq 30\text{pF}$: $Q \geq 350$ (C : Nominal capacitance) Insulation resistance: 1000 MΩ min.
		High Frequency Type	Appearance: No abnormality Capacitance change: Within $\pm 0.5\text{pF}$ Insulation resistance: 1000 MΩ min.
	High Permittivity (Class 2) Note 1		Appearance: No abnormality Capacitance change: Within $\pm 12.5\%$ (BJ, B7, C6, C7) Within $\pm 30\%$ (F) Dissipation factor: 5.0% max. (BJ, B7, C6, C7) 11.0% max. (F) Insulation resistance: 50 MΩμF or 1000 MΩ whichever is smaller.

【Test Methods and Remarks】

Class 1

	Standard	High Frequency Type
Preconditioning	None	
Temperature	40 $\pm$ 2°C	60 $\pm$ 2°C
Humidity	90 to 95%RH	
Duration	500+24/−0 hrs	
Recovery	6 to 24 hrs (Standard condition) Note 5	

Class 2

	All items
Preconditioning	Thermal treatment (at 150°C for 1 hr) Note 2
Temperature	40 $\pm$ 2°C
Humidity	90 to 95%RH
Duration	500+24/−0 hrs
Recovery	24 $\pm$ 2 hrs (Standard condition) Note 5

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

16. Humidity Loading

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance: No abnormality Capacitance change: Within $\pm 7.5\%$ or $\pm 0.75\text{pF}$, whichever is larger. Q : $C < 30\text{pF}$: $Q \geq 100 + 10C/3$ $C \geq 30\text{pF}$: $Q \geq 200$ (C : Nominal capacitance) Insulation resistance: 500 M Ω min.
		High Frequency Type	Appearance: No abnormality Capacitance change: $C \leq 2\text{pF}$: Within $\pm 0.4\text{pF}$ $C > 2\text{pF}$: Within $\pm 0.75\text{pF}$ (C : Nominal capacitance) Insulation resistance: 500 M Ω min.
	High Permittivity (Class 2) Note 1		Appearance: No abnormality Capacitance change: Within $\pm 12.5\%$ (BJ, B7, C6, C7) Within $\pm 30\%$ (F) Dissipation factor : 5.0% max. (BJ, B7, C6, C7) 11.0% max. (F) Insulation resistance: 25 M $\Omega\mu\text{F}$ or 500 M Ω , whichever is smaller.

【Test Methods and Remarks】

Class 1

	Standard	High Frequency Type
Preconditioning	None	
Temperature	$40 \pm 2^\circ\text{C}$	$60 \pm 2^\circ\text{C}$
Humidity	90 to 95%RH	
Duration	$500 + 24/-0$ hrs	
Applied voltage	Rated voltage	
Charge/discharge current	50mA max.	
Recovery	6 to 24 hrs (Standard condition) Note 5	

Class 2

	All items
Preconditioning	Voltage treatment (Rated voltage are applied for 1 hour at 40°C) Note 3
Temperature	$40 \pm 2^\circ\text{C}$
Humidity	90 to 95%RH
Duration	$500 + 24/-0$ hrs
Applied voltage	Rated voltage
Charge/discharge current	50mA max.
Recovery	24 ± 2 hrs (Standard condition) Note 5

17. High Temperature Loading

Specified Value	Temperature Compensating (Class 1)	Standard	Appearance: No abnormality Capacitance change: Within $\pm 3\%$ or $\pm 0.3\text{pF}$, whichever is larger. Q : $C < 10\text{pF}$: $Q \geq 200 + 10C$ $10 \leq C < 30\text{pF}$: $Q \geq 275 + 2.5C$ $C \geq 30\text{pF}$: $Q \geq 350$ (C : Nominal capacitance) Insulation resistance: 1000 M Ω min.
		High Frequency Type	Appearance: No abnormality Capacitance change: Within $\pm 3\%$ or $\pm 0.3\text{pF}$, whichever is larger. Insulation resistance: 1000 M Ω min.
	High Permittivity (Class 2) Note 1		Appearance: No abnormality Capacitance change: Within $\pm 12.5\%$ (BJ, B7, C6, C7) Within $\pm 30\%$ (F) Dissipation factor : 5.0% max. (BJ, B7, C6, C7) 11.0% max. (F) Insulation resistance: 50 M $\Omega\mu\text{F}$ or 1000 M Ω , whichever is smaller.

【Test Methods and Remarks】

Class 1

	Standard	High Frequency Type
Preconditioning	None	
Temperature	$125 \pm 3^\circ\text{C}$	
Duration	$1000 + 48/-0$ hrs	
Applied voltage	Rated voltage $\times 2$	
Charge/discharge current	50mA max.	
Recovery	6 to 24hr (Standard condition) Note 5	

Class 2

	BJ, F	C6	B7, C7
Preconditioning	Voltage treatment (Twice the rated voltage shall be applied for 1 hour at 85°C , 105°C or 125°C) Note 3, 4		
Temperature	$85 \pm 2^\circ\text{C}$	$105 \pm 3^\circ\text{C}$	$125 \pm 3^\circ\text{C}$
Duration	$1000 + 48/-0$ hrs		
Applied voltage	Rated voltage $\times 2$ Note 4		
Charge/discharge current	50mA max.		
Recovery	24 ± 2 hrs (Standard condition) Note 5		

Note 1 The figures indicate typical specifications. Please refer to individual specifications in detail.

Note 2 Thermal treatment : Initial value shall be measured after test sample is heat-treated at $150 \pm 0/-10^\circ\text{C}$ for an hour and kept at room temperature for 24 ± 2 hours.

Note 3 Voltage treatment : Initial value shall be measured after test sample is voltage-treated for an hour at both the temperature and voltage specified in the test conditions, and kept at room temperature for 24 ± 2 hours.

Note 4 Standard condition: Temperature: 5 to 35°C , Relative humidity: 45 to 85 % RH, Air pressure: 86 to 106kPa
When there are questions concerning measurement results, in order to provide correlation data, the test shall be conducted under the following condition.
Temperature: $20 \pm 2^\circ\text{C}$, Relative humidity: 60 to 70 % RH, Air pressure: 86 to 106kPa
Unless otherwise specified, all the tests are conducted under the "standard condition".

PRECAUTIONS

Precautions on the use of Multilayer Ceramic Capacitors

1. Circuit Design

- ◆ Verification of operating environment, electrical rating and performance
 1. A malfunction of equipment in fields such as medical, aerospace, nuclear control, etc. may cause serious harm to human life or have severe social ramifications. Therefore, any capacitors to be used in such equipment may require higher safety and reliability, and shall be clearly differentiated from them used in general purpose applications.
- ◆ Operating Voltage (Verification of Rated voltage)
 1. The operating voltage for capacitors must always be their rated voltage or less.
 If an AC voltage is loaded on a DC voltage, the sum of the two peak voltages shall be the rated voltage or less.
 For a circuit where an AC or a pulse voltage may be used, the sum of their peak voltages shall also be the rated voltage or less.
2. Even if an applied voltage is the rated voltage or less reliability of capacitors may be deteriorated in case that either a high frequency AC voltage or a pulse voltage having rapid rise time is used in a circuit.

2. PCB Design

- ◆ Pattern configurations (Design of Land-patterns)
 1. When capacitors are mounted on PCBs, the amount of solder used (size of fillet) can directly affect the capacitor performance. Therefore, the following items must be carefully considered in the design of land patterns:
 (1) Excessive solder applied can cause mechanical stresses which lead to chip breaking or cracking. Therefore, please consider appropriate land-patterns for proper amount of solder.
- (2) When more than one component are jointly soldered onto the same land, each component's soldering point shall be separated by solder-resist.
- ◆ Pattern configurations (Capacitor layout on PCBs)
 After capacitors are mounted on boards, they can be subjected to mechanical stresses in subsequent manufacturing processes (PCB cutting, board inspection, mounting of additional parts, assembly into the chassis, wave soldering of the boards, etc.). For this reason, land pattern configurations and positions of capacitors shall be carefully considered to minimize stresses.

- ◆ Pattern configurations (Design of Land-patterns)
 The following diagrams and tables show some examples of recommended land patterns to prevent excessive solder amounts.

(1) Recommended land dimensions for typical chip capacitors

- Multilayer Ceramic Capacitors : Recommended land dimensions (unit: mm)
 Wave-soldering

Type		107	212	316	325
Size	L	1.6	2.0	3.2	3.2
	W	0.8	1.25	1.6	2.5
A		0.8 to 1.0	1.0 to 1.4	1.8 to 2.5	1.8 to 2.5
B		0.5 to 0.8	0.8 to 1.5	0.8 to 1.7	0.8 to 1.7
C		0.6 to 0.8	0.9 to 1.2	1.2 to 1.6	1.8 to 2.5

Reflow-soldering

Type	042	063	105	107	212	316	325	432
Size	L	0.4	0.6	1.0	1.6	2.0	3.2	4.5
	W	0.2	0.3	0.5	0.8	1.25	1.6	2.5
A	0.15 to 0.25	0.20 to 0.30	0.45 to 0.55	0.8 to 1.0	0.8 to 1.2	1.8 to 2.5	1.8 to 2.5	2.5 to 3.5
B	0.15 to 0.20	0.20 to 0.30	0.40 to 0.50	0.6 to 0.8	0.8 to 1.2	1.0 to 1.5	1.0 to 1.5	1.5 to 1.8
C	0.15 to 0.30	0.25 to 0.40	0.45 to 0.55	0.6 to 0.8	0.9 to 1.6	1.2 to 2.0	1.8 to 3.2	2.3 to 3.5

- LWDC: Recommended land dimensions for reflow-soldering (unit: mm)

Type	105	107	212	
Size	L	0.52	0.8	1.25
	W	1.0	1.6	2.0
A	0.18 to 0.22	0.25 to 0.3	0.5 to 0.7	
B	0.2 to 0.25	0.3 to 0.4	0.4 to 0.5	
C	0.9 to 1.1	1.5 to 1.7	1.9 to 2.1	

(unit: mm)






- Array type: Recommended land dimensions for reflow-soldering (unit: mm)

Type	096 (2 circuits)	110 (2 circuits)	212 (2 circuits)	212 (4 circuits)
Size	L	0.9	1.37	2.0
	W	0.6	1.0	1.25
a	0.25 to 0.35	0.35 to 0.45	0.5 to 0.6	0.5 to 0.6
b	0.15 to 0.25	0.55 to 0.65	0.5 to 0.6	0.5 to 0.6
c	0.15 to 0.25	0.3 to 0.4	0.5 to 0.6	0.2 to 0.3
d	0.45	0.64	1.0	0.5

(2) Examples of good and bad solder application

Items	Not recommended	Recommended
Mixed mounting of SMD and leaded components	Lead wire of component	Solder-resist
Component placement close to the chassis	Chassis Solder (for grounding) Land	Solder-resist
Hand-soldering of leaded components near mounted components	Lead wire of component Soldering iron	Solder-resist
Horizontal component placement		Solder-resist

Land patterns for PCBs



To next page

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
 For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.



PRECAUTIONS

Precautions on the use of Multilayer Ceramic Capacitors

2. PCB Design


◆Pattern configurations (Capacitor layout on PCBs)

1-1. The following are examples of good and bad capacitor layouts ; capacitors shall be located to minimize any possible mechanical stresses from board warp or deflection.

Items	Not recommended	Recommended
Deflection of board		 Position the component at a right angle to the direction of the mechanical stresses that are anticipated.

Technical considerations

1-2. The amount of mechanical stresses given will vary depending on capacitor layout. Please refer to diagram below.



1-3. When PCB is split, the amount of mechanical stress on the capacitors can vary according to the method used. The following methods are listed in order from least stressful to most stressful: push-back, slit, V-grooving, and perforation. Thus, please consider the PCB, split methods as well as chip location.

3. Mounting

◆Adjustment of mounting machine

- When capacitors are mounted on PCB, excessive impact load shall not be imposed on them.
- Maintenance and inspection of mounting machines shall be conducted periodically.

Precautions




◆Selection of Adhesives

- When chips are attached on PCBs with adhesives prior to soldering, it may cause capacitor characteristics degradation unless the following factors are appropriately checked : size of land patterns, type of adhesive, amount applied, hardening temperature and hardening period. Therefore, please contact us for further information.

◆Adjustment of mounting machine

- When the bottom dead center of a pick-up nozzle is too low, excessive force is imposed on capacitors and causes damages. To avoid this, the following points shall be considerable.

- The bottom dead center of the pick-up nozzle shall be adjusted to the surface level of PCB without the board deflection.
- The pressure of nozzle shall be adjusted between 1 and 3 N static loads.
- To reduce the amount of deflection of the board caused by impact of the pick-up nozzle, supporting pins or back-up pins shall be used on the other side of the PCB. The following diagrams show some typical examples of good and bad pick-up nozzle placement:

Items	Not recommended	Recommended
Single-sided mounting		
Double-sided mounting		

Technical considerations

- As the alignment pin is worn out, adjustment of the nozzle height can cause chipping or cracking of capacitors because of mechanical impact on the capacitors. To avoid this, the monitoring of the width between the alignment pins in the stopped position, maintenance, check and replacement of the pin shall be conducted periodically.

◆Selection of Adhesives

Some adhesives may cause IR deterioration. The different shrinkage percentage of between the adhesive and the capacitors may result in stresses on the capacitors and lead to cracking. Moreover, too little or too much adhesive applied to the board may adversely affect components. Therefore, the following precautions shall be noted in the application of adhesives.



(1) Required adhesive characteristics

- The adhesive shall be strong enough to hold parts on the board during the mounting & solder process.
- The adhesive shall have sufficient strength at high temperatures.
- The adhesive shall have good coating and thickness consistency.
- The adhesive shall be used during its prescribed shelf life.
- The adhesive shall harden rapidly.
- The adhesive shall have corrosion resistance.
- The adhesive shall have excellent insulation characteristics.
- The adhesive shall have no emission of toxic gasses and no effect on the human body.

(2) The recommended amount of adhesives is as follows;

[Recommended condition]

Figure	212/316 case sizes as examples
a	0.3mm min
b	100 to 120 μ m
c	Adhesives shall not contact land



PRECAUTIONS

Precautions on the use of Multilayer Ceramic Capacitors

4. Soldering

Precautions

◆Selection of Flux

Since flux may have a significant effect on the performance of capacitors, it is necessary to verify the following conditions prior to use;

- (1) Flux used shall be less than or equal to 0.1 wt% (in Cl equivalent) of halogenated content. Flux having a strong acidity content shall not be applied.
- (2) When shall capacitors are soldered on boards, the amount of flux applied shall be controlled at the optimum level.
- (3) When water-soluble flux is used, special care shall be taken to properly clean the boards.

◆Soldering

Temperature, time, amount of solder, etc. shall be set in accordance with their recommended conditions.

Sn-Zn solder paste can adversely affect MLCC reliability.
Please contact us prior to usage of Sn-Zn solder.

◆Selection of Flux

1-1. When too much halogenated substance (Chlorine, etc.) content is used to activate flux, or highly acidic flux is used, it may lead to corrosion of terminal electrodes or degradation of insulation resistance on the surfaces of the capacitors.

1-2. Flux is used to increase solderability in wave soldering. However if too much flux is applied, a large amount of flux gas may be emitted and may adversely affect the solderability. To minimize the amount of flux applied, it is recommended to use a flux-bubbling system.


1-3. Since the residue of water-soluble flux is easily dissolved in moisture in the air, the residues on the surfaces of capacitors in high humidity conditions may cause a degradation of insulation resistance and reliability of the capacitors. Therefore, the cleaning methods and the capability of the machines used shall also be considered carefully when water-soluble flux is used.

◆Soldering



- Ceramic chip capacitors are susceptible to thermal shock when exposed to rapid or concentrated heating or rapid cooling.
- Therefore, the soldering must be conducted with great care so as to prevent malfunction of the components due to excessive thermal shock.
- Preheating : Capacitors shall be preheated sufficiently, and the temperature difference between the capacitors and solder shall be within 100 to 130°C.
- Cooling : The temperature difference between the capacitors and cleaning process shall not be greater than 100°C.

[Reflow soldering]

[Recommended conditions for eutectic soldering]



[Recommended condition for Pb-free soldering]




Caution

- ① The ideal condition is to have solder mass (fillet) controlled to 1/2 to 1/3 of the thickness of a capacitor.
- ② Because excessive dwell times can adversely affect solderability, soldering duration shall be kept as close to recommended times as possible.


Technical considerations

[Wave soldering]

[Recommended conditions for eutectic soldering]



[Recommended condition for Pb-free soldering]




Caution



- ① Wave soldering must not be applied to capacitors designated as for reflow soldering only.

[Hand soldering]

[Recommended conditions for eutectic soldering]



[Recommended condition for Pb-free soldering]



Caution

- ① Use a 50W soldering iron with a maximum tip diameter of 1.0 mm.
- ② The soldering iron shall not directly touch capacitors.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

■ PRECAUTIONS

Precautions on the use of Multilayer Ceramic Capacitors

5. Cleaning	
Precautions	◆Cleaning conditions - When PCBs are cleaned after capacitors mounting, Please select the appropriate cleaning solution in accordance with the intended use of the cleaning. (e.g. to remove soldering flux or other materials from the production process.) - Cleaning condition shall be determined after it is verified by using actual cleaning machine that the cleaning process does not affect capacitor's characteristics.
Technical considerations	- The use of inappropriate cleaning solutions can cause foreign substances such as flux residue to adhere to capacitors or deteriorate their outer coating, resulting in a degradation of the capacitor's electrical properties (especially insulation resistance). - Inappropriate cleaning conditions (insufficient or excessive cleaning) may adversely affect the performance of the capacitors. In the case of ultrasonic cleaning, too much power output can cause excessive vibration of PCBs which may lead to the cracking of capacitors or the soldered portion, or decrease the terminal electrodes' strength. Therefore, the following conditions shall be carefully checked; Ultrasonic output : 20 W/l or less Ultrasonic frequency : 40 kHz or less Ultrasonic washing period : 5 min. or less
6. Resin coating and mold	
Precautions	- With some type of resins, decomposition gas or chemical reaction vapor may remain inside the resin during the hardening period or while left under normal storage conditions resulting in the deterioration of the capacitor's performance. - When a resin's hardening temperature is higher than capacitor's operating temperature, the stresses generated by the excessive heat may lead to damage or destruction of capacitors. The use of such resins, molding materials etc. is not recommended.
7. Handling	
Precautions	◆Splitting of PCB - When PCBs are split after components mounting, care shall be taken so as not to give any stresses of deflection or twisting to the board. - Board separation shall not be done manually, but by using the appropriate devices. ◆Mechanical considerations Be careful not to subject capacitors to excessive mechanical shocks. - If ceramic capacitors are dropped onto a floor or a hard surface, they shall not be used. - Please be careful that the mounted components do not come in contact with or bump against other boards or components.
8. Storage conditions	
Precautions	◆Storage - To maintain the solderability of terminal electrodes and to keep packaging materials in good condition, care must be taken to control temperature and humidity in the storage area. Humidity should especially be kept as low as possible. •Recommended conditions Ambient temperature : Below 30°C Humidity : Below 70% RH The ambient temperature must be kept below 40°C. Even under ideal storage conditions, solderability of capacitor is deteriorated as time passes, so capacitors shall be used within 6 months from the time of delivery. •Ceramic chip capacitors shall be kept where no chlorine or sulfur exists in the air. - The capacitance values of high dielectric constant capacitors will gradually decrease with the passage of time. So care shall be taken to design circuits. Even if capacitance value decreases as time passes, it will get back to the initial value by a heat treatment at 150°C for 1hour.
Technical considerations	If capacitors are stored in a high temperature and humidity environment, it might rapidly cause poor solderability due to terminal oxidation and quality loss of taping/packaging materials. For this reason, capacitors shall be used within 6 months from the time of delivery. If exceeding the above period, please check solderability before using the capacitors.

* This catalog contains the typical specification only due to the limitation of space. When you consider purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) or CD catalogs.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

⊖ View [LMK042B7102KC-FW](#) on WIN SOURCE

⊖ [Taiyo Yuden](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management