



**THE DATASHEET OF  
AF1206F15.0TM**



## AirMatrix<sup>®</sup> Surface Mount Fuses

### AF1206F Series (Fast Acting, 1206 Size)



#### Features:

- Fast acting at 250% overload current level
- Excellent inrush current withstanding capability
- Extremely thin body for space saving
- Much safer with wire-in-air design
- Fiberglass enforced epoxy fuse body
- Copper termination with nickel and tin plating

#### Clearing Time Characteristics:


% of current rating	Clearing time at 25°C	
	Min.	Max.
100%	4 hours	-
250%	-	5 seconds

#### Shape and Dimensions:

Unit	Inch	mm
L	0.126 ± 0.008	3.20 ± 0.20
W	0.063 + 0.012 / -0.004	1.60 + 0.30 / -0.20
T	0.042 ± 0.006	1.08 ± 0.15
B	0.033 ± 0.012	0.85 ± 0.30

#### Applications:

- Notebook
- Backlight driver
- DC/DC converter
- Low voltage lighting power
- Automotive electronics
- Power adapter
- Panel & Battery pack
- Server & Medical device



#### Ordering Information:

Part Number	Current Rating (A)	Voltage Rating (V DC)	Interrupting Rating	Nominal Cold DCR ( $\Omega$ ) <sup>1</sup>	Nominal $I^2t$ (A <sup>2</sup> s)	Agency Approval (TUV)	Marking <sup>3</sup>
AF1206F1.50TM	1.50	65	50A@65V DC	0.050	0.37	✓	G
AF1206F1.60TM	1.60			0.043	0.52	✓	T
AF1206F2.00TM	2.00			0.032	0.88	✓	I
AF1206F2.50TM	2.50			0.028	1.10	✓	J
AF1206F3.00TM	3.00			0.022	1.90	✓	K
AF1206F3.15TM	3.15			0.020	2.20	✓	V
AF1206F3.50TM	3.50			0.018	2.60		L
AF1206F4.00TM	4.00			0.016	3.30	✓	M
AF1206F5.00TM	5.00	32	50A@32V DC	0.0130	5.40	✓	N
AF1206F6.30TM	6.30			0.0100	8.90	✓	O
AF1206F7.00TM	7.00			0.0092	10.4		P
AF1206F8.00TM	8.00			0.0084	13.5	✓	R
AF1206F10.0TM	10.0			0.0050	11.2	✓	Q
AF1206F12.0TM	12.0			0.0041	15.0		X
AF1206F15.0TM	15.0			0.0035	24.5	✓	Y


1. Measured at ≤10% rated current and 25 °C ambient

2. Melting  $I^2t$  at 0.001 second pre-arcing time.

3. White marking character code.


**AirMatrix<sup>®</sup> Surface Mount Fuses**  
**AF1206F Series (Fast Acting, 1206 Size)**

**Average Pre-arcing Time Curves:**



**AirMatrix<sup>®</sup> Surface Mount Fuses**  
**AF1206F Series (Fast Acting, 1206 Size)**

**Average  $I^2t$  vs.  $t$  Curves:**




## AirMatrix<sup>®</sup> Surface Mount Fuses

### AF1206F Series (Fast Acting, 1206 Size)

#### Temperature De-rating:

The ambient temperature affects the current carrying capacity of fuses. When a fuse is operating at a temperature higher than 25°C, the fuse shall be “de-rated” according to the de-rating curve.



#### Operating Temperature Range:

- 55°C ~+125°C (with de-rating)

#### Product Identification:

**AF 1206 F 1.50 T M**

(1) (2) (3) (4) (5)(6)

- Series Code:** AF Series
- Size Code:** L x W (inch), the first two digits - L (length), the last two digits - W (width)
- Characteristic Code:** F - Fast Acting
- Current Rating Code:** 1.50 - 1.50A
- Package Code:** T - Tape & Reel, B - Bulk
- Marking Code:** M - With marking

#### Agency Approval:

- Recognized Under the Components Program of Underwriters Laboratories. Certification #: UL-E232989
- TUV File Number: 50425087 (1.5-8A), 50425128 (10-15A)

#### Reliability Tests:


No.	Item	Condition	Criteria
1	Bend	2 mm bend	DCR change within $\pm 20\%$ ( $\pm 10\%$ for $\leq 1A$ ), no mechanical damage
2	Solderability	245°C, 5 seconds	New solder coverage $\geq 95\%$
3	Soldering Heat Resistance	260°C, 10 seconds	DCR change within $\pm 20\%$ ( $\pm 10\%$ for $\leq 1A$ ), new solder coverage 75% minimum, no mechanical damage
4	Terminal Strength	Gradually apply 1.8 kg force to the bottom of the part for 60 seconds	DCR change within $\pm 20\%$ , no mechanical damage
5	Life	80% rated current (75% for $< 1A$ ), 2000 hours, ambient temperature +20°C to +30°C	Voltage drop change within $\pm 10\%$
6	Thermal Shock	-65°C to +125°C, 100 cycles	DCR change within $\pm 10\%$ , no mechanical damage
7	Mechanical Vibration	5 – 3000 Hz, 0.4 inch double amplitude or 30 G peak	DCR change within $\pm 10\%$ , no mechanical damage
8	Mechanical Shock	1500 G, 0.5 milliseconds, half-sine shocks	DCR change within $\pm 10\%$ , no mechanical damage
9	Salt Spray	5% salt solution, 48 hours exposure	DCR change within $\pm 10\%$ , no excessive corrosion
10	Moisture Resistance	10 cycles	DCR change within $\pm 10\%$ , no excessive corrosion

## AirMatrix<sup>®</sup> Surface Mount Fuses

### AF1206F Series (Fast Acting, 1206 Size)

#### Recommended Land Pattern:


Chip Size	1206	Unit
L	0.173 (4.40)	Inch (mm)
G	0.059 (1.50)	Inch (mm)
H	0.071 (1.80)	Inch (mm)



#### Recommended Temperature Profile:

Profile Feature	Pb-Free Assembly
<b>Preheat/Soak</b>	
Temperature Min ( $T_{smin}$ )	150°C
Temperature Max ( $T_{smax}$ )	200°C
Time ( $t_s$ ) from ( $T_{smin}$ to $T_{smax}$ )	60~120 seconds
Ramp-up rate ( $T_L$ to $T_p$ )	3°C/second max.
Liquidous temperature ( $T_L$ )	217°C
Time ( $t_L$ ) maintained above $T_L$	60~150 seconds
Peak package body temperature ( $T_p$ )	260°C
Time ( $t_p$ )*within 5°C of the specified classification temperature ( $T_c$ )	30 seconds *
Ramp-down rate ( $T_p$ to $T_L$ )	6°C/second max.
Time 25°C to peak temperature	8 minutes max.
* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum	

#### \* Recommended Temperature Profile for Reflow Soldering



#### Recommended conditions for hand soldering:

- Appropriate temperature (max.) of soldering iron tip/soldering time (max.): 280°C / 10 s or 350°C / 3 s
- Using hot air rework station with tip that can melt the solder on both terminations at the same time is strongly recommended. Do not directly contact the chip termination with the tip of soldering iron.

#### Storage:

- The maximum ambient temperature shall not exceed 35°C. Storage temperatures higher than 35°C could result in the deformation of packaging materials.
- The maximum relative humidity recommended for storage is 75%. High humidity with high temperature can accelerate the oxidation of the solder plating on the termination and reduce the solderability of the components.
- The products shall not be stored in areas where harmful gases containing sulfur or chlorine are present.
- MSL=1

#### Packaging:

Chip Size	Parts on 13 inch (330 mm) Reel
1206	3,500

## Disclaimer

*Specifications are subject to change without notice. AEM products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive, aerospace, medical, life-saving applications, or any other application which requires especially high reliability for the prevention of such defect as may directly cause damage to the third party's life, body or property) not expressly set forth in applicable AEM product documentation. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Warranties granted by AEM shall be deemed void for products used for any purpose not expressly set forth in applicable AEM product documentation. AEM shall not be liable for any claims or damages arising out of products used in applications not expressly intended by AEM as set forth in applicable AEM product documentation. The sale and use of AEM products is subject to AEM terms and conditions of sale. Please refer to AEM's website for updated catalog and terms and conditions of sale.*



### **AEM Components (Suzhou) Co., Ltd**

**461 Zhongnan Street,  
China-Singapore Suzhou Industrial Park  
Jiangsu, P. R. China, 215026**

Tel: 86-512-6258-0028  
Fax: 86-512-6258-0018  
Email: [marketing@aemchina.com](mailto:marketing@aemchina.com)

### **AEM Components (USA), Inc.**

**6670 Cobra Way, San Diego, CA 92121, USA**

Tel: 1-858-750-6100  
Fax: 1-858-481-1123  
Email: [sales@aemcomponents.com](mailto:sales@aemcomponents.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View AF1206F15.0TM](#) on WIN SOURCE

 [AEM Inc](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management