



**THE DATASHEET OF
M81714/11-20D**



Product Description

Built and qualified to AS81714, ThermoKonnnect Single Wire Splices provide a reliable and maintainable connection for two-wire applications.

While standard TJS are pictured, ThermoKonnnect is happy to customize designs to your unique specifications.

*All use the standard M39029/1 pin contact.

Performance Specifications

DIELECTRIC WITHSTANDING VOLTAGE:

Sea Level: 1,500 VRMS
70,000 ft: 600 VRMS

INSULATION RESISTANCE:

5,000 megohms at 25°C

TEMPERATURE RATING:

-65°C to +200°C

CURRENT RATING:

Contact Size
 22 5 amps
 20 7.5 amps
 16 13 amps

Materials

INSULATOR BODY:

Copper Alloy

INTERNAL CONTACT:

Copper Alloy / Gold Finish, MIL-G-45204

GROMMET:

Silicone Elastomer



Single-Wire Splices

Bussing Type



MIL P/N 81714	WIRE SIZE	CONTACTS		GROMMET SEALING RANGE	
		P/N 39029	QTY	MAX	MIN
11-16D	16-20	/1-102	2	.109	.065
11-20D	20-24	/1-101	2	.083	.040
11-22D	22-26	/1-100	2	.060	.030

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [⊖ View M81714/11-20D on WIN SOURCE](#)
- [⊖ Manufacturer Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management