





**THE DATASHEET OF
BF22140-24B**





JKL PART NUMBER	-A- LENGTH	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) TYPICAL
BF2261-24B	61±1.5	RGB HIGH OUTPUT WHITE 8400° KELVIN	600 @ 0°C	200	5 ± 1	38,000±10%	50,000
BF22140-24B	140±3.0		990 @ 0°C	330	5 ± 1	38,000±10%	50,000
BF22160-24B	160±3.0		1065 @ 0°C	355	5 ± 1	38,000±10%	50,000
BF22258-24B	258 ^{+3.0} _{-0.0}		1600 @ 0°C	535	5 ± 1	38,000±10%	50,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
D RATED LIFE HRS. TO TYPICAL & 20,000 TO 50,000 8/19/09 C ADD MINIMUM TO RATED LIFE HRS. 7/16/09 B ADD BF2261-24B 6/19/04 A CORRECTION ON LENGTH DIM. 10/7/03 RELEASED TO CAD MULTI LIST 8/18/03		THIRDS ANGLE PROJECTION DRAWN BY L. WENGSTROM APPV'D BY L.R. DATE 8/19/09		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		SIZE A FSCM NO. 55335 DRAWING NO. BF 22-24B	
REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 8/18/03 REVISION DATE 8/19/09 REV. NO. D SHEET 1 OF 1	

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View BF22140-24B on WIN SOURCE](#)
- ⊖ [JKL Components Corp. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management