



THE DATASHEET OF
209159003101116



HORIZONTAL SOCKET BOARD-TO-BOARD: 20-9159-100



General Information



The 9159 Series board-to-board interconnect system allows two PCBs to be mated end-to-end to create LED lighting strips. Designed specifically for the unique Solid State Lighting (SSL) market that requires coplanar (horizontal-to-horizontal) board mating with a 5 amp current rating in the smallest package available. These single sided SMT connectors are perfect for both FR4 and metal boards where you need to mate the boards together to minimize separation. Available in both white and black insulation colors, they are ideal for both lighting and industrial applications. With sizes from 2p-6p, these high reliability connectors feature gold plated beryllium copper receptacle contacts for harsh environments.

APPLICATIONS

- Coplanar PCB mating in SSL products
- LED linear lighting strips
- Application Notes: Refer to 201-01-123
- Product Specification: Refer to 201-01-119

FEATURES AND BENEFITS

- Single sided SMT: supports FR4 and metal PCB's
- 5 Amp current rating: exceeds general market needs
- 5.5mm mated width: minimizes PCB space to decrease LED pitch
- Gold plated BeCu spring contacts: reliability for harsh environments
- Optional retaining clip: provides positive connector mating during vibration
- Available in white: supports SSL market preferences
- UL Approved

ELECTRICAL

- Current Rating: 5 Amps / Contact
- Voltage Rating: 125 VAC (RMS) or DC equivalent

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C
- Storage Temperature: -40°C to +70°C

MECHANICAL

- Insulator Material: Nylon: UL94V0
- Contact Material: BeCu
- Plating: Gold / Tin over Nickel
- Durability: 10 Cycles

HOW TO ORDER

20
Prefix
Socket

9159
Series

00X
Number of Ways
002 = 2
003 = 3
004 = 4
005 = 5
006 = 6

1
2 Part
PCB Strip
Connector

01
Connector
Pitch
01 = 3mm

X
Color
8 = Black
9 = White

16
Plating Option

Code	Contact	Bracket
16	Gold in Contact Area Gold on Solder Tail	Tin all over



SALES DRAWINGS
CLICK TO DOWNLOAD

Safety Standards: UL 1977-File #E90723



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 209159003101116 on WIN SOURCE](#)

 [AVX Corp/Kyocera Corp](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management