











THE DATASHEET OF BLN-PVRJ45-1



CCTV Baluns/Isolators/Hubs

By using a balun at each end of a UTP cable you can obtain:

- Lower material cost (CAT5 versus coax cable)
- Reduced install labor (pull time or cable may already be there)
- Longer cable runs (passive up to 2000 feet, active up to 1.5 miles)
- More versatile (4 cameras on 1 CAT5 cable)
- Future proofs system (can IP address the entire analog system plus cable in place for full IP digital system upgrade)

 <p>BLN-AT CCTV Balun, Active, Transmitter</p>	<p>PAIR</p>  <p>BLN-MTPT2 CCTV Balun, BNC Male and BNC Pigtail to Screw Terminal</p> <p>Distance: Up to 2500m (8200ft)</p>	<p>PAIR</p>  <p>BLN-PCVRJ452 CCTV Balun, Video / Power with Female Power Contact</p> <p>Distance: Up to 200m (650ft)</p>	 <p>BLN-PVRJ45-1 CCTV Balun, BNC Male with Power Lead to RJ45 Female, all pigtailed</p> <p>Distance: Up to 2500m (8200ft)</p>
<p>PAIR</p>  <p>BLN-PVRJ452 CCTV Balun, BNC Male with Power Lead to RJ45 Female, all pigtailed</p> <p>Distance: Up to 2500m (8200ft)</p>	<p>PAIR</p>  <p>BLN-RJ452 CCTV Balun, BNC Male to RJ45 Female</p> <p>Distance: Up to 2500m (8200ft)</p>	 <p>BLN-RJ45PT CCTV Balun, BNC Female to RJ45 Female with pigtail</p> <p>Distance: Up to 2500m (8200ft)</p>	<p>PAIR</p>  <p>BLN-STPT2 CCTV Balun, BNC pigtail to Screw terminal</p> <p>Distance: Up to 2500m (8200ft)</p>

CCTV Baluns/Isolators/Hubs

- Ground Loop Isolator provides improved security from troublesome ground loop distortion and eliminates the need to tear apart your system to search for signal disturbances caused by loops or wiring laid too close to power lines
- Transceiver Boxes convert BNC to RJ45 or screw terminals for use with UTP cabling



GEM-QUAD4x4TM
Quad Processor, Color, with Looping



GLI-BNCPJPT-1
Ground Loop Isolator, BNC Male to BNC Female with pigtail



H16P-RJ45BNC-2
CCTV Balun Hub, 16 Position BNC to RJ45 Female with Power pigtails



TRB-4BNCSTRJ45
Transceiver Box, 4 BNC Jacks to Screw Terminal or RJ45



TRB-8BNCVPPT
Transceiver Box, 8 Position with pigtails



TRB-RGBPTA
Transceiver Box, 3 RCA plugs (RGB) with pigtails and 1 RCA to RJ45



CCTV Baluns/Isolators/Hubs

Ordering Information

Part Number	Description
BLN-AT	CCTV Balun -- Active, Transmitter (max 5500 feet)
BLN-MTPT2	CCTV Balun -- BNC Male and BNC Pigtail to Toolless (max 1000 Feet). PAIR
BLN-PCVRJ452	CCTV Balun -- VIDEO/POWER with Female Power Contact, PAIR
BLN-PVRJ45-1	CCTV Balun -- BNC Male with Power Lead all pigtailed to RJ45 Female
BLN-PVRJ452	CCTV Balun -- BNC Male with Power Lead all pigtailed to RJ45 Female. PAIR
BLN-RJ452	CCTV Balun -- BNC Male to RJ45 Female. PAIR
BLN-RJ45PT	CCTV Balun -- BNC Male to RJ45 Female with 6 inch pigtail
BLN-STPT2	CCTV Balun -- BNC pigtail to screw terminal, 1000 feet. PAIR
GEM-QUAD4X4TM	Quad Processor - Color, with Looping
GLI-BNCPJPT-1	Ground Loop Isolator -- BNC Male to BNC Female with pigtail
H16P-RJ45BNC-2	CCTV Balun Hub -- 16 Position BNC to RJ45 Female with Power Pigtails. Can send signal distance of 100' - 300' depending on power supply. Use with BLN-PVRJ452 at Camera.
TRB-4BNCSTRJ45	Transceiver Box -- 4 Position, 4 BNC Jacks to Screw Terminal or RJ45
TRB-8BNCVPPT	Transceiver Box -- 8 Position with pigtails
TRB-RGBPTA	Transceiver Box -- 3 RCA (RGB) Plugs with Pigtails and 1 RCA Jack to 1 RJ45 Jack - Component Video, Analog Audio

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BLN-PVRJ45-1 on WIN SOURCE](#)
-  [Triplett Test Equipment and Tools Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management