



THE DATASHEET OF
4840.1210



, Plug, solder terminal, 5.5 mm, 2-pole,



See below:

Approvals and Compliances

Description

- Solder :
for cable mounting
- Low Voltage DC Plug and Socket
- DC Plug: 2-pole , straight

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

| | | | |
|-----------------------|-------------------|---------------------------------|-------------------------------|
| Diameter | 5.5 mm / 2.5 mm | Allowable Operation Temperature | -20°C to 70°C |
| Number of Poles | 2-pole | Terminal | solder terminal nickel-plated |
| Ratings DC | 1.0A / 12VDC | Style | straight |
| Dielectric Strength | 500VDC | Lifetime | 5000 Insertions |
| Insulation Resistance | > 100 MΩ @ 500VDC | | |




Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Compliances

The product complies with following Guide Lines

| Identification | Details | Initiator | Description |
|---|----------------------------|-------------|---|
|  | RoHS | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863 |
|  | China RoHS | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS. |
|  | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |

Dimensions [mm]



Cable diameter max. 4.0 mm

Variants

| Product group | Diameter [mm] | Number of Poles | Terminal | Order Number |
|----------------|---------------|-----------------|-----------------|--------------|
| DC Plug/Socket | 5.5 | 2-pole | solder terminal | 4840.1210 |

Availability for all products can be searched real-time: <https://www.schurter.com/en/info-center/support-tools/stock-check-distributors>

| | |
|-----------------------|---------|
| Packaging unit | 100 Pcs |
|-----------------------|---------|

Mating Outlets/Connectors

Category / Description



[DC Plugs / Sockets Overview complete](#)

| | |
|--|-----------|
| , Socket, solder terminal, 6.3 mm, 2-pole, | 4840.2210 |
| , Socket, PCB terminals, 6.0 mm, 2-pole, | 4840.2211 |
| , Plug, Cable, 5.5 mm, 2-pole, | 4840.5212 |

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 4840.1210 on WIN SOURCE](#)

 [Schurter Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management