



THE DATASHEET OF ZCE08





The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product Compatibility	XCMD XCKD XCKT XCKP

Associated body	ZCT26N12 ZCP37 ZCMD21L08R12 ZCT27G11 ZCMD81L1 ZCMD21L2 ZCT28G11 ZCMD37L2 ZCMD61M12 ZCT27N12 ZCMD81L5 ZCMD37L1 ZCMD41L1 ZCT26G11 ZCP28 ZCP31 ZCP21M12 ZCT21N12 ZCMD29L5 ZCMD41L2 ZCP21 ZCP29 ZCT25P16 ZCD39 ZCMD21L5 ZCD27 ZCD21M12 ZCT28P16 ZCMD29L1 ZCMD37L5 ZCD28 ZCT25N12 ZCD37 ZCMD25L2 ZCT26P16 ZCMD21L1 ZCD35 ZCMD61C12 ZCD29 ZCMD21L08U78 ZCD26 ZCMD29L2 ZCP27 ZCMD39L5 ZCD29M12 ZCMD25L1 ZCP29M12 ZCT28N12 ZCT27P16 ZCP26 ZCP35 ZCT21P16 ZCMD39L2 ZCP25 ZCD21 ZCP39 ZCMD69C12 ZCMD21M12 ZCMD25L5 ZCT25G11 ZCMD29C12 ZCD25 ZCMD41L5 ZCMD39L1 ZCMD21C12 ZCD31 ZCT21G11 ZCMD81L2
Movement of operating head	Linear
Type of operator	Ball bearing plunger spring return metal
Type of approach	Multi-directional approach

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	3389110190823
Nbr. of units in pkg.	1
Package weight(Lbs)	0.67 oz (19.0 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.59 in (1.5 cm)
Package 1 width	1.18 in (3 cm)
Package 1 Length	0.59 in (1.5 cm)

Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View ZCE08 on WIN SOURCE](#)

 [Manufacturer Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management