

nRF52833 Product Specification



Contents

nRF52833 Product Specification 3



1. nRF52833 Product Specification

This Product Specification contains functional descriptions, register tables, and electrical specifications, and is organized into chapters based on the modules and peripherals that are available in this IC.

- [nRF52833 Product Specification v1.7](#)
- [nRF52833 Product Specification v1.6](#)
- [nRF52833 Product Specification v1.5](#)
- [nRF52833 Product Specification v1.4](#)
- [nRF52833 Product Specification v1.3](#)
- [nRF52833 Product Specification v1.2](#)
- [nRF52833 Product Specification v1.0](#)

Note: The HTML rendition of the Product Specification corresponds to the latest version only. All versions are available as PDF files.

Features:

- Bluetooth® 5.1, IEEE 802.15.4-2006, 2.4 GHz transceiver
 - -96 dBm sensitivity in 1 Mbps Bluetooth low energy mode
 - -103 dBm sensitivity in 125 kbps Bluetooth low energy mode (long range)
 - -20 to +8 dBm TX power, configurable in 4 dB steps
 - On-air compatible with nRF52, nRF51, nRF24L, and nRF24AP Series devices
 - Supported data rates:
 - Bluetooth 5.1 – 2 Mbps, 1 Mbps, 500 kbps, and 125 kbps
 - IEEE 802.15.4-2006 – 250 kbps
 - Proprietary 2.4 GHz – 2 Mbps, 1 Mbps
 - Angle-of-arrival (AoA) and angle-of-departure (AoD) direction finding using Bluetooth
 - Single-ended antenna output (on-chip balun)
 - 128-bit AES/ECB/CCM/AAR co-processor (on-the-fly packet encryption)
 - 4.9 mA peak current in TX (0 dBm)
 - 4.6 mA peak current in RX
 - RSSI (1 dB resolution)
- Arm® Cortex®-M4 32-bit processor with FPU, 64 MHz
 - 217 EEMBC CoreMark® score running from flash memory
 - 52 µA/MHz running CoreMark from flash memory
 - 38 µA/MHz running CoreMark from RAM
 - Watchpoint and trace debug modules (DWT, ETM, and ITM)
- 512 kB flash and 128 kB RAM
- Advanced on-chip interfaces
 - USB 2.0 full speed (12 Mbps) controller
 - High-speed 32 MHz SPI
 - Type 2 near field communication (NFC-A) tag with wake-on field
 - Touch-to-pair support
 - Programmable peripheral interconnect (PPI)
 - 42 general purpose I/O pins
 - EasyDMA automated data transfer between memory and peripherals
- Nordic SoftDevice ready with support for concurrent multiprotocol
- 12-bit, 200 kbps ADC – 8 configurable channels with programmable gain
- 64 level comparator
- 15 level low-power comparator with wake-up from System OFF mode
- Temperature sensor
- Four 4 channel pulse width modulator (PWM) units with EasyDMA
- Audio peripherals – I²S, digital microphone interface (PDM)
- Five 32-bit timers with counter mode

Features:	
<ul style="list-style-type: none"> Serial wire debug (SWD) Rich set of security features <ul style="list-style-type: none"> Secure boot ready <ul style="list-style-type: none"> Flash access control list (ACL) Debug control and configuration Access port protection (CTRL-AP) Secure erase Flexible power management <ul style="list-style-type: none"> 1.7 V to 5.5 V supply voltage range On-chip DC/DC and LDO regulators with automated low current modes Automated peripheral power management Fast wake-up using 64 MHz internal oscillator 0.6 μA at 3 V in System OFF mode, no RAM retention 1.5 μA at 3 V in System ON mode, no RAM retention, wake on RTC 	<ul style="list-style-type: none"> Up to four SPI masters/three SPI slaves with EasyDMA Up to two I²C compatible two-wire master/slave Two UART (CTS/RTS) with EasyDMA Quadrature decoder (QDEC) Three real-time counters (RTC) Single crystal operation Operating temperature from -40°C to 105°C Package variants <ul style="list-style-type: none"> aQFN73™ package, 7 x 7 mm QFN40 package, 5 x 5 mm WLCSP package, 3.175 x 3.175 mm

Applications:	
<ul style="list-style-type: none"> Advanced computer peripherals and I/O devices <ul style="list-style-type: none"> Mouse Keyboard Multi-touch trackpad Advanced wearable devices <ul style="list-style-type: none"> Health/fitness sensors and monitoring devices Wireless payment enabled devices 	<ul style="list-style-type: none"> Internet of things (IoT) <ul style="list-style-type: none"> Smart home sensors and controllers Industrial IoT sensors and controllers Interactive entertainment devices <ul style="list-style-type: none"> Remote controls Gaming controllers

Revision history

About this document This document is organized into chapters that are based on the modules and peripherals available in the IC.

Block diagram This block diagram illustrates the overall system. Arrows with white heads indicate signals that share physical pins with other signals.

Recommended operating conditions The operating conditions are the physical parameters that the chip can operate within.

Absolute maximum ratings

Ordering information This chapter contains information on device marking, ordering codes, and container sizes.

Legal notices By using this documentation you agree to our terms and conditions of use. Nordic Semiconductor may change these terms and conditions at any time without notice.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View NRF52833-CJAA-B-R7 on WIN SOURCE](#)
- ⊖ [Nordic Semiconductors](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management