



THE DATASHEET OF
1.14.205.101/0000





SMT PRINTED CIRCUIT BOARD JUMPERS

SUPPLIED ON TAPE AND REEL


- Designed to link circuit board traces in applications where thru hole jumpers are not possible.
- All conductive polystyrene carrier meets ANSA/EIA-481 standard
- Low profile/space saving design
- Minimal PCB footprint

MATERIAL: .020 (.50) Copper, Silver Plate

Power Rating: 0.5 Watts at 158°F/70° C, with a current of 20 Amps and a connection temperature at 221°F/105° C or less




Mounting Detail




CAT. NO. 5100

CAT. NO. 5100TR - 500 pieces per reel




Mounting Detail




CAT. NO. 5102

CAT. NO. 5102TR - 500 pieces per reel



Mounting Detail



CAT. NO. 5104

CAT. NO. 5104TR - 2500 pieces per reel



HIGH CURRENT "TRUE" ZERO OHM SMT JUMPER

New series of "True" Zero ohm high current SMT Jumpers, designed to replace Zero ohm resistors without changing board designs or layouts. These new devices are uniquely suited as true zero ohm resistor replacements.


MATERIAL: .028 Copper, Silver plate

Power Rating: 0.5 Watts at 158°F/70° C, with a current of 20 Amps and a connection temperature at 221°F/105° C or less.


Tape & Reel Spec's: 12mm Wide, 4mm Pitch, 1,000 pieces per 7" reel meets ANSI/EIA-481 standards




Mounting Detail




CAT. NO. 5110




Mounting Detail



CAT. NO. 5106



Mounting Detail





CAT. NO. 5108


THM JUMPERS

- Unique wave leg design retains jumper in thru hole for wave soldering.
- May be used as a test point location

- Shorting Pin may be used in applications that require precise location of the legs.
- May also be used with micro-jacks (see pages 102-103)




Mounting Detail




MATERIAL: .020 (.50) Dia. Phosphor Bronze, Silver Plate

CAT. NO. 5025




Mounting Detail



MATERIAL: .020 (.50) Dia. Phosphor Bronze, Silver Plate

CAT. NO. 5026



| CAT. NO. | A Dim. |
|----------|-------------|
| 1430-1 | .200 (5.1) |
| 1430-2 | .250 (6.4) |
| 1430-4 | .400 (10.2) |
| 1430-5 | .500 (12.7) |

MATERIAL: Brass, Gold Plate

JUMPERS

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 1.14.205.101/0000](#) on WIN SOURCE

 [RAFI USA](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management