



**THE DATASHEET OF**  
**865060657012**



# LOW PROFILE SINGLE CONTACT: 9155-600



## General Information



Designers of ruggedized connectors for harsh environments continue to look for new products that reduce size and cost without compromising performance. KYOCERA AVX's new Ultra-Low Profile (ULP) compression contact is surface mounted to a PCB and provides a reliable compression connection to the mating board, even under extreme shock and vibration applications. With over 20 years of experience in 1-piece compression contacts, this innovative contact provides full connector performance functionality at the individual contact level. This allows individual contacts to be placed in any location or position on a PCB.

The high strength beryllium copper contact is gold-plated to maximize reliability and signal integrity. The current offering includes two contacts with nominal heights of 1.0mm and 1.5mm. Adding the "Z" axis tolerance range, the compressed height covers 0.75mm to 1.75mm. Contacts are supplied in tape and reel for easy SMT assembly.

### APPLICATIONS

- Industrial/Ruggedized handheld or portable devices
- BTB connection for any traditional power or signal application
- Ground connections between PCB's or housings
- Product Specification: Refer to 201-01-153
- Application Notes: Refer to 201-01-154

### FEATURES AND BENEFITS

- Reliable gold plated Beryllium Copper contacts for high cycle life and signal integrity up to 1000 cycles
- Tape and reel packaged for automated SMT placement
- Sweeping beam design for pluggable/module applications
- Three gold plating options to match end product environmental or expected life requirements

### ELECTRICAL

- Current Rating: 3 Amps
- Voltage Rating: UL 300 VAC (RMS) or DC equivalent  
Based on placement distance

### ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C
- Storage Temperature: -40°C to +70°C

### MECHANICAL

- Contact Material: Beryllium Copper
- Contact Plating: Gold over Nickel
- Durability: 50, 500 and 1000 cycles

### HOW TO ORDER

**70**  
Prefix

**9155**  
Series

**001**  
Number of Ways

**61X**

#### Contact Description

Code	Nominal Operating Height	Contact Operating Height Range
610	1.00mm	0.75mm to 1.25mm
615	1.50mm	1.25mm to 1.75mm

**00X**

#### Contact Description

Code	Gold Thickness	Description	Availability
004	0.1µm	Nickel under Plate, Gold on Nose Tin on Remainder	Standard
006	0.4µm	Nickel under Plate, Gold on Nose Tin on Remainder	Special Order
008	0.8µm	Nickel under Plate, Gold on Nose Tin on Remainder	Special Order



**SALES DRAWINGS**  
CLICK TO DOWNLOAD

Safety Standards: UL 1977-File #E90723, CSA C22.2 NO. 182.3



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at [www.kyocera-avx.com/disclaimer/](http://www.kyocera-avx.com/disclaimer/) by reference and should be reviewed in full before placing any order.

TDS-BTB-0011 | Rev 2

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 865060657012 on WIN SOURCE](#)

 [Wurth Electronics Inc Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management