








**THE DATASHEET OF
DF13-4P-1.25DSA(05)**



Applicable standard					
Rating	Operating Temperature range	-40 °C to +105°C (Note1)	Storage Temperature range	-10 °C to +60°C (Note3)	
	Operating Humidity range	20% to 80% (Note2)	Storage Humidity range	40% to 70% (Note3)	
	-	-	-	-	
	-	-	-	-	
Specifications					
Item	Test method	Requirements	QT	AT	
Construction					
General examination	Visually and by measuring instrument.	According to drawing.	X	X	
Marking	Confirmed visually.		X	X	
Mechanical characteristics 					
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.	No damage, crack or looseness of parts.	X	-	
Shock	490 m/s ² duration of pulse 11 ms at 3 times each for 3 both axial directions.	No damage, crack or looseness of parts.	X	-	
Environmental characteristics 					
Damp heat (Steady state)	Exposed at 40 ± 2°C , 90 to 95 % , 96 h. (After leaving the room temperature for 1~2h.)	No damage, crack or looseness of parts.	X	-	
Rapid change of temperature	Temperature -55°C→ +85°C Time 30min→ 30min Under 5 cycles. (The transferring time of the tank is 2~3 min) (After leaving the room temperature for 1~2h.)	No damage, crack or looseness of parts.	X	-	
Note 1: Include the temperature rising by current. Note 2: No condensing Note 3: Apply to the condition of long term storage for unused products before PCB on board. After PCB on board, operating temperature and humidity range is applied for interim strage during transportation.					
	Count	Description of revisions	Designed	Checked	Date
	2	DIS-H-008782	KT. ISHII	HK. UMEHARA	14. 05. 23
Remarks Unless otherwise specified, refer to IEC 60512.			Approved	KI. AKIYAMA	14. 01. 15
			Checked	MN. KENJO	14. 01. 15
			Designed	TO. HORII	14. 01. 15
			Drawn	TO. HORII	14. 01. 15
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			Drawing No.		ELC4-354088-00
	Specification sheet		Part No.	DF62W-WP	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL544-1014-6-00	 1/1

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View DF13-4P-1.25DSA\(05\) on WIN SOURCE](#)
- ⊖ [Hirose Electric Co Ltd Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management