



**THE DATASHEET OF  
XF3H-4555-31AR**



### Product Overview

The Qorvo TGF2819-FL is a 200 W ( $P_{3dB}$ ) discrete GaN on SiC HEMT which operates from DC to 4 GHz with a 50V supply rail. The device is in an industry standard air cavity package and is ideally suited for IFF, avionics, military and civilian radar, and test instrumentation. The device can support CW, pulsed and linear operations.


Lead-free and ROHS compliant

Evaluation boards are available upon request.



NI-360 Package

### Functional Block Diagram



### Key Features

- Frequency: DC to 4 GHz
  - Output Power ( $P_{3dB}$ )<sup>1</sup>: 257 W
  - Linear Gain<sup>1</sup>: 18 dB
  - Typical PAE<sub>3dB</sub><sup>1</sup>: 67.5%
  - Operating Voltage: 50 V
  - CW and Pulse capable
- Note 1: @ 3 GHz Load Pull

### TGF2819-FLEVB01 Performance

Freq.(GHz)	$P_{3dB}$ (W)	$G_{3dB}$ (dB)	$DE_{3dB}$ (%)
3.1	138.4	11.6	53.2
3.2	137.6	11.7	53.8
3.3	134.3	11.9	54.0
3.4	132.0	12.1	53.5
3.5	126.1	12.1	52.4

Pulse Width = 100 us, Duty Cycle = 20%,  
 $V_D = +32$  V,  $I_{DQ} = 250$  mA, 25°C Base Temperature

### TGF2819-FLEVB02 Performance

Freq.(GHz)	$P_{3dB}$ (W)	$G_{3dB}$ (dB)	$DE_{3dB}$ (%)
1.35	172.1	14.3	71.1
1.45	167.5	14.9	74.9
1.55	173.5	14.9	74.2
1.65	176.9	14.8	74.5
1.75	162.9	14.4	77.5

Pulse Width = 500 us, Duty Cycle = 50%,  
 $V_D = +50$  V,  $I_{DQ} = 200$  mA, 25°C Base Temperature

### Applications

- Military and civilian radar
- Professional and military radio communications
- Test instrumentation
- Wideband or narrowband amplifiers
- Jammers

### Ordering info

Part No.	Description
TGF2819-FL	DC–4 GHz, 50 V, 200 W GaN RF Transistor
TGF2819-FLEVB01	3.1 – 3.5 GHz EVB
TGF2819-FLEVB02	1.35 – 1.75 GHz EVB

### Absolute Maximum Ratings<sup>1,2</sup>

Parameter	Rating	Units
Breakdown Voltage, $BV_{DG}$	+145	V
Gate Voltage Range, $V_G$	-7 to +2	V
Drain Current, $I_{D_{MAX}}$	12	A
Power Dissipation <sup>(2)</sup> , $P_{DISS}$	207	W
RF Input Power <sup>(2)</sup> , $T = 25^\circ\text{C}$	+39.8	dBm
Channel Temperature, $T_{CH}$	275	$^\circ\text{C}$
Mounting Temperature (30 Seconds)	320	$^\circ\text{C}$
Storage Temperature	-65 to +150	$^\circ\text{C}$

Notes:

1. Operation of this device outside the parameter ranges given above may cause permanent damage.
2. Pulsed 100 us PW, 20% DC

### Recommended Operating Conditions<sup>1-4</sup>

Parameter	Min	Typ	Max	Units
Operating Temp. Range	-40	+25	+85	$^\circ\text{C}$
Drain Voltage Range, $V_D$	+32	+50	+55	V
Drain Bias Current, $I_{DQ}$		250		mA
Drain Current <sup>(4)</sup> , $I_D$	-	7.2	-	A
Gate Voltage <sup>(3)</sup> , $V_G$	-	-2.8	-	V
Channel Temperature ( $T_{CH}$ )	-	-	250	$^\circ\text{C}$
Power Dissipation <sup>(2,4)</sup> ( $P_D$ )	-	-	184	W
Power Dissipation <sup>(2)</sup> ( $P_D$ ), CW	-	-	98	W

Notes:

1. Electrical performance is measured under conditions noted in the electrical specifications table. Specifications are not guaranteed over all recommended operating conditions.
2. Package base at  $85^\circ\text{C}$
3. To be adjusted to desired  $I_{DQ}$
4. Pulsed, 100 us PW, 20% DC

### Measured Load Pull Performance – Power Tuned<sup>1</sup>

Parameter	Typical Values						Units
	2.7	2.9	3.1	3.3	3.5	3.7	
Frequency, F	2.7	2.9	3.1	3.3	3.5	3.7	GHz
Drain Voltage, $V_D$	50	50	50	50	50	50	V
Drain Bias Current, $I_{DQ}$	200	200	200	200	200	200	mA
Output Power at 3dB compression, $P_{3dB}$	54	53.5	53.2	53	53	52.7	dBm
Power Added Efficiency at 3dB compression, $PAE_{3dB}$	60.0	53.7	46.0	48.8	43	51.4	%
Gain at 3dB compression, $G_{3dB}$	13.9	14.3	13.3	16.5	14	15.5	dB

Notes:

1. Pulsed, 100 us Pulse Width, 20% Duty Cycle

### Measured Load Pull Performance – Efficiency Tuned<sup>1</sup>

Parameter	Typical Values						Units
	2.7	2.9	3.1	3.3	3.5	3.7	
Frequency, F	2.7	2.9	3.1	3.3	3.5	3.7	GHz
Drain Voltage, $V_D$	50	50	50	50	50	50	V
Drain Bias Current, $I_{DQ}$	200	200	200	200	200	200	mA
Output Power at 3dB compression, $P_{3dB}$	52.5	53.2	52.6	52.1	52.3	51.9	dBm
Power Added Efficiency at 3dB compression, $PAE_{3dB}$	65.5	64.3	54.4	52.2	53.7	53.9	%
Gain at 3dB compression, $G_{3dB}$	15.8	15.5	15.5	17.8	16.1	15.9	dB

Notes:

1. Pulsed, 100 us Pulse Width, 20% Duty Cycle

### 3.1 – 3.5 GHz EVB At 3.3 GHz Performance<sup>1,2</sup>

Parameter	Min	Typ	Max	Units
Linear Gain, $G_{LIN}$	–	15.0	–	dB
Output Power at 3dB compression point, P3dB	–	134.3	–	W
Drain Efficiency at 3dB compression point, DEFF3dB	–	54.0	–	%
Gain at 3dB compression point, G3dB	–	12.0	–	dB
Gate Leakage <sup>(2)</sup>	-31.7	–	–	mA

Notes:

1.  $V_D = +32\text{ V}$ ,  $I_{DQ} = 250\text{ mA}$ , Temp = +25 °C, Pulse Width = 100 us, Duty Cycle = 20%
2.  $V_D = +10\text{ V}$ ,  $V_G = -3.8\text{ V}$

### RF Characterization – Mismatch Ruggedness at 3.5 GHz

Symbol	Parameter	dB Compression	Typical
VSWR	Impedance Mismatch Ruggedness	3	10:1






Test conditions unless otherwise noted:  $T_A = 25\text{ °C}$ ,  $V_D = +32\text{ V}$ ,  $I_{DQ} = 250\text{ mA}$

Input drive power is determined at pulsed 3dB compression under matched condition at EVB output connector.

### Measured Load-Pull Smith Charts<sup>1, 2</sup>

Notes:







1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 200\text{ mA}$ , 100  $\mu\text{s}$  Pulse Width, 20% Duty Cycle
2. See page 12 for load pull reference planes where the performance was measured.



### Typical Measured Performance – Load-Pull Drive-up<sup>1</sup>

Note:







1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 200\text{ mA}$ , 100 us Pulse Width, 20% Duty Cycle



### Typical Measured Performance – Load-Pull Drive-up<sup>1</sup>

Note:





1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 200\text{ mA}$ , 100 us Pulse Width, 20% Duty Cycle



### Power Driveup Performance Over Temperatures Of 3.1 – 3.5 GHz EVB<sup>1, 2</sup>

Notes:





1. Test Conditions:  $V_D = 32\text{ V}$ ,  $I_{DQ} = 250\text{ mA}$ , 100 us Pulse Width, 20% Duty Cycle
2. The dissipation power limit is conservative because it is specified at DUT only without accounting for the loss of the output matching network.



### Power Driveup Performance At 25°C Of 3.1 – 3.5 GHz EVB<sup>1, 2</sup>

Notes:





1. Test Conditions:  $V_D = 32\text{ V}$ ,  $I_{DQ} = 250\text{ mA}$ , 100 us Pulse Width, 20% Duty Cycle
2. The dissipation power limit is conservative because it is specified at DUT only without accounting for the loss of the output matching network..



### Power Driveup Performance At 25°C Of 1.35 – 1.75 GHz EVB<sup>1,2</sup>


Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 200\text{ mA}$ , 500 us Pulse Width, 50% Duty Cycle
2. The dissipation power limit is conservative because it is specified at DUT only without accounting for the loss of the output matching network..



### Thermal and Reliability Information – Pulsed<sup>1-4</sup>

**Peak IR Surface Temperature**  
Package Base Fixed at 85 °C, Duty Cycle = 20%




Parameter	Conditions	Values	Units
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 139^{\circ}C$ , $P_{DISS} = 101 W$ , 100 us PW, 20% DC	0.54	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 148^{\circ}C$ , $P_{DISS} = 115 W$ , 100 us PW, 20% DC	0.55	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 165^{\circ}C$ , $P_{DISS} = 144 W$ , 100 us PW, 20% DC	0.55	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 183^{\circ}C$ , $P_{DISS} = 173 W$ , 100 us PW, 20% DC	0.56	$^{\circ}C/W$

Notes:

1. Based on expected carrier amplifier efficiency of Doherty.
2.  $P_{OUT}$  assumes 25% peaking amplifier contribution of total average Doherty rated power.
3. Thermal resistance is measured to package backside.
4. Refer to the following document: [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#)

### Thermal and Reliability Information – CW<sup>1-4</sup>




Parameter	Conditions	Values	Units
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 139^{\circ}C$ CW: $P_{DISS} = 57.6 W$	0.99	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 175^{\circ}C$ CW: $P_{DISS} = 86.4 W$	1.04	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 193^{\circ}C$ CW: $P_{DISS} = 100.8 W$	1.08	$^{\circ}C/W$
Thermal Resistance, Peak IR Surface Temperature at Average Power ( $\theta_{JC}$ )	$T_{CASE} = +85^{\circ}C$ , $T_{CH} = 213^{\circ}C$ CW: $P_{DISS} = 115.2 W$	1.11	$^{\circ}C/W$

Notes:

1. Based on expected carrier amplifier efficiency of Doherty.
2.  $P_{OUT}$  assumes 25% peaking amplifier contribution of total average Doherty rated power.
3. Thermal resistance is measured to package backside.
4. Refer to the following document: [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#)

## Pin Layout<sup>1</sup>




**Notes:**

- The TGF2819-FL will be marked with the “TGF2819-FL” designator and a lot code marked below the part designator. The “YY” represents the last two digits of the calendar year the part was manufactured, the “WW” is the work week of the assembly lot start, the “MXXX” is the production lot number, and the “ZZZ” is an auto-generated serial number.

Pin	Symbol	Description
1	RF IN / V <sub>G</sub>	Gate
2	RF OUT / V <sub>D</sub>	Drain
3	Source	Source / Ground / Backside of part


## Mechanical Drawing<sup>1-7</sup>



### Note:

1. All dimensions are in inches. Angles are in degrees.
2. Dimension tolerance is  $\pm 0.005$  inches, unless otherwise noted.
3. Material:  
Package Base: Ceramic / Metal  
Package Lid: Ceramic
4. Package exposed metallization is gold plated.
5. Part is epoxy sealed.
6. Part meets industry NI360 footprint.
7. Body dimensions do not include epoxy runout which can be up to 0.020 inches per side.

### 3.1 – 3.5 GHz Application Circuit - Schematic




Bias-up Procedure	Bias-down Procedure
1. Set $V_G$ to -4 V.	1. Turn off RF signal.
2. Set $I_D$ current limit to 260 mA.	2. Turn off $V_D$ .
3. Apply 32 V $V_D$ .	3. Wait 2 seconds to allow drain capacitor to discharge.
4. Slowly adjust $V_G$ until $I_D$ is set to 250 mA.	4. Turn off $V_G$ .
5. Set $I_D$ current limit to 2 A (Pulsed operation.)	
6. Apply RF.	

### 3.1 – 3.5 GHz Application Circuit - Bill of Materials


Reference Design	Value	Qty	Manufacturer	Part Number
R1	100Ω	1	Vishay/Dale	CRCW0603100RJNTA
C1, C2	5.6pF	2	ATC	600S5R6BW250XT
C3	1.0pF	1	ATC	600S1R0AT250XT
L1	22nH	1	Coilcraft	0805CS-220XJEC
R2	10Ω	1	Vishay/Dale	CRCW060310R0JNTA
C4	10uF	1	Murata	C1632X5R0J106M130AC
L2	12nH	1	Coilcraft	A04TJLC
C5	2400pF	1	Murata	C08BL242X-5UN-X0T
C6	1000pF	1	ATC	800B102JT50XT
C7	220uF	1	Panasonic	EEEFK1H221P
C8	15pF	1	ATC	600S150FT250XT

**3.1 – 3.5 GHz Application Circuit - Layout**

Board material is RO4350B 0.020" thickness with 2oz copper cladding. Overall EVB size is 3" x 4".



### 1.35 – 1.75 GHz Application Circuit - Schematic




Bias-up Procedure	Bias-down Procedure
2. Set $V_G$ to -4 V.	3. Turn off RF signal.
4. Set $I_D$ current limit to 220 mA.	4. Turn off $V_D$ .
5. Apply 50 V $V_D$ .	5. Wait 2 seconds to allow drain capacitor to discharge.
6. Slowly adjust $V_G$ until $I_D$ is set to 200 mA.	7. Turn off $V_G$ .
8. Set $I_D$ current limit to 3.5 A (Pulsed operation.)	
9. Apply RF.	

### 1.35 – 1.75 GHz Application Circuit - Bill of Materials


Reference Design	Value	Qty	Manufacturer	Part Number
C1, C8	1 uF	2	Murata	GCM188R71C105KA64D
C2	1.8 pF	1	ATC	600S1R8AT250X
C3, C6	22 pF	2	ATC	600S220FT250XT
C7	2.7 pF	1	ATC	600S2R7BW250XT
C4, C5	10 nF	2	Capax Technologies	0603X103K101S
C9	1 uF	1	TDK	CGA4J3X7S2A105K125AB
C10	220 uF	1	Panasonic	EEVTG1J221Q
L1	10 nH	1	Coilcraft	0603CS-10NXJEW
L2	12.5 nH	1	Coilcraft	A04TJLC
R1, R2	5.6 Ohm	2	Panasonic	ERJ-1TRQJ5R6U
R3	215 Ohm	1	Panasonic	ERA-8AEB2150V
R6	10 Ohm	1	Vishay	CRCW060310R0JNTA
R4, R5	50 Ohm	2	Vishay	CRCW060351R1FKEA

### 1.35 – 1.75 GHz Application Circuit - Layout

Board material is RO4350B 0.020" thickness with 2oz copper cladding. Overall EVB size is 3" x 4".



**Recommended Solder Temperature Profile**



### Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1A (250 V)	ANSI/ESDA/JEDEC Standard JS-001
ESD – Charged Device Model (CDM)	Class C3 (1000 V)	ANSI/ESDA/JEDEC Standard JS-002
MSL – Moisture Sensitivity Level	MSL 3	IPC/JEDEC Standard J-STD-020



### Solderability

Compatible with both lead-free (260°C max. reflow temp.) and tin/lead (245°C max. reflow temp.) soldering processes.

Solder profiles available upon request.

Contact plating: Electrolytic Au over Ni

### RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free



### Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: [www.qorvo.com](http://www.qorvo.com)

Tel: 1-844-890-8163

Email: [customer.support@qorvo.com](mailto:customer.support@qorvo.com)

### Important Notice


The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2026 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View XF3H-4555-31AR on WIN SOURCE](#)

 [Omron Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management