





**THE DATASHEET OF  
LH1532AACTR**





## Dual 1 Form A Solid-State Relay (Normally Open)



### FEATURES

- Dual channel
- Current limit protection
- Isolation test voltage 5300 V<sub>RMS</sub>
- Typical R<sub>ON</sub> 22 Ω
- Load voltage 350 V
- Clean bounce free switching
- Low power consumption
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### APPLICATIONS

- General telecom switching
- Security equipment
- Instrumentation
- Industrial controls

### AGENCY APPROVALS

- UL1577, file no. E52744

### DESCRIPTION

The LH1532 dual 1 Form A relays are SPST normally open switches that can replace electromechanical relays in many applications. They are constructed using a GaAlAs LED for actuation control and MOSFET switches for the output. In addition, the LH1532 SSRs employ current-limiting circuitry to provide overvoltage protection.

| ORDERING INFORMATION |   |   |   |   |   |                      |                    |   |                  |   |     |     |
|----------------------|---|---|---|---|---|----------------------|--------------------|---|------------------|---|-----|-----|
| L                    | H | 1 | 5 | 3 | 2 | A                    | #                  | # | T                | R | DIP | SMD |
| PART NUMBER          |   |   |   |   |   | ELECTR.<br>VARIATION | PACKAGE<br>CONFIG. |   | TAPE AND<br>REEL |   |     |     |
| <b>PACKAGE</b>       |   |   |   |   |   | <b>UL</b>            |                    |   |                  |   |     |     |
| SMD-8, tubes         |   |   |   |   |   | LH1532AAC            |                    |   |                  |   |     |     |
| SMD-8, tape and reel |   |   |   |   |   | LH1532AACTR          |                    |   |                  |   |     |     |
| DIP-8, tubes         |   |   |   |   |   | LH1532AB             |                    |   |                  |   |     |     |



| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |               |            |             |      |
|--|---------------|------------|-------------|------|
| PARAMETER  | CONDITIONS    | SYMBOL     | VALUE       | UNIT |
| <b>INPUT</b>   |               |            |             |      |
| IRED continuous forward current  |               | $I_F$      | 50          | mA   |
| IRED reverse voltage   |               | $V_R$      | 5           | V    |
| Input power dissipation  |               | $P_{diss}$ | 80          | mW   |
| <b>OUTPUT</b>  |               |            |             |      |
| DC or peak AC load voltage   |               | $V_L$      | 350         | V    |
| Continuous DC load current at 25 °C, one channel   |               | $I_L$      | 120         | mA   |
| Continuous DC load current at 25 °C, two channels  |               | $I_L$      | 110         | mA   |
| SSR output power dissipation   |               | $P_{diss}$ | 550         | mW   |
| <b>SSR</b>   |               |            |             |      |
| Ambient temperature range  |               | $T_{amb}$  | -40 to +85  | °C   |
| Storage temperature range  |               | $T_{stg}$  | -40 to +150 | °C   |
| Soldering temperature  | t = 10 s max. | $T_{sld}$  | 260         | °C   |

**Note**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability

| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |             |      |      |      |            |
|--|--|-------------|------|------|------|------------|
| PARAMETER  | TEST CONDITION   | SYMBOL      | MIN. | TYP. | MAX. | UNIT       |
| <b>INPUT</b>   |  |             |      |      |      |            |
| IRED forward current, switch turn-on   | $I_L = 100\text{ mA}$ , t = 10 ms                      | $I_{Fon}$   | -    | 0.25 | 2    | mA         |
| IRED forward current, switch turn-off  | $V_L = \pm 350\text{ V}$                               | $I_{Foff}$  | 0.05 | 0.15 | -    | mA         |
| IRED forward voltage   | $I_F = 10\text{ mA}$                                   | $V_F$       | 1.15 | 1.36 | 1.45 | V          |
| <b>OUTPUT</b>  |  |             |      |      |      |            |
| On-resistance  | $I_F = 5\text{ mA}$ , $I_L = 50\text{ mA}$             | $R_{ON}$    | -    | 22   | 27   | $\Omega$   |
| Off-resistance   | $I_F = 0\text{ mA}$ , $V_L = \pm 100\text{ V}$         | $R_{OFF}$   | 0.5  | 5000 | -    | G $\Omega$ |
| Off-state leakage current  | $I_F = 0\text{ mA}$ , $V_L = \pm 100\text{ V}$         | $I_O$       | -    | < 1  | 200  | nA         |
|  | $I_F = 0\text{ mA}$ , $V_L = \pm 350\text{ V}$         | $I_O$       | -    | 6    | 1000 | nA         |
| Output capacitance   | $I_F = 0\text{ mA}$ , $V_L = 1\text{ V}$ , 1 MHz       | $C_O$       | -    | 39   | -    | pF         |
|  | $I_F = 0\text{ mA}$ , $V_L = 50\text{ V}$ , 1 MHz      | $C_O$       | -    | 6    | -    | pF         |
| Current limit AC/DC  | $I_F = 5\text{ mA}$ , t = 5 ms, $V_L = \pm 6\text{ V}$ | $I_{limit}$ | 170  | 300  | 450  | mA         |
| <b>TRANSFER</b>  |  |             |      |      |      |            |
| Capacitance (input to output)  | $V_{IO} = 1\text{ V}$                                  | $C_{IO}$    | -    | 1    | -    | pF         |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements

| <b>SWITCHING CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |           |      |      |      |      |
|---|--|-----------|------|------|------|------|
| PARAMETER   | TEST CONDITION                             | SYMBOL    | MIN. | TYP. | MAX. | UNIT |
| Turn-on time  | $I_F = 5\text{ mA}$ , $I_L = 50\text{ mA}$ | $t_{on}$  | -    | 0.13 | 2.5  | ms   |
| Turn-off time   | $I_F = 5\text{ mA}$ , $I_L = 50\text{ mA}$ | $t_{off}$ | -    | 0.05 | 2.5  | ms   |





Fig. 1 - Timing Schematic



| SAFETY AND INSULATION RATINGS                |  |            |                |                    |
|--|--|------------|----------------|--------------------|
| PARAMETER                                    | TEST CONDITION   | SYMBOL     | VALUE          | UNIT               |
| Climatic classification                      | According to IEC 68 part 1   |            | 40 / 85 / 21   |                    |
| Pollution degree                             | According to DIN VDE 0109  |            | 2              |                    |
| Comparative tracking index                   | Insulation group IIIa  | CTI        | 175            |                    |
| Maximum rated withstanding isolation voltage | According to UL1577, t = 1 min   | $V_{ISO}$  | 5300           | $V_{RMS}$          |
| Maximum transient isolation voltage          | According to DIN EN 60747-5-5  | $V_{IOTM}$ | 8000           | $V_{peak}$         |
| Maximum repetitive peak isolation voltage    | According to DIN EN 60747-5-5  | $V_{IORM}$ | 890            | $V_{peak}$         |
| Isolation resistance                         | $V_{IO} = 500\text{ V}, T_{amb} = 25\text{ }^{\circ}\text{C}$  | $R_{IO}$   | $\geq 10^{12}$ | $\Omega$           |
|  | $V_{IO} = 500\text{ V}, T_{amb} = 100\text{ }^{\circ}\text{C}$   | $R_{IO}$   | $\geq 10^{11}$ | $\Omega$           |
| Output safety power                          |  | $P_{SO}$   | 600            | mW                 |
| Input safety current                         |  | $I_{SI}$   | 240            | mA                 |
| Safety temperature                           |  | $T_S$      | 175            | $^{\circ}\text{C}$ |
| Creepage distance                            |  |            | $\geq 7$       | mm                 |
| Clearance distance                           |  |            | $\geq 7$       | mm                 |
| Insulation thickness                         |  | DTI        | $\geq 0.4$     | mm                 |
| Input to output test voltage, method B       | $V_{IORM} \times 1.875 = V_{PR}$ , 100 % production test with $t_M = 1\text{ s}$ , partial discharge $< 5\text{ pC}$ | $V_{PR}$   | 1669           | $V_{peak}$         |
| Input to output test voltage, method A       | $V_{IORM} \times 1.6 = V_{PR}$ , 100 % sample test with $t_M = 10\text{ s}$ , partial discharge $< 5\text{ pC}$      | $V_{PR}$   | 1424           | $V_{peak}$         |

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits




Fig. 2 - Safety Power Dissipation vs. Ambient Temperature




Fig. 3 - Safety Input Current vs. Ambient Temperature



## TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 4 - Maximum Load Current vs. Ambient Temperature




Fig. 7 - Normalized Forward Current for Switch Turn-On vs. Ambient Temperature




Fig. 5 - Forward Voltage vs. Ambient Temperature




Fig. 8 - Normalized On-Resistance vs. Ambient Temperature




Fig. 6 - Forward Current vs. Forward Voltage




Fig. 9 - Output Capacitance vs. Load Voltage




Fig. 10 - Off-State Leakage Current vs. Load Voltage




Fig. 13 - Turn-Off Time vs. Forward Current




Fig. 11 - Turn-On Time vs. Forward Current




Fig. 14 - Normalized Turn-Off Time vs. Ambient Temperature






Fig. 12 - Normalized Turn-On Time vs. Ambient Temperature




## PACKAGE DIMENSIONS (in millimeters)



### SMD-8



### Recommended footprint



### DIP-8





**PACKAGE MARKING** (example)




Fig. 15 - LH1532

**Note**

- Tape and reel suffix (TR) is not part of the package marking

**PACKING INFORMATION** (in millimeters)




Fig. 16 - Tape and Reel Packing

| TAPE AND REEL PACKING |            |
|-----------------------|------------|
| TYPE                  | UNITS/REEL |
| SMD-8                 | 1000       |

| TUBE PACKING |            |           |           |
|--------------|------------|-----------|-----------|
| TYPE         | UNITS/TUBE | TUBES/BOX | UNITS/BOX |
| SMD-8        | 50         | 40        | 2000      |
| DIP-8        | 50         | 40        | 2000      |



SOLDER PROFILES




Fig. 17 - Wave Soldering Double Wave Profile According to J-STD-020 for DIP Devices




Fig. 18 - Lead (Pb)-free Reflow Solder Profile According to J-STD-020 for SMD Devices

HANDLING AND STORAGE CONDITIONS

ESD level: HBM class 2

Floor life: unlimited

Conditions: T<sub>amb</sub> < 30 °C, RH < 60 %

Moisture sensitivity level 1, according to J-STD-020



## Footprint and Schematic Information for LH1532


The footprint and schematic symbols for the following parts can be accessed using the associated links. They are available in Eagle, Altium, KiCad, OrCAD / Allegro, Pulsonix, and PADS.

Note that the 3D models for these parts can be found on the Vishay product page.



| PART NUMBER | FOOTPRINT / SCHEMATIC  |
|-------------|--|
| LH1532AAC   | <a href="http://www.snapeda.com/parts/LH1532AAC/Vishay/view-part">www.snapeda.com/parts/LH1532AAC/Vishay/view-part</a>     |
| LH1532AACTR | <a href="http://www.snapeda.com/parts/LH1532AACTR/Vishay/view-part">www.snapeda.com/parts/LH1532AACTR/Vishay/view-part</a> |
| LH1532AB    | <a href="http://www.snapeda.com/parts/LH1532AB/Vishay/view-part">www.snapeda.com/parts/LH1532AB/Vishay/view-part</a>       |
| LH1532FP    | <a href="http://www.snapeda.com/parts/LH1532FP/Vishay/view-part">www.snapeda.com/parts/LH1532FP/Vishay/view-part</a>       |
| LH1532FPTR  | <a href="http://www.snapeda.com/parts/LH1532FPTR/Vishay/view-part">www.snapeda.com/parts/LH1532FPTR/Vishay/view-part</a>   |

For technical issues and product support, please contact [optocoupleranswers@vishay.com](mailto:optocoupleranswers@vishay.com).

DIP



SMD





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View LH1532AACTR](#) on WIN SOURCE

 [Vishay](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management