



**THE DATASHEET OF
MAX9052BEUA+T**



MAX9038–MAX9043/ MAX9050–MAX9053

Micropower, Single-Supply, UCSP/SOT23 Comparator + Precision Reference ICs

General Description

The MAX9038–MAX9043 and MAX9050–MAX9053 feature combinations of low-power comparators and precision voltage references. Their operating voltage range makes them ideal for both 3V and 5V systems. The MAX9039/MAX9040/MAX9041/MAX9050/MAX9051 have a single comparator and reference consuming only 40µA of supply current. The MAX9042/MAX9043/MAX9052/MAX9053 have dual comparators and one reference, and consume only 55µA of supply current. Low-voltage operation and low supply current make these devices ideal for battery-operated systems.

The comparators feature rail-to-rail inputs and outputs, with a common-mode input voltage range that extends 250mV beyond the supply rails. Input bias current is typically 1.0pA, and input offset voltage is typically 0.5mV. Internal hysteresis ensures clean output switching, even with slow-moving input signals. The output stage features a unique design that limits supply current surges while switching, virtually eliminating supply glitches typical of many other comparators. This design also minimizes overall power consumption under dynamic conditions. The comparator outputs have rail-to-rail, push-pull output stages except the MAX9038 has an open-drain output that sinks and sources up to 8mA. The propagation delay is 400ns, even with the low-operating supply current.

The reference output voltage is set to 1.23V in the MAX9038/MAX9039, to 2.048V in the MAX9040–MAX9043, and to 2.500V in the MAX9050–MAX9053. The MAX9040–MAX9043 and the MAX9050–MAX9053 are offered in two grades: an A grade with 0.4% initial accuracy and 6ppm/°C tempco, and a B grade with 1% initial accuracy (except MAX9038/MAX9039 have an initial accuracy of ±0.4%) and 100ppm/°C tempco. The voltage references feature a proprietary curvature-correction circuit and laser-trimmed thin-film resistors. These series-mode references can sink or source up to 500µA of load current.

Applications

- Precision Battery Management
- Window Comparators
- IR Receivers
- Level Translators
- Digital Line Receivers

Typical Operating Circuit and Functional Diagrams appear at end of data sheet.

UCSP is a trademark of Maxim Integrated Products, Inc.

Features

- Comparator + Precision Reference in UCSP/SOT23
- 2.5V to 5.5V Single-Supply Operation (MAX9038–MAX9043)
- Low Supply Current (MAX9038/MAX9039/MAX9040/MAX9041/MAX9050/MAX9051)
 - 40µA Quiescent
 - 50µA with 100kHz Switching
 - Open-Drain Output MAX9038
- 400ns Propagation Delay
- Rail-to-Rail Inputs
- Rail-to-Rail Output Stage Sinks and Sources 8mA
- Internal ±3mV Hysteresis
- Voltage Reference Offers
 - ±0.4% (max) Initial Accuracy (A Grade)
 - 6ppm/°C (typ) Temperature Coefficient (A Grade)
 - Stable for 0 to 4.7nF Capacitive Loads


Ordering Information

| PART | TEMP RANGE | PIN-PACKAGE | TOP MARK |
|---------------|-----------------|-------------|----------|
| MAX9038BABT+T | -40°C to +125°C | 6 UCSP | ADW |
| MAX9039BEBT+T | -40°C to +85°C | 6 UCSP | AAZ |
| MAX9040AEUK+T | -40°C to +85°C | 5 SOT23 | ADNW |
| MAX9040BEUK+T | -40°C to +85°C | 5 SOT23 | ADNX |
| MAX9041AEUT+T | -40°C to +85°C | 6 SOT23 | AAHF |
| MAX9041BEUT+T | -40°C to +85°C | 6 SOT23 | AAHH |
| MAX9041AESA | -40°C to +85°C | 8 SO | — |
| MAX9041BESA | -40°C to +85°C | 8 SO | — |

+Denotes lead(Pb)-free/RoHS-compliant package.

*Ordering Information continued at end of data sheet.
Selector Guide appears at end of data sheet.*

Pin Configurations



Absolute Maximum Ratings

| | | | |
|--|--|---|-----------------|
| Supply Voltage (V_{CC} to V_{EE})..... | -0.3V to +6V | 6-Pin SOT23 (derate 8.70mW/°C above +70°C) | 696mW |
| OUT (MAX9038)..... | -0.3V to +6V | 8-Pin SO (derate 5.88mW/°C above +70°C)..... | 471mW |
| All Other Pins | ($V_{EE} - 0.3V$) to ($V_{CC} + 0.3V$) | 8-Pin μ MAX® (derate 4.1mW/°C above +70°C)..... | 330mW |
| Current into Input Pins | $\pm 20mA$ | 10-Pin μ MAX (derate 5.6mW/°C above +70°C)..... | 444mW |
| Output Short-Circuit Duration | | Operating Temperature Range..... | -40°C to +85°C |
| (OUT_, REF) | Indefinite Short Circuit to Either Supply | Junction Temperature..... | +150°C |
| Continuous Power Dissipation ($T_A = +70^\circ C$) | | Storage Temperature Range..... | -65°C to +150°C |
| 5-Pin SOT23 (derate 7.10mW/°C above +70°C) | 571mW | Lead Temperature (soldering, 10s) | +300°C |
| 6-Bump UCSP (derate 3.9mW/°C above +70°C)..... | 308mW | Bump Reflow Temperature (Note 1)..... | +235°C |

Note 1: This device is constructed using a unique set of packaging techniques that impose a limit on the thermal profile the device can be exposed to during board-level solder attach and rework. This limit permits only the use of the solder profiles recommended in the industry-standard specification, JEDEC 020A, paragraph 7.6, Table 3 for IR/VPR and Convection Packaging Reflow. Preheating is required. Hand or wave soldering is not allowed.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Electrical Characteristics—A Grade (0.4% Initial Accuracy)

($V_{CC} = +5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | | MIN | TYP | MAX | UNITS |
|--|------------|---|--------------------------------------|-----------------|-------------|-----------------|---------|
| Supply Voltage Range (Note 3) | V_{CC} | MAX9040–MAX9043 | | 2.5 | | 5.5 | V |
| | | MAX9050–MAX9053 | | 2.7 | | 5.5 | |
| Supply Current | I_{CC} | MAX9040/MAX9041/ MAX9050/MAX9051 | $V_{CC} = 2.7V$ | | 47 | 67 | μA |
| | | | $V_{CC} = 5V$ | | 52 | 72 | |
| | | MAX9042/MAX9043/ MAX9052/MAX9053 | $V_{CC} = 2.7V$ | | 55 | 80 | |
| | | | $V_{CC} = 5V$ | | 60 | 85 | |
| COMPARATORS | | | | | | | |
| Input Offset Voltage (Note 4) | V_{OS} | Over entire common-mode range | $T_A = +25^\circ C$ | | ± 0.5 | ± 5.0 | mV |
| | | | $T_A = -40^\circ C$ to $+85^\circ C$ | | | ± 7.0 | |
| Input Hysteresis | V_{HYST} | | | | ± 3.0 | | mV |
| Input Bias Current (Notes 5, 6, 7) | I_B | Specified common-mode range | | | ± 0.001 | ± 10.0 | nA |
| Input Offset Current (Note 5) | I_{OS} | Specified common-mode range | | | ± 0.5 | | pA |
| Common-Mode Voltage Range (Notes 5, 8) | CMVR | $T_A = +25^\circ C$ | | $V_{EE} - 0.25$ | | $V_{CC} + 0.25$ | V |
| | | $T_A = -40^\circ C$ to $+85^\circ C$ | | V_{EE} | | V_{CC} | |
| Common-Mode Rejection Ratio (Note 5) | CMRR | Specified common-mode range | | 52 | 80 | | dB |
| Power-Supply Rejection Ratio | PSRR | MAX9040–MAX9043, $2.5V \leq V_{CC} \leq 5.5V$ | | 55 | 80 | | dB |
| | | MAX9050–MAX9053, $2.5V \leq V_{CC} \leq 5.5V$ | | 55 | 80 | | |
| Input Capacitance (Note 5) | C_{IN} | | | | 2.5 | | pF |
| Output Short-Circuit Current | I_{SC} | $V_{OUT} = V_{EE}$ or V_{CC} | $V_{CC} = 5V$ | | 95 | | mA |
| | | | $V_{CC} = 2.7V$ | | 35 | | |
| Output Voltage Low | V_{OL} | $V_{CC} = 5V$, $I_{SINK} = 8mA$ | | | 0.2 | 0.55 | V |
| | | $V_{CC} = 2.7V$, $I_{SINK} = 3.5mA$ | | | 0.15 | 0.4 | |

μ MAX is a registered trademark of Maxim Integrated Products, Inc.

Electrical Characteristics —A Grade (0.4% Initial Accuracy) (continued)

($V_{CC} = +5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|--|---------------------------------|--|-----------------|-------|-------|-----------------|---|
| Output Voltage High | V_{OH} | $V_{CC} = 5V$, $I_{SOURCE} = 8mA$ | 4.45 | 4.85 | | V | |
| | | $V_{CC} = 2.7V$, $I_{SOURCE} = 3.5mA$ | 2.3 | 2.55 | | | |
| Output Rise/Fall Times | t_R/t_F | $C_L = 15pF$ | | 40 | | ns | |
| | | $C_L = 50pF$ | | 50 | | | |
| | | $C_L = 200pF$ | | 80 | | | |
| Output Propagation Delay (Note 9) | t_{PD+}/t_{PD-} | $C_L = 15pF$, $V_{CC} = 2.7V$ | | 450 | | ns | |
| | | 50mV overdrive 100mV overdrive | | 400 | | | |
| Power-Up Time | t_{PU} | Time to V_{OUT} valid logic state | | 20 | | μs | |
| VOLTAGE REFERENCE | | | | | | | |
| Output Voltage | V_{REF} | $T_A = +25^\circ C$ | MAX9040–MAX9043 | 2.040 | 2.048 | 2.056 | V |
| | | | MAX9050–MAX9053 | 2.490 | 2.500 | 2.510 | |
| Output Voltage Temperature Coefficient (Note 10) | TCV_{REF} | $\mu MAX/SO$ | | 6 | 30 | ppm/ $^\circ C$ | |
| | | SOT23 | | 6 | 50 | | |
| Line Regulation | $\Delta V_{REF}/\Delta V_{CC}$ | $2.5V \leq V_{CC} \leq 5.5V$, MAX9040–MAX9043 | | +50 | +200 | $\mu V/V$ | |
| | | $2.7V \leq V_{CC} \leq 5.5V$, MAX9050–MAX9053 | | +50 | +200 | | |
| Load Regulation | $\Delta V_{REF}/\Delta I_{REF}$ | Sourcing, $0\mu A \leq I_{REF} \leq 500\mu A$ | | 2 | 4 | $\mu V/\mu A$ | |
| | | Sinking, $-500\mu A \leq I_{REF} \leq 0\mu A$ | | 3.5 | 6 | | |
| Output Short-Circuit Current | I_{SC} | $V_{REF} = V_{EE}$ or V_{CC} | | 4 | | mA | |
| Thermal Hysteresis (Note 11) | T_{HYST} | | | 130 | | ppm | |
| Long-Term Stability | | 1000h at $T_A = +25^\circ C$ | | 50 | | ppm | |
| Noise Voltage | E_{OUT} | $f = 0.1Hz$ to $10Hz$ | | 40 | | μV_{P-P} | |
| | | $f = 10Hz$ to $10kHz$ | | 105 | | μV_{RMS} | |
| Ripple Rejection | $\Delta V_{REF}/\Delta V_{CC}$ | $V_{CC} = 5V \pm 100mV$, $f = 120Hz$ | | 84 | | dB | |
| Turn-On Settling Time | $t_R(V_{REF})$ | To $V_{REF} = 1\%$ of final value | | 200 | | μs | |
| Capacitive-Load Stability Range (Note 7) | $C_L(V_{REF})$ | | 0 | | 4.7 | nF | |

Electrical Characteristics—B Grade (1% Initial Accuracy) (Note 12)

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|-------------------------------|----------|---|-----------------|-----|-----|---------|-----|
| Supply Voltage Range (Note 3) | V_{CC} | MAX9038–MAX9043 | 2.5 | | 5.5 | V | |
| | | MAX9050–MAX9053 | 2.7 | | 5.5 | | |
| Supply Current | I_{CC} | MAX9038/MAX9039/ MAX9040/MAX9041/ MAX9050/MAX9051 | $V_{CC} = 2.7V$ | | 40 | μA | |
| | | | $V_{CC} = 5.0V$ | | 45 | | 100 |
| | | MAX9042/MAX9043/ MAX9052/MAX9053 | $V_{CC} = 2.7V$ | | 55 | | |
| | | | $V_{CC} = 5.0V$ | | 60 | | 130 |

Electrical Characteristics—B Grade (1% Initial Accuracy) (Note 12) (continued)

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|--|-------------------|--|---------------------------|--------|----------|--------|---|
| COMPARATOR | | | | | | | |
| Input Offset Voltage (Note 4) | V_{OS} | Over entire common-mode range | | ±1 | ±9.0 | mV | |
| Input Hysteresis | V_{HYST} | | | ±3.0 | | mV | |
| Input Bias Current (Notes 5, 6, 7) | I_B | Specified common-mode range | | ±0.001 | ±25.0 | nA | |
| Input Offset Current (Note 5) | I_{OS} | Specified common-mode range | | ±0.5 | | pA | |
| Common-Mode Voltage Range (Notes 5, 8) | CMVR | | V_{EE} | | V_{CC} | V | |
| Common-Mode Rejection Ratio (Note 5) | CMRR | Specified common-mode range | 52 | 80 | | dB | |
| Power-Supply Rejection Ratio | PSRR | MAX9038–MAX9043, $2.5V \leq V_{CC} \leq 5.5V$ | 55 | 80 | | dB | |
| | | MAX9050–MAX9053, $2.7V \leq V_{CC} \leq 5.5V$ | 55 | 80 | | | |
| Input Capacitance (Note 5) | C_{IN} | | | 2.5 | | pF | |
| Output Short-Circuit Current | I_{SC} | $V_{OUT} = V_{EE}$ or V_{CC} | $V_{CC} = 5V$ | 95 | | mA | |
| | | | $V_{CC} = 2.7V$ | 35 | | | |
| Output Voltage Low | V_{OL} | $V_{CC} = 5V$, $I_{SINK} = 8mA$ | | 0.2 | 0.55 | V | |
| | | $V_{CC} = 2.7V$, $I_{SINK} = 3.5mA$ | | 0.15 | | | |
| Output Voltage High (Except MAX9038) | V_{OH} | $V_{CC} = 5V$, $I_{SOURCE} = 8mA$ | 4.45 | 4.85 | | V | |
| | | $V_{CC} = 2.7V$, $I_{SOURCE} = 3.5mA$ | | 2.55 | | | |
| Output Leakage | | MAX9038 | | | 0.5 | μA | |
| Output Rise/Fall Times | t_R/t_F | $C_L = 15pF$ | | 40 | | ns | |
| | | $C_L = 50pF$ | | 50 | | | |
| | | $C_L = 200pF$ | | 80 | | | |
| Output Rise Time | t_R | $R_{PU} = 10k\Omega$, $C_L = 15pF$, MAX9038 | | 400 | | ns | |
| | | $R_{PU} = 10k\Omega$, $C_L = 50pF$, MAX9038 | | 1180 | | | |
| | | $R_{PU} = 10k\Omega$, $C_L = 200pF$, MAX9038 | | 5580 | | | |
| Output Propagation Delay (Note 9) | t_{PD+}/t_{PD-} | $C_L = 15pF$, $V_{CC} = 2.7V$ | 50mV overdrive | 450 | | ns | |
| | | | 100mV overdrive | 400 | | | |
| Output Rising Propagation Delay (Note 9) | t_{PD+} | $R_{PU} = 10k\Omega$, $C_L = 15pF$, MAX9038 | | 500 | | ns | |
| | | $R_{PU} = 10k\Omega$, $C_L = 50pF$, MAX9038 | | 1540 | | | |
| | | $R_{PU} = 10k\Omega$, $C_L = 200pF$, MAX9038 | | 3350 | | | |
| Power-Up Time | t_{PU} | Time to V_{OUT} valid logic state | | 20 | | μs | |
| VOLTAGE REFERENCE | | | | | | | |
| Output Voltage | V_{REF} | $T_A = +25^\circ C$ | MAX9038/MAX9039 (Note 12) | 1.225 | 1.230 | 1.235 | V |
| | | | MAX9040–MAX9043 | 2.028 | 2.048 | 2.068 | |
| | | | MAX9050–MAX9053 | 2.475 | 2.500 | 2.525 | |
| Output Voltage Temperature Coefficient (Note 10) | TCV_{REF} | | | 20 | 100 | ppm/°C | |

Electrical Characteristics—B Grade (1% Initial Accuracy) (Note 12) (continued)

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS |
|--|---------------------------------|---|-----------------|-----|------|---------------|
| Line Regulation | $\Delta V_{REF}/\Delta V_{CC}$ | $2.5V \leq V_{CC} \leq 5.5V$ | MAX9038–MAX9043 | +50 | +200 | $\mu V/V$ |
| | | | MAX9050–MAX9053 | +50 | +200 | |
| Load Regulation | $\Delta V_{REF}/\Delta I_{REF}$ | Sourcing: $0\mu A \leq I_{REF} \leq 500\mu A$ | | 2 | 4 | $\mu V/\mu A$ |
| | | Sinking: $-500\mu A \leq I_{REF} \leq 0\mu A$ | | 3.5 | 6 | |
| Output Short-Circuit Current | I_{SC} | $V_{REF} = V_{EE}$ or V_{CC} | | 4 | | mA |
| Thermal Hysteresis (Note 11) | T_{HYST} | | | 130 | | ppm |
| Long-Term Stability | | 1000h at $T_A = +25^\circ C$ | | 100 | | ppm |
| Ripple Rejection | $\Delta V_{REF}/\Delta V_{CC}$ | $V_{CC} = 5V \pm 100mV$, $f = 120Hz$ | | 84 | | dB |
| Turn-On Settling Time | $t_R(V_{REF})$ | To $V_{REF} = 1\%$ of final value | | 200 | | μs |
| Capacitive Load Stability Range (Note 7) | $C_L(V_{REF})$ | | 0 | | 4.7 | nF |

Note 2: All devices are 100% production tested at $T_A = +25^\circ C$. Limits over the extended temperature range are guaranteed by design.

Note 3: Supply voltage range guaranteed by PSRR test on comparator and line regulation of REF.

Note 4: V_{OS} is defined as the center of the input-referred hysteresis band.

Note 5: For the comparators with the inverting input (IN-) uncommitted.

Note 6: Input bias current is the average of the inverting and noninverting input bias currents.

Note 7: Not production tested. Guaranteed by design.

Note 8: Guaranteed by CMRR test.

Note 9: $V_{OVERDRIVE}$ is beyond the offset and hysteresis determined trip point.

Note 10: Temperature coefficient is measured by the box method; i.e., the maximum ΔV_{REF} is divided by the maximum ΔT .


Note 11: Thermal hysteresis is defined as the change in V_{REF} at $+25^\circ C$ before and after cycling the device from T_{MIN} to T_{MAX} .

Note 12: MAX9038/MAX9039 has an initial accuracy of $\pm 0.4\%$.


Typical Operating Characteristics

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = +25^\circ C$, unless otherwise noted.)


MAX9039/MAX9040/MAX9041/MAX9050/MAX9051
SUPPLY CURRENT vs. TEMPERATURE



MAX9042/MAX9043/MAX9052/MAX9053
SUPPLY CURRENT vs. TEMPERATURE










MAX9039/MAX9040/MAX9041/MAX9050/MAX9051
SUPPLY CURRENT vs. SWITCHING FREQUENCY










Typical Operating Characteristics (continued)

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = +25^\circ C$, unless otherwise noted.)



Typical Operating Characteristics (continued)


($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = +25^\circ C$, unless otherwise noted.)



Typical Operating Characteristics (continued)


($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = +25^\circ C$, unless otherwise noted.)

SWITCHING CURRENT (OUT RISING EDGE)




100ns/div
A = IN+, 100mV/div
B = OUT, 5V/div
C = I_{CC}, 1mA/div

SWITCHING CURRENT (OUT FALLING EDGE)




100ns/div
A = IN+, 100mV/div
B = OUT, 5V/div
C = I_{CC}, 1mA/div

POWER-UP DELAY (OUT)




5ms/div
A = V_{CC}, 2V/div
B = OUT, 1V/div

POWER-UP DELAY (REF)




100µs/div
A = V_{CC}, 2V/div
B = REF, 1V/div
C = REF, 50mV/div, 2.048V OFFSET


INPUT BIAS CURRENT
vs. INPUT VOLTAGE



MAX904 /MAX905
REFERENCE OUTPUT VOLTAGE
TEMPERATURE DRIFT





MAX9039
REFERENCE OUTPUT VOLTAGE
TEMPERATURE DRIFT



Typical Operating Characteristics (continued)

($V_{CC} = 5V$, $V_{EE} = 0V$, $V_{CM} = 0V$, $V_{PU} = 1.8V$, $R_{PU} = 10k\Omega$, $I_{OUT} = 0A$, $I_{REF} = 0A$, $T_A = +25^\circ C$, unless otherwise noted.)



Pin Description

| PIN | | | | | | NAME | FUNCTION |
|--------------------|--------------------|--------------------|------|--------------------|--------------------|----------|--|
| MAX9038 MAX9039 | MAX9040 MAX9050 | MAX9041 MAX9051 | | MAX9042 MAX9052 | MAX9043 MAX9053 | | |
| UCSP | SOT23 | SOT23 | SO | SO/ μ MAX | μ MAX | | |
| A2 | 1 | 1 | 6 | — | — | OUT | Comparator Output |
| A1 | 2 | 2 | 4 | 4 | 5 | V_{EE} | Negative Supply Voltage |
| B1 | 3 | 3 | 3 | — | — | IN+ | Comparator Noninverting Input |
| B3 | 4 | 5 | 1 | 2 | 2 | REF | Reference Voltage Output |
| A3 | 5 | 6 | 7 | 8 | 10 | V_{CC} | Positive Supply Voltage |
| B2 | — | 4 | 2 | — | — | IN- | Comparator Inverting Input |
| — | — | — | 5, 8 | — | 9 | N.C. | No Connection. Not internally connected. |
| — | — | — | — | 1 | 1 | OUTA | Comparator A Output |
| — | — | — | — | 3 | 4 | INA+ | Comparator A Noninverting Input |
| — | — | — | — | 5 | 6 | INB+ | Comparator B Noninverting Input |
| — | — | — | — | 6 | 7 | INB- | Comparator B Inverting Input |
| — | — | — | — | 7 | 8 | OUTB | Comparator B Output |
| — | — | — | — | — | 3 | INA- | Comparator A Inverting Input |

Detailed Description

The MAX9038–MAX9043 and MAX9050–MAX9053 feature single/dual, low-power, low-voltage comparators and a precision voltage reference. They operate from a single 2.5V to 5.5V (MAX903_/MAX904_) or 2.7V to 5.5V (MAX905_) supply. The single comparators with reference, (MAX9038/MAX9039/MAX9040/MAX9041/MAX9050/MAX9051) consume only 40µA of supply current, while the dual comparators with reference (MAX9042/MAX9043/MAX9052/MAX9053) consume only 55µA of supply current. Their common-mode input range extends 0.25V beyond each rail. Internal hysteresis ensures clean output switching, even with slow-moving input signals.

The output stage employs a unique design that minimizes supply current surges while switching, virtually eliminating the supply glitches typical of many other comparators. Large internal output drivers allow rail-to-rail output swing that can sink and source up to 8mA of current.

The precision reference uses a proprietary curvature-correction circuit and laser-trimmed thin-film resistors, resulting in a temperature coefficient of less than 30ppm/°C over the extended temperature range and initial accuracy of 0.4% (A grade). The reference output voltage is set to 1.23V in the MAX9038/MAX9039, 2.048V in the MAX9040–MAX9043, and to 2.500V in the MAX9050–MAX9053.

Comparator Input Stage Circuitry

The devices' input common-mode range extends from ($V_{EE} - 0.25V$) to ($V_{CC} + 0.25V$). These comparators may operate at any differential input voltage within these limits. Input bias current is typically 1.0pA if the input voltage is between the supply rails. Comparator inputs are protected from overvoltage by internal body diodes connected to the supply rails. As the input voltage exceeds the supply rails,




Figure 1. Additional Hysteresis

these body diodes become forward biased and begin to conduct. Consequently, bias currents increase exponentially as the input voltage exceeds the supply rails.

Comparator Output Stage Circuitry

The comparators in these devices contain a unique output stage capable of rail-to-rail operation with loads up to 8mA. Many comparators consume orders-of-magnitude more current during switching than during steady-state operation. However, with this family of comparators, the supply current change during an output transition is extremely small. The *Typical Operating Characteristics* graph Supply Current vs. Switching Frequency shows the minimal supply current increase as the output switching frequency approaches 1MHz. This characteristic reduces the need for power-supply filter capacitors to reduce glitches created by comparator switching currents. Another advantage realized in high-speed, battery-powered applications is a substantial increase in battery life. The MAX9038 is an opendrain output comparator that can be used in logic-level translation or many other applications where voltage level translation is important.

Applications Information

Additional Hysteresis

These comparators have ±3mV internal hysteresis. Additional hysteresis can be generated with two resistors using positive feedback (Figure 1). Use the following procedure to calculate resistor values:

- 1) Calculate the trip points of the comparator using these formulas:

$$V_{TH} = V_{REF} + \left(\frac{(V_{CC} - V_{REF})R2}{R1 + R2} \right)$$

$$V_{TL} = V_{REF} \left(1 - \frac{R2}{R1 + R2} \right)$$

V_{TH} is the threshold voltage at which the comparator switches its output from high to low as V_{IN} rises above the trip point. V_{TL} is the threshold voltage at which the comparator switches its output from low to high as V_{IN} drops below the trip point.

- 2) The hysteresis band will be:
- 3) In this example, let $V_{CC} = 5V$ and $V_{REF} = 2.5V$:

$$V_{HYS} = V_{TH} - V_{TL} = V_{CC} \left(\frac{R2}{R1 + R2} \right)$$




Figure 2. Time Averaging of the Input Signal for Data Recovery

$$V_{TH} = 2.5 + 2.5 \left(\frac{R2}{R1 + R2} \right)$$

and

$$V_{TL} = 2.5 \left(1 - \frac{R2}{R1 + R2} \right)$$

- 4) Select R2. In this example, we will choose 1kΩ.
- 5) Select V_{HYS}. In this example, we will choose 50mV.
- 6) Solve for R1:

$$V_{HYS} = V_{CC} \left(\frac{R2}{R1 + R2} \right)$$

$$0.050 = 5 \left(\frac{1000}{R1 + 1000} \right)$$

where R1 ≈ 100kΩ, V_{TH} = 2.525V, and V_{TL} = 2.475V.

Board Layout and Bypassing

Power-supply bypass capacitors are not typically needed, but would be called for in cases where supply impedance is high, supply leads are long, or excessive noise is expected on the supply lines. Use 100nF bypass capacitors under these conditions. Minimize signal trace lengths to reduce stray capacitance.

Reference Output/Load Capacitance

The MAX9038/MAX9039/MAX904_/MAX905_ do not require an output capacitor on REF for frequency stability. They are stable for capacitive loads up to 4.7nF. However, in applications where the load or the supply can experience step changes, an output capacitor will reduce the amount of overshoot (or undershoot) and assist the circuit's transient response. When an application is not subject to transient conditions, the REF capacitor can be omitted.

Biasing for Data Recovery

Digital data is often embedded into a bandwidth- and amplitude-limited analog path. Recovering the data can be difficult. Figure 2 compares the input signal to a time-averaged version of itself. This self-biases the threshold to the average input voltage for optimal noise margin.

Even severe phase distortion is eliminated from the digital output signal. Be sure to choose R1 and C1 so that:

$$f_{CAR} \gg \frac{1}{2\pi R1 C1}$$

where f_{CAR} is the fundamental carrier frequency of the digital data stream.


Functional Diagrams



Selector Guide

| PART | COMPARATORS PER PACKAGE | V _{REF} (V) | IN- CONNECTIONS |
|---------|-------------------------|----------------------|-------------------------|
| MAX9038 | 1 | 1.230 | Uncommitted |
| MAX9039 | 1 | 1.230 | Uncommitted |
| MAX9040 | 1 | 2.048 | REF |
| MAX9041 | 1 | 2.048 | Uncommitted |
| MAX9050 | 1 | 2.500 | REF |
| MAX9051 | 1 | 2.500 | Uncommitted |
| MAX9042 | 2 | 2.048 | REF/Uncommitted |
| MAX9043 | 2 | 2.048 | Uncommitted/Uncommitted |
| MAX9052 | 2 | 2.500 | REF/Uncommitted |
| MAX9053 | 2 | 2.500 | Uncommitted/Uncommitted |

Pin Configurations (continued)




Ordering Information (continued)

| PART | TEMP RANGE | PIN-PACKAGE | TOP MARK |
|-----------------------|----------------|-------------|----------|
| MAX9042 AEUA | -40°C to +85°C | 8 μMAX | — |
| MAX9042BEUA | -40°C to +85°C | 8 μMAX | — |
| MAX9042AESA | -40°C to +85°C | 8 SO | — |
| MAX9042BESA | -40°C to +85°C | 8 SO | — |
| MAX9043 AEUB | -40°C to +85°C | 10 μMAX | — |
| MAX9043BEUB | -40°C to +85°C | 10 μMAX | — |
| MAX9050 AEUK+T | -40°C to +85°C | 5 SOT23 | ADNW |
| MAX9050BEUK+T | -40°C to +85°C | 5 SOT23 | ADNY |
| MAX9051 AEUT+T | -40°C to +85°C | 6 SOT23 | AAHG |
| MAX9051BEUT+T | -40°C to +85°C | 6 SOT23 | AAHI |
| MAX9051AESA | -40°C to +85°C | 8 SO | — |
| MAX9051BESA | -40°C to +85°C | 8 SO | — |
| MAX9052 AEUA | -40°C to +85°C | 8 μMAX | AAHG |
| MAX9052BEUA | -40°C to +85°C | 8 μMAX | AAHI |
| MAX9052AESA | -40°C to +85°C | 8 SO | — |
| MAX9052BESA | -40°C to +85°C | 8 SO | — |
| MAX9053 AEUB | -40°C to +85°C | 10 μMAX | — |
| MAX9053BEUB | -40°C to +85°C | 10 μMAX | — |

+Denotes lead(Pb)-free/RoHS-compliant package.

Typical Operating Circuit



Chip Information

PROCESS: CMOS

MAX9038–MAX9043/
MAX9050–MAX9053

Micropower, Single-Supply, UCSP/SOT23
Comparator + Precision Reference ICs

Package Information

For the latest package outline information and land patterns (footprints), go to www.maximintegrated.com/packages. Note that a “+”, “#”, or “-” in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE | PACKAGE CODE | OUTLINE NO. | LAND PATTERN NO. |
|--------------|--------------|-------------------------|-------------------------|
| 6 UCSP | B6-3 | 21-0097 | — |
| 5 SOT23 | — | 21-0057 | 90-0174 |
| 6 SOT23 | — | 21-0058 | 90-0175 |
| 8 SO | — | 21-0041 | 90-0096 |
| 8 FMAX | — | 21-0036 | 90-0092 |
| 10 FMAX | — | 21-0061 | 90-0330 |

Revision History

| REVISION NUMBER | REVISION DATE | DESCRIPTION | PAGES CHANGED |
|-----------------|---------------|---|-----------------|
| 0 | 10/99 | Initial release | — |
| 1 | 1/00 | Corrections to initial release | — |
| 2 | 4/00 | Adding new part | — |
| 3 | 4/00 | Increase in Max Supply Current specifications | — |
| 4 | 10/02 | Adding UCSP package for MAX9039 | — |
| 5 | 10/07 | Adding input current ratings in <i>Absolute Maximum Ratings</i> , style changes | — |
| 6 | 3/09 | Update <i>Chip Information</i> , <i>Package Information</i> , correct MAX9053 part number, style changes | 1, 2, 10, 12–19 |
| 7 | 3/13 | Updated the <i>General Description</i> , <i>Electrical Characteristics</i> , and the <i>Package Information</i> | 1, 3-5, 13 |
| 8 | 9/13 | Added the MAX9038 and lead-free information to the data sheet. | 1–15 |
| 9 | 11/15 | Added MAX9039BEBT+T10 to <i>Ordering Information</i> | 1 |
| 10 | 1/17 | Removed MAX9039BEBT+T10 from <i>Ordering Information</i> table | 1 |

For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at www.maximintegrated.com.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the *Electrical Characteristics* table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View MAX9052BEUA+T on WIN SOURCE](#)
- ⊖ [Maxim Integrated Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management