



**THE DATASHEET OF
MEM2012P10R0T001**



3-terminal Filters(SMD) For Wide-band

Conformity to RoHS Directive

MEM Series MEM2012P Type

FEATURES

- Multilayer chip EMC filter that is small and low-profile due to the use of a π -type circuit.
- Entirely monolithic structure results in high reliability.
- Due to closed magnetic circuit architecture, high-density installation becomes possible, and crosstalk generation is prevented.
- Steep attenuation characteristic plot. Highly effective noise suppression.
- Covers a wide range of frequencies.
- π -type circuit with 1 coil / 2 capacitors construction.

APPLICATIONS

Computers, computer peripherals, VCRs, TVs, car audio equipment, printers, game machines, etc.

TEMPERATURE RANGES

| | |
|-------------------|--------------|
| Operating/Storage | -40 to +85°C |
|-------------------|--------------|

PRODUCT IDENTIFICATION

| | | | | |
|-----|------|-----|------|-----|
| MEM | 2012 | P | 10R0 | T |
| (1) | (2) | (3) | (4) | (5) |

- (1) Series name
 (2) Dimensions L×W
 (3) π -type circuit
 (4) Cutoff frequency 10R0:10MHz
 (5) Packaging style T:Taping

PACKAGING STYLE AND QUANTITIES

| Packaging style | Quantity |
|-----------------|--------------------|
| Taping | 4000 pieces / reel |

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN



Weight: 8mg



Dimensions in mm

ELECTRICAL CHARACTERISTICS

| Part No. | Cutoff frequency (MHz) | Attenuation (dB)min. | Rated voltage Edc(V)max. | Rated current Idc(mA)max. |
|--------------|------------------------|----------------------|--------------------------|---------------------------|
| MEM2012P10R0 | 10 | 20[0.2 to 2GHz] | 12 | 200 |
| MEM2012P25R0 | 25 | 20[0.3 to 2GHz] | 12 | 200 |
| MEM2012P50R0 | 50 | 20[0.4 to 2GHz] | 12 | 200 |
| MEM2012P75R0 | 75 | 20[0.7 to 2GHz] | 12 | 200 |
| MEM2012P101R | 100 | 20[1.5 to 2GHz] | 12 | 200 |

- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- Please contact our Sales office when your application are considered the following:
The device's failure or malfunction may directly endanger human life (e.g. application for automobile/aircraft/medical/nuclear power devices, etc.)

- All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS ATTENUATION vs. FREQUENCY CHARACTERISTICS



MEASURING CIRCUIT



RECOMMENDED SOLDERING CONDITION REFLOW SOLDERING



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View MEM2012P10R0T001 on WIN SOURCE](#)
- ⊖ [TDK Corporation](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management