



THE DATASHEET OF MINISMDC150-2



Raychem Circuit Protection
 308 Constitution Drive
 Menlo Park, CA 94025-1164
 800-227-4856
 FAX 800-227-4866

RAYCHEM
PolySwitch®
PTC Devices
 Overcurrent Protection Device

PRODUCT: miniSMD150
 DOCUMENT: SCD 24264
 PCN: 439545
 REV LETTER: F
 REV DATE: OCTOBER 25, 2000
 PAGE NO.: 1 OF 1

Specification Status: RELEASED

Maximum Electrical Rating

Voltage: 6V_{DC}
Short Circuit Current: 100A

Notes:

1. All terminations are tin/lead plated.
2. Devices can be wave soldered.
3. Drawing not to scale

Marking:





TABLE I. DIMENSIONS:

	A		B		C		D	E	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN	MAX
mm:	4.37	4.73	3.07	3.41	0.28	0.48	0.25	0.20	0.50
in:	(0.172)	(0.186)	(0.121)	(0.134)	(0.011)	(0.019)	(0.010)	(0.008)	(0.020)

TABLE II. PERFORMANCE RATINGS:

IHOLD ** RATED CURRENT	HOLD CURRENT AT TEMPERATURE**				TIME TO TRIP ** @ 8.0A	RESISTANCE VALUES		**TRIPPED-STATE POWER DISSIPATION	
	AMPERES AT 20°C HOLD	AMPERES AT - 40°C HOLD	AMPERES AT 20°C HOLD	AMPERES AT 55°C HOLD		OHMS AT 20°C			WATTS AT 20°C MAX
						MIN	MAX*		
1.5	2.30	1.50	1.00	0.5	0.040	0.110	0.8		

* Maximum resistance is measured 1 hour after reflow.

**Values Specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents: PS300, E. N. SMD1.0x



Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View MINISMDC150-2 on WIN SOURCE](#)
-  [Littelfuse Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management