

Features


- Dual TVS in Common Anode Configuration
- 24W/40W Peak Power Dissipation Rating @ 1.0ms (Unidirectional)
- 225mW Power Dissipation
- Ideally Suited for Automated Insertion
- Low Leakage
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT23
- Case Material: Molded Plastic "Green" Molding Compound. UL Flammability Classification 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Solderable per MIL-STD-202, Method 208 (e3)
- Polarity: See Diagram
- Lead Free Plating (Matte Tin Finish Annealed over Alloy 42 Leadframe).
- ESD Rating Exceeding 16kV per the Human Body Model (Note 9)
- Marking Information: See Below
- Ordering Information: See Below
- Weight: 0.008 grams (Approximate)



Top View



Device Schematic


Ordering Information (Note 5)

| Part Number | Qualification | Case | Packaging |
|------------------------------|---------------|-------|--------------------|
| (Type Number)-7*-F | Commercial | SOT23 | 3,000/Tape & Reel |
| (Type Number)Q-7*-F (Note 4) | Automotive | SOT23 | 3,000/Tape & Reel |
| MMBZ27VALQ-13-F (Note 4) | Automotive | SOT23 | 10,000/Tape & Reel |

* Example: 5.6V type = MMBZ5V6AL-7-F.

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
 2. See <http://www.diodes.com> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 4. Automotive products are AEC-Q101 qualified and are PPAP capable. Automotive, AEC-Q101 and standard products are electrically and thermally the same, except where specified. For more information, please refer to <https://www.diodes.com/quality/product-compliance-definitions/>.
 5. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.

Marking Information



xxx = Product type marking code,
See Electrical Characteristics Table, Pages 2
YM = Date Code Marking
Y = Year (ex: F = 2018)
M = Month (ex: 9 = September)

Date Code Key

| Year | 2006 | 2007 | 2008 | 2009 | | 2018 | 2019 | 2020 | 2021 | 2022 | 2023 | 2024 | 2025 |
|------|------|------|------|------|-------|------|------|------|------|------|------|------|------|
| Code | T | U | V | W | | F | G | H | I | J | K | L | M |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|--|-----------------|-------|------|
| Peak Power Dissipation: MMBZ5V6AL - MMBZ10VAL (Note 7) | P _{PK} | 24 | W |
| Peak Power Dissipation: MMBZ15VAL - MMBZ33VAL (Note 7) | P _{PK} | 40 | W |

Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|--|-----------------------------------|-------------|------|
| Power Dissipation (Note 6) | P _D | 225 | mW |
| Thermal Resistance, Junction to Ambient Air (Note 6) | R _{θJA} | 556 | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -65 to +150 | °C |

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

24 Watt (V_F = 0.9V max @ I_F = 10mA)

| Type Number | Marking Code | V _{RWM} | Max Reverse Current, I _R @ V _{RWM} (Note 8) | Breakdown Voltage | | | @ I _T | Max. Clamping Voltage, V _C @ I _{PP} (Note 7) | | Typical Temperature Coefficient of Reverse Voltage T _C (mV/°C) |
|-------------|--------------|------------------|---|------------------------------|-----|------|------------------|--|-----------------|--|
| | | | | V _{BR} (Note 8) (V) | | | | V _C | I _{PP} | |
| | | | | Volts | μA | Min | | Nom | Max | |
| MMBZ5V6AL | K9A | 3 | 5.0 | 5.32 | 5.6 | 5.88 | 20 | 8.0 | 3.0 | 1.8 |

24 Watt (V_F = 0.9V max @ I_F = 10mA)

| Type Number | Marking Code | V _{RWM} | Max Reverse Current, I _R @ V _{RWM} (Note 8) | Breakdown Voltage | | | @ I _T | Max. Clamping Voltage, V _C @ I _{PP} (Note 7) | | Typical Temperature Coefficient of Reverse Voltage T _C (%/°C) |
|-------------|--------------|------------------|---|------------------------------|-----|------|------------------|--|-----------------|---|
| | | | | V _{BR} (Note 8) (V) | | | | V _C | I _{PP} | |
| | | | | Volts | μA | Min | | Nom | Max | |
| MMBZ6V2AL | K9B | 3.0 | 0.5 | 5.89 | 6.2 | 6.51 | 1.0 | 8.7 | 2.76 | +0.04 |
| MMBZ6V8AL | K9C | 4.5 | 0.5 | 6.46 | 6.8 | 7.14 | 1.0 | 9.6 | 2.5 | +0.045 |
| MMBZ9V1AL | K9D | 6.0 | 0.3 | 8.65 | 9.1 | 9.56 | 1.0 | 14 | 1.7 | +0.065 |
| MMBZ10VAL | K9E | 6.5 | 0.3 | 9.50 | 10 | 10.5 | 1.0 | 14.2 | 1.7 | +0.065 |

40 Watt (V_F = 0.9V max @ I_F = 10mA)

| Type Number | Marking Code | V _{RWM} | Max. Reverse Current, I _R @ V _{RWM} (Note 8) | Breakdown Voltage | | | @ I _T | Max. Clamping Voltage, V _C @ I _{PP} (Note 7) | | Typical Temperature Coefficient of Reverse Voltage T _C (%/°C) |
|-------------|--------------|------------------|--|------------------------------|----|-------|------------------|--|-----------------|---|
| | | | | V _{BR} (Note 8) (V) | | | | V _C | I _{PP} | |
| | | | | Volts | nA | Min | | Nom | Max | |
| MMBZ15VAL | K9K | 12 | 50 | 14.25 | 15 | 15.75 | 1.0 | 21 | 1.9 | +0.080 |
| MMBZ18VAL | K9L | 14.5 | 50 | 17.10 | 18 | 18.90 | 1.0 | 25 | 1.6 | +0.090 |
| MMBZ20VAL | K9N | 17 | 50 | 19.00 | 20 | 21.00 | 1.0 | 28 | 1.4 | +0.090 |
| MMBZ27VAL | K9Q | 22 | 50 | 25.65 | 27 | 28.35 | 1.0 | 40 | 1.0 | +0.090 |
| MMBZ33VAL | K9T | 26 | 50 | 31.35 | 33 | 34.65 | 1.0 | 46 | 0.87 | +0.090 |

- Notes:
- Device mounted on FR-4 PCB pad layout (2oz copper) as shown on Diodes website at <http://www.diodes.com/package-outlines.html>.
 - Non-repetitive current pulse per Figure 2 and derate above T_A = +25°C per Figure 2.
 - Short duration pulse test used to minimize self-heating effect.
 - MMBZ5V6AL and MMBZ15VAL exceed 16kV ESD rating, all other voltages exceed 8kV ESD rating.




Fig. 1 Pulse Derating Curve




Fig. 2 Pulse Waveform




Fig. 3 Typical Capacitance vs. Bias Voltage
(Lower curve is Bidirectional mode,
Upper curve is Unidirectional mode)




Fig. 4 Typical Capacitance vs. Bias Voltage
(Lower curve is Bidirectional mode,
Upper curve is Unidirectional mode)




Fig. 5 Steady State Power Derating Curve




Fig. 6 Pulse Rating Curve, P_{pk} (W) vs. Pulse Width (ms)

Power is defined as $P_{pk} = V_C \times I_{pp}$





Fig. 7 Pulse Rating Curve, $P_{pk(NOM)}$ (W) vs. Pulse Width (ms)

Power is defined as $P_{pk(NOM)} = V_{BR(NOM)} \times I_{pp}$
 where $V_{BR(NOM)}$ is the nominal reverse breakdown voltage measured at the low test current used for voltage classification

Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SOT23




| SOT23 | | | |
|----------------------|-------|-------|-------|
| Dim | Min | Max | Typ |
| A | 0.37 | 0.51 | 0.40 |
| B | 1.20 | 1.40 | 1.30 |
| C | 2.30 | 2.50 | 2.40 |
| D | 0.89 | 1.03 | 0.915 |
| F | 0.45 | 0.60 | 0.535 |
| G | 1.78 | 2.05 | 1.83 |
| H | 2.80 | 3.00 | 2.90 |
| J | 0.013 | 0.10 | 0.05 |
| K | 0.890 | 1.00 | 0.975 |
| K1 | 0.903 | 1.10 | 1.025 |
| L | 0.45 | 0.61 | 0.55 |
| L1 | 0.25 | 0.55 | 0.40 |
| M | 0.085 | 0.150 | 0.110 |
| a | 0° | 8° | -- |
| All Dimensions in mm | | | |

Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SOT23



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 2.0 |
| X | 0.8 |
| X1 | 1.35 |
| Y | 0.9 |
| Y1 | 2.9 |

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

www.diodes.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View MMBZ6V2AL-7-F on WIN SOURCE](#)
- ⊖ [Diodes Incorporated Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management