



**THE DATASHEET OF
NLC252018T-1R0K-S**



Inductors

For Power Line SMD

NLC Series NLC2520 Type

FEATURES

- The NLC series feature low DC resistance and high current handling capacities, making them ideal for power supply line applications.
- They are available in 4 form factors ranging from 2520 to 5650.

APPLICATIONS


Portable telephones, personal computers, hard disk drives, and other electronic equipment.

SPECIFICATIONS


Operating temperature range	-20 to +85°C
Storage temperature range	-40 to +85°C [Unit of products]

RECOMMENDED SOLDERING CONDITIONS

REFLOW SOLDERING




FLOW SOLDERING



IRON SOLDERING

Perform soldering at 250°C on 30W max. within 5 seconds.

VAPOR-PHASING



FLUX AND CLEANING

Rosin-based flux is recommended.

Cleaning Conditions

Solvent	Chlorine-based solvent (Do not use acid or alkali solvents.)
Time	2min max.

PRODUCT IDENTIFICATION

NLC	252018	T-	2R2	M
(1)	(2)	(3)	(4)	(5)

(1) Series name

(2) Dimensions L×W×T

252018	2.5×2.0×1.8mm
322522	3.2×2.5×2.2mm
453232	4.5×3.2×3.2mm
565050	5.6×5.0×5.0mm

(3) Packaging style

T	Taping(reel)
---	--------------

(4) Inductance value

1R0	1μH
330	33μH

(5) Inductance tolerance

K	±10%
M	±20%

PACKAGING STYLE AND QUANTITIES


Packaging style	Type	Quantity
Taping	NLC252018T	2000 pieces/reel
	NLC322522T	2000 pieces/reel
	NLC453232T	500 pieces/reel
	NLC565050T	400 pieces/reel

Inductors

For Power Line
SMD

NLC Series NLC2520 Type

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN




ELECTRICAL CHARACTERISTICS

Inductance (μH)	Inductance tolerance	Q ref.	Test frequency L, Q (MHz)	Self-resonant frequency (MHz)min.	DC resistance (Ω)±30%	Rated current (mA)max.	Part No.
1	±20%	20	7.96	200	0.34	475	NLC252018T-1R0M
1.5	±20%	20	7.96	165	0.42	435	NLC252018T-1R5M
2.2	±20%	20	7.96	95	0.5	390	NLC252018T-2R2M
3.3	±20%	20	7.96	55	0.65	340	NLC252018T-3R3M
4.7	±20%	20	7.96	43	0.8	285	NLC252018T-4R7M
6.8	±20%	20	7.96	39	1	275	NLC252018T-6R8M
10	±10%	30	2.52	32	1.69	210	NLC252018T-100K
15	±10%	30	2.52	21	2.2	175	NLC252018T-150K
22	±10%	30	2.52	18	2.8	160	NLC252018T-220K
33	±10%	30	2.52	16	4.2	120	NLC252018T-330K


- Test equipment L, Q: YHP4194A IMPEDANCE ANALYZER+YHP16085A+YHP16093B+TF-1, or equivalent
SRF: HP8753C NETWORK ANALYZER (Z_{in}=Z_{out}=50Ω), or equivalent
Rdc: MATSUSHITA VP-2941A DIGITAL MILLIOHM METER, or equivalent

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE CHANGE vs. DC SUPERPOSITION CHARACTERISTICS





IMPEDANCE vs. FREQUENCY CHARACTERISTICS



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View NLC252018T-1R0K-S on WIN SOURCE](#)
-  [TDK Corporation](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management