



**THE DATASHEET OF  
NSR0240P2T5G**



# NSR0240P2T5G

## Schottky Barrier Diode

Schottky barrier diodes are optimized for very low forward voltage drop and low leakage current and are used in a wide range of dc–dc converter, clamping and protection applications in portable devices. NSR0240P2 in a SOD–923 miniature package enables designers to meet the challenging task of achieving higher efficiency and meeting reduced space requirements.

### Features

- Very Low Forward Voltage Drop – 460 mV @ 100 mA
- Low Reverse Current – 0.2  $\mu$ A @ 25 V VR
- 200 mA of Continuous Forward Current
- Power Dissipation of 240 mW with Minimum Trace
- Very High Switching Speed
- Low Capacitance – CT = 7 pF
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC–Q101 Qualified and PPAP Capable
- This is a Pb–Free Device

### Typical Applications

- LCD and Keypad Backlighting
- Camera Photo Flash
- Buck and Boost dc–dc Converters
- Reverse Voltage and Current Protection
- Clamping & Protection

### Markets

- Mobile Handsets
- MP3 Players
- Digital Camera and Camcorders
- Notebook PCs & PDAs
- GPS

### MAXIMUM RATINGS

| Rating  | Symbol    | Value               | Unit |
|---|-----------|---------------------|------|
| Reverse Voltage                               | $V_R$     | 40                  | V    |
| Forward Current (DC)                          | $I_F$     | 200                 | mA   |
| Non–Repetitive Peak Forward Surge Current     | $I_{FSM}$ | 2.0                 | A    |
| ESD Rating: Human Body Model<br>Machine Model | ESD       | Class 1C<br>Class A |      |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



ON Semiconductor®


[www.onsemi.com](http://www.onsemi.com)

## 40 V SCHOTTKY BARRIER DIODE



SOD–923  
CASE 514AB

### MARKING DIAGRAM



P = Specific Device Code  
M = Month Code  
■ = Pb–Free Package  
(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device        | Package              | Shipping†          |
|---------------|----------------------|--------------------|
| NSR0240P2T5G  | SOD–923<br>(Pb–Free) | 8000 / Tape & Reel |
| NSVR0240P2T5G | SOD–923<br>(Pb–Free) | 8000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# NSR0240P2T5G

## THERMAL CHARACTERISTICS

| Characteristic   | Symbol                   | Min | Typ | Max         | Unit                            |
|--|--------------------------|-----|-----|-------------|---------------------------------|
| Thermal Resistance<br>Junction-to-Ambient (Note 1)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$ | $R_{\theta JA}$<br>$P_D$ |     |     | 520<br>240  | $^\circ\text{C}/\text{W}$<br>mW |
| Thermal Resistance<br>Junction-to-Ambient (Note 2)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$ | $R_{\theta JA}$<br>$P_D$ |     |     | 175<br>710  | $^\circ\text{C}/\text{W}$<br>mW |
| Junction and Storage Temperature Range   | $T_J, T_{stg}$           |     |     | -55 to +150 | $^\circ\text{C}$                |

- Mounted onto a 4 in square FR-4 board 10 mm sq. 1 oz. Cu 0.06" thick single sided. Operating to steady state.
- Mounted onto a 4 in square FR-4 board 1 in sq. 1 oz. Cu 0.06" thick single sided. Operating to steady state.

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic   | Symbol | Min | Typ                  | Max                   | Unit          |
|--|--------|-----|----------------------|-----------------------|---------------|
| Reverse Leakage<br>( $V_R = 25\text{ V}$ )<br>( $V_R = 40\text{ V}$ )                              | $I_R$  |     | 0.2<br>0.8           | 0.55<br>5.0           | $\mu\text{A}$ |
| Forward Voltage ( $I_F = 10\text{ mA}$ )<br>( $I_F = 100\text{ mA}$ )<br>( $I_F = 200\text{ mA}$ ) | $V_F$  |     | 0.34<br>0.46<br>0.54 | 0.365<br>0.50<br>0.60 | V             |
| Total Capacitance<br>( $V_R = 1.0\text{ V}, f = 1\text{ MHz}$ )                                    | $C_T$  |     | 7.0                  |                       | pF            |




Figure 1. Forward Voltage




Figure 2. Leakage Current







Figure 3. Total Capacitance

# NSR0240P2T5G

## PACKAGE DIMENSIONS

**SOD-923**  
CASE 514AB  
ISSUE C




**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM            | MILLIMETERS |      |      | INCHES    |       |       |
|----------------|-------------|------|------|-----------|-------|-------|
|                | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A              | 0.34        | 0.37 | 0.40 | 0.013     | 0.015 | 0.016 |
| b              | 0.15        | 0.20 | 0.25 | 0.006     | 0.008 | 0.010 |
| c              | 0.07        | 0.12 | 0.17 | 0.003     | 0.005 | 0.007 |
| D              | 0.75        | 0.80 | 0.85 | 0.030     | 0.031 | 0.033 |
| E              | 0.55        | 0.60 | 0.65 | 0.022     | 0.024 | 0.026 |
| H <sub>E</sub> | 0.95        | 1.00 | 1.05 | 0.037     | 0.039 | 0.041 |
| L              | 0.19 REF    |      |      | 0.007 REF |       |       |
| L2             | 0.05        | 0.10 | 0.15 | 0.002     | 0.004 | 0.006 |

**SOLDERING FOOTPRINT\***



See Application Note AND8455/D for more mounting details

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**ON Semiconductor** and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

**PUBLICATION ORDERING INFORMATION**

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View NSR0240P2T5G on WIN SOURCE](#)

 [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management