







**THE DATASHEET OF
PE-68628**



ISDN U-INTERFACE TRANSFORMERS

For Applications with 2B1Q and 4B3T Coding




-  Matched to leading transceiver ICs
-  Parts meet ANSI T1.601-1992 and ETSI ETR 080
-  Transformer models with 2000Vrms to 3000Vrms minimum isolation
-  UL recognized

Electrical Specifications @ 25°C — Operating Temperature 0°C to 70°C


Isolation Voltage (Vrms MIN)	Part Number	Turns Ratio Line:Chip (±3%)	Line Side Pins	OCL Line side (mH)	DCR Line Side (Ω)	DCR Chip Side (Ω)	IDC (mA)	Lead Length	Package/Schematic
2000 Vrms	PE-65575*	1.65:1	(1-4)	13.0-18.0	5.2 ±15%	3.0 ±15%	50	0.15 ± 0.03 (3,81 ± 0,76)	IU-3/W ⁴
	PE-65578	1.32:1	(1-4)	7.0-8.3	2.4 MAX	2.7 MAX	55	0.15 ± 0.03 (3,81 ± 0,76)	IU-3/X
	PE-65579	2.00:1	(1-5)	25.5-28.5	11.6 MAX	6.4 MAX	60	0.17 ± 0.04 (4,32 ± 1,02)	IU-5/Y
	PE-65581	1.50:1	(4-2)	14.2-15.8	16.0 MAX	2.5 MAX	60	0.17 ± 0.04 (4,32 ± 1,02)	IU-5/Z
	PE-65583	1.50:1	(4-2)	25.6-29.0	20.0 MAX	3.0 MAX	60	0.16 ± 0.03 (4,06 ± 0,76)	IU-5/Z ²
	PE-65584	1.50:1	(1-5)	25.6-29.0	20.0 MAX	3.0 MAX	60	0.17 ± 0.04 (4,32 ± 1,02)	IU-5/Y ²
2500 Vrms	PE-68628*	1.25:1	(1-5)	26.5-29.5	12.0 MAX	7.0 MAX	80	0.16 ± 0.03 (4,06 ± 0,76)	IU-5/Y ²
	PE-68631	1.50:1	(4-2)	25.6-29.0	20.0 MAX	3.0 MAX	60	0.13 ± 0.03 (3,30 ± 0,76)	IU-7/Z ²
	PE-68681	1.50:1	(1-5)	25.6-28.4	20.0 MAX	3.0 MAX	60	0.13 ± 0.03 (3,30 ± 0,76)	IU-7/Y ²
3000Vrms	PE-68668*	1.25:1	(1-5)	26.5-29.5	13.0 MAX	7.5 MAX	80	0.13 ± 0.03 (3,30 ± 0,76)	IU-7/Y ²
	PE-68669*	1.65:1	(1-4)	13.0-18.0	5.2 ±15%	3.0 ±15%	50	0.13 ± 0.03 (3,30 ± 0,76)	IU-3/W

NOTE: For surface mount versions of these parts, please see data sheet T614. New small surface mount package available. Contact Pulse Application Engineering at (619) 674-8100 for more information. *Operating temperature range: -40°C to 85°C.

Mechanicals



Schematics



Dimensions: $\frac{\text{Inches}}{\text{mm}}$
 Unless otherwise specified,
 all tolerances are $\pm \frac{.010}{0,25}$

ISDN U-INTERFACE TRANSFORMERS

For Applications with 2B1Q and 4B3T Coding



Additional Specifications

Return Loss (2B1Q) (10 and 25Hz)	Longitudinal Balance (2B1Q)		Longitudinal Balance (4B3T)		Surge Voltage Resistability (ALL)	
20dB MIN	28Hz to 40kHz	55dB MIN	5kHz	20dB MIN	Metallic @ 800V Peak	10/700µsec
—	Above 40kHz	-20dB/decade	20kHz-150kHz	40dB MIN	Long. @ 2400V Peak	10/560µsec
—	—	—	1MHz	36dB MIN	—	—

Transformer Selection

Company	Chip	Coding	Transformer 2000Vrms Isolation	Transformer High Isolation Models
Motorola	MC145472	2B1Q	PE-65579	—
Motorola	MC145572	2B1Q	PE-68628	PE-68668
National	TP 3410	2B1Q	PE-65583 ⁽¹⁾	PE-68631
			PE-65584 ⁽¹⁾	PE-68681
Siemens	PEB 2091	2B1Q	PE-65575 ⁽⁴⁾	PE-68669
Siemens	PEB 2090 PEB 20901	4B3T	PE-65578	—
Thomson	SD 5411	2B1Q	PE-65581	—

For More Information:

Pulse Worldwide Headquarters

12220 World Trade Dr.
San Diego, CA 92128
U.S.A.

www.pulseeng.com

Tel: 858 674 8100

Fax: 858 674 8262

Pulse Europe

Einsteinstrasse 1
D-71083 Herrenberg
Germany

Tel: 49 7032 7806 0

Fax: 49 7032 7806 12

Pulse China Headquarters

B402, Shenzhen
Tech-Innovation International
Tenth Kejinan Rd.
High-Tech Industrial Park
Nanshan District, Shenzhen
China

Tel: 86 755 33966678

Fax: 86 755 33966700

Pulse North China

Room 1503
XinYin Building
No. 888 YiShan Rd.
Shanghai 200233
China

Tel: 86 21 54643211/2

Fax: 86 21 54643210

Pulse South Asia

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324

Tel: 65 6287 8998

Fax: 65 6280 0080

Pulse North Asia

No. 26
Kao Ching Rd.
Yang Mei Chen
Tao Yuan Hsien
Taiwan, R. O. C.

Tel: 886 3 4641811

Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2007. Pulse Engineering, Inc. All rights reserved.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View PE-68628 on WIN SOURCE](#)

 [Pulse Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management