




# THE DATASHEET OF STPS140U



## 40 V power Schottky rectifier



### Features

- Very small conduction losses
- Negligible switching losses
- Low forward voltage drop
- Surface mount miniature packages
- Avalanche rated
- ECOPACK<sup>®</sup>2 compliant

### Applications

- Reverse polarity protection
- Set-top box power supply
- TV power supply
- Battery charger

### Description

Single chip Schottky rectifiers suited to switched mode power supplies and high frequency DC to DC converters.

Packaged in SMA and SMB, the **STPS140** is ideal for use in surface mounting and used in low voltage, high frequency inverters, free-wheeling and polarity protection applications.

Product status	
STPS140	
Product summary	
Symbol	Value
$I_{F(AV)}$	1 A
$V_{RRM}$	40 V
$T_{j(max.)}$	150 °C
$V_{F(typ.)}$	0.43 V

# 1 Characteristics

**Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)**

Symbol	Parameter	Value	Unit	
$V_{RRM}$	Repetitive peak reverse voltage	40	V	
$I_{F(RMS)}$	Forward rms current	7	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$ , square wave	SMA $T_L = 130\text{ °C}$	1	A
		SMB $T_L = 135\text{ °C}$		
$I_{FSM}$	Surge non repetitive forward current	$t_p = 10\text{ ms}$ sinusoidal	60	A
$P_{ARM}$	Repetitive peak avalanche power	$t_p = 10\text{ }\mu\text{s}$ , $T_j = 125\text{ °C}$	65	W
$T_{stg}$	Storage temperature range	-65 to +150	°C	
$T_j$	Operating junction temperature <sup>(1)</sup>	+150	°C	

1.  $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$  condition to avoid thermal runaway for a diode on its own heatsink.

**Table 2. Thermal resistance parameter**

Symbol	Parameter	Max. value	Unit
$R_{th(j-l)}$	Junction to lead	SMA	30
		SMB	25

For more information, please refer to the following application note :

- AN5088 : Rectifiers thermal management, handling and mounting recommendations

**Table 3. Static electrical characteristics**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_R^{(1)}$	Reverse leakage current	$T_j = 25\text{ °C}$	-		12	$\mu\text{A}$
		$T_j = 100\text{ °C}$	-	0.25	2	mA
$V_F^{(2)}$	Forward voltage drop	$T_j = 25\text{ °C}$	-		0.55	V
		$T_j = 125\text{ °C}$	-	0.43		
		$T_j = 25\text{ °C}$	-		0.65	
		$T_j = 125\text{ °C}$	-	0.53	0.60	

1. Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$







2. Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$






To evaluate the conduction losses, use the following equation:

$$P = 0.40 \times I_{F(AV)} + 0.10 \times I_{F(RMS)}^2$$

For more information, please refer to the following application notes related to the power losses :

- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses on a power diode

**1.1 Characteristics (curves)**
**Figure 1. Average forward power dissipation versus average forward current**

**Figure 2. Average forward current versus ambient temperature (SMA,  $\delta = 0.5$ )**

**Figure 3. Average forward current versus ambient temperature (SMB,  $\delta = 0.5$ )**

**Figure 4. Normalized avalanche power derating versus pulse duration ( $T_j = 125$  °C)**

**Figure 5. Relative variation of thermal impedance junction to ambient versus pulse duration (SMA)**

**Figure 6. Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)**


**Figure 7. Reverse leakage current versus reverse voltage applied (typical values)**

**Figure 8. Junction capacitance versus reverse voltage applied (typical values)**

**Figure 9. Forward voltage drop versus forward current (maximum values)**

**Figure 10. Thermal resistance junction to ambient versus copper surface under each lead (typical values)**

**Figure 11. Thermal resistance junction to ambient versus copper surface under each lead (typical values)**



## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK®** packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 2.1 SMB package information

- Epoxy meets UL94, V0
- Lead-free package


Figure 12. SMB package outline



**Table 4. SMB package mechanical data**

Ref.	Dimensions			
	Millimeters		Inches (for reference only)	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.074	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.076	0.087
c	0.15	0.40	0.005	0.016
D	3.30	3.95	0.129	0.156
E	5.10	5.60	0.200	0.220
E1	4.05	4.60	0.159	0.181
L	0.75	1.50	0.029	0.059

**Figure 13. SMB recommended footprint**



## 2.2 SMA package information

- Epoxy meets UL94, V0
- Cooling method : by conduction (C)

Figure 14. SMA package outline





Table 5. SMA package mechanical data

Ref.	Dimensions			
	Millimeters		Inches (for reference only)	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.097
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.40	0.006	0.016
D	2.25	2.90	0.089	0.114
E	4.80	5.35	0.189	0.211
E1	3.95	4.60	0.156	0.181
L	0.75	1.50	0.030	0.059

Figure 15. SMA recommended footprint in mm (inches)



### 3 Ordering information

**Table 6. Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
STPS140A	S140	SMA	68 mg	5000	Tape and reel
STPS140U	G14	SMB	107 mg	2500	Tape and reel

## Revision history

**Table 7. Document revision history**

Date	Revision	Changes
Jul-2003	7.2	Last update.
Aug-2004	7.3	SMA package dimensions update. Reference A1 max. changed from 2.70 mm (0.106 inch.) to 2.03 mm (0.080).
21-Nov-2018	8	Updated <a href="#">Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)</a> , <a href="#">Figure 4. Normalized avalanche power derating versus pulse duration (T<sub>j</sub> = 125 °C)</a> , <a href="#">Section 2.1</a> and <a href="#">Section 2.2</a> .

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.



ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View STPS140U on WIN SOURCE](#)
-  [STMicroelectronics Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management