



# THE DATASHEET OF STPS30L60CT



### Features


- Low forward voltage drop
- Negligible switching losses
- Low thermal resistance
- Avalanche capability specified

### Description

These dual center tap Schottky rectifiers are suited for switched mode power supplies and high frequency DC to DC converters.

Packaged in TO-220FPAB, TO-220AB narrow leads, TO-220AB, D<sup>2</sup>PAK, I<sup>2</sup>PAK and TO-247, this device is intended for use in high frequency inverters.

Figure 1. Electrical characteristics (a)



- a.  $V_{ARM}$  and  $I_{ARM}$  must respect the reverse safe operating area defined in [Figure 12](#).  $V_{AR}$  and  $I_{AR}$  are pulse measurements ( $t_p < 1 \mu s$ ).  $V_R$ ,  $I_R$ ,  $V_{RRM}$  and  $V_F$  are static characteristics




Table 1. Device summary

| Symbol      | Value    |
|-------------|----------|
| $I_{F(AV)}$ | 2 x 15 A |
| $V_{RRM}$   | 60 V     |
| $T_J(max)$  | 150 °C   |
| $V_F(max)$  | 0.56 V   |

# 1 Characteristics

**Table 2. Absolute ratings (limiting values, per diode)**

| Symbol                          | Parameter   |  |   | Value                   | Unit     |   |
|---------------------------------|---|--|---|-------------------------|----------|---|
| V <sub>RRM</sub>                | Repetitive peak reverse voltage                       |  |   | 60                      | V        |   |
| I <sub>F(RMS)</sub>             | Forward rms current                                   |  |   | 30                      | A        |   |
| I <sub>F(AV)</sub>              | Average forward current                               | TO-220AB narrow leads,<br>TO-220AB, I <sup>2</sup> PAK, D <sup>2</sup> PAK,<br>TO-247, δ = 0.5 | T <sub>c</sub> = 130 °C   | Per diode<br>Per device | 15<br>30 | A |
|                                 |   | TO-220FPAB, δ = 0.5  | T <sub>c</sub> = 110 °C   | Per diode<br>Per device | 15<br>30 |   |
| I <sub>FSM</sub>                | Surge non repetitive forward current                  |  | t <sub>p</sub> = 10 ms, sinusoidal  |                         | 230      | A |
| I <sub>RRM</sub>                | Repetitive peak reverse current                       |  | t <sub>p</sub> = 2 μs square, F = 1 kHz                                   |                         | 2        | A |
| P <sub>ARM</sub> <sup>(1)</sup> | Repetitive peak avalanche power                       |  | t <sub>p</sub> = 1 μs, T <sub>j</sub> = 25 °C                             |                         | 7800     | W |
| V <sub>ARM</sub> <sup>(2)</sup> | Maximum repetitive peak avalanche voltage             |  | t <sub>p</sub> < 1 μs, T <sub>j</sub> < 150 °C,<br>I <sub>AR</sub> < 29 A |                         | 80       | V |
| V <sub>ASM</sub> <sup>(2)</sup> | Maximum single pulse peak avalanche voltage           |  | t <sub>p</sub> < 1 μs, T <sub>j</sub> < 150 °C,<br>I <sub>AR</sub> < 29 A |                         | 80       | V |
| T <sub>stg</sub>                | Storage temperature range                             |  |   | -65 to + 175            | °C       |   |
| T <sub>j</sub>                  | Maximum operating junction temperature <sup>(3)</sup> |  |   | 150                     | °C       |   |
| dV/dt                           | Critical rate of rise reverse voltage                 |  |   | 10000                   | V/μs     |   |

1. For temperature or pulse time duration deratings, refer to [Figure 4](#) and [Figure 5](#). More details regarding the avalanche energy measurements and diode validation in the avalanche are provided in the application notes AN1768 and AN2025.
2. Refer to [Figure 12](#).
3.  $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$  condition to avoid thermal runaway for a diode on its own heatsink

**Table 3. Thermal resistances**

| Symbol               | Parameter        |  |           | Value | Unit |
|----------------------|------------------|--|-----------|-------|------|
| R <sub>th(j-c)</sub> | Junction to case | TO-220AB narrow leads,<br>TO-220AB, I <sup>2</sup> PAK, D <sup>2</sup> PAK, TO-247 | Per diode | 1.5   | °C/W |
|                      |                  |  | Total     | 0.8   |      |
|                      |                  | TO-220FPAB   | Per diode | 4.7   |      |
|                      |                  |  | Total     | 3.95  |      |
| R <sub>th(c)</sub>   | Coupling         | TO-220AB narrow leads, TO-220AB, I <sup>2</sup> PAK,<br>D <sup>2</sup> PAK, TO-247 | 0.1       |       |      |
|                      |                  | TO-220FPAB   | 3.2       |       |      |

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j(\text{diode 1}) = P(\text{diode1}) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode2}) \times R_{th(c)}$$


**Table 4. Static electrical characteristics (per diode)**

| Symbol      | Parameter               | Tests conditions                  |                     | Min. | Typ. | Max. | Unit          |
|-------------|-------------------------|-----------------------------------|---------------------|------|------|------|---------------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25\text{ }^\circ\text{C}$  | $V_R = V_{RRM}$     |      |      | 480  | $\mu\text{A}$ |
|             |                         | $T_j = 125\text{ }^\circ\text{C}$ |                     |      | 77   | 130  | $\text{mA}$   |
| $V_F^{(1)}$ | Forward voltage drop    | $T_j = 25\text{ }^\circ\text{C}$  | $I_F = 15\text{ A}$ |      |      | 0.6  | V             |
|             |                         | $T_j = 125\text{ }^\circ\text{C}$ | $I_F = 15\text{ A}$ |      | 0.5  | 0.56 |               |
|             |                         | $T_j = 25\text{ }^\circ\text{C}$  | $I_F = 30\text{ A}$ |      |      | 0.75 |               |
|             |                         | $T_j = 125\text{ }^\circ\text{C}$ | $I_F = 30\text{ A}$ |      | 0.65 | 0.7  |               |


1. Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation:  $P = 0.42 \times I_{F(AV)} + 0.009 \times I_{F(RMS)}^2$


**Figure 2. Average forward power dissipation versus average forward current (per diode)**




**Figure 3. Average forward current versus ambient temperature (delta = 0.5, per diode)**




**Figure 4. Normalized avalanche power derating versus pulse duration**




**Figure 5. Normalized avalanche power derating versus junction temperature**




**Figure 6. Relative variation of thermal impedance junction to case versus pulse duration**



**Figure 7. Relative variation of thermal impedance junction to case versus pulse duration (TO-220FPAB)**



**Figure 8. Reverse leakage current versus reverse voltage applied (typical values, per diode)**



**Figure 9. Junction capacitance versus reverse voltage applied (typical values, per diode)**




Figure 10. Forward voltage drop versus forward current (maximum values, per diode)




Figure 11. Thermal resistance junction to ambient versus copper surface under tab for D<sup>2</sup>PAK





Figure 12. Reverse safe operating area ( $t_p < 1\ \mu\text{s}$ ,  $T_j < 150\ ^\circ\text{C}$ )



## 2 Package information

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)
- Recommended torque values: TO-220AB, TO-220AB narrow leads, and TO-220FPAB 0.4 to 0.6 N·m, TO-247 0.55 N·m (1.0 N·m maximum)

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

**Table 5. TO-220FPAB dimensions**

| Ref. | Dimensions  |      |           |       |
|------|-------------|------|-----------|-------|
|      | Millimeters |      | Inches    |       |
|      | Min.        | Max. | Min.      | Max.  |
| A    | 4.4         | 4.6  | 0.173     | 0.181 |
| B    | 2.5         | 2.7  | 0.098     | 0.106 |
| D    | 2.5         | 2.75 | 0.098     | 0.108 |
| E    | 0.45        | 0.70 | 0.018     | 0.027 |
| F    | 0.75        | 1    | 0.030     | 0.039 |
| F1   | 1.15        | 1.70 | 0.045     | 0.067 |
| F2   | 1.15        | 1.70 | 0.045     | 0.067 |
| G    | 4.95        | 5.20 | 0.195     | 0.205 |
| G1   | 2.4         | 2.7  | 0.094     | 0.106 |
| H    | 10          | 10.4 | 0.393     | 0.409 |
| L2   | 16 Typ.     |      | 0.63 Typ. |       |
| L3   | 28.6        | 30.6 | 1.126     | 1.205 |
| L4   | 9.8         | 10.6 | 0.386     | 0.417 |
| L5   | 2.9         | 3.6  | 0.114     | 0.142 |
| L6   | 15.9        | 16.4 | 0.626     | 0.646 |
| L7   | 9.00        | 9.30 | 0.354     | 0.366 |
| Dia. | 3.00        | 3.20 | 0.118     | 0.126 |




Table 6. TO-220AB dimensions

| Ref.  | Dimensions  |       |            |       |
|-------|-------------|-------|------------|-------|
|       | Millimeters |       | Inches     |       |
|       | Min.        | Max.  | Min.       | Max.  |
| A     | 4.40        | 4.60  | 0.173      | 0.181 |
| C     | 1.23        | 1.32  | 0.048      | 0.051 |
| D     | 2.40        | 2.72  | 0.094      | 0.107 |
| E     | 0.49        | 0.70  | 0.019      | 0.027 |
| F     | 0.61        | 0.88  | 0.024      | 0.034 |
| F1    | 1.14        | 1.70  | 0.044      | 0.067 |
| F2    | 1.14        | 1.70  | 0.044      | 0.067 |
| G     | 4.95        | 5.15  | 0.194      | 0.202 |
| G1    | 2.40        | 2.70  | 0.094      | 0.106 |
| H2    | 10          | 10.40 | 0.393      | 0.409 |
| L2    | 16.4 typ.   |       | 0.645 typ. |       |
| L4    | 13          | 14    | 0.511      | 0.551 |
| L5    | 2.65        | 2.95  | 0.104      | 0.116 |
| L6    | 15.25       | 15.75 | 0.600      | 0.620 |
| L7    | 6.20        | 6.60  | 0.244      | 0.259 |
| L9    | 3.50        | 3.93  | 0.137      | 0.154 |
| M     | 2.6 typ.    |       | 0.102 typ. |       |
| Diam. | 3.75        | 3.85  | 0.147      | 0.151 |





Table 7. TO-220AB narrow leads dimensions




| Ref. | Dimensions  |      |       |        |      |       |
|------|-------------|------|-------|--------|------|-------|
|      | Millimeters |      |       | Inches |      |       |
|      | Min.        | Typ. | Max.  | Min.   | Typ. | Max.  |
| A    | 4.40        |      | 4.60  | 0.17   |      | 0.18  |
| b    | 0.61        |      | 0.88  | 0.024  |      | 0.034 |
| b1   | 0.95        |      | 1.20  | 0.037  |      | 0.047 |
| c    | 0.48        |      | 0.70  | 0.019  |      | 0.027 |
| D    | 15.25       |      | 15.75 | 0.60   |      | 0.62  |
| D1   | 1.27        |      |       | 0.05   |      |       |
| E    | 10.00       |      | 10.40 | 0.39   |      | 0.41  |
| e    | 2.40        |      | 2.70  | 0.094  |      | 0.106 |
| e1   | 4.95        |      | 5.15  | 0.19   |      | 0.20  |
| F    | 1.23        |      | 1.32  | 0.048  |      | 0.052 |
| H1   | 6.20        |      | 6.60  | 0.24   |      | 0.26  |
| J1   | 2.40        |      | 2.72  | 0.095  |      | 0.107 |
| L    | 13.00       |      | 14.00 | 0.51   |      | 0.55  |
| L1   | 2.60        |      | 2.90  | 0.102  |      | 0.114 |
| L20  | 15.40       |      |       | 0.61   |      |       |
| L30  | 28.90       |      |       | 1.14   |      |       |
| ØP   | 3.75        |      | 3.85  | 0.147  |      | 0.151 |
| Q    | 2.65        |      | 2.95  | 0.104  |      | 0.116 |

Table 8. D<sup>2</sup>PAK dimensions

| Ref. | Dimensions  |       |            |       |
|------|-------------|-------|------------|-------|
|      | Millimeters |       | Inches     |       |
|      | Min.        | Max.  | Min.       | Max.  |
| A    | 4.40        | 4.60  | 0.173      | 0.181 |
| A1   | 2.49        | 2.69  | 0.098      | 0.106 |
| A2   | 0.03        | 0.23  | 0.001      | 0.009 |
| B    | 0.70        | 0.93  | 0.027      | 0.037 |
| B2   | 1.14        | 1.70  | 0.045      | 0.067 |
| C    | 0.45        | 0.60  | 0.017      | 0.024 |
| C2   | 1.23        | 1.36  | 0.048      | 0.054 |
| D    | 8.95        | 9.35  | 0.352      | 0.368 |
| E    | 10.00       | 10.40 | 0.393      | 0.409 |
| G    | 4.88        | 5.28  | 0.192      | 0.208 |
| L    | 15.00       | 15.85 | 0.590      | 0.624 |
| L2   | 1.27        | 1.40  | 0.050      | 0.055 |
| L3   | 1.40        | 1.75  | 0.055      | 0.069 |
| M    | 2.40        | 3.20  | 0.094      | 0.126 |
| R    | 0.40 typ.   |       | 0.016 typ. |       |
| V2   | 0°          | 8°    | 0°         | 8°    |

Figure 13. Footprint (dimensions in millimeters)



Devices in I<sup>2</sup>PAK with nickel-plated back frame must NOT be mounted by frame soldering like SMDs. Such devices are intended to be through-hole mounted ONLY and in no circumstances shall ST be held liable for any lack of performance or damage arising out of soldering of nickel-plated back frames.

**Table 9. I<sup>2</sup>PAK dimensions**

| Ref. | Dimensions  |       |        |       |
|------|-------------|-------|--------|-------|
|      | Millimeters |       | Inches |       |
|      | Min.        | Max.  | Min.   | Max.  |
| A    | 4.40        | 4.60  | 0.173  | 0.181 |
| A1   | 2.40        | 2.72  | 0.094  | 0.107 |
| b    | 0.61        | 0.88  | 0.024  | 0.035 |
| b1   | 1.14        | 1.70  | 0.044  | 0.067 |
| c    | 0.49        | 0.70  | 0.019  | 0.028 |
| c2   | 1.23        | 1.32  | 0.048  | 0.052 |
| D    | 8.95        | 9.35  | 0.352  | 0.368 |
| e    | 2.40        | 2.70  | 0.094  | 0.106 |
| e1   | 4.95        | 5.15  | 0.195  | 0.203 |
| E    | 10          | 10.40 | 0.394  | 0.409 |
| L    | 13          | 14    | 0.512  | 0.551 |
| L1   | 3.50        | 3.93  | 0.138  | 0.155 |
| L2   | 1.27        | 1.40  | 0.050  | 0.055 |





Table 10. TO-247 dimensions



| Ref. | Dimensions  |       |       |        |       |       |
|------|-------------|-------|-------|--------|-------|-------|
|      | Millimeters |       |       | Inches |       |       |
|      | Min.        | Typ.  | Max.  | Min.   | Typ.  | Max.  |
| A    | 4.85        |       | 5.15  | 0.191  |       | 0.203 |
| D    | 2.20        |       | 2.60  | 0.086  |       | 0.102 |
| E    | 0.40        |       | 0.80  | 0.015  |       | 0.031 |
| F    | 1.00        |       | 1.40  | 0.039  |       | 0.055 |
| F1   |             | 3.00  |       |        | 0.118 |       |
| F2   |             | 2.00  |       |        | 0.078 |       |
| F3   | 2.00        |       | 2.40  | 0.078  |       | 0.094 |
| F4   | 3.00        |       | 3.40  | 0.118  |       | 0.133 |
| G    |             | 10.90 |       |        | 0.429 |       |
| H    | 15.45       |       | 15.75 | 0.608  |       | 0.620 |
| L    | 19.85       |       | 20.15 | 0.781  |       | 0.793 |
| L1   | 3.70        |       | 4.30  | 0.145  |       | 0.169 |
| L2   |             | 18.50 |       |        | 0.728 |       |
| L3   | 14.20       |       | 14.80 | 0.559  |       | 0.582 |
| L4   |             | 34.60 |       |        | 1.362 |       |
| L5   |             | 5.50  |       |        | 0.216 |       |
| M    | 2.00        |       | 3.00  | 0.078  |       | 0.118 |
| V    |             | 5°    |       |        | 5°    |       |
| V2   |             | 60°   |       |        | 60°   |       |
| Dia. | 3.55        |       | 3.65  | 0.139  |       | 0.143 |

### 3 Ordering information

Table 11. Ordering information

| Order code     | Marking      | Package                  | Weight | Base qty | Delivery mode |
|----------------|--------------|--------------------------|--------|----------|---------------|
| STPS30L60CW    | STPS30L60CW  | TO-247                   | 4.4 g  | 30       | Tube          |
| STPS30L60CT    | STPS30L60CT  | TO-220AB                 | 2.3 g  | 50       | Tube          |
| STPS30L60CG    | STPS30L60CG  | D <sup>2</sup> PAK       | 1.5 g  | 50       | Tube          |
| STPS30L60CG-TR | STPS30L60CG  | D <sup>2</sup> PAK       | 1.5 g  | 1000     | Tape and reel |
| STPS30L60CR    | STPS30L60CR  | I <sup>2</sup> PAK       | 1.49 g | 50       | Tube          |
| STPS30L60CFP   | STPS30L60CFP | TO-220FPAB               | 2.0 g  | 50       | Tube          |
| STPS30L60CTN   | STPS30L60CTN | TO-220AB<br>narrow leads | 1.9 g  | 50       | Tube          |

### 4 Revision history

Table 12. Document revision history

| Date        | Revision | Description of changes   |
|-------------|----------|--|
| July-2003   | 3B       | Initial release  |
| 16-Oct-2006 | 4        | Reformatted to current standards. Corrected dimensions for I <sup>2</sup> PAK in Table 5.  |
| 28-Nov-2006 | 5        | Added TO-220FPAB package. Added STPS30L60CG-TR to ordering information.  |
| 07-Mar-2007 | 6        | Updated thermal parameters in Table 2.   |
| 31-Mar-2007 | 7        | Updated T <sub>C</sub> = 110 °C in Table 1.  |
| 25-Aug-2008 | 8        | Reformatted to current standards. Updated ECOPACK statement. Updated torque values and dimension illustration for TO-247 in <a href="#">Section 2</a> .  |
| 07-Feb-2011 | 9        | Added electrical diagram on first page. Added parameters V <sub>ARM</sub> and V <sub>ASM</sub> to <a href="#">Table 2</a> . Added <a href="#">Figure 12</a> . Updated and added warning paragraph above <a href="#">Table 9</a> . Updated <a href="#">Table 11</a> . |
| 15-Jun-2012 | 10       | Added TO-220AB narrow leads package.   |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies



Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View STPS30L60CT on WIN SOURCE](#)
-  [STMicroelectronics Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management