



**THE DATASHEET OF
TLE2426IDR**



TLE2426, TLE2426Y THE "RAIL SPLITTER" PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

- 1/2 V_I Virtual Ground for Analog Systems
- Self-Contained 3-terminal TO-226AA Package
- Micropower Operation . . . 170 μA Typ, $V_I = 5\text{ V}$
- Wide V_I Range . . . 4 V to 40 V
- High Output-Current Capability
 - Source . . . 20 mA Typ
 - Sink . . . 20 mA Typ

- Excellent Output Regulation
 - $-45\ \mu\text{V}$ Typ at $I_O = 0$ to $-10\ \text{mA}$
 - $+15\ \mu\text{V}$ Typ at $I_O = 0$ to $+10\ \text{mA}$
- Low-Impedance Output . . . $0.0075\ \Omega$ Typ
- Noise Reduction Pin (D, JG, and P Packages Only)


description

In signal-conditioning applications utilizing a single power source, a reference voltage equal to one-half the supply voltage is required for termination of all analog signal grounds. Texas Instruments presents a precision virtual ground whose output voltage is always equal to one-half the input voltage, the TLE2426 "rail splitter."

The unique combination of a high-performance, micropower operational amplifier and a precision-trimmed divider on a single silicon chip results in a precise V_O/V_I ratio of 0.5 while sinking and sourcing current. The TLE2426 provides a low-impedance output with 20 mA of sink and source capability while drawing less than 280 μA of supply current over the full input range of 4 V to 40 V. A designer need not pay the price in terms of board space for a conventional signal ground consisting of resistors, capacitors, operational amplifiers, and voltage references. The performance and precision of the TLE2426 is available in an easy-to-use, space saving, 3-terminal LP package. For increased performance, the optional 8-pin packages provide a noise-reduction pin. With the addition of an external capacitor (C_{NR}), peak-to-peak noise is reduced while line ripple rejection is improved.

Initial output tolerance for a single 5-V or 12-V system is better than 1% with 3.6% over the full 40-V input range. Ripple rejection exceeds 12 bits of accuracy. Whether the application is for a data acquisition front end, analog signal termination, or simply a precision voltage reference, the TLE2426 eliminates a major source of system error.

INPUT/OUTPUT TRANSFER CHARACTERISTICS



AVAILABLE OPTIONS

| PACKAGED DEVICES | | | | | CHIP FORM (Y) |
|------------------|-------------------|------------------|--------------|-----------------|---------------|
| T_A | SMALL OUTLINE (D) | CERAMIC DIP (JG) | PLASTIC (LP) | PLASTIC DIP (P) | |
| 0°C to 70°C | TLE2426CD | — | TLE2426CLP | TLE2426CP | |



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1998, Texas Instruments Incorporated

TLE2426, TLE2426Y THE "RAIL SPLITTER" PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

| | | | | | |
|----------------|-----------|------------|------------|-----------|----------|
| -40°C to 85°C | TLE2426ID | — | TLE2426ILP | TLE2426IP | TLE2426Y |
| -55°C to 125°C | TLE2426MD | TLE2426MJG | TLE2426MLP | TLE2426MP | |



The D and LP packages are available taped and reeled in the commercial temperature range only. Add R suffix to the device type (e. g., TLC2426CDR). Chips are tested at 25°C.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


description (continued)

The C-suffix devices are characterized for operation from 0°C to 70°C. The I suffix devices are characterized for operation from -40°C to 85°C. The M suffix devices are characterized over the full military temperature range of -55°C to 125°C.



TLE2426Y chip information

This chip, properly assembled, displays characteristics similar to the TLE2426C. Thermal compression or ultrasonic bonding may be used on the doped aluminum bonding pads. The chips may be mounted with conductive epoxy or a gold-silicon preform.



electrical characteristics at specified free-air temperature, $V_I = 5\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426C | | | UNIT |
|---|---|---------------------------------|------------|----------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 5\text{ V}$ | | | 2.48 | 2.5 | 2.52 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 5\text{ V}$ | | Full range | 2.475 | | 2.525 | |
| Temperature coefficient of output voltage | | | Full range | 25 | | ppm/°C | |
| Supply current | No load | $V_I = 5\text{ V}$ | 25°C | 170 | 300 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 400 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, $V_O = 5\text{ V}$ | | 25°C | 26 | | mA | |
| | Sourcing current, $V_O = 0$ | | | -47 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $C_{NR} = 0$ | 25°C | 120 | | µV | |
| | | $C_{NR} = 1\text{ }\mu\text{F}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.1\%$ | | 25°C | 20 | | µs | |
| | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.01\%$ | | | 160 | | | |

† Full range is 0°C to 70°C.

‡ The listed values are not production tested.

TLE2426, TLE2426Y
THE “RAIL SPLITTER”
PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

electrical characteristics at specified free-air temperature, $V_I = 12\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426C | | | UNIT |
|---|---|---------------------------------|------------|-------------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 12\text{ V}$ | | | 5.95 | 6 | 6.05 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 12\text{ V}$ | | Full range | 5.945 6.055 | | | |
| Temperature coefficient of output voltage | | | Full range | 35 | | ppm/°C | |
| Supply current | No load | $V_I = 12\text{ V}$ | 25°C | 195 | 300 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 400 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, $V_O = 12\text{ V}$ | | 25°C | 31 | | mA | |
| | Sourcing current, $V_O = 0$ | | | -70 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $C_{NR} = 0$ | 25°C | 120 | | µV | |
| | | $C_{NR} = 1\text{ µF}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%, I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%, I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }12\text{ V}, V_O\text{ to }0.1\%$ | | 25°C | 20 | | µs | |
| | $V_I = 0\text{ to }12\text{ V}, V_O\text{ to }0.01\%$ | | | 120 | | | |

† Full range is 0°C to 70°C.

‡ The listed values are not production tested.



electrical characteristics at specified free-air temperature, $V_I = 5\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426I | | | UNIT |
|---|---|---------------------------------|------------|----------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 5\text{ V}$ | | | 2.48 | 2.5 | 2.52 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 5\text{ V}$ | | Full range | 2.47 | | 2.53 | |
| Temperature coefficient of output voltage | | | Full range | 25 | | ppm/°C | |
| Supply current | No load | $V_I = 5\text{ V}$ | 25°C | 170 | 300 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 400 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | µV | |
| | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | | |
| | $I_O = 0\text{ to }8\text{ mA}$ | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }20\text{ mA}$ | | 25°C | 65 | ±235 | µV | |
| | | | Full range | ±250 | | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, | $V_O = 5\text{ V}$ | 25°C | 26 | | mA | |
| | Sourcing current, | $V_O = 0$ | | -47 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $C_{NR} = 0$ | 25°C | 120 | | µV | |
| | | $C_{NR} = 1\text{ µF}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.1\%$ | | 25°C | 20 | | µs | |
| | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.01\%$ | | | 160 | | | |

† Full range is -40°C to 85°C.

‡ The listed values are not production tested.

TLE2426, TLE2426Y
THE “RAIL SPLITTER”
PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

electrical characteristics at specified free-air temperature, $V_I = 12\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426I | | | UNIT |
|---|--|---------------------------------|------------|----------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 12\text{ V}$ | | | 5.95 | 6 | 6.05 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 12\text{ V}$ | | Full range | 5.935 | | 6.065 | |
| Temperature coefficient of output voltage | | | Full range | 35 | | ppm/°C | |
| Supply current | No load | $V_I = 12\text{ V}$ | 25°C | 195 | 300 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 400 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | | |
| | | | | | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | µV | |
| | $I_O = 0\text{ to }8\text{ mA}$ | | Full range | ±250 | | | |
| | $I_O = 0\text{ to }20\text{ mA}$ | | 25°C | 65 | ±235 | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, $V_O = 12\text{ V}$ | | 25°C | 31 | | mA | |
| | Sourcing current, $V_O = 0$ | | | -70 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $CNR = 0$ | 25°C | 120 | | µV | |
| | | $CNR = 1\text{ µF}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }12\text{ V}$, $V_O\text{ to }0.1\%$ | | 25°C | 20 | | µs | |
| | $V_I = 0\text{ to }12\text{ V}$, $V_O\text{ to }0.01\%$ | | | 120 | | | |

† Full range is -40°C to 85°C.

‡ The listed values are not production tested.



electrical characteristics at specified free-air temperature, $V_I = 5\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426M | | | UNIT |
|---|---|---------------------------------|------------|----------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 5\text{ V}$ | | | 2.48 | 2.5 | 2.52 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 5\text{ V}$ | | Full range | 2.465 | | 2.535 | |
| Temperature coefficient of output voltage | | | Full range | 25 | | ppm/°C | |
| Supply current | No load | $V_I = 5\text{ V}$ | 25°C | 170 | 300 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 400 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | µV | |
| | $I_O = 0\text{ to }3\text{ mA}$ | | Full range | ±250 | | | |
| | $I_O = 0\text{ to }20\text{ mA}$ | | 25°C | 65 | ±235 | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, $V_O = 5\text{ V}$ | | 25°C | 26 | | mA | |
| | Sourcing current, $V_O = 0$ | | | -47 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $C_{NR} = 0$ | 25°C | 120 | | µV | |
| | | $C_{NR} = 1\text{ µF}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.1\%$ | | 25°C | 20 | | µs | |
| | $V_I = 0\text{ to }5\text{ V}$, $V_O\text{ to }0.01\%$ | | | 120 | | | |

† Full range is -55°C to 125°C.

‡ The listed values are not production tested.

TLE2426, TLE2426Y
THE “RAIL SPLITTER”
PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

electrical characteristics at specified free-air temperature, $V_I = 12\text{ V}$, $I_O = 0$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | T_A † | TLE2426M | | | UNIT |
|---|--|---------------------------------|------------|----------|------|--------|------|
| | | | | MIN | TYP | MAX | |
| Output voltage | $V_I = 4\text{ V}$ | | 25°C | 1.98 | 2 | 2.02 | V |
| | $V_I = 12\text{ V}$ | | | 5.95 | 6 | 6.05 | |
| | $V_I = 40\text{ V}$ | | | 19.8 | 20 | 20.2 | |
| | $V_I = 12\text{ V}$ | | Full range | 5.925 | | 6.075 | |
| Temperature coefficient of output voltage | | | Full range | 35 | | ppm/°C | |
| Supply current | No load | $V_I = 12\text{ V}$ | 25°C | 195 | 250 | µA | |
| | | $V_I = 4\text{ to }40\text{ V}$ | Full range | 350 | | | |
| Output voltage regulation (sourcing current)‡ | $I_O = 0\text{ to }-10\text{ mA}$ | | 25°C | -45 | ±160 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }-20\text{ mA}$ | | 25°C | -150 | ±450 | µV | |
| | | | Full range | ±250 | | | |
| Output voltage regulation (sinking current)‡ | $I_O = 0\text{ to }10\text{ mA}$ | | 25°C | 15 | ±160 | µV | |
| | $I_O = 0\text{ to }8\text{ mA}$ | | Full range | ±250 | | | |
| | $I_O = 0\text{ to }20\text{ mA}$ | | 25°C | 65 | ±235 | | |
| Output impedance | | | 25°C | 7.5 | 22.5 | mΩ | |
| Noise-reduction impedance | | | 25°C | 110 | | kΩ | |
| Short-circuit current | Sinking current, $V_O = 12\text{ V}$ | | 25°C | 31 | | mA | |
| | Sourcing current, $V_O = 0$ | | | -70 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz to }10\text{ kHz}$ | $C_{NR} = 0$ | 25°C | 120 | | µV | |
| | | $C_{NR} = 1\text{ µF}$ | | 30 | | | |
| Output voltage current step response | $V_O\text{ to }0.1\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 290 | | µs | |
| | | $C_L = 100\text{ pF}$ | | 275 | | | |
| | $V_O\text{ to }0.01\%$, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 25°C | 400 | | | |
| | | $C_L = 100\text{ pF}$ | | 390 | | | |
| Step response | $V_I = 0\text{ to }12\text{ V}$, $V_O\text{ to }0.1\%$ | | 25°C | 12 | | µs | |
| | $V_I = 0\text{ to }12\text{ V}$, $V_O\text{ to }0.01\%$ | | | 120 | | | |

† Full range is -55°C to 125°C.

‡ The listed values are not production tested.



electrical characteristics at specified free-air temperature, $V_I = 5\text{ V}$, $I_O = 0$, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | TLE2426Y | | | UNIT |
|---|--|---------------------------|-----|-----|------------------|
| | | MIN | TYP | MAX | |
| Output voltage | $V_I = 5\text{ V}$ | 2.5 | | | V |
| Supply current | No load | 170 | | | μA |
| Output voltage regulation (sourcing current) [†] | $I_O = 0$ to -10 mA | -45 | | | μV |
| | $I_O = 0$ to -20 mA | -150 | | | |
| Output voltage regulation (sinking current) [†] | $I_O = 0$ to 10 mA | 15 | | | μV |
| | $I_O = 0$ to 20 mA | 65 | | | |
| Output impedance | | 7.5 | | | $\text{m}\Omega$ |
| Noise-reduction impedance | | 110 | | | $\text{k}\Omega$ |
| Short-circuit current | Sinking current, $V_O = 5\text{ V}$ | 26 | | | mA |
| | Sourcing current, $V_O = 0$ | -47 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz}$ to 10 kHz | $C_{NR} = 0$ | 120 | | μV |
| | | $C_{NR} = 1\ \mu\text{F}$ | 30 | | |
| Output voltage current step response | V_O to 0.1%, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 290 | | μs |
| | | $C_L = 100\text{ pF}$ | 275 | | |
| | V_O to 0.01%, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 400 | | |
| | | $C_L = 100\text{ pF}$ | 390 | | |
| Step response | $V_I = 0$ to 5 V , V_O to 0.1% | $C_L = 100\text{ pF}$ | 20 | | μs |
| | $V_I = 0$ to 5 V , V_O to 0.01% | | 160 | | |

[†] The listed values are not production tested.

electrical characteristics at specified free-air temperature, $V_I = 12\text{ V}$, $I_O = 0$, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | TLE2426Y | | | UNIT |
|---|---|---------------------------|-----|-----|------------------|
| | | MIN | TYP | MAX | |
| Output voltage | $V_I = 12\text{ V}$ | 6 | | | V |
| Supply current | No load | 195 | | | μA |
| Output voltage regulation (sourcing current) [†] | $I_O = 0$ to -10 mA | -45 | | | μV |
| | $I_O = 0$ to -20 mA | -150 | | | |
| Output voltage regulation (sinking current) [†] | $I_O = 0$ to 3 mA | 15 | | | μV |
| | $I_O = 0$ to 20 mA | 65 | | | |
| Output impedance | | 7.5 | | | $\text{m}\Omega$ |
| Noise-reduction impedance | | 110 | | | $\text{k}\Omega$ |
| Short-circuit current | Sinking current, $V_O = 12\text{ V}$ | 31 | | | mA |
| | Sourcing current, $V_O = 0$ | -70 | | | |
| Output noise voltage, rms | $f = 10\text{ Hz}$ to 10 kHz | $C_{NR} = 0$ | 120 | | μV |
| | | $C_{NR} = 1\ \mu\text{F}$ | 30 | | |
| Output voltage current, step response | V_O to 0.1%, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 290 | | μs |
| | | $C_L = 100\text{ pF}$ | 275 | | |
| | V_O to 0.01%, $I_O = \pm 10\text{ mA}$ | $C_L = 0$ | 400 | | |
| | | $C_L = 100\text{ pF}$ | 390 | | |
| Step response | $V_I = 0$ to 12 V , V_O to 0.1% | $C_L = 100\text{ pF}$ | 12 | | μs |
| | $V_I = 0$ to 12 V , V_O to 0.01% | | 120 | | |





[†] The listed values are not production tested.

TYPICAL CHARACTERISTICS

Table Of Graphs

| | | FIGURE |
|--|-------------------------|---------------|
| Output voltage | Distribution | 1,2 |
| Output voltage change | vs Free-air temperature | 3 |
| Output voltage error | vs Input voltage | 4 |
| Input bias current | vs Input voltage | 5 |
| | vs Free-air temperature | 6 |
| Output voltage regulation | vs Output current | 7 |
| Output impedance | vs Frequency | 8 |
| Short-circuit output current | vs Input voltage | 9,10 |
| | vs Free-air temperature | 11,12 |
| Ripple rejection | vs Frequency | 13 |
| Spectral noise voltage density | vs Frequency | 14 |
| Output voltage response to output current step | vs Time | 15 |
| Output voltage power-up response | vs Time | 16 |
| Output current | vs Load capacitance | 17 |

TYPICAL CHARACTERISTICS†



† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TLE2426, TLE2426Y
THE "RAIL SPLITTER"
PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

TYPICAL CHARACTERISTICS†




Figure 5




Figure 6




Figure 7




Figure 8

† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS†

SHORT-CIRCUIT OUTPUT CURRENT
 vs
 INPUT VOLTAGE




Figure 9

SHORT-CIRCUIT OUTPUT CURRENT
 vs
 INPUT VOLTAGE




Figure 10

SHORT-CIRCUIT OUTPUT CURRENT
 vs
 FREE-AIR TEMPERATURE




Figure 11

SHORT-CIRCUIT OUTPUT CURRENT
 vs
 FREE-AIR TEMPERATURE




Figure 12

† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TLE2426, TLE2426Y
THE "RAIL SPLITTER"
PRECISION VIRTUAL GROUND

SLOS098D – AUGUST 1991 – REVISED MAY 1998

TYPICAL CHARACTERISTICS

**RIPPLE REJECTION
 vs
 FREQUENCY**




Figure 13

**SPECTRAL NOISE VOLTAGE DENSITY
 vs
 FREQUENCY**




Figure 14

**OUTPUT VOLTAGE RESPONSE
 TO OUTPUT CURRENT STEP**




Figure 15

OUTPUT VOLTAGE POWER-UP RESPONSE




Figure 16



TYPICAL CHARACTERISTICS

STABILITY RANGE
OUTPUT CURRENT
VS
LOAD CAPACITANCE




Figure 17

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| TLE2426CD | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426C | Samples |
| TLE2426CDG4 | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426C | Samples |
| TLE2426CDR | ACTIVE | SOIC | D | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426C | Samples |
| TLE2426CDRG4 | ACTIVE | SOIC | D | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426C | Samples |
| TLE2426CLP | ACTIVE | TO-92 | LP | 3 | 1000 | Pb-Free (RoHS) | CU SN | N / A for Pkg Type | | 2426C | Samples |
| TLE2426CLPE3 | ACTIVE | TO-92 | LP | 3 | 1000 | Pb-Free (RoHS) | CU SN | N / A for Pkg Type | | 2426C | Samples |
| TLE2426CLPR | ACTIVE | TO-92 | LP | 3 | 2000 | Pb-Free (RoHS) | CU SN | N / A for Pkg Type | | 2426C | Samples |
| TLE2426CP | ACTIVE | PDIP | P | 8 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | N / A for Pkg Type | | TLE2426CP | Samples |
| TLE2426ID | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426I | Samples |
| TLE2426IDG4 | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426I | Samples |
| TLE2426IDR | ACTIVE | SOIC | D | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426I | Samples |
| TLE2426IDRG4 | ACTIVE | SOIC | D | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | | 2426I | Samples |
| TLE2426ILP | ACTIVE | TO-92 | LP | 3 | 1000 | Pb-Free (RoHS) | CU SN | N / A for Pkg Type | | 2426I | Samples |
| TLE2426ILPR | ACTIVE | TO-92 | LP | 3 | 2000 | Pb-Free (RoHS) | CU SN | N / A for Pkg Type | | 2426I | Samples |
| TLE2426IP | ACTIVE | PDIP | P | 8 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | N / A for Pkg Type | | TLE2426IP | Samples |
| TLE2426IPE4 | ACTIVE | PDIP | P | 8 | 50 | Green (RoHS & no Sb/Br) | CU NIPDAU | N / A for Pkg Type | | TLE2426IP | Samples |
| TLE2426MD | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -55 to 125 | 2426M | Samples |

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|----------------|
| TLE2426MDG4 | ACTIVE | SOIC | D | 8 | 75 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -55 to 125 | 2426M | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLE2426 :

- Automotive: [TLE2426-Q1](#)

- Enhanced Product: [TLE2426-EP](#)

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TLE2426CDR | SOIC | D | 8 | 2500 | 330.0 | 12.4 | 6.4 | 5.2 | 2.1 | 8.0 | 12.0 | Q1 |
| TLE2426IDR | SOIC | D | 8 | 2500 | 330.0 | 12.4 | 6.4 | 5.2 | 2.1 | 8.0 | 12.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TLE2426CDR | SOIC | D | 8 | 2500 | 350.0 | 350.0 | 43.0 |
| TLE2426IDR | SOIC | D | 8 | 2500 | 350.0 | 350.0 | 43.0 |



D0008A

PACKAGE OUTLINE

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

NOTES:

- Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
- This drawing is subject to change without notice.
- This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
- This dimension does not include interlead flash.
- Reference JEDEC registration MS-012, variation AA.

EXAMPLE BOARD LAYOUT

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE
 EXPOSED METAL SHOWN
 SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

- 6. Publication IPC-7351 may have alternate designs.
- 7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE
BASED ON .005 INCH [0.125 MM] THICK STENCIL
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

P (R-PDIP-T8)

PLASTIC DUAL-IN-LINE PACKAGE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. Falls within JEDEC MS-001 variation BA.

GENERIC PACKAGE VIEW

LP 3

TO-92 - 5.34 mm max height

TRANSISTOR OUTLINE



Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.

4040001-2/F

LP0003A



PACKAGE OUTLINE

TO-92 - 5.34 mm max height


TO-92



4215214/B 04/2017

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Lead dimensions are not controlled within this area.
4. Reference JEDEC TO-226, variation AA.
5. Shipping method:
 - a. Straight lead option available in bulk pack only.
 - b. Formed lead option available in tape and reel or ammo pack.
 - c. Specific products can be offered in limited combinations of shipping medium and lead options.
 - d. Consult product folder for more information on available options.



LAND PATTERN EXAMPLE
STRAIGHT LEAD OPTION
NON-SOLDER MASK DEFINED
SCALE:15X




LAND PATTERN EXAMPLE
FORMED LEAD OPTION
NON-SOLDER MASK DEFINED
SCALE:15X

TAPE SPECIFICATIONS

LP0003A

TO-92 - 5.34 mm max height

TO-92



FOR FORMED LEAD OPTION PACKAGE

4215214/B 04/2017

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View TLE2426IDR on WIN SOURCE](#)

 [Texas Instruments](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management