




# THE DATASHEET OF SMF45A



### SMF Series



#### Agency Approvals


AGENCY	AGENCY FILE NUMBER
	E230531

#### Maximum Ratings and Thermal Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation at T <sub>A</sub> = 25°C by 10/1000µs (Note 1)	P <sub>PPM</sub>	200	W
Thermal Resistance Junction- to-Ambient	R <sub>θJA</sub>	220	°C/W
Thermal Resistance Junction- to-Lead	R <sub>θJL</sub>	100	°C/W
Operating Temperature Range	T <sub>J</sub>	-65 to 150	°C
Storage Temperature Range	T <sub>STG</sub>	-65 to 175	°C

**Notes:**  
1. Non-repetitive current pulse, per Fig. 4 and derated above T<sub>J</sub> (initial) = 25°C per Fig. 3.

#### Functional Diagram



#### Description

The SMF series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

SMF package is 50% smaller in footprint when compare to SMA package and delivering one of the low height profiles (1.1mm) in the industry.

#### Features

- 200W peak pulsepower capability at 10/1000µs waveform, repetition rate (duty cycle): 0.01 %
- Compatible with industrial standard package SOD-123FL
- Low profile: maximum height of 1.1mm.
- Low inductance, excellent clamping capability
- For surface mounted applications to optimize board space
- High temperature to reflow soldering guaranteed: 260°C/40sec
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- ESD protection of data lines in accordance with IEC 61000-4-2
- EFT protection of data lines in accordance with IEC 61000-4-4
- Fast response time: typically less than 1.0ns from 0 Volts to V<sub>BR</sub> min
- Glass passivated junction
- Built-in strain relief
- Plastic package is flammability rated V-0 per Underwriters Laboratories
- Meet MSL level1, per J-STD-020, LF maximum peak of 260°C
- Matte tin lead-free plated
- Halogen-free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/ JEDEC J-STD-609A.01)

#### Applications

SMF devices are ideal for the protection of I/O interfaces, V<sub>CC</sub> bus and other vulnerable circuit used in cellular phones, portable devices, business machines, power supplies and other consumer applications.

#### Additional Information



Datasheet



Resources



Samples


### Electrical Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Part Number	Marking Code	Breakdown Voltage $V_{BR}$ (Volts) @ $I_T$		Test Current $I_T$ (mA)	Reverse Stand off Voltage $V_R$ (V)	Maximum Reverse Leakage @ $V_R$ $I_R$ ( $\mu\text{A}$ )	Maximum Peak Pulse Current $I_{PP}$ (A)	Maximum Clamping Voltage @ $I_{PP}$ $V_C$ (V)	Agency Approval 
		MIN	MAX						
SMF5.0A	AE	6.40	7.00	10	5.0	400	21.7	9.2	X
SMF6.0A	AG	6.67	7.37	10	6.0	400	19.4	10.3	X
SMF6.5A	AK	7.22	7.98	10	6.5	250	17.9	11.2	X
SMF7.0A	AM	7.78	8.60	10	7.0	100	16.7	12.0	X
SMF7.5A	AP	8.33	9.21	1	7.5	50	15.5	12.9	X
SMF8.0A	AR	8.89	9.83	1	8.0	25	14.7	13.6	X
SMF8.5A	AT	9.44	10.40	1	8.5	10	13.9	14.4	X
SMF9.0A	AV	10.00	11.10	1	9.0	5	13.0	15.4	X
SMF10A	AX	11.10	12.30	1	10	2.5	11.8	17.0	X
SMF11A	AZ	12.20	13.50	1	11	2.5	11.0	18.2	X
SMF12A	BE	13.30	14.70	1	12	2.5	10.1	19.9	X
SMF13A	BG	14.40	15.90	1	13	1.0	9.3	21.5	X
SMF14A	BK	15.60	17.20	1	14	1.0	8.6	23.2	X
SMF15A	BM	16.70	18.50	1	15	1.0	8.2	24.4	X
SMF16A	BP	17.80	19.70	1	16	1.0	7.7	26.0	X
SMF17A	BR	18.90	20.90	1	17	1.0	7.2	27.6	X
SMF18A	BT	20.00	22.10	1	18	1.0	6.8	29.2	X
SMF20A	BV	22.20	24.50	1	20	1.0	6.2	32.4	X
SMF22A	BX	24.40	26.90	1	22	1.0	5.6	35.5	X
SMF24A	BZ	26.70	29.50	1	24	1.0	5.1	38.9	X
SMF26A	CE	28.90	31.90	1	26	1.0	4.8	42.1	X
SMF28A	CG	31.10	34.40	1	28	1.0	4.4	45.4	X
SMF30A	CK	33.30	36.80	1	30	1.0	4.1	48.4	X
SMF33A	CM	36.70	40.60	1	33	1.0	3.8	53.3	X
SMF36A	CP	40.00	44.20	1	36	1.0	3.4	58.1	X
SMF40A	CR	44.40	49.10	1	40	1.0	3.1	64.5	X
SMF43A	CT	47.80	52.80	1	43	1.0	2.9	69.4	X
SMF45A	CV	50.00	55.30	1	45	1.0	2.8	72.7	X
SMF48A	CX	53.30	58.90	1	48	1.0	2.6	77.4	X
SMF51A	CZ	56.70	62.70	1	51	1.0	2.4	82.4	X
SMF54A	DE	60.00	66.30	1	54	1.0	2.3	87.1	X
SMF58A	RG	64.40	71.20	1	58	1.0	2.1	93.6	
SMF60A	RK	66.70	73.70	1	60	1.0	1.8	96.8	
SMF64A	RM	71.10	78.60	1	64	1.0	1.7	103.0	
SMF70A	RP	77.80	86.00	1	70	1.0	1.5	113.0	
SMF75A	RR	83.30	92.10	1	75	1.0	1.4	121.0	
SMF78A	RT	86.70	95.80	1	78	1.0	1.4	126.0	
SMF85A	RV	94.40	104.00	1	85	1.0	1.3	137.0	
SMF90A	RW	100.00	111.00	1	90	1.0	1.2	146.0	
SMF100A	RX	111.00	123.00	1	100	1.0	1.1	162.0	

**Notes:**

- $V_{BR}$  measured after  $I_T$  applied for 300 $\mu\text{s}$ ,  $I_T$  = square wave pulse or equivalent.
- Surge current waveform per 10/1000 $\mu\text{s}$  exponential wave and derated per Fig.2.
- All terms and symbols are consistent with ANSI/IEEE C62.35.


**I-V Curve Characteristics**




- $P_{PPM}$  Peak Pulse Power Dissipation** – Max power dissipation
- $V_R$  Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- $V_{BR}$  Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current ( $I_T$ )
- $V_C$  Clamping Voltage** – Peak voltage measured across the TVS at a specified  $I_{ppm}$  (peak impulse current)
- $I_R$  Reverse Leakage Current** – Current measured at  $V_R$
- $V_F$  Forward Voltage Drop for Uni-directional**

**Ratings and Characteristic Curves** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

**Figure 1 - TVS Transients Clamping Waveform**




**Figure 2 - Peak Pulse Power Rating Curve**




continues on next page.

### Ratings and Characteristic Curves ( $T_A=25^\circ\text{C}$ unless otherwise noted) (Continued)


**Figure 3 - Peak Pulse Power Derating Curve**




**Figure 4 - Pulse Waveform - 10/1000 $\mu\text{S}$**



**Figure 5 - Forward Voltage**




**Figure 6 - Typical Junction Capacitance**



**Figure 7 - Peak Forward Voltage Drop vs. Peak Forward Current**




**Figure 8 - Maximum Non-Repetitive Forward Surge Current Uni-Directional Only**



### Soldering Parameters

Reflow Condition		Lead-free assembly
Pre Heat	- Temperature Min ( $T_{s(min)}$ )	150°C
	- Temperature Max ( $T_{s(max)}$ )	200°C
	- Time (min to max) ( $t_s$ )	60 – 180 secs
Average ramp up rate (Liquidus Temp ( $T_A$ ) to peak)		3°C/second max
$T_{s(max)}$ to $T_A$ - Ramp-up Rate		3°C/second max
Reflow	- Temperature ( $T_A$ ) (Liquidus)	217°C
	- Time (min to max) ( $t_s$ )	60 – 150 seconds
Peak Temperature ( $T_p$ )		260 <sup>+0/-5</sup> °C
Time within 5°C of actual peak Temperature ( $t_p$ )		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature ( $T_p$ )		8 minutes Max.
Do not exceed		260°C




### Physical Specifications

<b>Case</b>	SOD-123FL plastic over glass passivated junction
<b>Polarity</b>	Color band denotes cathode except bipolar
<b>Terminal</b>	Matte tin-plated leads, solderable per JESD22-B102


### Environmental Specifications

<b>High Temp. Storage</b>	JESD22-A103
<b>HTRB</b>	JESD22-A108
<b>Temperature Cycling</b>	JESD22-A104
<b>MSL</b>	JEDEC-J-STD-020, Level 1
<b>H3TRB</b>	JESD22-A101
<b>RSH</b>	JESD22-A111

### Dimensions - SOD-123FL Package




Mounting Pad Layout




Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A	2.50	2.90	0.0984	0.1142
B	3.40	3.90	0.1339	0.1535
C	0.70	1.20	0.0275	0.0472
D	1.50	2.00	0.0591	0.0787
E	0.35	0.90	0.0138	0.0354
F	0.05	0.26	0.0020	0.0102
G	0.00	0.10	0.000	0.0039
H	0.95	1.10	0.0374	0.0433

### Part Numbering System




### Part Marking System



### Packaging Options

Part number	Component Package	Quantity	Packaging Option	Packaging Specification
SMFXXX	SOD-123FL	3000	Tape & Reel – 8mm tape/7" reel	EIA RS-481
SMFXXX-T13	SOD-123FL	10000	Tape & Reel – 8mm tape/13" reel	EIA RS-481

### Tape and Reel Specification



**Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).**

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SMF45A on WIN SOURCE](#)

 [Littelfuse Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management