



**THE DATASHEET OF
KBJ610G-BP**





Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

Features

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)

Maximum Ratings

- UL Recognized File # E165989
- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Mounting Torque: 5.0 in-lbs Maximum

MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
KBJ6005G	50V	35V	50V
KBJ601G	100V	70V	100V
KBJ602G	200V	140V	200V
KBJ604G	400V	280V	400V
KBJ606G	600V	420V	600V
KBJ608G	800V	560V	800V
KBJ610G	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Maximum Average Forward Rectified Current @ $T_C=110^\circ\text{C}$	$I_{F(AV)}$	6.0 A 2.8 A	with heatsink ⁽¹⁾ without heatsink
Peak Forward Surge Current	I_{FSM}	170A	8.3ms, half sine
Maximum Forward Voltage	V_F	1.0V	$I_{FM} = 3.0\text{A};$ $T_A=25^\circ\text{C}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	5.0uA 500uA	$T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$
I^2t Rating for fusing	I^2t	120 A ² S	$t < 8.0\text{ms}$
Typical Thermal Resistance	R_{JC}	1.5 °C/W	Note 1
Typical Junction Capacitance	C_J	80pF	Measured at $F=1.0\text{MHz}$ $V_R=4.0\text{V}$


Note 1: Unit Mounted on 75mm x 75mm x 1.6mm Cu Plate Heatsink

2: High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7

KBJ6005G THRU KBJ610G

6.0 Amp Glass Passivated Bridge Rectifiers 50 to 1000 Volts

KBJ



DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.976	.992	24.80	25.20	
B	.579	.602	14.70	15.30	
C	.154	.161	3.90	4.10	
D	.173	.189	4.40	4.80	
E	.134	.150	3.40	3.80	
F	.122	.134	3.10	3.40	∅
G	.130	.146	3.30	3.70	
H	.035	.043	0.90	1.10	
I	.059	.075	1.50	1.90	
J	.669	.709	17.00	18.00	
K	.287	.303	7.30	7.70	
L	.098	.114	2.50	2.90	
M	.024	.031	0.60	0.80	
N	.366	.413	9.30	10.50	
O	.118X45°		3.0X45°		
P	.122	.134	3.10	3.40	∅



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1K/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.



CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View KBJ610G-BP on WIN SOURCE](#)
-  [Micro Commercial Co](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management