



- △04 PERFORMANCE REQUIREMENTS (Dry as Molded):**
1. STRAP INSERTION < 5 lb.
 2. MINIMUM WIRE BUNDLE DIAMETER = 3/8"
 3. LOOP TENSILE > 120 lb.
 4. STUD INSERTION < 10 lb.
 5. STUD PULLOUT > 110 lb.

PART NUMBER	OVERALL LENGTH	MAX BUNDLE DIA
WSS380	9.7	2.25
WSI380	12.7	3.25
WSR380	15.7	4.125

INVENTORS

HellermannTyton®

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER SHOWN ON THIS DRAWING ARE EXCLUSIVE PROPERTY OF HELLERMANN TYTON

name	date	city, state
G GEIGER	3/17/03	JACKSON, WI

REVISION

level	△04
by	G G G
date	11/25/09
ECN #	011439
part level	B

DIMENSIONS

.XXXX=	±0.005/[.127]
.XXX=	±0.010/[.25]
.XX=	±0.02/[.5]
.X=	±0.25/[6,4]
∠	±0.5
unless otherwise specified	
units	inches/[mm]

PART

number	see table	phase	△04 PRODUCTION
name	T120 WIDE STRAP W/ 3/8" STUD MOUNT		
material	IMPACT MODIFIED, HEAT STABILIZED UV RESISTANT, NYLON 6/6 BLACK		

DRAWING

FORMAT	AH version J	CAD	PRO-E	scale	3/2
computer file number	previous number				
drawn	G GEIGER	checked	K Christian	approved	
date	8/29/02	checked	11/25/09	approved	
type	CUSTOMER			sheet	1 of 1
number	CT2127010CST				

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 157-00405 on WIN SOURCE](#)

 [HellermannTyton](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management