



THE DATASHEET OF MMZ0603S102ET000

Chip beads

For general signal line

GHz noise countermeasure (general signal line, high-speed signal line)

MMZ-E series



MMZ0603-E type



FEATURES

- Noise reduction solution for general signal line.
- Compared to the MMZ series, it is a product that increases the SRF to GHz bands and can countermeasure noise at wide frequencies with 1 element.
- Compared to the MMZ series, it can attain high impedance at GHz bands.
- Various frequency characteristics with 4 materials of different features for countermeasures against everything from general signals to high-speed signals.
- Operating temperature range: -55 to +125°C

APPLICATION

- Noise removal for mobile devices such as smartphones and tablet terminals, and various modules.
- Noise removal for PCs and recorders, household appliances such as STBs, smart grids, and industrial equipment.

PART NUMBER CONSTRUCTION

MMZ	0603	S	121	E	T	000
Series name	LxWxT dimensions 0.6x0.3x0.3 mm	Material name	Impedance (Ω) at 100MHz	Characteristic type	Packaging style	Internal code


CHARACTERISTICS SPECIFICATION TABLE

Impedance [100MHz]		[1GHz]		DC resistance		Rated current		Part No.
(Ω)	Tolerance	(Ω)	Tolerance	(Ω) max.		(mA) max.		
120	±25%	200	±40%	0.37		250		MMZ0603S121ET000
240	±25%	400	±40%	0.71		200		MMZ0603S241ET000
600	±25%	1000	±40%	1.60		150		MMZ0603S601ET000
1000	±25%	1800	±40%	2.60		125		MMZ0603S102ET000
120	±25%	300	±40%	0.44		250		MMZ0603A121ET000
240	±25%	600	±40%	0.86		200		MMZ0603A241ET000
330	±25%	750	±40%	1.00		220		MMZ0603A331ET000
470	±25%	1000	±40%	1.30		185		MMZ0603A471ET000
600	±25%	1500	±40%	1.70		160		MMZ0603A601ET000
1000	±25%	2300	±40%	2.90		130		MMZ0603A102ET000
33	±25%	200	±40%	0.6		250		MMZ0603D330ET000
47	±25%	300	±40%	0.76		200		MMZ0603D470ET000
120	±25%	1000	±40%	2.4		125		MMZ0603D121ET000
160	±25%	1400	±40%	2.90		125		MMZ0603D161ET000
56	±25%	700	±40%	1.9		150		MMZ0603F560ET000
75	±25%	950	±40%	2.6		125		MMZ0603F750ET000

Measurement equipment

Measurement item	Product No.	Manufacturer
Impedance	E4991A+16197	Keysight Technologies
DC resistance	Type-7556	Yokogawa


* Equivalent measurement equipment may be used.




MMZ0603-E type

Z VS. FREQUENCY CHARACTERISTICS (BY SERIES)


MMZ0603S-E series




MMZ0603A-E series



MMZ0603D-E series




MMZ0603F-E series




MMZ0603-E type

Z, X, R VS. FREQUENCY CHARACTERISTICS


MMZ0603S121ET000




MMZ0603S241ET000




MMZ0603S601ET000




MMZ0603S102ET000




MMZ0603A121ET000




MMZ0603A241ET000




MMZ0603A331ET000




MMZ0603A471ET000




MMZ0603A601ET000




MMZ0603A102ET000




MMZ0603D330ET000




MMZ0603D470ET000




MMZ0603D121ET000



MMZ0603F560ET000




MMZ0603F750ET000



MMZ0603-E type


Z, X, R VS. FREQUENCY CHARACTERISTICS

MMZ0603D161ET000



MMZ0603-E type


SHAPE & DIMENSIONS



Dimensions in mm


PACKAGING STYLE

REEL DIMENSIONS




Dimensions in mm

RECOMMENDED LAND PATTERN




Dimensions in mm

TAPE DIMENSIONS




Dimensions in mm

RECOMMENDED REFLOW PROFILE



Type	A	B	K
MMZ0603-E	0.38±0.05	0.68±0.05	0.5max.



Dimensions in mm

PACKAGE QUANTITY

Package quantity	15,000 pcs/reel
------------------	-----------------

TEMPERATURE RANGE, INDIVIDUAL WEIGHT

Operating temperature range	Storage temperature range*	Individual weight
-55 to +125°C	-55 to +125°C	0.3 mg

* The storage temperature range is for after the assembly.

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

REMINDERS

- The storage period is within 12 months. Be sure to follow the storage conditions (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ View [MMZ0603S102ET000](#) on WIN SOURCE
- ⊖ [TDK Corporation](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management