



**THE DATASHEET OF
SMBJ5347B-TP**



**SMBJ5338B
THRU
SMBJ5388B**

Features

- Low Profile Package for Surface Mounting(Flat Handling Surface for Accurate Placement)
- Zener Voltage 5.1V to 200V
- High Surge Current Capability
- For Available Tolerances-see Note 1
- Available on Tape and Reel (see E1A std RS-481)
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Halogen free available upon request by adding suffix "-HF"

Mechanical Data

- Standard JEDEC Outlines as Shown
- Marking: See page 2
- Maximum Temperature for Soldering: 260°C for 10 Seconds
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


Electrical Characteristics @ 25°C Unless Otherwise Specified

| | | |
|------------------------------------|-----------------------------------|-------------------|
| Forward Voltage at 1.0A Current | V _F | 1.2Volts |
| Steady State Power Dissipation | P _(AV) | 5Watts See Note 2 |
| Operating and Storage Temperatures | T _J , T _{STG} | -55°C to +150°C |
| Thermal Resistance | R _{θJL} | 15°C/W |
| | R _{θJA} | 90°C/W |

- Note: 1.High Tempertaure Solder Exemptions Applied,see EU Directive Annex 7.
2. Lead temperature at 75°C = TL at mounting plane. Derate linearly above 75°C to zero power at 150 °C
3. Ambient temperature at 15°C = TA at mounting plane. Derate linearly above 15°C to zero power at 150 °C


**5 Watt
Surface Mount Silicon
Zener Diode
5.1 to 200 Volts**

**DO-214AA
(SMB) (Lead Frame)**



| DIM | INCHES | | MM | | NOTE |
|-----|--------|------|------|------|------|
| | MIN | MAX | MIN | MAX | |
| A | .075 | .095 | 1.91 | 2.41 | |
| B | .077 | .083 | 1.96 | 2.10 | |
| C | .002 | .008 | .05 | .20 | |
| D | ---- | .02 | ---- | .51 | |
| E | .030 | .060 | .76 | 1.52 | |
| G | .200 | .220 | 5.08 | 5.59 | |
| H | .160 | .187 | 4.06 | 4.75 | |
| J | .130 | .155 | 3.30 | 3.94 | |

**SUGGESTED SOLDER
PAD LAYOUT**



SMBJ5338B thru SMBJ5388B



Micro Commercial Components


ELECTRICAL CHARACTERISTICS @25°C

| MCC PART NUMBER | REGULATOR VOLTAGE V_Z | TEST CURRENT I_Z | MAXIMUM DYNAMIC IMPEDANCE Z_{ZT} | MAXIMUM REVERSE CURRENT I_R | TEST VOLTAGE V_R | MAXIMUM REGULATOR CURRENT I_{ZM} | MAXIMUM DYNAMIC KNEE IMPEDANCE $Z_{ZK}@1.0mA$ | MAXIMUM SURGE CURRENT I_{ZSM} | MAXIMUM VOLTAGE REGULATION |
|-----------------|-------------------------|--------------------|------------------------------------|-------------------------------|--------------------|------------------------------------|---|---------------------------------|----------------------------|
| | VOLTS | mA | OHMS | μA | VOLTS | mA | OHMS | A | VOLTS |
| SMBJ5338B | 5.1 | 240 | 1.5 | 1 | 1 | 930 | 400 | 14.4 | 0.39 |
| SMBJ5339B | 5.6 | 220 | 1 | 1 | 2 | 865 | 400 | 13.4 | 0.25 |
| SMBJ5340B | 6 | 200 | 1 | 1 | 3 | 790 | 300 | 12.7 | 0.19 |
| SMBJ5341B | 6.2 | 200 | 1 | 1 | 3 | 765 | 200 | 12.4 | 0.1 |
| SMBJ5342B | 6.8 | 175 | 1 | 10 | 5.2 | 700 | 200 | 11.5 | 0.15 |
| SMBJ5343B | 7.5 | 175 | 1.5 | 10 | 5.7 | 630 | 200 | 10.7 | 0.15 |
| SMBJ5344B | 8.2 | 150 | 1.5 | 10 | 6.2 | 580 | 200 | 10 | 0.2 |
| SMBJ5345B | 8.7 | 150 | 2 | 10 | 6.6 | 545 | 200 | 9.5 | 0.2 |
| SMBJ5346B | 9.1 | 150 | 2 | 7.5 | 6.9 | 520 | 150 | 9.2 | 0.22 |
| SMBJ5347B | 10 | 125 | 2 | 5 | 7.6 | 475 | 125 | 8.6 | 0.22 |
| SMBJ5348B | 11 | 125 | 2.5 | 5 | 8.4 | 430 | 125 | 8 | 0.25 |
| SMBJ5349B | 12 | 100 | 2.5 | 2 | 9.1 | 395 | 125 | 7.5 | 0.25 |
| SMBJ5350B | 13 | 100 | 2.5 | 1 | 9.9 | 365 | 100 | 7 | 0.25 |
| SMBJ5351B | 14 | 100 | 2.5 | 1 | 10.6 | 340 | 75 | 6.7 | 0.25 |
| SMBJ5352B | 15 | 75 | 2.5 | 1 | 11.5 | 315 | 75 | 6.3 | 0.25 |
| SMBJ5353B | 16 | 75 | 2.5 | 1 | 12.2 | 295 | 75 | 6 | 0.3 |
| SMBJ5354B | 17 | 70 | 2.5 | 0.5 | 12.9 | 280 | 75 | 5.8 | 0.35 |
| SMBJ5355B | 18 | 65 | 2.5 | 0.5 | 13.7 | 264 | 75 | 5.5 | 0.4 |
| SMBJ5356B | 19 | 65 | 3 | 0.5 | 14.4 | 250 | 75 | 5.3 | 0.4 |
| SMBJ5357B | 20 | 65 | 3 | 0.5 | 15.2 | 237 | 75 | 5.1 | 0.4 |
| SMBJ5358B | 22 | 50 | 3.5 | 0.5 | 16.7 | 216 | 75 | 4.7 | 0.45 |
| SMBJ5359B | 24 | 50 | 3.5 | 0.5 | 18.2 | 198 | 100 | 4.4 | 0.55 |
| SMBJ5360B | 25 | 50 | 4 | 0.5 | 19 | 190 | 110 | 4.3 | 0.55 |
| SMBJ5361B | 27 | 50 | 5 | 0.5 | 20.6 | 176 | 120 | 4.1 | 0.6 |
| SMBJ5362B | 28 | 50 | 6 | 0.5 | 21.2 | 170 | 130 | 3.9 | 0.6 |
| SMBJ5363B | 30 | 40 | 8 | 0.5 | 22.8 | 158 | 140 | 3.7 | 0.6 |
| SMBJ5364B | 33 | 40 | 10 | 0.5 | 25.1 | 144 | 150 | 3.5 | 0.6 |
| SMBJ5365B | 36 | 30 | 11 | 0.5 | 27.4 | 132 | 160 | 3.3 | 0.65 |
| SMBJ5366B | 39 | 30 | 14 | 0.5 | 29.7 | 122 | 170 | 3.1 | 0.65 |
| SMBJ5367B | 43 | 30 | 20 | 0.5 | 32.7 | 110 | 190 | 2.8 | 0.7 |
| SMBJ5368B | 47 | 25 | 25 | 0.5 | 35.8 | 100 | 210 | 2.7 | 0.8 |
| SMBJ5369B | 51 | 25 | 27 | 0.5 | 38.8 | 93 | 230 | 2.5 | 0.9 |
| SMBJ5370B | 56 | 20 | 35 | 0.5 | 42.6 | 86 | 280 | 2.3 | 1 |
| SMBJ5371B | 60 | 20 | 40 | 0.5 | 45.5 | 79 | 350 | 2.2 | 1.2 |
| SMBJ5372B | 62 | 20 | 42 | 0.5 | 47.1 | 76 | 400 | 2.1 | 1.35 |
| SMBJ5373B | 68 | 20 | 44 | 0.5 | 51.7 | 70 | 500 | 2 | 1.5 |
| SMBJ5374B | 75 | 20 | 45 | 0.5 | 56 | 63 | 620 | 1.9 | 1.6 |
| SMBJ5375B | 82 | 15 | 65 | 0.5 | 62.2 | 58 | 720 | 1.8 | 1.8 |
| SMBJ5376B | 87 | 15 | 75 | 0.5 | 66 | 54.5 | 760 | 1.7 | 2 |
| SMBJ5377B | 91 | 15 | 75 | 0.5 | 69.2 | 52.5 | 760 | 1.6 | 2.2 |
| SMBJ5378B | 100 | 12 | 90 | 0.5 | 76 | 47.5 | 800 | 1.5 | 2.3 |
| SMBJ5379B | 110 | 12 | 125 | 0.5 | 83.6 | 43 | 1000 | 1.4 | 2.5 |
| SMBJ5380B | 120 | 10 | 170 | 0.5 | 91.2 | 39.5 | 1150 | 1.3 | 2.5 |
| SMBJ5381B | 130 | 10 | 190 | 0.5 | 98.8 | 36.6 | 1250 | 1.2 | 2.5 |
| SMBJ5382B | 140 | 8.0 | 230 | 0.5 | 106 | 34 | 1500 | 1.2 | 2.5 |
| SMBJ5383B | 150 | 8.0 | 330 | 0.5 | 114 | 31.6 | 1500 | 1.1 | 3 |
| SMBJ5384B | 160 | 8.0 | 350 | 0.5 | 122 | 29.4 | 1650 | 1.1 | 3 |
| SMBJ5385B | 170 | 8.0 | 380 | 0.5 | 129 | 28 | 1750 | 1.0 | 3 |
| SMBJ5386B | 180 | 5.0 | 430 | 0.5 | 137 | 26.4 | 1750 | 1.0 | 4 |
| SMBJ5387B | 190 | 5.0 | 450 | 0.5 | 144 | 25 | 1850 | 0.9 | 5 |
| SMBJ5388B | 200 | 5.0 | 480 | 0.5 | 152 | 23.6 | 1850 | 0.9 | 5 |

SMBJ5338B thru SMBJ5388B



Micro Commercial Components



Note 1 Devices listed have a $\pm 5\%$ tolerance on nominal V_Z . Suffix C denotes a $\pm 2\%$

Note 2 Nominal Zener Voltage (V_Z) is tested with a 40 ± 10 milliseconds pulse current at 25°C to avoid self-heat affection.

Note 3 The Zener impedance (Z_{ZT} or Z_{ZK}) is derived from the 60 Hz ac voltage, which results when an ac current having a rms value equal to 10% of the dc zener current (I_{ZT} or I_{ZK}) is superimposed on I_{ZT} or I_{ZK} respectively.

Note 4 The Maximum Reverse (leakage) Current is specified for devices with $\pm 20\%$ and $\pm 10\%$ voltage tolerances on nominal V_Z in another column.

Note 5 The Maximum Zener Current (I_{ZM}) shown is for $\pm 5\%$ tolerance devices. I_{ZM} for $\pm 10\%$ and $\pm 20\%$ devices can be calculated using the formula:

$$I_{ZM} = \frac{P}{V_{ZM}}$$

Where " V_{ZM} " is V_Z at the high end of the voltage tolerance specified and "P" is the rated power of the device.

Note 6 The Surge Current (I_{SM}) is specified as the maximum peak of a nonrecurring sine wave of 8.3 milliseconds duration.

Note 7 Voltage Regulation (ΔV_Z) is the difference between the voltage measured at 10% and 50% I_{ZM} .

RATING AND CHARACTERISTICS CURVES
SMBJ5338B THRU SMBJ5388B




Fig. 1-POWER TEMPERATURE DERATING CURVE




Fig. 2-TEMPERATURE COEFFICIENT-RANGE FOR UNITS 6 TO 51 VOLTS



Fig. 3-ZENER VOLTAGE VERSUS ZENER CURRENT
VZ = 6.8 THRU 10 VOLTS



Fig. 4-ZENER VOLTAGE VERSUS ZENER CURRENT
VZ = 11 THRU 51 VOLTS



Micro Commercial Components

Ordering Information :

| Device | Packing |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.



CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SMBJ5347B-TP](#) on WIN SOURCE
-  [Micro Commercial Co](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management