THE DATASHEET OF

NGB8204NT4

NGB8204N

Ignition IGBT
18 Amps, 400 Volts

N−Channel D²PAK

This Logic Level Insulated Gate Bipolar Transistor (IGBT) features monolithic circuitry integrating ESD and Overvoltage clamped protection for use in inductive coil drivers applications. Primary uses include Ignition, Direct Fuel Injection, or wherever high voltage and high current switching is required.

Features

- Ideal for Coil−on−Plug Applications
- Gate−Emitter ESD Protection
- Temperature Compensated Gate−Collector Voltage Clamp Limits Stress Applied to Load
- Integrated ESD Diode Protection
- New Design Increases Unclamped Inductive Switching (UIS) Energy Per Area
- Low Threshold Voltage to Interface Power Loads to Logic or Microprocessor Devices
- Low Saturation Voltage
- High Pulsed Current Capability
- Integrated Gate−Emitter Resistor (R_{GE})
- Emitter Ballasting for Short−Circuit Capability
- Pb−Free Package is Available

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CES}	430	V_{DC}
Collector−Gate Voltage	V_{CER}	430	V_{DC}
Gate−Emitter Voltage	V_{GE}	18	V_{DC}
Collector Current−Continuous @ T_C = 25°C − Pulsed	I_C	18 50	A_{DC} A_{AC}
ESD (Human Body Model) R = 1500 Ω, C = 100 pF	ESD	8.0	kV
ESD (Machine Model) R = 0 Ω, C = 200 pF	ESD	800	V
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	115 0.77	W W/°C
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to +175	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

ON Semiconductor®

http://onsemi.com

18 AMPS, 400 VOLTS
$V_{CE(on)}$ ≤ 2.0 V @
I_C = 10 A, V_{GE} ≥ 4.5 V





D²PAK
CASE 418B
STYLE 4

MARKING DIAGRAM



GB8204N = Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping†
NGB8204NT4	D²PAK	800 / Tape & Reel
NGB8204NT4G	D²PAK (Pb−Free)	800 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2006

UNCLAMPED COLLECTOR−TO−EMITTER AVALANCHE CHARACTERISTICS (−55° ≤ T_J ≤ 175°C)

Characteristic	Symbol	Value	Unit
Single Pulse Collector−to−Emitter Avalanche Energy V_{CC} = 50 V, V_{GE} = 5.0 V, Pk I_L = 21.1 A, L = 1.8 mH, Starting T_J = 25°C V_{CC} = 50 V, V_{GE} = 5.0 V, Pk I_L = 18.3 A, L = 1.8 mH, Starting T_J = 125°C	E_{AS}	 400 300	mJ
Reverse Avalanche Energy V_{CC} = 100 V, V_{GE} = 20 V, Pk I_L = 25.8 A, L = 6.0 mH, Starting T_J = 25°C	$E_{AS(R)}$	 2000	mJ

MAXIMUM SHORT−CIRCUIT TIMES (−55°C ≤ T_J ≤ 150°C)

Short Circuit Withstand Time 1 (See Figure 17, 3 Pulses with 10 ms Period)	t_{sc1}	750	μs
Short Circuit Withstand Time 2 (See Figure 18, 3 Pulses with 10 ms Period)	t_{sc2}	5.0	ms

THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	1.3	°C/W
Thermal Resistance, Junction−to−Ambient D^2PAK (Note 1)	$R_{\theta JA}$	50	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 5 seconds (Note 2)	T_L	275	°C

1. When surface mounted to an FR4 board using the minimum recommended pad size.
2. For further details, see Soldering and Mounting Techniques Reference Manua, SOLDERRM/D.

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Collector−Emitter Clamp Voltage	BV_{CES}	I_C = 2.0 mA	T_J = −40°C to 150°C	380	395	420	V_{DC}
		I_C = 10 mA	T_J = −40°C to 150°C	390	405	430	
Zero Gate Voltage Collector Current	I_{CES}	V_{CE} = 350 V, V_{GE} = 0 V	T_J = 25°C	−	2.0	10	μA_{DC}
			T_J = 150°C	−	10	40*	
			T_J = −40°C	−	1.0	10	
Reverse Collector−Emitter Leakage Current	I_{ECS}	V_{CE} = −24 V	T_J = 25°C	−	0.7	1.0	mA
			T_J = 150°C	−	12	25*	
			T_J = −40°C	−	0.1	1.0	
Reverse Collector−Emitter Clamp Voltage	$B_{VCES(R)}$	I_C = −75 mA	T_J = 25°C	27	33	37	V_{DC}
			T_J = 150°C	30	36	40	
			T_J = −40°C	25	32	35	
Gate−Emitter Clamp Voltage	BV_{GES}	I_G = 5.0 mA	T_J = −40°C to 150°C	11	13	15	V_{DC}
Gate−Emitter Leakage Current	I_{GES}	V_{GE} = 10 V	T_J = −40°C to 150°C	384	640	700	μA_{DC}
Gate Emitter Resistor	R_{GE}	−	T_J = −40°C to 150°C	10	16	26	$_k\Omega$
ON CHARACTERISTICS (Note 3)							
Gate Threshold Voltage	$V_{GE(th)}$	I_C = 1.0 mA, V_{GE} = V_{CE}	T_J = 25°C	1.1	1.4	1.9	V_{DC}
			T_J = 150°C	0.75	1.0	1.4	
			T_J = −40°C	1.2	1.6	2.1*	
Threshold Temperature Coefficient (Negative)	−	−	−	−	3.4	−	mV/°C

*Maximum Value of Characteristic across Temperature Range.

3. Pulse Test: Pulse Width ≤ 300 μS, Duty Cycle ≤ 2%.

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
ON CHARACTERISTICS (Note 3)							
Collector−to−Emitter On−Voltage	$V_{CE(on)}$	I_C = 6.0 A, V_{GE} = 4.0 V	T_J = 25°C	1.0	1.4	1.6	V_{DC}
			T_J = 150°C	0.9	1.3	1.6	
			T_J = −40°C	1.1	1.45	1.7*	
		I_C = 8.0 A, V_{GE} = 4.0 V	T_J = 25°C	1.3	1.6	1.9*	
			T_J = 150°C	1.2	1.55	1.8	
			T_J = −40°C	1.4	1.6	1.9*	
		I_C = 10 A, V_{GE} = 4.0 V	T_J = 25°C	1.4	1.8	2.0	
			T_J = 150°C	1.5	1.8	2.0	
			T_J = −40°C	1.4	1.8	2.1*	
		I_C = 15 A, V_{GE} = 4.0 V	T_J = 25°C	1.8	2.2	2.5	
			T_J = 150°C	2.0	2.4	2.6*	
			T_J = −40°C	1.7	2.1	2.5	
		I_C = 10 A, V_{GE} = 4.5 V	T_J = 25°C	1.3	1.8	2.0*	
			T_J = 150°C	1.3	1.75	2.0*	
			T_J = −40°C	1.4	1.8	2.0*	
Forward Transconductance	gfs	V_{CE} = 5.0 V, I_C = 6.0 A	T_J = −40°C to 150°C	8.0	14	25	Mhos
DYNAMIC CHARACTERISTICS							
Input Capacitance	C_{ISS}	V_{CC} = 25 V, V_{GE} = 0 V f = 1.0 MHz	T_J = −40°C to 150°C	400	800	1000	pF
Output Capacitance	C_{OSS}			50	75	100	
Transfer Capacitance	C_{RSS}			4.0	7.0	10	
SWITCHING CHARACTERISTICS							
Turn−Off Delay Time (Resistive)	$t_{d(off)}$	V_{CC} = 300 V, I_C = 6.5 A R_G = 1.0 kΩ, R_L = 46 Ω,	T_J = 25°C	–	4.0	10	μSec
Fall Time (Resistive)	t_f	V_{CC} = 300 V, I_C = 6.5 A R_G = 1.0 kΩ, R_L = 46 Ω,	T_J = 25°C	–	9.0	15	
Turn−On Delay Time	$t_{d(on)}$	V_{CC} = 10 V, I_C = 6.5 A R_G = 1.0 kΩ, R_L = 1.5 Ω	T_J = 25°C	–	0.7	4.0	μSec
Rise Time	t_r	V_{CC} = 10 V, I_C = 6.5 A R_G = 1.0 kΩ, R_L = 1.5 Ω	T_J = 25°C	–	4.5	7.0	

*Maximum Value of Characteristic across Temperature Range.

3. Pulse Test: Pulse Width ≤ 300 μS, Duty Cycle ≤ 2%.

TYPICAL ELECTRICAL CHARACTERISTICS (unless otherwise noted)



Figure 1. Output Characteristics



Figure 2. Output Characteristics



Figure 3. Output Characteristics



Figure 4. Transfer Characteristics



Figure 5. Collector−to−Emitter Saturation Voltage versus Junction Temperature



Figure 6. Collector−to−Emitter Voltage versus Gate−to−Emitter Voltage



Figure 7. Collector−to−Emitter Voltage versus Gate−to−Emitter Voltage



Figure 8. Capacitance Variation



Figure 9. Gate Threshold Voltage versus Temperature



Figure 10. Minimum Open Secondary Latch Current versus Temperature



Figure 11. Typical Open Secondary Latch Current versus Temperature



Figure 12. Inductive Switching Fall Time versus Temperature



Figure 13. Single Pulse Safe Operating Area (Mounted on an Infinite Heatsink at T_A = 25°C)



Figure 14. Single Pulse Safe Operating Area (Mounted on an Infinite Heatsink at T_A = 125°C)



Figure 15. Pulse Train Safe Operating Area (Mounted on an Infinite Heatsink at T_C = 25°C)



Figure 16. Pulse Train Safe Operating Area (Mounted on an Infinite Heatsink at T_C = 125°C)



Figure 17. Circuit Configuration for Short Circuit Test #1



Figure 18. Circuit Configuration for Short Circuit Test #2



Figure 19. Transient Thermal Resistance (Non−normalized Junction−to−Ambient mounted on minimum pad area)

PACKAGE DIMENSIONS

D²PAK 3
CASE 418B–04
ISSUE J



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 418B–01 THRU 418B–03 OBSOLETE, NEW STANDARD 418B–04.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.035	0.51	0.89
E	0.045	0.055	1.14	1.40
F	0.310	0.350	7.87	8.89
G	0.100 BSC		2.54 BSC	
H	0.080	0.110	2.03	2.79
J	0.018	0.025	0.46	0.64
K	0.090	0.110	2.29	2.79
L	0.052	0.072	1.32	1.83
M	0.280	0.320	7.11	8.13
N	0.197 REF		5.00 REF	
P	0.079 REF		2.00 REF	
R	0.039 REF		0.99 REF	
S	0.575	0.625	14.60	15.88
V	0.045	0.055	1.14	1.40

STYLE 4:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR



VIEW W–W

SOLDERING FOOTPRINT*



*For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81–3–5773–3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View NGB8204NT4 on WIN SOURCE
- ON Semiconductor Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management