Microsemi
POWER PRODUCTS GROUP

APTGF30A60T1G

Phase leg NPT IGBT Power Module

V_{CES} = 600V
I_C = 30A @ Tc = 80°C





Pins 1/2 ; 3/4 ; 5/6 must be shorted together

Application

- Welding converters
- Switched Mode Power Supplies
- Uninterruptible Power Supplies
- Motor control

Features

- Non Punch Through (NPT) Fast IGBT
  - Low voltage drop
  - Low tail current
  - Switching frequency up to 100 kHz
  - Soft recovery parallel diodes
  - Low diode VF
  - Low leakage current
  - RBSOA and SCSOA rated
- Very low stray inductance
  - Symmetrical design
- Internal thermistor for temperature monitoring
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS Compliant

Absolute maximum ratings

Symbol	*Parameter*		*Max ratings*	*Unit*
V_{CES}	Collector - Emitter Breakdown Voltage		600	V
I_C	Continuous Collector Current	T_C = 25°C	42	A
		T_C = 80°C	30	
I_{CM}	Pulsed Collector Current	T_C = 25°C	100	
V_{GE}	Gate – Emitter Voltage		±20	V
P_D	Maximum Power Dissipation	T_C = 25°C	140	W
RBSOA	Reverse Bias Safe Operating Area	T_j = 125°C	60A@500V	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ T_j = 25°C unless otherwise specified

Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	V_{GE} = 0V V_{CE} = 600V	T_j = 25°C			250	µA
			T_j = 125°C			500	
$V_{CE(on)}$	Collector Emitter on Voltage	V_{GE} =15V I_C = 30A	T_j = 25°C	1.7	2.0	2.45	V
			T_j = 125°C		2.2		
$V_{GE(th)}$	Gate Threshold Voltage	V_{GE} = V_{CE}, I_C = 1mA		4		6	V
I_{GES}	Gate – Emitter Leakage Current	V_{GE} = 20V, V_{CE} = 0V				400	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	V_{GE} = 0V V_{CE} = 25V f = 1MHz		1350		pF
C_{oes}	Output Capacitance			193		
C_{res}	Reverse Transfer Capacitance			120		
Q_g	Total gate Charge	V_{GE} = 15V V_{Bus} = 300V I_C =30A		99		nC
Q_{ge}	Gate – Emitter Charge			10		
Q_{gc}	Gate – Collector Charge			60		
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (25°C) V_{GE} = 15V V_{Bus} = 400V I_C = 30A R_G = 6.8Ω		30		ns
T_r	Rise Time			12		
$T_{d(off)}$	Turn-off Delay Time			80		
T_f	Fall Time			15		
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (125°C) V_{GE} = 15V V_{Bus} = 400V I_C = 30A R_G = 6.8Ω		32		ns
T_r	Rise Time			12		
$T_{d(off)}$	Turn-off Delay Time			90		
T_f	Fall Time			21		
E_{on}	Turn-on Switching Energy	V_{GE} = 15V V_{Bus} = 400V I_C = 30A R_G = 6.8Ω T_j = 125°C		0.3		mJ
E_{off}	Turn-off Switching Energy	T_j = 125°C		0.8		

Reverse diode ratings and characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V_{RRM}	Maximum Peak Repetitive Reverse Voltage			600			V
I_{RM}	Maximum Reverse Leakage Current	V_R=600V	T_j = 25°C			25	µA
			T_j = 125°C			500	
I_F	DC Forward Current		Tc = 80°C		25		A
V_F	Diode Forward Voltage	I_F = 25A			1.8	2.2	V
		I_F = 50A			2.2		
		I_F = 25A	T_j = 125°C		1.6		
t_{rr}	Reverse Recovery Time	I_F = 25A V_R = 400V di/dt =200A/µs	T_j = 25°C		30		ns
			T_j = 125°C		175		
Q_{rr}	Reverse Recovery Charge		T_j = 25°C		55		nC
			T_j = 125°C		485		

Thermal and package characteristics

Symbol	Characteristic			Min	Typ	Max	Unit
R_{thJC}	Junction to Case Thermal Resistance	IGBT				0.9	°C/W
		Diode				1.4	
V_{ISOL}	RMS Isolation Voltage, any terminal to case t =1 min, 50/60Hz			4000			V
T_J	Operating junction temperature range			-40		150	°C
T_{STG}	Storage Temperature Range			-40		125	
T_C	Operating Case Temperature			-40		100	
Torque	Mounting torque	To heatsink	M4	2		3	N.m
Wt	Package Weight					80	g

Temperature sensor NTC (see application note APT0406 on www.microsemi.com for more information).

Symbol	Characteristic	Min	Typ	Max	Unit
R_{25}	Resistance @ 25°C		50		kΩ
$B_{25/85}$	T_{25} = 298.15 K		3952		K

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$

T: Thermistor temperature
R_T: Thermistor value at T

SP1 Package outline (dimensions in mm)



See application note 1904 - Mounting Instructions for SP1 Power Modules on www.microsemi.com

Typical Performance Curve


















Turn-On Delay Time vs Collector Current
td(on), Turn-On Delay Time (ns)
V_{GE} = 15V
Tj = 125°C
V_{CE} = 400V
R_G = 6.8Ω
I_{CE}, Collector to Emitter Current (A)


Turn-Off Delay Time vs Collector Current
td(off), Turn-Off Delay Time (ns)
V_{GE}=15V, T_J=125°C
V_{GE}=15V, T_J=25°C
V_{CE} = 400V
R_G = 6.8Ω
I_{CE}, Collector to Emitter Current (A)


Current Rise Time vs Collector Current
tr, Rise Time (ns)
V_{CE} = 400V
R_G = 6.8Ω
V_{GE}=15V, T_J=125°C
I_{CE}, Collector to Emitter Current (A)


Current Fall Time vs Collector Current
tf, Fall Time (ns)
T_J = 125°C
T_J = 25°C
V_{CE} = 400V, V_{GE} = 15V, R_G = 6.8Ω
I_{CE}, Collector to Emitter Current (A)


Turn-On Energy Loss vs Collector Current
E_{on}, Turn-On Energy Loss (mJ)
V_{CE} = 400V
R_G = 6.8Ω
T_J=125°C, V_{GE}=15V
I_{CE}, Collector to Emitter Current (A)


Turn-Off Energy Loss vs Collector Current
E_{off}, Turn-off Energy Loss (mJ)
V_{CE} = 400V
V_{GE} = 15V
R_G = 6.8Ω
T_J = 125°C
I_{CE}, Collector to Emitter Current (A)


Switching Energy Losses vs Gate Resistance
Switching Energy Losses (mJ)
Eoff, 30A
Eon, 30A
V_{CE} = 400V
V_{GE} = 15V
T_J= 125°C
Gate Resistance (Ohms)


Reverse Bias Safe Operating Area
I_C, Collector Current (A)
V_{CE}, Collector to Emitter Voltage (V)


Capacitance vs Collector to Emitter Voltage
C, Capacitance (pF)
10000
1000
100
10
Cies
Coes
Cres
0
10
20
30
40
50
VCE, Collector to Emitter Voltage (V)


Operating Frequency vs Collector Current
Fmax, Operating Frequency (kHz)
280
240
200
160
120
80
40
0
VCE = 400V
D = 50%
RG = 6.8Ω
TJ = 125°C
TC= 75°C
ZVS
ZCS
hard
switching
0
10
20
30
40
50
IC, Collector Current (A)


Maximum Effective Transient Thermal Impedance, Junction to Case vs Pulse Duration
Thermal Impedance (°C/W)
1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
0.9
0.7
0.5
0.3
0.1
0.05
Single Pulse
Note:
PDM
t1
t2
Duty Factor D = t1/t2
Peak TJ = PDM x ZθJC + TC
0.00001
0.0001
0.001
0.01
0.1
1
10
Rectangular Pulse Duration (Seconds)

DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at http://www.microsemi.com/legal/tnc.asp

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or directly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View APTGF30A60T1G on WIN SOURCE
- Microsemi Corporation Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management