



SAW filters for infrastructure systems

Series/Type: B3807

The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B39331B3807U310		2012-01-13	2012-12-31	2013-03-30

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at www.epcos.com/sales.

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


Data Sheet

 Ceramic package **QCC8C**
Features

- Low-loss IF filter for W-CDMA base station
- Usable bandwidth 15 MHz
- Ceramic SMD package

Terminals


- Gold plated



Dimensions in mm, approx. weight 0,10 g

Pin configuration

7	Input
6	Input Ground
3	Output
2	Output Ground
1, 4, 5, 8	Ground



Type	Ordering code	Marking and Package according to	Packing according to
B3807	B39331-B3807-U310	C61157-A7-A56	F61074-V8070-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T	-40/ +85	°C
Storage temperature range	T_{stg}	-40/ +85	°C
DC voltage	V_{DC}	0	V
Source power	P_s	15	dBm

SAW Components
B3807
Low-Loss Filter
326,4 MHz
Data Sheet
Characteristics


Operating temperature:	$T = -10 \dots +80 \text{ }^\circ\text{C}$
Terminating source impedance:	$Z_S = 50 \text{ } \Omega$ and matching network
Terminating load impedance:	$Z_S = 50 \text{ } \Omega$ and matching network

		min.	typ.	max.	
Nominal frequency	f_N	—	326,4	—	MHz
Minimum insertion attenuation	α_{\min}	—	2,0	4,0	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	$f_N - 2,5 \text{ MHz} \dots f_N + 2,5 \text{ MHz}$	—	0,3	0,5	dB
	$f_N - 7,5 \text{ MHz} \dots f_N + 7,5 \text{ MHz}$	—	1,0	3,0	dB
Pass bandwidth					
	$\alpha_{\text{rel}} \leq 1,0 \text{ dB}$	—	15	—	MHz
	$\alpha_{\text{rel}} \leq 10 \text{ dB}$	—	20	—	MHz
Relative attenuation (relative to α_{\min})	α_{rel}				
	10,0 MHz ... $f_N - 18,0 \text{ MHz}$	40	50	—	dB
	$f_N - 38,395 \text{ MHz} \dots f_N - 38,405 \text{ MHz}$	43	50	—	dB
	$f_N - 19,195 \text{ MHz} \dots f_N - 19,205 \text{ MHz}$	43	50	—	dB
	$f_N - 18,0 \text{ MHz} \dots f_N - 12,5 \text{ MHz}$	13	15	—	dB
	$f_N + 12,5 \text{ MHz} \dots f_N + 30,0 \text{ MHz}$	11	13	—	dB
	$f_N + 30,0 \text{ MHz} \dots f_N + 450,0 \text{ MHz}$	25	30	—	dB
Group delay ripple (p-p)	$\Delta\tau$				
	$f_N - 7,5 \text{ MHz} \dots f_N - 2,5 \text{ MHz}$	—	90	110	ns
	$f_N - 2,5 \text{ MHz} \dots f_N + 2,5 \text{ MHz}$	—	15	25	ns
	$f_N + 2,5 \text{ MHz} \dots f_N + 7,5 \text{ MHz}$	—	50	65	ns
Return Loss					
	$f_N - 2,5 \text{ MHz} \dots f_N + 2,5 \text{ MHz}$	10	11	—	dB
	$f_N - 7,0 \text{ MHz} \dots f_N + 7,0 \text{ MHz}$	8	10	—	dB
	$f_N - 7,5 \text{ MHz} \dots f_N + 7,5 \text{ MHz}$	5	8	—	dB
Impedance at f_N (without matching)¹					
Input: $Z_{\text{IN}} = R_{\text{IN}} \parallel C_{\text{IN}}$		—	72 0,4	—	$\Omega \parallel \text{pF}$
Output: $Z_{\text{OUT}} = R_{\text{OUT}} \parallel C_{\text{OUT}}$		—	73 0,2	—	$\Omega \parallel \text{pF}$
Temperature coefficient of frequency	TC_f	—	- 70	—	ppm/K

¹(port extensions directly at filter)

Data Sheet
Matching network to 50 Ω

(Element values depend upon PCB layout)



$$L_{s1} = 22 \text{ nH}$$


$$C_{p2} = 2,7 \text{ pF}$$

$$C_{p3} = 2,7 \text{ pF}$$


$$L_{s4} = 22 \text{ nH}$$

Data Sheet

Normalized frequency response



Normalized frequency response (pass band)



Published by EPCOS AG**Surface Acoustic Wave Components Division, SAW MC IS****P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.



This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View B39331B3807U310W3 on WIN SOURCE](#)
-  [Qualcomm Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management