

Surface Mount Type

POSCAP



Series : TA

- ◆ This product is not intended for use in any driving application or any other critical functions that affect passenger safety. (e.g. Powertrain, ABS, Engine ECU, Airbag, etc.)
If the intended use of TA/TV series products is for use in other automotive related applications, please contact our sales team.
All requests are subject to approval.

Features

- Guaranteed at 85 °C 85 %RH ● RoHS compliance, Halogen free

Specifications

Size code	B2	D2E	D3L
Category temperature range	-55 °C to +105 °C		
Rated voltage range	4 V.DC to 10 V.DC	2.5 V.DC to 10 V.DC	
Category voltage range	4 V.DC to 10 V.DC	2.5 V.DC to 10 V.DC	
Rated capacitance range	47µF to 100 µF	68 µF to 470 µF	150 µF to 680 µF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)		
Leakage current	Please see the attached characteristics list		
Dissipation factor (tan δ)	Please see the attached characteristics list		
Surge voltage (V.DC)	Rated voltage × 1.15		
Endurance	+105 °C, 2000 h, (B2 size : 1000 h) rated voltage applied		
	Capacitance change	Within ±20 % of the initial value	
	tan δ	≤ 1.5 times of the initial limit	
	DC leakage current	Within the initial limit	
Damp heat (Steady State)	+85 °C, 85 % to 90 %, 500 h, rated voltage applied		
	Capacitance change	Within +50 %, -20 % of the initial value (2R5TAE470M(F), 2R5TAE330M(F, I), 2R5TAE220M(F, 9))	
	tan δ	≤ 1.5 times of the initial limit	
	DC leakage current	Within the initial limit	

Marking

D2E, D3L Size	B2 Size																		
<table border="1"> <tr> <th>R. Voltage (V.DC)</th> <td>2.5</td> <td>4.0</td> <td>6.3</td> <td>10.0</td> </tr> <tr> <th>Code</th> <td>e</td> <td>g</td> <td>j</td> <td>A</td> </tr> </table>	R. Voltage (V.DC)	2.5	4.0	6.3	10.0	Code	e	g	j	A	<table border="1"> <tr> <th>R. Cap. (µF)</th> <td>47</td> <td>68</td> <td>100</td> </tr> <tr> <th>Code</th> <td>S7</td> <td>W7</td> <td>A8</td> </tr> </table>	R. Cap. (µF)	47	68	100	Code	S7	W7	A8
R. Voltage (V.DC)	2.5	4.0	6.3	10.0															
Code	e	g	j	A															
R. Cap. (µF)	47	68	100																
Code	S7	W7	A8																

Dimensions (not to scale)

Unit : mm					
Size Code	L±0.3*1	W±0.2	H±0.2*2	S±0.2	W1±0.1
B2	3.5	2.8	1.9	0.8	2.2
D2E	7.3	4.3	1.8	1.3	2.4
D3L	7.3	4.3	2.8	1.3	2.4

* Externals of figure are the reference.
* 1 ±0.2 : B2
* 2 ±0.1 : B2, D2E

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (µF)	Case size (mm)			Size code	Specifications				Standard		Floor life							
						L	W	H		Ripple*1 (mA.r.m.s.)	ESR*2 (mΩ max.)	tan δ*3	LC*4 (µA)	Part number	Min. Packaging Qty (pcs)	Reflow Temp ≤ 260°C	Reflow Temp ≤ 250°C						
TA	2.5	105	2.5	105	220	7.3	4.3	1.8	D2E	3900	9	0.10	110.0	2R5TAE220M9	3000	3	3						
										3100	15	0.10	55.0	2R5TAE220MF	3000								
										2400	25	0.10	55.0	2R5TAE220M	3000								
		3100	15	0.10	82.5	2R5TAE330MF	3000																
		2800	18	0.10	82.5	2R5TAE330MI	3000																
		2400	25	0.10	82.5	2R5TAE330M	3000																
		3100	15	0.10	117.5	2R5TAE470MF	3000																
		2400	25	0.10	117.5	2R5TAE470M	3000																
		3100	15	0.10	170.0	2R5TAE680MFL	2500																
		2400	25	0.10	170.0	2R5TAE680ML	2500																
		4	105	4.0	105	100	3.8	2.8		1.9	B2	1100	70	0.08	40.0			4TAB100M	2000				
												2800	18	0.10	88.0			4TAE220MI	3000				
	2400								25			0.10	88.0	4TAE220M	3000								
	105		4.0	105	220	7.3	4.3	2.8	D3L	2800		18	0.10	188.0	4TAE470MIL			2500					
										2400		25	0.10	188.0	4TAE470ML			2500					
										2400		25	0.10	188.0	4TAE470ML			2500					
	6.3	105	6.3	105	47	3.5	2.8	1.9		B2	1100	70	0.08	29.6	6TAB47M			2000					
											1100	70	0.08	42.8	6TAB68M			2000					
											2400	25	0.10	94.5	6TAE150M			3000					
		105	6.3	105	150	7.3	4.3	1.8	D2E		2800	18	0.10	138.6	6TAE220MI			3000					
											2400	25	0.10	138.6	6TAE220M			3000					
											2400	25	0.10	138.6	6TAE220M			3000					
	10	105	6.3	105	330	7.3	4.3	2.8		D3L	2400	25	0.10	207.9	6TAE330ML			2500					
											105	10.0	105	47	3.5			2.8	1.9	B2	1100	70	0.08
105											10.0	105	68	7.3	4.3	1.8	D2E	2400	25	0.10	68.0	10TAE68M	3000
105		10.0	105	150	7.3	4.3	2.8	D3L	2400		25	0.10	150.0	10TAE150ML	2500								
									2400		25	0.10	220.0	10TAE220ML	2500								
									2400		25	0.10	220.0	10TAE220ML	2500								

*1 Ripple current (100 kHz/ +45 °C), *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".

Guidelines and precautions regarding the technical information and use of our products described in this online catalog.

- If you want to use our products described in this online catalog for applications requiring special qualities or reliability, or for applications where the failure or malfunction of the products may directly jeopardize human life or potentially cause personal injury (e.g. aircraft and aerospace equipment, traffic and transportation equipment, combustion equipment, medical equipment, accident prevention, anti-crime equipment, and/or safety equipment), it is necessary to verify whether the specifications of our products fit to such applications. Please ensure that you will ask and check with our inquiry desk as to whether the specifications of our products fit to such applications use before you use our products.
- The quality and performance of our products as described in this online catalog only apply to our products when used in isolation. Therefore, please ensure you evaluate and verify our products under the specific circumstances in which our products are assembled in your own products and in which our products will actually be used.
- If you use our products in equipment that requires a high degree of reliability, regardless of the application, it is recommended that you set up protection circuits and redundancy circuits in order to ensure safety of your equipment.
- The products and product specifications described in this online catalog are subject to change for improvement without prior notice. Therefore, please be sure to request and confirm the latest product specifications which explain the specifications of our products in detail, before you finalize the design of your applications, purchase, or use our products.
- The technical information in this online catalog provides examples of our products' typical operations and application circuits. We do not guarantee the non-infringement of third party's intellectual property rights and we do not grant any license, right, or interest in our intellectual property.
- If any of our products, product specifications and/or technical information in this online catalog is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially with regard to security and export control, shall be observed.



<Regarding the Certificate of Compliance with the EU RoHS Directive/REACH Regulations>

- The switchover date for compliance with the RoHS Directive/REACH Regulations varies depending on the part number or series of our products.
- When you use the inventory of our products for which it is unclear whether those products are compliant with the RoHS Directive/REACH Regulation, please select "Sales Inquiry" in the website inquiry form and contact us.

We do not take any responsibility for the use of our products outside the scope of the specifications, descriptions, guidelines and precautions described in this online catalog.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 6TAE330ML on WIN SOURCE](#)
-  [Panasonic Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management