

OPIA500B, OPIA4N35, OPIA4N33 OPIA2110, OPIA2210, OPIA5010, OPIA6010 SMD and SOP Packages




Features:

- 3,750 or 5,000 Vrms electrical isolation
- Choice of a Single and Dual LED
- Phototransistor or Photo Darlington Sensor
- Low-cost plastic Dual-In-Line (DIP) package

Agency Approvals:

- UL Certification No: E58730
- VDE No: 40026624,40026625



Description:

The OPIA series optocouplers are designed for applications that use an analog output (Phototransistor or Photo Darlington) in a dual-in-line package. A wide selection of configurations are available. With typical isolation voltage of 3,750 or 5,000 Volts(RMS), these product meet typical power system isolation requirements.

Theory of operation: The LED transmitter is used to illuminate the Photosensor providing electrical isolation between two power systems while maintaining the ability to transmit information from one power system to the other. In many applications, analog signal levels may be required to be transmitted between two power systems while maintaining isolation between the power systems up to 5,000 Volts(RMS). A variety of LED and photosensor configurations are available depending on the system requirements.

The ratio Current Transfer Ratio (CTR) is determined using the output current and input current for analog photosensors. CTR ratios can range from as low as 5 to over 9,000 depending on the device.

$$CTR = \frac{\text{Photosensor - Current}}{\text{LED - Current}} = \frac{20mA}{10mA} * 100 = 200$$

All SMD product is shipped in tape and reel with "TR" identified on the end of the part number.
Example: OPI4N35ATRE is a 6-Pin SMD shipped in tape and reel (TR).

Applications:

- High voltage isolation
- PCBoard power system isolation
- Industrial equipment power isolation
- Medical equipment power isolation
- Office equipment







RoHS

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33 OPIA2110, OPIA2210, OPIA5010, OPIA6010 SMD and SOP Packages



Package Outline Dimensions and Schematics: Top-View



| Part Number | Pin # | | | | | |
|-------------|-------|-----|---|---|---|---|
| | 1 | 2 | 3 | 4 | 5 | 6 |
| OPIA500 | A | | K | E | C | B |
| OPIA4N35 | A | K | | E | C | B |
| OPIA5010 | A | K | | E | C | B |
| OPIA4N33 | A | K | | E | C | B |
| OPIA2210 | A | K | | E | C | B |
| OPIA6010 | A-K | K-A | | E | C | B |
| OPIA2110 | A | K | | E | C | |

| Symbol | Definition | Symbol | Definition | Symbol | Definition | Symbol | Definition | Symbol | Definition |
|--------|------------|--------|------------|--------|------------|--------|------------|--------|------------|
| A | Anode | B | Base | C | Collector | E | Emitter | K | Cathode |

Analog Output Devices Ordering Information

| Part Number | Isolation Voltage Max. (Vrms) | CTR Min/Typ/Max | Typ. Tr / Tf (µs) R _L = 100 ohms | Package | Configuration |
|-------------|-------------------------------|-----------------|--|-----------|-----------------|
| OPIA500B | 3,750 | 19 / - / 50 | LH-HL 0.8 / 0.8 (1.9K) | 5-Pin SOP | AK—KCE |
| OPIA4N35A | 5,000 | 60 / - / 600 | 5 / 4 | 6-Pin SMD | A K—B C E |
| OPIA5010A | 5,000 | 600 / - / 9,000 | 60 / 50 | 6-Pin SMD | A K—B C E (Dar) |
| OPIA4N33A | 5,000 | 500 / 4,000 / - | 5 / 60 | 6-Pin SMD | A K—B C E (Dar) |
| OPIA2210A | 5,000 | 50 / - / 600 | 2 / 3 | 6-Pin SMD | A K—B C E |
| OPIA6010A | 5,000 | 50 / - / 600 | 2 / 3 | 6-Pin SMD | A K, K A—B C E |
| OPIA2110A | 5,000 | 40 / - / 400 | 4 / 3 | 6-Pin SMD | A K—C E |

Configuration: Definition of Terms
LED Identification—Sensor Identification

| | | | | |
|--------|-----------|---------------|-------------|--------------------------|
| LED | A = Anode | K = Cathode | E = Emitter | (Dar) = Photo Darlington |
| Sensor | B = Base | C = Collector | | |

| | | |
|-----------|--|----------------------|
| Packaging | Part Number Suffix: TU = Ship in Tubes TR = Tape and Reel | Example: OPI4N35ATRE |
|-----------|--|----------------------|

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33 OPIA2110, OPIA2210, OPIA5010, OPIA6010 SMD and SOP Packages



Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| | |
|--|--|
| Storage Temperature | -55° C to +125° C |
| Operating Temperature OPIA4N35, OPIA5010, OPIA4N33 OPIA500 OPIA2210, OPIA6010, OPIA2110 | -30° C to +100° C -55° C to +85° C -55° C to +125° C |
| Isolation voltage (1 minute) OPIA6XX Series OPIA500 | 5,000 Vrms 3,750 Vrms |
| Total Package Power Dissipation OPIA6XX Series OPIA500 | 200 mW 100 mW |
| Lead Soldering Temperature (1/16" (1.6 mm) from case for 5 seconds with soldering iron) | 260° C |

Input Diode

| | |
|--|----------------|
| Continuous Forward Current OPIA6XX Series OPIA500 | 50 mA 25 mA |
| Peak Forward current (1 μs pulse width, 300 pps) OPIA6XX Series OPIA500 | 1 A 200 mA |
| Reverse Voltage OPIA6XX Series OPIA500 | 6 V 5 V |
| Power Dissipation OPIA6XX Series OPIA500 | 70 mW 45 mW |

Output Phototransistor

| | |
|--|--------------------------------|
| Collector-Emitter Voltage OPIA4N35, OPIA6010, OPIA2110 OPIA2210 OPIA5010 OPIA4N33 | 60 V 350 V 300 V 30 V |
| Emitter-Collector Voltage OPIA4N35, OPIA2110 OPIA2210, OPIA6010 OPIA5010, OPIA4N33 | 6 V 7 V - |
| Collector Current OPIA4N35, OPIA2210, OPIA6010, OPIA2110 OPIA5010, OPIA4N33 | 50 mA 150 mA |
| Power Dissipation OPIA500 OPIA4N35, OPIA2110 OPIA5010, OPIA4N33, OPIA2210, OPIA6010 | 100 mW 150 mW 200 mW |

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33
OPIA2110, OPIA2210, OPIA5010, OPIA6010
SMD and SOP Packages



Electrical Characteristics: (OPIA500B)

| | Parameter | Symbol | Conditions | MIN. | TYP. | MAX. | Unit |
|--------------------------|---|----------------------|---|--------------------|--------------------|------|-------|
| Input | Forward voltage | V _F | I _F =16mA | • • | 1.7 | 1.95 | V |
| | Reverse current | I _R | V _R =5V | • • | • • | 10 | uA |
| | Terminal capacitance | C _t | V=0, f=1MHZ | • • | 60 | 250 | pF |
| Output | High level output current (1) | I _{OH} (1) | I _F =0, V _{CC} =5.5V, V _O =5.5V | - | 3 | 500 | nA |
| | High level output current (2) | I _{OH} (2) | I _F =0, V _{CC} =15V, V _O =15V | - | - | 1.0 | uA |
| | High level output current (3) (*6) | I _{OH} (3) | | - | - | 50 | uA |
| | High level supply current (1) | I _{CCH} (1) | I _F =0, V _{CC} =15V, V _O =Open | - | 0.02 | 1.0 | uA |
| | High level supply current (2) (*6) | I _{CCH} (2) | | - | - | 2.0 | uA |
| | Low level supply current | I _{CCL} | I _F =16mA, V _{CC} =15V, V _O =Open | - | 120 | - | uA |
| | Low level supply voltage | V _L | I _F =16mA, V _{CC} =4.5V, I _O =2.4mA | • • | - | 0.4 | V |
| Transfer characteristics | Current transfer ratio (1) | CTR(1) | I _F =16mA, V _{CC} =4.5V, V _O =0.4V, RL=1.9K ohm | 19 | • • | 50 | % |
| | Current transfer ratio (2) (*6) | CTR(2) | RL=1.9K ohm | 15 | • • | - | % |
| | Isolation resistance | R _{ISO} | DC=500V, 40 to 60%RH | 5x10 ¹⁰ | 1x10 ¹¹ | - | ohm |
| | Floating capacitance | C _f | V=0, f=1MHZ | • • | 0.6 | 1.0 | pF |
| | "High-->Low" propagation delay time | t _{PHL} | I _F =16mA, V _{CC} =5V, RL=1.9K ohm | • • | 0.2 | 0.8 | us |
| | "High-->Low" propagation delay time | t _{PLH} | | - | 0.4 | 0.8 | us |
| | Instantaneous common mode rejection voltage (High level output) | CMH | I _F =0, V _{CC} =5V, V _{CM} =1.0KV(p-p), RL=1.9K ohm | 15 | 30 | - | KV/us |
| | Instantaneous common mode rejection voltage (High level output) | CML | I _F =16mA, V _{CC} =5V, V _{CM} =1.0KV(p-p), RL=1.9K ohm | -15 | -30 | - | KV/us |

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33
OPIA2110, OPIA2210, OPIA5010, OPIA6010
SMD and SOP Packages



Electrical Characteristics (OPIA6XX Series)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|-----------|-----|-----|-----|-------|-----------------|
|--------|-----------|-----|-----|-----|-------|-----------------|

Input Diode

| | | | | | | |
|----------|--|----------|------------|------------|---------------|--|
| V_f | Forward Voltage OPIA4N35, OPIA5010, OPIA4N33, OPIA604, OPIA2110 OPIA2210 | - 1.0 | 1.2 1.2 | 1.4 1.3 | V | $I_F = 20 \text{ mA}$ $I_F = 10 \text{ mA}$ |
| V_{FM} | Peek Forward Voltage OPIA4N35, OPIA5010, OPIA4N33, OPIA604 OPIA2210, OPIA2110 | - - | - - | 3.5 3.0 | V | $I_{FM} = 500 \text{ mA}$ |
| I_r | Reverse Current OPIA4N35, OPIA5010, OPIA4N33, OPIA604, OPIA2110 OPIA2210 | - - | - - | 10 10 | μA | $V_R = 4 \text{ V}$ $V_R = 5 \text{ V}$ |
| C_t | Terminal Capacitance OPIA4N35, OPIA5010, OPIA4N33, OPIA604, OPIA2110 OPIA2210 | - - | 30 30 | - - | pf | $V = 0.0 \text{ V}, f = 1\text{K Hz}$ $V = 0.0 \text{ V}, f = 1\text{M Hz}$ |

Output Phototransistor—OPIA4N35D, OPIA2210D, OPIA6010D, OPIA2110D

| | | | | | | |
|-----------|--|-------------|-------------|---------------|---------------|---|
| I_{CEO} | Collector dark Current OPIA4N35, OPIA6010, OPIA2110 OPIA2210 | - - | - 10 | 100 200 | nA | $I_F = 0 \text{ mA}, V_{CE} = 20 \text{ V}$ $I_F = 0 \text{ mA}, V_{CE} = 300 \text{ V}$ |
| V_{CEO} | Collector-emitter Saturation Voltage OPIA4N35, OPIA6010, OPIA2110 OPIA2210 | - - | 0.1 - | 0.3 0.4 | V | $I_F = 20 \text{ mA}, I_C = 1 \text{ mA}$ $I_F = 8 \text{ mA}, I_C = 2.4 \text{ mA}$ |
| f_c | Cutt-Off frequency | - | 80 | - | K Hz | $V_{CC} = 5 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ |
| t_r | Rise Time OPIA4N35, OPIA6010 OPIA2210 OPIA2110 | - - - | 5 2 4 | 20 - 20 | μs | $V_{CC} = 5 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 10 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 2 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ |
| t_f | Fall Time OPIA4N35, OPIA6010 OPIA2210 OPIA2110 | - - - | 4 3 3 | 20 - 20 | μs | $V_{CC} = 5 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 10 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 2 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ |

Continued on Next Page

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33
OPIA2110, OPIA2210, OPIA5010, OPIA6010
SMD and SOP Packages



Electrical Characteristics (OPIA6XX Series) - Continued from Previous Page

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|-----------|-----|-----|-----|-------|-----------------|
|--------|-----------|-----|-----|-----|-------|-----------------|

Output PhotoDarlington—OPIA5010D, OPIA4N332D

| | | | | | | |
|-----------|--|--------|----------|------------|---------|---|
| I_{CEO} | Collector dark Current OPIA5010 OPIA4N33 | - - | - - | 1.0 0.1 | μA | $I_F = 0 \text{ mA}, V_{CE} = 200 \text{ V}$ $I_F = 0 \text{ mA}, V_{CE} = 10 \text{ V}$ |
| V_{CEO} | Collector-emitter Saturation Voltage OPIA5010 OPIA4N33 | - - | - - | 1.5 1.0 | V | $I_F = 20 \text{ mA}, I_C = 5 \text{ mA}$ $I_F = 8 \text{ mA}, I_C = 2 \text{ mA}$ |
| f_c | Cutt-Off frequency OPIA5010, OPIA4N33 | - | 7.0 | - | K Hz | $V_{CC} = 5 \text{ V}, I_C = 2 \text{ mA}, R_L = 100 \Omega$ |
| t_r | Rise Time OPIA5010 OPIA4N33 | - - | 60 5 | 300 40 | μs | $V_{CC} = 2 \text{ V}, I_C = 20 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 10 \text{ V}, I_C = 50 \text{ mA}, R_L = 100 \Omega$ |
| t_f | Fall Time OPIA5010 OPIA4N33 | - - | 50 60 | 250 100 | μs | $V_{CC} = 2 \text{ V}, I_C = 20 \text{ mA}, R_L = 100 \Omega$ $V_{CC} = 10 \text{ V}, I_C = 50 \text{ mA}, R_L = 100 \Omega$ |

Coupled Characteristics Phototransistor/Photodarlington

| | | | | | | |
|-----------|--|------------------------------------|--------------------------------|--|-----|---|
| CTR | Current Transfer Ratio OPIA4N35 OPIA5010 OPIA4N33 OPIA2210 OPIA6010 OPIA2110 | 60 600 500 50 60 40 | - - 4,000 - - - | 600 9,000 - 600 600 400 | % | $I_F = 2 \text{ mA}, V_{CE} = 5.0 \text{ V}$ $I_F = 2 \text{ mA}, V_{CE} = 5.0 \text{ V}$ $I_F = 10 \text{ mA}, V_{CE} = 10.0 \text{ V}$ $I_F = 5 \text{ mA}, V_{CE} = 5.0 \text{ V}$ $I_F = 1 \text{ mA}, V_{CE} = 5.0 \text{ V}$ $I_F = 10 \text{ mA}, V_{CE} = 5.0 \text{ V}$ |
| C_f | Floating Capacitance | - | 0.6 | 1.0 | pF | $V = 0.0 \text{ V}, f = 1 \text{ M Hz}$ |
| R_{ISO} | Isolation resistance | 5×10^{10} | 10^{11} | - | ohm | DC500V |

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA4N35

Fig.1 Current Transfer Ratio vs. Forward Current




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector Dark Current vs. Ambient Temperature




Fig.4 Forward Current vs. Ambient Temperature





Fig.5 Forward Current vs. Forward Voltage



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA4N35

Fig.6 Collector Current vs. Collector-emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.9 Collector-emitter Saturation Voltage vs. Forward Current




Fig.10 Response Time vs. Load Resistance





Fig.11 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA5010

Fig. 4 Forward Current vs. Ambient Temperature




Fig. 5 Forward Current vs. Forward Voltage




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Collector Dark Current vs. Ambient Temperature




Fig. 6 Collector Current vs. Collector-emitter Voltage





Fig. 7 Relative Current Transfer Ratio vs. Ambient Temperature



OPTeK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA5010

Fig. 1 Current Transfer Ratio vs. Forward Current




Fig. 8 Collector-emitter Saturation Voltage vs. Forward Current





Fig. 9 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA4N33

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Current Transfer Ratio vs. Forward Current





Fig. 6 Collector Current vs. Collector-emitter Voltage



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA4N33

Fig.11 Collector-emitter Saturation Voltage vs. Forward current




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.9 Collector Dark Current vs. Ambient Temperature





Fig.10 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA2210

Fig.1 Current Transfer Ratio vs. Forward Current




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector Dark Current vs. Ambient Temperature




Fig.4 Forward Current vs. Ambient Temperature





Fig.5 Forward Current vs. Forward Voltage



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA2210

Fig.6 Collector Current vs. Collector-emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.9 Collector-emitter Saturation Voltage vs. Forward Current




Fig.10 Response Time vs. Load Resistance





Fig.11 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA6010

Fig.1 Current Transfer Ratio vs. Forward Current




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector Dark Current vs. Ambient Temperature




Fig.4 Forward Current vs. Ambient Temperature




Fig.5 Forward Current vs. Forward Voltage




Fig.6 Collector Current vs. Collector-emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature





Fig.8 Collector-emitter Saturation Voltage vs. Ambient Temperature



OPTeK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA6010

Fig.9 Collector-emitter Saturation Voltage vs. Forward Current




Fig.10 Response Time vs. Load Resistance





Fig.11 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA2110

Fig.1 Current Transfer Ratio vs. Forward Current




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector Dark Current vs. Ambient Temperature




Fig.4 Forward Current vs. Ambient Temperature





Fig.5 Forward Current vs. Forward Voltage



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA2110

Fig.6 Collector Current vs. Collector-Emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-Emitter Saturation Voltage vs. Ambient Temperature




Fig.9 Collector-Emitter Saturation Voltage vs. Forward Current




Fig.10 Response Time vs. Load Resistance





Fig.11 Response Time vs. Load Resistance



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

**OPIA500B, OPIA4N35, OPIA4N33
OPIA2110, OPIA2210, OPIA5010, OPIA6010
SMD and SOP Packages**



Quality / Reliability Requirements

| Parameter | Failure Criteria | Conditions |
|----------------------------|------------------|---|
| HTRB D I _{C(OFF)} | ± 10% | 11 samples after 500Hrs |
| | 0 Fail | @ VCE = 5.0VDC, Ta = 70°C |
| HTFB D I _{C(ON)} | ± 10% | 50 samples after 96Hrs |
| | 0 Fail | @ Max P _D , Ta = 25°C |
| MTTF @ 90% confidence | 150,000 Min. | @ 25°C, 25mADC |
| Moisture Sensitivity Level | MSL 1 | per JDEC std J-STD-020B |
| Lead Solderability | 0 Fail | per Method 208 of MIL-STD-202. |
| Glass Transition of body | 125°C Min. | DSC test method |
| Temperature Humidity-Bias | ± 20% | 85°C, 85%RH, 500Hrs, 80% min I _{ceo} |
| Temperature Cycle | ± 20% | per Method 1010.7 of MIL-STD-883E |
| High Temperature Storage | ± 20% | 85°C, 500Hrs |
| Autoclave | 0 Fail | T _A = 121°C, Pressure = 15psi, Humidity = 100%, Time = 96Hrs |

Note: This is to be performed when a change occurs to form, fit or function.

**Government and Industry Standard
Compliance Requirements**

European Union’s Reduction of Hazardous Substances (RoHS) Directive 2002/95/EC






Label Identification

DESCRIPTION:

Size: 3” (7.4 cm) X 2.2” (5.5 cm)
Lettering shall be black on white background.
Format shall be as:

Notes:

1. The DATE CODE is a 4-digit code for date of manufacture where YY is the last two digits of the year, and WW is week number of manufacture.
2. The LOT I.D. is the manufacturing location lot identification where Y is the year of manufacture, NNNN is a sequential lot identifier, and DDD is the day of the year of manufacture. – or use equivalent label format.

| |
|---|
|  Carrollton, TX, USA MADE IN TAIWAN <small>RoHS compliant</small> |
| OPTEK P/N <u> OPIA2110A-TR </u>  |
| QTY. <u> N/A </u>  |
| DATE CODE <u> (Y Y W W) </u>  |
| LOT I.D. <u> (Y - N N N N D D D) </u>  |

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

**OPIA500B, OPIA4N35, OPIA4N33
OPIA2110, OPIA2210, OPIA5010, OPIA6010
SMD and SOP Packages**



Packaging Information:

| Optek's Optocoupler Part Numbers | | Packaging Quantities | | Tube | | Inner | | | Small Carton | | | Medium Carton | | | Large Carton | | |
|----------------------------------|---|----------------------|----|--------|--------|-----------------|--------|---------------------|--------------|--------------|-----------------------|---------------|--------------|---------------------|--------------|--------------|--|
| | | | | Qty | Weight | 52 x 7 x 7.5 cm | | 53.5 x 16 x 17.5 cm | | | 53.5 x 30.7 x 17.5 cm | | | 53.5 x 30.7 x 25 cm | | | |
| | | | | | | Qty | Weight | Qty | Weight | Gross Weight | Qty | Weight | Gross Weight | Qty | Weight | Gross Weight | |
| P/H and SMD | 4-PIN OPIA400D/A, OPIA410D/A - OPIA413D/A | 100 | 44 | 3,000 | 1.40 | 12,000 | 6.0 | 6.5 | 24,000 | 12.0 | 12.5 | 36,000 | 18.0 | 18.5 | | | |
| | 6-PIN OPIA6XXD/A Series | 65 | 44 | 1,950 | 1.50 | 7,800 | 6.5 | 7.0 | 15,600 | 12.0 | 12.5 | 23,400 | 18.5 | 19.0 | | | |
| | 8-PIN OPIA8XXD Series and OPID804D | 48 | 44 | 1,440 | 1.44 | 5,760 | 6.0 | 6.5 | 11,520 | 12.0 | 12.5 | 17,290 | 18.0 | 18.5 | | | |
| M/F SOP | 4-PIN and 5-PIN OPIA401B - OPIA404B, OPIA414B, OPIA500B | 100 | 24 | 6,000 | 1.60 | 24,000 | 6.5 | 7.0 | 48,000 | 13.0 | 13.5 | 72,000 | 19.5 | 20.0 | | | |
| SSOP | 4-PIN OPIA405C - OPIA409C | 170 | -- | 10,200 | -- | | | | | | | | | | | | |

P/H = Pin-Hole Packages (Referred as D = Dual-In-Line Package)

SMD = Standard Surface Mount Packages (Referred as A = 6.5mil SMD)

M/F or SOP = Mini-Flat Packages or Small Outside Packages (Referred as B = 4.40mil SMD w/ 2.54mil Lead-Spacing)


SSOP = Shrink SOP Packages (Referred as C = 3.60mil SMD with 1.27mil Lead-Spacing)

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33 OPIA2110, OPIA2210, OPIA5010, OPIA6010 SMD and SOP Packages




Tube Packaging Specifications—SMD (TU):




DIMENSIONS ARE IN: INCHES [MILLIMETERS]

TOLERANCE: ± 0.008 INCHES
[± 0.2 MILLIMETERS]




Quantity: 6-pin: 65pcs/tube

Tube Packaging Specifications— SOP (Mini-flats) (TU):



DIMENSIONS ARE IN: INCHES [MILLIMETERS]

TOLERANCE: ± 0.008 INCHES
[± 0.2 MILLIMETERS]



Quantity: 5-pin: 100pcs/tube


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPIA500B, OPIA4N35, OPIA4N33 OPIA2110, OPIA2210, OPIA5010, OPIA6010 SMD and SOP Packages




Tape and Reel Packaging Specifications—SMD —(TR):

0.157 ± 0.004
[4.0 ± 0.1]




Direction:



DIMENSIONS ARE IN: INCHES [MILLIMETERS]
TOLERANCE: ± 0.008 INCHES
[± 0.2 MILLIMETERS]

Reel:




Quantity: 6-pin: 1000pcs/Reel

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


OPIA500B, OPIA4N35, OPIA4N33
 OPIA2110, OPIA2210, OPIA5010, OPIA6010
 SMD and SOP Packages



Tape and Reel Packaging Specifications—SOP (Mini-Flat) — (TR):




Direction:



DIMENSIONS ARE IN: INCHES [MILLIMETERS]
 TOLERANCE: ± 0.008 INCHES
 [± 0.2 MILLIMETERS]

Reel:



Quantity: 5-pin: 1000pcs/Reel

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View OPIA4N35ATUE](#) on WIN SOURCE

 [TT Electronics](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management