



## BAT42W/BAT43W SURFACE MOUNT SCHOTTKY BARRIER DIODE



### Features

- Low Turn-on Voltage
- Fast Switching
- PN Junction Guard Ring Transient and ESD Protection
- Designed for Surface Mount Application
- Plastic Material —UL Recognition Flammability Classification 94V-0
- Green Products in Compliance with the ROHS Directive
- This is a Pb – Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

### Circuit Diagram



### Mechanical Data

- Case: SOD-123, Molded Plastic
- Terminals: Plated leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.01 grams(approx.)

### Maximum Ratings @<sub>T<sub>A</sub></sub>=25°C unless otherwise specified


Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	BAT42W/BAT43W	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	30	V
RMS Reverse Voltage	$V_{R(RMS)}$	21	V
Forward Continuous Current	$I_{FM}$	0.2	A
Repetitive Peak Forward Current @ <sub>t&lt;1.0s</sub>	$I_{FRM}$	500	mA
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	4.0	A
Power Dissipation	$P_d$	500	mW
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	200	°C/W
Junction Temperature Range	$T_J$	125	°C
Storage Temperature Range	$T_{STG}$	-55 to +150	°C

**Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified**


Characteristic	Symbol	Min	Typ	Max	Units	Test Condition
Reverse Breakdown Voltage	V <sub>(BR)</sub>	30	-	-	V	I <sub>R</sub> =10μA
Forward Voltage	All Types	V <sub>F</sub>	-	-	1.0	V I <sub>F</sub> =200mA
	BAT42W	V <sub>F</sub>	-	-	0.4	V I <sub>F</sub> =10mA
	BAT42W	V <sub>F</sub>	-	-	0.65	V I <sub>F</sub> =50mA
	BAT43W	V <sub>F</sub>	0.26	-	0.33	V I <sub>F</sub> =2mA
	BAT43W	V <sub>F</sub>	-	-	0.45	V I <sub>F</sub> =15mA
Reverse Leakage Current	I <sub>R</sub>	-	-	0.5	μA	V <sub>R</sub> =25V
Junction Capacitance	C <sub>j</sub>	-	-	10	pF	V <sub>R</sub> =1.0V, f=1.0MHz

**SOD-123 Suggested Pad Layout**



- Note:
1. Controlling dimension: in millimeters.
  2. General tolerance: ±0.05mm.
  3. The pad layout is for reference purposes only.

**Mechanical Dimensions SOD-123**



SYMBOL	Millimeters		Inches	
	MIN.	MAX.	MIN.	MAX.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.450	0.650	0.018	0.026
c	0.080	0.150	0.003	0.006
D	1.500	1.700	0.059	0.067
E	2.600	2.800	0.102	0.110
E1	3.550	3.850	0.140	0.152
L	0.500 REF.		0.020 REF.	
L1	0.250	0.450	0.010	0.018
$\theta$	0°	8°	0°	8°

**Ordering Information**

Device	Package	Shipping
BAT42(43)W	SOD-123 (Pb-Free)	3000pcs / reel

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.


**Marking Diagram**



BAT42W

BAT43W

**Carrier Tape Specification SOD-123**





SYMBOL	Millimeters	
	Min.	Max.
A	1.80	1.90
B	3.89	3.99
C	1.52	1.62
d	1.45	1.65
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.30

**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BAT43W on WIN SOURCE](#)
-  [SMC Diode Solutions](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management