

FM260 Formaldehyde and TVOC Meter

Simultaneous real-time display of HCHO/CH₂O (Formaldehyde) and TVOC (Total Volatile Organic Compounds) concentrations in the air

Features:

- Two selectable units of measure (ppm, mg/m³)
- Fuel Cell Formaldehyde Sensor Technology for high accuracy measurement
- Backlit dual LCD
- Audible and visual high/low alarms for HCHO
- Auto power off conserves battery life
- Includes rechargeable 7.4V Li-Po battery and AC charger/adaptor
- One year warranty

Applications:

Potential sources for TVOCs include paints, finishes, adhesives, cigarette smoke, pesticides, personal care products, car exhaust, new furnishings, wall coverings, household cleaners, and cooking fuels. Chemicals include: Acetone, Ethylene Glycol, Formaldehyde, Xylene, 1,3-butadiene, Tetrachloroethene, Hydrogen Sulfide, Ammonia, Toluene, Benzene, Methylene Chloride, Perchloroethylene and MTBE.



Specifications

Formaldehyde (HCHO/CH ₂ O) Range	0.00 to 5.00 mg/m ³ (ppm)
Accuracy	±5% FS
Resolution	0.01 mg/m ³ (ppm)
TVOC Range	0.00 to 9.99 mg/m ³ (ppm)
Accuracy	±5% FS
Resolution	0.01 mg/m ³ (ppm)
Response Time	≤ 2 seconds
Power	Rechargeable 7.4V Li-Po Battery
Dimensions	6.5 x 2.4 x 1" (165 x 60 x 25mm)
Weight	20.6oz (584g)

Ordering Information:

FM260 Formaldehyde and TVOC Meter



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View FM260 on WIN SOURCE](#)
- [Triplett Test Equipment and Tools Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management