



**THE DATASHEET OF  
ADV7510BSTZ-225**





### FEATURES

#### General

- Incorporates HDMI (v.1.3 with Deep Color, x.v.Color)
- 225 MHz supports 12-bit Deep Color operation in all video formats up to 1080p
- Supports Gamut Metadata Packet transmission
- Integrated CEC buffer/controller
- Compatible with DVI v.1.0, and HDCP v.1.3
- Video/audio inputs accept logic levels from 1.8 V to 3.3 V

#### Digital video

- Programmable two-way color space converter
- Supports RGB, YCbCr, and DDR
- Supports ITU656-based embedded syncs
- Auto input video format timing detection (CEA-861-D)

#### Digital audio

- Supports standard S/PDIF for stereo LPCM or compressed audio up to 192 kHz
- 8-channel uncompressed LPCM I<sup>2</sup>S audio up to 192 kHz

#### Special features for easy system design

- On-chip MPU with I<sup>2</sup>C master to perform HDCP operations and EDID reading operations
- 5 V tolerant I<sup>2</sup>C and HPD I/Os, no extra device needed
- No audio master clock needed for supporting S/PDIF and I<sup>2</sup>S
- On-chip MPU reports HDMI events through interrupts and registers

### GENERAL DESCRIPTION

The ADV7510 is a 225 MHz High Definition Multimedia Interface (HDMI™) transmitter, which is ideal for home entertainment products including DVD players/recorders, digital set top boxes, A/V receivers, gaming consoles, and PCs.

The digital video interface contains an HDMI and a DVI v.1.0-compatible transmitter, and supports all HDTV formats (including 1080p with 12-bit Deep Color). The ADV7510 also supports x.v.Color™, high bit rate audio, digital theater sound (DTS), and programmable AVI InfoFrames features.

For more information about the ADV7510, email: [flatpanel\\_apps@analog.com](mailto:flatpanel_apps@analog.com).

#### Rev. SpA

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

### FUNCTIONAL BLOCK DIAGRAM




Figure 1.

With the inclusion of HDCP, the ADV7510 allows the secure transmission of protected content as specified by the HDCP v.1.3 protocol.

The ADV7510 supports both S/PDIF and 8-channel I<sup>2</sup>S audio. Its high fidelity 8-channel I<sup>2</sup>S can transmit either stereo or 7.1 surround audio up to 768 kHz. The S/PDIF can carry compressed audio including Dolby® Digital, DTS®, and THX®.

Fabricated in an advanced CMOS process, the ADV7510 is provided in a 100-lead LQFP surface-mount plastic package and is specified over the 0°C to +85°C temperature range.

**ADV7510**

**NOTES**

I<sup>2</sup>C refers to a communications protocol originally developed by Philips Semiconductors (now NXP Semiconductors).

©2008–2009 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.  
D07350F-0-11/09(SpA)



[www.analog.com](http://www.analog.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View ADV7510BSTZ-225 on WIN SOURCE](#)
- ⊖ [Analog Devices Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management