

Device Features

- OIP3 = 32.0 dBm @ 1900 MHz
- Gain = 22.2 dB @ 1900 MHz
- Output P1 dB = 19.0 dBm @ 1900 MHz
- Patented temperature compensation
- Patented Over Voltage Protection Circuit
- RoHS2-compliant SOT-89 SMT package




Product Description

BeRex's BG18D is a high performance InGaP/GaAs HBT MMIC amplifier is internally matched to 50 Ohms and uses a patented **temperature compensation** circuit to provide stable current over the operating temperature range without the need for external components and a patented **over voltage protection** circuit to protect a internal device. The BG18D is designed for high linearity gain block applications that require excellent gain flatness. It is packaged in a RoHS2-compliant with SOT-89 surface mount package.

Applications

- Base station Infrastructure/RFID
- Commercial/Industrial/Military wireless system

Applications Circuit



*C1, C2, C3 = 100 pF ± 5%; C4 = 1000 pF ± 5%; C5 = 10uF; L1 = 33nH ± 5%

*C1, C2 = 10nF; L1 = 2.7uH for IF Bandwidth

*Optimum value of L1 may vary with board design.

Electrical Specifications

Device performance _ measured on a BeRex evaluation board at 25°C, Vc=5V, 50 Ω system.

Parameter	Conditions	Min	Typ	Max	Unit
Operational Frequency Range		5		4000	MHz
Test Frequency			1900		MHz
Gain		20.7	22.2		dB
Input Return Loss			-22.0		dB
Output Return Loss			-20.0		dB
Output IP3	7 dBm / tone , Δf=1 MHz	29.0	32.0		dBm
Output P1dB		18.0	19.0		dBm
Noise Figure			4.3		dB

Recommended Operating Conditions

Parameter	Min	Typ	Max	Unit
Bandwidth	5		4000	MHz
I _c @ (V _c = 5V)	66	83	100	mA
V _c	3.5	5.0	5.25	V
dG/dT		-0.004		dB/°C
R _{TH}		50		°C/W
Operating Case Temperature	-40		+85	°C

Electrical specifications are measured at specified test conditions.

Specifications are not guaranteed over all recommended operating conditions.

Absolute Maximum Ratings

Parameter	Rating	Unit
Storage Temperature	-55 to +155	°C
Junction Temperature	+170	°C
Supply Voltage	+6.0	V
Supply Current	160	mA
Input RF Power	23	dBm

Operation of this device above any of these parameters may result in permanent damage.

5-4000 MHz Cascadable InGaP HBT Gain Block

Typical Performance (Vc = 5V, Ic = 80mA, T = 25°C)

Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	24.9	24.6	24.4	24.1	23.8	21.9	21.4	20.5	14.2
S11	dB	13.1	14.4	15.3	16.5	20.6	21.7	21.7	21.2	19.5
S22	dB	8.3	10.7	12.4	13.9	23.0	31.0	36.8	30.9	5.2
P1	dBm	18.1	19.3	19.6	19.7	19.9	19.3	19.6	18.2	12.5
OIP3	dBm	36.5	35.5	36.0	35.5	35.0	32.5	33.0	31.0	21.0
NF	dB	5.0	4.7	4.8	4.9	4.9	5.0	5.2	5.5	6.0

Typical Performance (Vc = 4.7V, Ic = 64mA, T = 25°C)

Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	24.5	24.3	24.1	23.8	23.7	21.8	21.3	20.6	14.2
S11	dB	12.2	13.3	14.1	15.3	18.7	22.8	22.5	21.5	19.0
S22	dB	7.8	10.1	11.7	13.0	20.8	27.0	30.0	34.7	5.3
P1	dBm	17.2	17.9	17.9	17.9	18.2	18.3	18.6	17.4	11.9
OIP3	dBm	32.0	31.5	32.5	32.0	32.0	31.5	32.0	30.0	20.0
NF	dB	4.7	4.4	4.6	4.6	4.6	4.7	4.8	5.1	5.5

Typical Performance (Vc = 4.5V, Ic = 54mA, T = 25°C)



Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	24.3	24.0	23.9	23.6	23.5	21.8	21.3	20.6	14.3
S11	dB	11.6	12.5	13.2	14.2	17.2	22.6	22.0	20.8	19.3
S22	dB	7.5	9.7	11.2	12.4	19.0	24.5	26.8	36.1	5.3
P1	dBm	15.6	16.0	16.5	16.7	16.7	17.6	17.9	16.7	11.5
OIP3	dBm	29.0	29.0	29.5	29.5	29.5	29.5	30.0	28.0	19.5
NF	dB	4.4	4.0	4.2	4.3	4.1	4.2	4.3	4.5	4.7

Typical Performance (Vc = 4.0V, Ic = 34mA, T = 25°C)

Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	22.8	22.7	22.6	22.4	22.5	21.2	20.8	20.2	14.3
S11	dB	9.3	9.7	10.1	10.7	12.5	17.7	17.1	16.1	21.8
S22	dB	6.2	7.9	9.1	10.0	13.8	18.0	19.2	23.6	5.5
P1	dBm	10.3	10.8	11.3	11.6	11.4	12.8	15.0	14.7	10.6
OIP3	dBm	23.0	22.5	23.0	23.0	20.5	20.5	22.0	20.5	17.5
NF	dB	4.4	4.0	4.2	4.3	4.1	4.2	4.3	4.5	4.7

Typical Performance (Vc = 3.5V, Ic = 21mA, T = 25°C)


Freq	MHz	70	150	250	500	900	1900	2140	2450	3500
S21	dB	18.0	18.0	17.9	17.9	18.6	18.5	18.5	18.4	14.3
S11	dB	5.2	5.1	5.1	5.3	5.8	7.3	7.2	6.8	16.2
S22	dB	3.6	4.6	5.1	5.5	6.7	8.7	9.1	10.3	7.2
P1	dBm	4.4	5.0	5.4	5.3	4.2	4.9	10.4	12.9	10.0
OIP3	dBm	17.5	17.5	17.0	17.5	18.0	19.5	20.0	21.0	16.0
NF	dB	4.2	3.9	4.2	4.2	4.1	4.1	4.1	4.3	4.4

V-I Characteristics

BeRex SOT89 Evaluation Board


*Dielectric constant _ 4.2 *RF pattern width 52mil *31mil thick FR4 PCB

Typical Device Data

S-parameters (Vc=5V, Ic=83mA, T=25°C)





S-Parameter







(Vdevice = 5.0V, Icc = 83mA, T = 25 °C, calibrated to device leads)






Freq [MHz]	S11 [Mag]	S11 [Ang]	S21 [Mag]	S21 [Ang]	S12 [Mag]	S12 [Ang]	S22 [Mag]	S22 [Ang]
100	0.396	-172.9	21.635	167.2	0.037	13.3	0.348	-31.5
500	0.463	152.6	16.700	143.9	0.049	1.9	0.181	-58.7
1000	0.409	123.5	15.718	118.7	0.046	-3.2	0.105	-97.0
1500	0.333	96.2	14.241	91.3	0.048	-5.2	0.052	178.7
2000	0.206	68.2	12.533	65.3	0.047	-11.8	0.099	90.5
2500	0.095	30.0	12.252	39.1	0.047	-15.5	0.206	50.8
3000	0.034	-168.1	10.439	2.7	0.044	-18.6	0.309	25.6
3500	0.159	160.8	7.002	-23.6	0.045	-22.9	0.392	-7.8
4000	0.233	126.3	5.014	-41.4	0.043	-26.8	0.048	-33.6

Typical Performance
 (Vc = 5V, Ic = 80mA, T = 25°C)


Pin-Pout-Gain



OIP3


ACPR

Gain Flatness


Package Outline Dimension




- NOTE:**
 1. DIMENSIONS IN MILLIMETERS.
- ⚠ DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.5mm PER END. DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.5mm PER SIDE.
 - ⚠ DIMENSIONS D AND E1 ARE DETERMINED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
 - ⚠ DATUMS A, B AND D TO BE DETERMINED 0.18mm FROM THE LEAD TIP.
 - ⚠ TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.

SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.40	1.50	1.60	
A1	0.00	—	0.10	
b	0.38	0.42	0.48	
b1	0.48	0.52	0.58	
b2	1.79	1.82	1.87	
c	0.40	0.42	0.46	
D	4.40	4.50	4.70	2,3
E	3.70	4.00	4.30	
E1	2.40	2.50	2.70	2,3
E2	0.80	1.00	1.20	
E3	0.40	0.50	0.60	
e	1.50 TYP.			
φ	4° TYP.			
R	0.15 TYP.			
R1	—	—	0.20	
SYMBOL	TOLERANCES OF FORM AND POSITION		NOTE	
aaa	0.15			
bbb	0.20			
ccc	0.10			
ddd	0.10			

Suggested PCB Land Pattern and PAD Layout


PCB Land Pattern




Note : All dimension _ millimeters

PCB lay out _ on BeRex website

PCB Mounting



Package Marking




YY = Year, WW = Working Week,
XX = Wafer No.

Pin 1

Tape & Reel

SOT89



Packaging information:

Tape Width (mm): 12
Reel Size (inches): 7
Device Cavity Pitch (mm): 8
Devices Per Reel: 1000

Lead plating finish

100% Tin Matte finish

(All BeRex products undergoes a 1 hour, 150 degree C, Anneal bake to eliminate thin whisker growth concerns.)

MSL / ESD Rating

ESD Rating:	Class 1C
Value:	Passes <2000V
Test:	Human Body Model (HBM)
Standard:	JEDEC Standard JESD22-A114
MSL Rating:	Level 1 at +260°C convection reflow
Standard:	JEDEC Standard J-STD-020



Proper ESD procedures should be followed when handling this device.

RoHS Compliance

This part is compliant with Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) Directive 2011/65/EU as amended by Directive 2015/863/EU.



This product also is compliant with a concentration of the Substances of Very High Concern (SVHC) candidate list which are contained in a quantity of less than 0.1%(w/w) in each components of a product and/or its packaging placed on the European Community market by the BeRex and Suppliers.

NATO CAGE code:

2	N	9	6	F
---	---	---	---	---

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BG18D on WIN SOURCE](#)
-  [BeRex Corporation Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management