



**THE DATASHEET OF
T435-600W**



SCRs, Triacs, AC switches and A.S.D™



**High commutation and voltage immunity
for appliances, charging and industrial power switching**

Content

- Product tree
- AC switches
- ACST overvoltage self-protect
- ACS™ overvoltage self-protect
- Thyristors (SCRs)
- High-temperature Thyristors (Standard and sensitive Thyristors)
- Thyristor application-specific
- Application-specific ignitors
- Triacs
- high-Temperature Triacs T-Series
- high-temperature Triacs H-Series
- Standard and Snubberless™
- Standard and Snubberless™
- 1200 V TRIACS, Snubberless™
- Automatic voltage switches
- Diacs
- Trigger diodes



Triacs

| | High Temperature | Standard | Logic Level | Snubberless™ | AVS | VBO min | VBO max | T _J max |
|-------------------------------------|------------------|-------------|------------------|--------------|-------------|---------|---------|--------------------|
| I _{TRMS} max | 4 - 30 A | 1 - 40 A | 0.8 - 16 A | 4 - 25 A | 8 - 12 A | | | |
| V _{DRM} , V _{RRM} | 600 - 800 V | 600 - 800 V | 600 - 800 V | 600 - 1200 V | 500 - 600 V | | | |
| I _{FSM} max | 30 - 270 A | 8 - 400 A | 8 - 160 A | 30 - 250 A | 65 - 100 A | | | |
| I _{GT} max | 10 - 50 mA | 25 - 50 mA | 3 - 50 mA | 10 - 50 mA | 5 - 10 mA | | | |
| T _J max | 150 °C | 125 °C | 110 - 125 °C | 125 °C | 125 °C | | | |
| | 3 or 4 quadrants | | 3 or 4 quadrants | 3 quadrants | | | | |

SCR

| | High Temperature | Standard | Logic Level |
|-------------------------------------|--------------------|--------------|-------------|
| I _{TRMS} max | 12 - 80 A | 6 - 50 A | 0.8 - 12 A |
| V _{DRM} , V _{RRM} | 600 - 1200 V | 600 - 1200 V | 600 - 800 V |
| I _{FSM} max | 120 - 670 A | 70 - 700 A | 7 - 110 A |
| I _{GT} max | 5 - 50 mA | 5 - 80 mA | 1 - 200 µA |
| T _J max | 150 °C | 125 °C | 125 °C |
| | Automotive options | | |

AC Switches

| | ACS |
|-------------------------------------|-------------|
| I _{TRMS} max | 0.8 - 2 A |
| V _{DRM} , V _{RRM} | 600 - 800 V |
| I _{FSM} max | 7.3 - 20 A |
| I _{GT} max | 5 - 10 mA |
| T _J max | 125 °C |

AC switches

ACST OVERVOLTAGE SELF-PROTECTED SWITCHES

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering gate current | Clamping voltage | Rate of decrease of commutating on-state current | Rising ratio of off voltage |
|-------------|--|---------------------------------|----------------------|-----------------------------------|--|----------------------|-------------------------|-------------------------|--|-----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T_J) | I_{GT} (I, II, III) | V_{CL} (@100 μ A) | (dI/dt) _c min (@ T_J max) | dV/dt (@ T_J max) |
| | | | max (A) | max (V) | max (A) | max (°C) | max (mA) | min (V) | min (A/ms) | min (V/ μ s) |
| ACST210-8 | DPAK, TO-220FPAB | Overvoltage protected AC switch | 2 | 800 | 8 | 125 | 10, 10, 10 | 850 | 0.5 | 500 |
| ACST310-8 | TO-220FPAB | Overvoltage protected AC switch | 3 | 800 | 20 | 125 | 10, 10, 10 | 850 | 1 | 1000 |
| ACST410-8 | DPAK, TO-220FPAB | Overvoltage protected AC switch | 4 | 800 | 30 | 125 | 10, 10, 10 | 850 | 2 | 500 |
| ACST435-8 | DPAK, TO-220FPAB | Overvoltage protected AC switch | 4 | 800 | 30 | 125 | 35, 35, 35 | 850 | 5 | 1000 |
| ACST610-8 | D ² PAK, TO-220AB, TO-220FPAB | Overvoltage protected AC switch | 6 | 800 | 45 | 125 | 10, 10, 10 | 850 | 3.5 | 500 |
| ACST830-8 | D ² PAK, TO-220AB, TO-220FPAB | Overvoltage protected AC switch | 8 | 800 | 80 | 125 | 30, 30, 30 | 850 | 8 | 2000 |
| ACST1010-7 | TO-220AB, TO-220FPAB | Overvoltage protected AC switch | 10 | 700 | 100 | 125 | 10, 10, 10 | 850 | 4.4 | 200 |
| ACST1035-7 | TO-220AB, TO-220FPAB | Overvoltage protected AC switch | 10 | 700 | 100 | 125 | 35, 35, 35 | 850 | 12 | 2000 |
| ACST1035-8 | TO-220FPAB | Overvoltage protected AC switch | 10 | 800 | 90 | 150 | 35, 35, 35 | 850 | 5 | 2000 |
| ACST1210-7 | D ² PAK, TO-220AB | Overvoltage protected AC switch | 12 | 700 | 120 | 125 | 10, 10, 10 | 850 | 5.3 | 200 |
| ACST1235-7 | D ² PAK, TO-220AB | Overvoltage protected AC switch | 12 | 700 | 120 | 125 | 35, 35, 35 | 850 | 14 | 2000 |
| ACST1235-8 | TO-220FPAB | Overvoltage protected AC switch | 12 | 800 | 100 | 150 | 35, 35, 35 | 850 | 6 | 2000 |
| ACST1635-8 | TO-220FPAB | Overvoltage protected AC switch | 16 | 800 | 140 | 150 | 35, 35, 35 | 850 | 4 | 300 |

ACS™ OVERVOLTAGE SELF-PROTECTED SWITCHES

| Part number | Package | General description | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM}/V_{RRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_J) | Triggering gate current I_{GT} (I, II, III) | Clamping voltage V_{CL} (@100 μ A) | Rate of decrease of commutating on-state current (di/dt) _c min (@ T_J max) | Rising ratio of off voltage dV/dt (@ T_J max) |
|--------------------|----------------------------------|---|--------------------------------------|--|---|-----------------------------------|--|---|--|--|
| | | | max (A) | max (V) | max (A) | max ($^{\circ}$ C) | max (mA) | min (V) | min (A/ms) | min (V/ μ s) |
| ACS102-6T | SO-8, TO-92 | Overvoltage protected AC switch | 0.2 | 600 | 7.3 | 125 | 5, 5 | 650 | 0.15 | 300 |
| ACS302-6 | SO-20 | Overvoltage protected triple AC switch (ACS™) | 3 x 0.2 | 600 | 7.3 | 125 | 5, 5 | 650 | 0.15 | 300 |
| ACS108-8T | SOT223 | Overvoltage protected AC switch | 0.8 | 800 | 13 | 125 | 5, 5 | 850 | 0.8 | 300 |
| ACS108 | SOT-223, TO-92 | Overvoltage protected AC switch (ACS™) | 0.8 | 800 | 13 | 125 | 10, 10 | 850 | 2 | 400 |
| ACS108-8SUN | SMBFlat-3L | Overvoltage protected AC switch (ACS™) | 0.8 | 800 | 13 | 125 | 10, 10 | 850 | 2 | 400 |
| ACS110 | SOT-223 | Overvoltage protected AC switch | 1 | 700 | 8 | 125 | 10, 10 | 750 | 0.5 | 500 |
| ACS120 | DPAK, TO-220AB, TO-220FPAB | Overvoltage protected AC switch | 2 | 700 | 20 | 125 | 10, 10 | 750 | 1 | 500 |

Thyristors (SCRs)

HIGH-TEMPERATURE THYRISTORS (SCRs)

| Part number | Package | Description | Thyristor, SCR type | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM} / V_{BRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T) | Triggering gate current I_{GT} | Rising ratio of off voltage dV/dt (@ $T_{j,max}$) |
|-----------------------------------|---|---------------------------|----------------------|-----------------------------------|---|--|--------------------------|----------------------------------|--|
| | | | | max (A) | max (V) | max (A) | max (°C) | max (mA) | min (V/μs) |
| TN1205H-6 | D ² PAK, TO 220AB | High-temperature 12A SCRs | High-temperature SCR | 12 | 600 | 120 | 150 | 5 | 100 |
| TN1605H-6 | TO220AB, TO220FPAB, D ² PAK | High-temperature 16A SCRs | High-temperature SCR | 16 | 600 | 140 | 150 | 6 | 200 |
| TN1610H-6 | TO220AB, TO220FPAB | High-temperature 16A SCRs | High-temperature SCR | 16 | 600 | 140 | 150 | 10 | 1000 |
| TN2010H-6 | TO220AB, TO220FPAB, D ² PAK | High-temperature 20A SCRs | High-temperature SCR | 20 | 600 | 180 | 150 | 10 | 400 |
| TN2015H-6 | TO220T, TO220FPAB | High-temperature 20A SCRs | High-temperature SCR | 20 | 600 | 180 | 150 | 15 | 750 |
| TN4015H-6 | D ² PAK, TO220AB Ins, TO220T | High-temperature 40A SCRs | High-temperature SCR | 40 | 600 | 360 | 150 | 15 | 500 |
| TM8050H-8W | TO-247 | High-temperature 80A SCRs | High-temperature SCR | 80 | 800 | 670 | 150 | 50 | 1000 |
| TM8050H-8D3 | D3PAK-2L | High-temperature 80A SCRs | High-temperature SCR | 80 | 800 | 670 | 150 | 50 | 1000 |
| TN3050H-12GY^(*) | D2PAK | High-temperature 30A SCRs | Automotive grade SCR | 30 | 1200 | 300 | 150 | 50 | 1000 |
| TN5050H-12WY | TO247 | High-temperature 50A SCRs | Automotive grade SCR | 50 | 1200 | 580 | 150 | 50 | 1000 |

Note: (*) Under development, ready in Q4/2016

STANDARD AND SENSITIVE THYRISTORS (SCRs)

| Part number | Package | General description | Thyristor, SCR type | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM} / V_{BRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_j) | Triggering gate current I_{GT} | Rising ratio of off voltage dV/dt (@ T_j max) |
|----------------------------|--------------------------------|---------------------|---------------------|-----------------------------------|---|--|--------------------------------|----------------------------------|---|
| | | | | max (A) | max (V) | max (A) | max (°C) | max (mA) | min (V/μs) |
| Standard thyristors | | | | | | | | | |
| TYN606 | TO-220AB | 6 A Standard SCRs | Standard | 6 | 600 | 70 | 125 | 15 | 200 |
| TN805-600B | DPAK | 8 A Standard SCRs | Standard | 8 | 600 | 70 | 125 | 5 | 50 |
| TN815-600B | DPAK | 8 A Standard SCRs | Standard | 8 | 600 | 70 | 125 | 15 | 150 |
| TYN608 | TO-220AB | 8 A Standard SCRs | Standard | 8 | 600 | 95 | 125 | 15 | 150 |
| TN815-800B | DPAK | 8 A Standard SCRs | Standard | 8 | 800 | 70 | 125 | 15 | 150 |
| TYN610 | TO-220AB | 10 A Standard SCRs | Standard | 10 | 600 | 100 | 125 | 15 | 200 |
| TYN810 | TO-220AB | 10 A Standard SCRs | Standard | 10 | 800 | 100 | 125 | 15 | 200 |
| TN1205T-600B | DPAK | 12 A Standard SCRs | Standard | 12 | 600 | 115 | 125 | 5 | 100 |
| TYN612M | TO-220AB, TO-220FPAB | 12 A Standard SCRs | Standard | 12 | 600 | 120 | 125 | 5 | 50 |
| TXN612 | TO-220AB Ins | 12 A Standard SCRs | Standard | 12 | 600 | 120 | 125 | 15 | 200 |
| TYN612 | TO-220AB | 12 A Standard SCRs | Standard | 12 | 600 | 140 | 125 | 15, 5 | 40 |
| TN1215 | D ² PAK, DPAK, IPAK | 12 A Standard SCRs | Standard | 12 | 800 | 140 | 125 | 15 | 200 |
| TYN812 | TO-220AB | 12 A Standard SCRs | Standard | 12 | 800 | 140 | 125 | 15, 5 | 40 |
| TYN1012 | TO-220AB | 12 A Standard SCRs | Standard | 12 | 1000 | 140 | 125 | 15, 5 | 40 |
| TYN1212 | TO-220AB | 12 A Standard SCR | Standard | 12 | 1200 | 120 | 125 | 15 | 200 |
| TN1515-600B | DPAK | 15 A Standard SCRs | Standard | 15 | 600 | 150 | 125 | 15 | 200 |
| TXN616B | TO-220AB Ins | 16 A Standard SCRs | Standard | 16 | 600 | 155 | 125 | 15 | 200 |
| TYN616 | TO-220AB | 16 A Standard SCRs | Standard | 16 | 600 | 190 | 125 | 25 | 500 |
| TYN816 | TO-220AB | 16 A Standard SCRs | Standard | 16 | 600 | 190 | 125 | 25 | 500 |
| TYN816 | TO-220AB | 16 A Standard SCRs | Standard | 16 | 800 | 190 | 125 | 25 | 500 |
| TN1625-1000G | D ² PAK | 16 A Standard SCRs | Standard | 16 | 1000 | 190 | 125 | 25 | 500 |
| TXN625 | TO-220AB Ins | 25 A Standard SCRs | Standard | 25 | 600 | 300 | 125 | 40 | 1000 |

STANDARD AND SENSITIVE THYRISTORS (SCRs)

| Part number | Package | General description | Thyristor, SCR type | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM} / V_{BRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_j) | Triggering gate current I_{GT} | Rising ratio of off voltage dV/dt (@ T_j max) |
|-----------------------------|----------------------------|----------------------------|---------------------|-----------------------------------|---|--|--------------------------------|----------------------------------|---|
| | | | | max (A) | max (V) | max (A) | max (°C) | max (mA) | min (V/ μ s) |
| TYN625 | T0-220AB | 25 A Standard SCRs | Standard | 25 | 600 | 300 | 125 | 40 | 1000 |
| TN2540 | D ² PAK | 25 A Standard SCRs | Standard | 25 | 800 | 300 | 125 | 40 | 1000 |
| TYN825 | T0-220AB | 25 A Standard SCRs | Standard | 25 | 800 | 300 | 125 | 40 | 1000 |
| TYN1225 | T0-220AB | 25 A Standard SCR | Standard | 25 | 1200 | 300 | 125 | 40 | 1000 |
| BTW68-600 | TOP 3 ISOL | 30 A Standard SCRs | Standard | 30 | 600 | 400 | 125 | 50 | 500 |
| BTW68-800 | TOP 3 ISOL | 30 A Standard SCRs | Standard | 30 | 800 | 400 | 125 | 50 | 500 |
| BTW68 | TOP 3 ISOL | 30 A Standard SCRs | Standard | 30 | 1200 | 400 | 125 | 50 | 500 |
| TYN640 | T0-220AB | 40 A Standard SCRs | Standard | 40 | 600 | 460 | 125 | 35 | 1000 |
| TYN840 | T0-220AB | 40 A Standard SCRs | Standard | 40 | 800 | 460 | 125 | 35 | 1000 |
| BTW67-600 | RD-91 | 50 A Standard SCRs | Standard | 50 | 600 | 580 | 125 | 80 | 1000 |
| BTW69-600 | TOP 3 ISOL | 50 A Standard SCRs | Standard | 50 | 600 | 580 | 125 | 80 | 1000 |
| BTW69-800 | TOP 3 ISOL | 50 A Standard SCRs | Standard | 50 | 800 | 580 | 125 | 80 | 1000 |
| BTW67-1000 | RD-91 | 50 A Standard SCRs | Standard | 50 | 1000 | 580 | 125 | 80 | 1000 |
| BTW69-1000 | TOP 3 ISOL | 50 A Standard SCRs | Standard | 50 | 1000 | 580 | 125 | 80 | 1000 |
| BTW69-1200N | TOP 3 | 50 A Standard SCRs | Standard | 50 | 1200 | 700 | 125 | 50 | 1000 |
| Sensitive thyristors | | | | | | | | | |
| XL0840 | T0-92 | 0.8 A Sensitive gate SCRs | Logic level | 0.8 | 400 | 7 | 125 | 0.2 | 75 |
| P011XX | SOT-223, T0-92 | 0.8 A Sensitive gate SCRs | Logic level | 0.8 | 600 | 7 | 125 | 0.05, 0.025 | 75 |
| P010XX | SOT-223, SOT-23, T0-92 | 0.8 A Sensitive gate SCRs | Logic level | 0.8 | 600 | 7 | 125 | 0.001, 0.2 | 100, 200 |
| X006 | T0-92 | 0.8 A Sensitive gate SCRs | Logic level | 0.8 | 600 | 9 | 125 | 0.2 | 25 |
| X00619 | SOT-223, T0-92 | 0.8 A Sensitive gate SCRs | Logic level | 0.8 | 600 | 9 | 125 | 0.2 | 40 |
| X02 | SMBflat-3L, SOT-223, T0-92 | 1.25 A Sensitive gate SCRs | Logic level | 1.25 | 600, 800 | 22.5 | 125 | 0.05, 0.2 | 15, 10 |

STANDARD AND SENSITIVE THYRISTORS (SCRs)

| Part number | Package | General description | Thyristor, SCR type | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM}/V_{BRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_j) | Triggering gate current I_{GT} | Rising ratio of off voltage dV/dt (@ T_j max) |
|--|----------------------------------|---|--|-----------------------------------|---|--|--------------------------------|----------------------------------|---|
| | | | | max (A) | max (V) | max (A) | max (°C) | max (mA) | min (V/ μ s) |
| X04 | TO-202-3 | 4 A Sensitive gate SCRs | Logic level | 4 | 600, 800 | 30 | 125 | 0.05, 0.2 | 15, 10 |
| TS420 | DPAK, IPAK, TO-220AB | 4 A Sensitive gate SCRs | Logic level | 4 | 600 | 30 | 125 | 0.2 | 5 |
| TS820 | DPAK, IPAK, TO-220AB, TO-220FPAB | 8 A Sensitive gate SCRs | Logic level | 8 | 600 | 70 | 125 | 0.2 | 5 |
| TS1220 | DPAK, IPAK, TO-220AB, TO-220FPAB | 12 A Sensitive gate SCRs | Logic level | 12 | 600 | 110 | 125 | 0.2 | 5 |
| High voltage sensitive thyristors | | | | | | | | | |
| TS110-7 | SMBflat-3L, TO-92 | High surge voltage 1.25 A SCR for circuit breaker | Logic level, 1250 V surge voltage for circuit breakers | 1.25 | 700 | 25 | 125 | 0.1 | 15 |
| TS110-8 | SMBflat-3L, TO-92, S08 | High surge voltage 1.25 A SCR for circuit breaker | Logic level, 1250 V surge voltage for circuit breakers | 1.25 | 800 | 20 | 125 | 0.1 | 200 |

Thyristor application-specific discretés (ASD®)

APPLICATION-SPECIFIC IGNITORS

| Part number | Package | General description | RMS on-state current | Repetitive surge peak onstate current | Peak repeat off voltage | Peak repeat reverse voltage | Breakover voltage | Breakover voltage | Junction temperature | Critical rate of rise of on-state current |
|-------------|----------------|--------------------------------|----------------------|---------------------------------------|-------------------------|-----------------------------|-------------------|-------------------|----------------------|---|
| | | | $I_{T(RMS)}$ | I_{TRM} | V_{DRM} | V_{RRM} | V_{BO} | V_{BO} | T_J | of on-state current (di/dt) |
| | | | max (A) | typ (A) | max (V) | max (V) | min (V) | max (V) | max (°C) | max (A/μs) |
| FLC01 | DPAK, IPAK | Fire lighter circuit | - | 190 | 200 | - | 206 | 233 | 125 | 120 |
| FLC10 | DPAK | Fire lighter circuit | - | 240 | 20 | - | 200 | 250 | 125 | 200 |
| FLC21 | T0-92 | Low power fire lighter circuit | - | 90 | 135 | 135 | 140 | 160 | 125 | 50 |
| LIC01 | DPAK, IPAK | Light ignition circuit | 1.2 | 50 | 180 | 180 | 195 | 215 | 125 | 80 |
| P0130 | T0-92 | 0.8 A SCRs | 0.8 | 7 | 100 | 100 | - | - | 125 | 50 |
| TN22 | IPAK, T0-220AB | Starlight | 2 | 20 | 400 | 400 | 1200 | 1500 | 110 | 50 |

HIGH-TEMPERATURE TRIACS T-SERIES

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Gate triggering quadrants | Triggering gate current I _{GT} (I, II, III, IV) | Rate of decrease of commutating on-state current (di/dt) _c (@T _j max) | Rising rate of off voltage dV/dt (@T _j max) |
|--------------------|--------------|--------------------------------------|----------------------|------------------------------------|--|--|---------------------------|--|---|--|
| | | | I _{T(RMS)} | V _{DRM} /V _{RRM} | I _{TSM} | | | (I, II, III, IV) | (di/dt) _c (@T _j max) | dV/dt (@T _j max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | | min (A/ms) | min (V/μs) |
| T435T-600FP | TO-220FPAB | 4-Amp Snubberless™ Triacs | 4 | 600 | 30 | 125 | I, II, III | 35, 35, 35 | 5.3 | 750 |
| T610T-8FP | TO-220FPAB | 6-Amp Triacs - Logic Level gate | 6 | 800 | 45 | 150 | I, II, III | 10, 10, 10 | 3.7 ⁽²⁾ | 170 |
| T610T-8T | TO-220AB | 6-Amp Triacs - Logic Level gate | 6 | 800 | 45 | 150 | I, II, III | 10, 10, 10 | 3.7 ⁽²⁾ | 170 |
| T635T-8FP | TO-220FPAB | 6-Amp Snubberless™ Triac | 6 | 800 | 45 | 150 | I, II, III | 35, 35, 35 | 3 | 1000 ⁽¹⁾ |
| T635T-8T | TO-220AB | 6-Amp Snubberless™ Triac | 6 | 800 | 45 | 150 | I, II, III | 35, 35, 35 | 3 | 1000 ⁽¹⁾ |
| T810T-6I | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 600 | 60 | 125 | I, II, III | 10, 10, 10 | 2.5 ⁽²⁾ | 50 ⁽¹⁾ |
| T810T-8FP | TO-220FPAB | 8-Amp Snubberless™ Triacs | 8 | 800 | 60 | 150 | I, II, III | 10, 10, 10 | 4.2 ⁽²⁾ | 170 |
| T810T-8T | TO-220AB | 8-Amp Snubberless™ Triacs | 8 | 800 | 60 | 150 | I, II, III | 10, 10, 10 | 4.2 ⁽²⁾ | 170 |
| T820T-6I | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 600 | 60 | 125 | I, II, III | 20, 20, 20 | 2 ⁽²⁾ | 500 ⁽¹⁾ |
| T825T-6I | TO-220AB Ins | 8-Amp 4-quadrant Standard Triacs | 8 | 600 | 60 | 125 | I, II, III, IV | 25, 25, 25, 40 | 2 ⁽²⁾ | 300 ⁽¹⁾ |
| T830-8FP | TO-220FPAB | 8-Amp Snubberless™ Triacs | 8 | 800 | 80 | 125 | I, II, III | 30, 30, 30 | 10 | 2500 |
| T835T-6I | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 600 | 60 | 125 | I, II, III | 35, 35, 35 | 6.5 ⁽²⁾ | 1000 ⁽¹⁾ |
| T835T-8FP | TO-220FPAB | 8-Amp Snubberless™ Triac | 8 | 800 | 60 | 150 | I, II, III | 35, 35, 35 | 4 | 1000 ⁽¹⁾ |
| T835T-8T | TO-220AB | 8-Amp Snubberless™ Triac | 8 | 800 | 60 | 150 | I, II, III | 35, 35, 35 | 4 | 1000 ⁽¹⁾ |
| T1210T-6I | TO-220AB Ins | 12-Amp 3-quadrant Logic Level Triacs | 12 | 600 | 90 | 125 | I, II, III | 10, 10, 10 | 3 ⁽²⁾ | 50 ⁽¹⁾ |
| T1220T-6I | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 600 | 90 | 125 | I, II, III | 20, 20, 20 | 3 ⁽¹⁾ | 500 ⁽¹⁾ |
| T1225T-6I | TO-220AB Ins | 12-Amp 4-quadrant Standard Triacs | 12 | 600 | 90 | 125 | I, II, III, IV | 25, 25, 25, 40 | 3 ⁽¹⁾ | 50 ⁽¹⁾ |
| T1235T-6I | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 600 | 90 | 125 | I, II, III | 35, 35, 35 | 10 ⁽¹⁾ | 1000 ⁽¹⁾ |
| T1210T-8FP | TO-220FPAB | 12-Amp 3-quadrant Logic Level Triacs | 12 | 800 | 90 | 150 | I, II, III | 10, 10, 10 | 2.7 | 170 |

HIGH-TEMPERATURE TRIACS T-SERIES

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Gate triggering quadrants | Triggering gate current I _{GT} (I, II, III, IV) | Rate of decrease of commutating on-state current (di/dt) _c (@T _j max) | Rising rate of off voltage dV/dt (@T _j max) |
|-------------------|--------------|--------------------------------------|----------------------|------------------------------------|--|--|---------------------------|--|---|--|
| | | | I _{T(RMS)} | V _{DRM} /V _{RRM} | I _{TSM} | max (°C) | | (I, II, III, IV) | (di/dt) _c (@T _j max) | dV/dt (@T _j max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| T1210T-8T | TO-220AB | 12-Amp 3-quadrant Logic Level Triacs | 12 | 800 | 90 | 150 | I, II, III | 10, 10, 10 | 2.7 | 170 |
| T1235T-8FP | TO-220FPAB | 12-Amp Snubberless™ Triac | 12 | 800 | 100 | 150 | I, II, III | 35, 35, 35 | 6 | 1000 ⁽¹⁾ |
| T1235T-8T | TO-220AB | 12-Amp Snubberless™ Triac | 12 | 800 | 100 | 150 | I, II, III | 35, 35, 35 | 6 | 1000 ⁽¹⁾ |
| T1610T-6I | TO-220AB Ins | 16-Amp 3-quadrant Logic Level Triacs | 16 | 600 | 120 | 125 | I, II, III | 10, 10, 10 | 3 ⁽²⁾ | 20 ⁽¹⁾ |
| T1620T-6I | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 600 | 120 | 125 | I, II, III | 20, 20, 20 | 3 ⁽¹⁾ | 500 ⁽¹⁾ |
| T1635T-6I | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 600 | 120 | 125 | I, II, III | 35, 35, 35 | 12 ⁽¹⁾ | 1000 ⁽¹⁾ |
| T1610T-8I | TO-220AB Ins | 16-Amp 3-quadrant Logic Level Triac | 16 | 800 | 120 | 150 | I, II, III | 10, 10, 10 | 5.4 ⁽²⁾ | 50 |
| T1610T-8FP | TO-220FPAB | 16-Amp 3-quadrant Logic Level Triacs | 16 | 800 | 120 | 150 | I, II, III | 10, 10, 10 | 15 ⁽²⁾ | 170 |
| T1610T-8T | TO-220AB | 16-Amp 3-quadrant Logic Level Triacs | 16 | 800 | 120 | 150 | I, II, III | 10, 10, 10 | 15 ⁽²⁾ | 170 |
| T1620T-8I | TO-220AB Ins | Snubberless™ 16-Amp Triac | 16 | 800 | 120 | 150 | I, II, III | 20, 20, 20 | 4.5 | 500 |
| T1625T-8I | TO-220AB Ins | 16-Amp 4-quadrant Standard Triac | 16 | 800 | 120 | 150 | I, II, III, IV | 25, 25, 25, 50 | 6 ⁽²⁾ | 300 |
| T1635T-8I | TO-220AB Ins | Snubberless™ 16-Amp Triac | 16 | 800 | 120 | 150 | I, II, III | 35, 35, 35 | 12 ⁽²⁾ | 1000 |
| T1635T-8FP | TO-220FPAB | 16-Amp Snubberless™ Triac | 16 | 800 | 120 | 150 | I, II, III | 35, 35, 35 | 8 | 1000 |
| T1635T-8T | TO-220AB | 16-Amp Snubberless™ Triac | 16 | 800 | 120 | 150 | I, II, III | 35, 35, 35 | 8 | 1000 |

Note (1) : parameter at 150 °C ;

Note (2) : parameter at 0.1 V/us and 150 °C

HIGH-TEMPERATURE TRIACS H-SERIES

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Triggering quadrants | Triggering gate current I _{GT} (I, II, III) | Rate of decrease of commutating on-state current (di/dt) _c (@T _j max) | Rising rate of off voltage dV/dt (@T _j max) |
|-------------|--|--|----------------------|-----------------------------------|--|--|----------------------|--|---|--|
| | | | I _{T(RMS)} | | | | | | | |
| T410H | TO 220AB | 4-Amp sensitive Triacs - Logic Level | 4 | 600 | 40 | 150 | I, II, III | 10, 10, 10 | 1.5 ⁽¹⁾ | 75 |
| T610H | TO 220AB | 6-Amp sensitive Triacs - Logic Level | 6 | 600 | 60 | 150 | I, II, III | 10, 10, 10 | 2.3 ⁽¹⁾ | 75 |
| T810H | D ² PAK, TO-220AB | 8-Amp sensitive Triacs - Logic Level | 8 | 600 | 80 | 150 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 75 |
| T835H | D ² PAK, TO-220AB, TO-220AB Ins | 8-Amp Triacs - Snubberless™ | 8 | 600 | 80 | 150 | I, II, III | 35, 35, 35 | 11 | 1000 |
| T850H | D ² PAK, TO-220AB, TO-220AB Ins | 8-Amp Triacs - Snubberless™ | 8 | 600 | 80 | 150 | I, II, III | 50, 50, 50 | 14 | 1500 |
| T1010H | D ² PAK, TO-220AB | 10-Amp sensitive gate Triacs - Logic Level | 10 | 600 | 100 | 150 | I, II, III | 10, 10, 10 | 3.8 ⁽¹⁾ | 75 |
| T1035H | D ² PAK, TO-220AB, TO-220AB Ins | 10-Amp Triacs - Snubberless™ | 10 | 600 | 100 | 150 | I, II, III | 35, 35, 35 | 13 | 1000 |
| T1050H | D ² PAK, TO-220AB, TO-220AB Ins | 10-Amp Triacs - Snubberless™ | 10 | 600 | 100 | 150 | I, II, III | 50, 50, 50 | 18 | 1500 |
| T1235H | D ² PAK, TO-220AB, TO-220AB Ins | 12-Amp Triacs - Snubberless™ | 12 | 600 | 120 | 150 | I, II, III | 10, 10, 10 | 16 | 1000 |
| T1250H | D ² PAK, TO-220AB, TO-220AB Ins | 12-Amp Triacs - Snubberless™ | 12 | 600 | 120 | 150 | I, II, III | 50, 50, 50 | 21 | 1500 |
| T1610H | TO-220AB | 16-Amp Triacs - Logic Level | 16 | 600 | 160 | 150 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 100 |
| T1635H | D ² PAK, TO-220AB, TO-220AB Ins | 16-Amp Triacs - Snubberless™ | 16 | 600 | 160 | 150 | I, II, III | 35, 35, 35 | 21 | 1000 |
| T1650H | D ² PAK, TO-220AB, TO-220AB Ins | 16-Amp Triacs - Snubberless™ | 16 | 600 | 160 | 150 | I, II, III | 50, 50, 50 | 28 | 1500 |
| T2035H | D ² PAK, TO-220AB, TO-220AB Ins | 20-Amp Triacs - Snubberless™ | 20 | 600 | 200 | 150 | I, II, III | 35, 35, 35 | 27 | 1000 |
| T2050H | TO-220AB | 20-Amp Triacs - Snubberless™ | 20 | 600 | 200 | 150 | I, II, III | 50, 50, 50 | 36 | 1500 |
| T3035H | TO-220AB, TO-220AB Ins | 30-Amp Triacs - Snubberless™ | 30 | 600 | 270 | 150 | I, II, III | 35, 35, 35 | 33 | 1000 |
| T3050H | TO-220AB, TO-220AB Ins | 30-Amp Triacs - Snubberless™ | 30 | 600 | 270 | 150 | I, II, III | 50, 50, 50 | 44 | 1500 |

Note (1) Parameter at 10 V/μs

STANDARD AND SNUBBERLESS™ TRIACS, 0.8 A - 1 A

| Part number | Package | General description | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM}/V_{RRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_J) | Triggering quadrants | Triggering gate current I_{GT} (I, II, III, IV) | Rate of rise of turn off voltage $(dV/dt)_c$ min ($@T_J$ max) | Rising ratio of off voltage dV/dt ($@T_J$ max) |
|-------------|----------------------------|----------------------------|-----------------------------------|---|--|--------------------------------|----------------------|---|--|---|
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (V/μs) | min (V/μs) |
| Z00607 | T0-92 | 0.8-Amp Logic Level Triacs | 0.8 | 600 | 9 | 110 | I, II, III, IV | 5, 5, 5, 7 | 0.35 | 10 |
| Z0103M | SMBflat-3L, SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 600 | 8 | 125 | I, II, III, IV | 3, 3, 3, 5 | 0.44 | 10 |
| Z0107M | SMBflat-3L, SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 600 | 8 | 125 | I, II, III, IV | 5, 5, 5, 7 | 0.44 | 20 |
| Z0109M | SMBflat-3L, SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 600 | 8 | 125 | I, II, III, IV | 10, 10, 10, 10 | 0.44 | 50 |
| Z0109M1 | SO-8 | 1-Amp Logic Level Triacs | 1 | 600 | 8 | 125 | I, II, III, IV | 10, 10, 10, 10 | 0.44 | 50 |
| Z0110M | SOT-223, T0-92 | 1-Amp Standard Triacs | 1 | 600 | 8 | 125 | I, II, III, IV | 25, 25, 25, 25 | 0.44 | 100 |
| Z0103N | SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 800 | 8 | 125 | I, II, III, IV | 3, 3, 3, 5 | 0.44 | 10 |
| Z0107N | SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 800 | 8 | 125 | I, II, III, IV | 5, 5, 5, 7 | 0.44 | 20 |
| Z0109N | SOT-223, T0-92 | 1-Amp Logic Level Triacs | 1 | 800 | 8 | 125 | I, II, III, IV | 10, 10, 10, 10 | 0.44 | 50 |
| Z0110N | SOT-223, T0-92 | 1-Amp Standard Triacs | 1 | 800 | 8 | 125 | I, II, III, IV | 25, 25, 25, 25 | 0.44 | 100 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current $I_{T(RMS)}$ | Repetitive peak off-state voltage V_{DRM}/V_{RRM} | Non repetitive surge peak on-state current I_{TSM} | Junction temperature (T_J) | Triggering quadrants | Triggering gate current I_{GT} (I, II, III, IV) | Rate of decrease of commutating on-state current $(di/dt)_c$ ($@T_J$ max) | Rising rate of off voltage dV/dt ($@T_J$ max) |
|--|----------------------|--------------------------|-----------------------------------|---|--|--------------------------------|----------------------|---|--|--|
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| 4 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | |
| Z0402MF | T0-202-3 | 4-Amp Logic Level Triacs | 4 | 600 | 20 | 125 | I, II, III, IV | 3, 3, 3, 3 | 0.5 | 10 |
| Z0405MF | T0-202-3 | 4-Amp Logic Level Triacs | 4 | 600 | 20 | 125 | I, II, III, IV | 5, 5, 5, 5 | 1 | 20 |
| Z0409MF | T0-202-3 | 4-Amp Logic Level Triacs | 4 | 600 | 20 | 125 | I, II, III, IV | 10, 10, 10, 10 | 2 | 100 |
| Z0410MF | T0-202-3 | 4-Amp Standard Triacs | 4 | 600 | 20 | 125 | I, II, III, IV | 25, 25, 25, 25 | 5 | 200 |
| T405-600 | DPAK, IPAK, T0-220AB | 4-Amp Logic Level Triacs | 4 | 600 | 30 | 125 | I, II, III | 5, 5, 5 | 0.9 | 20 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage | | |
|--|----------------------|---------------------------|----------------------|------------------------------------|--|--|----------------------|----------------------------------|--|----------------------------|------------|------------|
| | | | I _{TRMS} | V _{DRM} /V _{RRM} | I _{TSM} | (°C) | | I _{GT} (I, II, III, IV) | (di/dt) _c (@T _j max) | (@T _j max) | | |
| | | | max (A) | max (V) | max (A) | max (°C) | | | | max (mA) | min (A/ms) | min (V/μs) |
| T410-600 | DPAK, IPAK, TO-220AB | 4-Amp Logic Level Triacs | 4 | 600 | 30 | 125 | I, II, III | 10, 10, 10 | 2 | 40 | | |
| T405Q-600 | DPAK, IPAK | 4-Amp Logic Level Triacs | 4 | 600 | 35 | 125 | I, II, III, IV | 5, 5, 5, 10 | 1.8 | 10 | | |
| T435-600 | DPAK, IPAK, TO-220AB | 4-Amp Snubberless™ Triacs | 4 | 600 | 35 | 125 | I, II, III | 35, 35, 35 | 2.5 | 400 | | |
| BTB04-600SL | TO-220AB | 4-Amp Standard Triacs | 4 | 600 | 35 | 125 | I, II, III, IV | 10, 10, 10, 25 | 1.8 | 75 | | |
| Z0402NF | TO-202-3 | 4-Amp Logic Level Triacs | 4 | 800 | 20 | 125 | I, II, III, IV | 3, 3, 3, 3 | 0.5 | 10 | | |
| Z0405NF | TO-202-3 | 4-Amp Logic Level Triacs | 4 | 800 | 20 | 125 | I, II, III, IV | 5, 5, 5, 5 | 1 | 20 | | |
| Z0409NF | TO-202-3 | 4-Amp Logic Level Triacs | 4 | 800 | 20 | 125 | I, II, III, IV | 10, 10, 10, 10 | 2 | 100 | | |
| Z0410NF | TO-202-3 | 4-Amp Standard Triacs | 4 | 800 | 20 | 125 | I, II, III, IV | 25, 25, 25, 25 | 5 | 200 | | |
| T405-800 | DPAK, IPAK | 4-Amp Logic Level Triacs | 4 | 800 | 30 | 125 | I, II, III | 5, 5, 5 | 0.9 | 20 | | |
| T410-800 | DPAK, IPAK, TO-220AB | 4-Amp Logic Level Triacs | 4 | 800 | 30 | 125 | I, II, III | 10, 10, 10 | 2 | 40 | | |
| T435-800 | DPAK, IPAK, TO-220AB | 4-Amp Snubberless™ Triacs | 4 | 800 | 30 | 125 | I, II, III | 35, 35, 35 | 2.5 | 400 | | |
| 6 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | | | |
| BTB06-600TW | TO-220AB | 6-Amp Logic Level Triacs | 6 | 600 | 60 | 125 | I, II, III | 5, 5, 5 | 1.2 ⁽²⁾ | 20 | | |
| BTA06-600TW | TO-220AB Ins | 6-Amp Logic Level Triacs | 6 | 600 | 60 | 125 | I, II, III | 5, 5, 5 | 1.2 ⁽²⁾ | 20 | | |
| BTB06-600SW | TO-220AB | 6-Amp Logic Level Triacs | 6 | 600 | 60 | 125 | I, II, III | 10, 10, 10 | 2.4 ⁽²⁾ | 40 | | |
| BTA06-600SW | TO-220AB Ins | 6-Amp Logic Level Triacs | 6 | 600 | 60 | 125 | I, II, III | 10, 10, 10 | 2.4 ⁽²⁾ | 40 | | |
| BTB06-600C | TO-220AB | 6-Amp Standard Triacs | 6 | 600 | 60 | 125 | I, II, III, IV | 25, 25, 25, 50 | 2.7 ⁽²⁾ | 200 | | |
| BTA06-600C | TO-220AB Ins | 6-Amp Standard Triacs | 6 | 600 | 60 | 125 | I, II, III, IV | 25, 25, 25, 50 | 2.7 ⁽²⁾ | 200 | | |
| BTB06-600CW | TO-220AB | 6-Amp Snubberless™ Triacs | 6 | 600 | 60 | 125 | I, II, III | 35, 35, 35 | 3.5 | 400 | | |
| BTA06T-600CWRG | TO-220AB Ins | 6-Amp Snubberless™ Triacs | 6 | 600 | 45 | 125 | I, II, III | 35, 35, 35 | 8 | 750 | | |
| BTA06-600CW | TO-220AB Ins | 6-Amp Snubberless™ Triacs | 6 | 600 | 60 | 125 | I, II, III | 35, 35, 35 | 3.5 | 400 | | |
| BTB06-600BW | TO-220AB | 6-Amp Snubberless™ Triacs | 6 | 600 | 60 | 125 | I, II, III | 50, 50, 50 | 5.3 | 1000 | | |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage | |
|--|--------------|---------------------------|----------------------|------------------------------------|--|--|----------------------|----------------------------------|--|----------------------------|------------|
| | | | I _{TRMS} | V _{DRM} /V _{RRM} | I _{TSM} | (°C) | | I _{GT} (I, II, III, IV) | (di/dt) _c (@T _j max) | (@T _j max) | |
| | | | max (A) | max (V) | max (A) | max (°C) | | | | min (A/ms) | min (V/μs) |
| BTA06-600BW | TO-220AB Ins | 6-Amp Snubberless™ Triacs | 6 | 600 | 60 | 125 | I, II, III | 50, 50, 50 | 5.3 | 1000 | |
| BTB06-600B | TO-220AB | 6-Amp Standard Triacs | 6 | 600 | 60 | 125 | I, II, III, IV | 50, 50, 50, 100 | 2.7 ⁽²⁾ | 400 | |
| BTA06-600B | TO-220AB Ins | 6-Amp Standard Triacs | 6 | 600 | 60 | 125 | I, II, III, IV | 50, 50, 50, 100 | 2.7 ⁽²⁾ | 400 | |
| BTB06-800TW | TO-220AB | 6-Amp Logic Level Triacs | 6 | 800 | 60 | 125 | I, II, III | 5, 5, 5 | 1.2 ⁽²⁾ | 20 | |
| BTA06-800TW | TO-220AB Ins | 6-Amp Logic Level Triacs | 6 | 800 | 60 | 125 | I, II, III | 5, 5, 5 | 1.2 ⁽²⁾ | 20 | |
| BTB06-800SW | TO-220AB | 6-Amp Logic Level Triacs | 6 | 800 | 60 | 125 | I, II, III | 10, 10, 10 | 2.4 ⁽²⁾ | 40 | |
| BTA06-800SW | TO-220AB Ins | 6-Amp Logic Level Triacs | 6 | 800 | 60 | 125 | I, II, III | 10, 10, 10 | 2.4 ⁽²⁾ | 40 | |
| BTB06-800C | TO-220AB | 6-Amp Standard Triacs | 6 | 800 | 60 | 125 | I, II, III, IV | 25, 25, 25, 50 | 2.7 ⁽¹⁾ | 200 | |
| BTA06-800C | TO-220AB Ins | 6-Amp Standard Triacs | 6 | 800 | 60 | 125 | I, II, III, IV | 25, 25, 25, 50 | 2.7 ⁽¹⁾ | 200 | |
| BTB06-800CW | TO-220AB | 6-Amp Snubberless™ Triacs | 6 | 800 | 60 | 125 | I, II, III | 35, 35, 35 | 3.5 | 400 | |
| BTA06-800CW | TO-220AB Ins | 6-Amp Snubberless™ Triacs | 6 | 800 | 60 | 125 | I, II, III | 35, 35, 35 | 3.5 | 400 | |
| BTB06-800BW | TO-220AB | 6-Amp Snubberless™ Triacs | 6 | 800 | 60 | 125 | I, II, III | 50, 50, 50 | 5.3 | 1000 | |
| BTA06-800BW | TO-220AB Ins | 6-Amp Snubberless™ Triacs | 6 | 800 | 60 | 125 | I, II, III | 50, 50, 50 | 5.3 | 1000 | |
| BTB06-800B | TO-220AB | 6-Amp Standard Triacs | 6 | 800 | 60 | 125 | I, II, III, IV | 50, 50, 50, 100 | 2.7 ⁽²⁾ | 400 | |
| BTA06-800B | TO-220AB Ins | 6-Amp Standard Triacs | 6 | 800 | 60 | 125 | I, II, III, IV | 50, 50, 50, 100 | 2.7 ⁽²⁾ | 400 | |
| 8 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | | |
| BTB08-600TW | TO-220AB | 8-Amp Logic Level Triacs | 8 | 600 | 80 | 125 | I, II, III | 5, 5, 5 | 1.5 ⁽¹⁾ | 20 | |
| BTA08-600TW | TO-220AB Ins | 8-Amp Logic Level Triacs | 8 | 600 | 80 | 125 | I, II, III | 5, 5, 5 | 1.5 ⁽¹⁾ | 20 | |
| BTB08-600SW | TO-220AB | 8-Amp Logic Level Triacs | 8 | 600 | 80 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 | |
| BTA08-600SW | TO-220AB Ins | 8-Amp Logic Level Triacs | 8 | 600 | 80 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 | |
| T810-600 | D2PAK, IPAK | 8-Amp Logic Level Triacs | 8 | 600 | 80 | 125 | I, II, III | 10, 10, 10 | 2.8 | 40 | |
| BTB08-600C | TO-220AB | 8-Amp Standard Triacs | 8 | 600 | 80 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 | |
| BTA08-600C | TO-220AB Ins | 8-Amp Standard Triacs | 8 | 600 | 80 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 | |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|--------------------|--------------|---------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T) | | I_{GT} (I, II, III, IV) | (dI/dt) _c (@T _j max) | (@T _j max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| BTB08-600CW | TO-220AB | 8-Amp Snubberless™ Triacs | 8 | 600 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| BTA08-600CW | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 600 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| T835-600 | D2PAK | 8-Amp Snubberless™ Triacs | 8 | 600 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| BTB08-600BW | TO-220AB | 8-Amp Snubberless™ Triacs | 8 | 600 | 80 | 125 | I, II, III | 50, 50, 50 | 7 | 1000 |
| BTA08-600BW | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 600 | 80 | 125 | I, II, III | 50, 50, 50 | 7 | 1000 |
| BTB08-600B | TO-220AB | 8-Amp Standard Triacs | 8 | 600 | 80 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| BTA08-600B | TO-220AB Ins | 8-Amp Standard Triacs | 8 | 600 | 80 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| BTB08-800TW | TO-220AB | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 5, 5, 5 | 1.5 ⁽¹⁾ | 20 |
| BTA08-800TW | TO-220AB Ins | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 5, 5, 5 | 1.5 ⁽¹⁾ | 20 |
| BTB08-800SW | TO-220AB | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| BTA08-800SW | TO-220AB Ins | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| T810-800B | DPAK | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 10, 10, 10 | 2.8 | 40 |
| BTB08-800C | TO-220AB | 8-Amp Standard Triacs | 8 | 800 | 80 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| BTA08-800C | TO-220AB Ins | 8-Amp Standard Triacs | 8 | 800 | 80 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| BTB08-800CW | TO-220AB | 8-Amp Snubberless™ Triacs | 8 | 800 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| BTA08-800CW | TO-220AB Ins | 8-Amp Snubberless™ Triacs | 8 | 800 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| T835-800B | DPAK | 8-Amp Snubberless™ Triacs | 8 | 800 | 80 | 125 | I, II, III | 35, 35, 35 | 4.5 | 400 |
| BTB08-800BW | TO-220AB | 8-Amp Snubberless™ Triacs | 8 | 800 | 80 | 125 | I, II, III | 50, 50, 50 | 7 | 1000 |
| BTA08-800BW | TO-220AB Ins | 8-Amp Logic Level Triacs | 8 | 800 | 80 | 125 | I, II, III | 50, 50, 50 | 7 | 1000 |
| BTB08-800B | TO-220AB | 8-Amp Standard Triacs | 8 | 800 | 80 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| BTA08-800B | TO-220AB Ins | 8-Amp Standard Triacs | 8 | 800 | 80 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|--|--------------|----------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|-----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T) | | I_{GT} (I, II, III, IV) | (dI/dt) _c (@T _j max) | dV/dt (@T _j max) |
| 10 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | |
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| BTB10-600C | T0-220AB | 10-Amp Standard Triacs | 10 | 600 | 100 | 125 | I, II, III, IV | 25, 25, 25, 50 | 4.4 ⁽²⁾ | 200 |
| BTA10-600C | T0-220AB Ins | 10-Amp Standard Triacs | 10 | 600 | 100 | 125 | I, II, III, IV | 25, 25, 25, 50 | 4.4 ⁽²⁾ | 200 |
| BTB10-600CW | T0-220AB | 10-Amp Snubberless™ Triacs | 10 | 600 | 100 | 125 | I, II, III | 35, 35, 35 | 5.5 | 1000 |
| BTA10-600CW | T0-220AB Ins | 10-Amp Snubberless™ Triacs | 10 | 600 | 100 | 125 | I, II, III | 35, 35, 35 | 5.5 | 1000 |
| BTA10-600BW | T0-220AB Ins | 10-Amp Snubberless™ Triacs | 10 | 600 | 100 | 125 | I, II, III | 50, 50, 50 | 9 | 1000 |
| BTB10-600BW | T0-220AB | 10-Amp Snubberless™ Triacs | 10 | 600 | 100 | 125 | I, II, III | 50, 50, 50 | 9 | 1000 |
| BTB10-600B | T0-220AB | 10-Amp Standard Triacs | 10 | 600 | 100 | 125 | I, II, III, IV | 50, 50, 50, 100 | 4.4 ⁽²⁾ | 400 |
| BTA10-600B | T0-220AB Ins | 10-Amp Standard Triacs | 10 | 600 | 100 | 125 | I, II, III, IV | 50, 50, 50, 100 | 4.4 ⁽²⁾ | 400 |
| BTA10-600GP | T0-220AB Ins | 10-Amp Standard Triacs | 10 | 600 | 120 | 125 | I, II, III, IV | 25, 25, 25, 100 | 2.2 | 30 |
| BTB10-800C | T0-220AB | 10-Amp Standard Triacs | 10 | 800 | 100 | 125 | I, II, III, IV | 25, 25, 25, 50 | 4.4 ⁽²⁾ | 200 |
| BTA10-800C | T0-220AB Ins | 10-Amp Standard Triacs | 10 | 800 | 100 | 125 | I, II, III, IV | 25, 25, 25, 50 | 4.4 ⁽²⁾ | 200 |
| BTB10-800CW | T0-220AB | 10-Amp Snubberless™ Triacs | 10 | 800 | 100 | 125 | I, II, III | 35, 35, 35 | 5.5 | 1000 |
| BTA10-800CW | T0-220AB Ins | 10-Amp Snubberless™ Triacs | 10 | 800 | 100 | 125 | I, II, III | 35, 35, 35 | 5.5 | 1000 |
| BTB10-800BW | T0-220AB | 10-Amp Snubberless™ Triacs | 10 | 800 | 100 | 125 | I, II, III | 50, 50, 50 | 9 | 1000 |
| BTA10-800BW | T0-220AB Ins | 10-Amp Snubberless™ Triacs | 10 | 800 | 100 | 125 | I, II, III | 50, 50, 50 | 9 | 1000 |
| BTB10-800B | T0-220AB | 10-Amp Standard Triacs | 10 | 800 | 100 | 125 | I, II, III, IV | 50, 50, 50, 100 | 4.4 ⁽²⁾ | 400 |
| BTA10-800B | T0-220AB Ins | 10-Amp Standard Triacs | 10 | 800 | 100 | 125 | I, II, III, IV | 50, 50, 50, 100 | 4.4 ⁽²⁾ | 400 |
| 12 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | |
| BTB12-600TW | T0-220AB | 12-Amp Logic Level Triacs | 12 | 600 | 120 | 125 | I, II, III | 5, 5, 5 | 1 ⁽¹⁾ | 20 |
| BTA12-600TW | T0-220AB Ins | 12-Amp Logic Level Triacs | 12 | 600 | 120 | 125 | I, II, III | 5, 5, 5 | 1 ⁽¹⁾ | 20 |
| BTA12-600SW | T0-220AB Ins | 12-Amp Logic Level Triacs | 12 | 600 | 120 | 125 | I, II, III | 10, 10, 10 | 2.9 ⁽¹⁾ | 40 |
| BTB12-600SW | T0-220AB | 12-Amp Logic Level Triacs | 12 | 600 | 120 | 125 | I, II, III | 10, 10, 10 | 2.9 ⁽¹⁾ | 40 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|--------------------|--------------------|----------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T) | | I_{GT} (I, II, III, IV) | (di/dt) _c (@T _j max) | (@T _j max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | | | min (V/μs) |
| BTB12-600C | TO-220AB | 12-Amp Standard Triacs | 12 | 600 | 120 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| BTA12-600C | TO-220AB Ins | 12-Amp Standard Triacs | 12 | 600 | 120 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| T1235-600G | D ² PAK | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| BTB12-600CW | TO-220AB | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| BTA12-600CW | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| T1250-600G | D ² PAK | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 50, 50, 50 | 12 | 1000 |
| BTB12-600BW | TO-220AB | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 50, 50, 50 | 12 | 1000 |
| BTA12-600BW | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 600 | 120 | 125 | I, II, III | 50, 50, 50 | 12 | 1000 |
| BTB12-600B | TO-220AB | 12-Amp Standard Triacs | 12 | 600 | 120 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| BTA12-600B | TO-220AB Ins | 12-Amp Standard Triacs | 12 | 600 | 120 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| BTB12-800TW | TO-220AB | 12-Amp Logic Level Triacs | 12 | 800 | 120 | 125 | I, II, III | 5, 5, 5 | 1 ⁽¹⁾ | 20 |
| BTA12-800TW | TO-220AB Ins | 12-Amp Logic Level Triacs | 12 | 800 | 120 | 125 | I, II, III | 5, 5, 5 | 1 ⁽¹⁾ | 20 |
| T1210-800G | D ² PAK | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 10, 10, 10 | 2.9 | 40 |
| BTB12-800SW | TO-220AB | 12-Amp Logic Level Triacs | 12 | 800 | 120 | 125 | I, II, III | 10, 10, 10 | 2.9 ⁽¹⁾ | 40 |
| BTA12-800SW | TO-220AB Ins | 12-Amp Logic Level Triacs | 12 | 800 | 120 | 125 | I, II, III | 10, 10, 10 | 2.9 ⁽¹⁾ | 40 |
| BTB12-800C | TO-220AB | 12-Amp Standard Triacs | 12 | 800 | 120 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| BTA12-800C | TO-220AB Ins | 12-Amp Standard Triacs | 12 | 800 | 120 | 125 | I, II, III, IV | 25, 25, 25, 50 | 5.3 ⁽²⁾ | 200 |
| BTB12-800CW | TO-220AB | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| BTA12-800CW | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| T1235-800G | D ² PAK | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 35, 35, 35 | 6.5 | 500 |
| BTB12-800BW | TO-220AB | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 50, 50, 50 | 12 | 1000 |
| BTA12-800BW | TO-220AB Ins | 12-Amp Snubberless™ Triacs | 12 | 800 | 120 | 125 | I, II, III | 50, 50, 50 | 12 | 1000 |
| BTB12-800B | TO-220AB | 12-Amp Standard Triacs | 12 | 800 | 120 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|---|--------------------|----------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T) | | I_{GT} (I, II, III, IV) | (dI/dt) _c (@T _J max) | (@T _J max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| BTA12-800B | TO-220AB Ins | 12-Amp Standard Triacs | 12 | 800 | 120 | 125 | I, II, III, IV | 50, 50, 50, 100 | 5.3 ⁽¹⁾ | 400 |
| 16 A Standard, Logic Level and Snubberless™ Triacs | | | | | | | | | | |
| BTB16-600SW | TO-220AB | 16-Amp Logic Level Triacs | 16 | 600 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| BTA16-600SW | TO-220AB Ins | 16-Amp Logic Level Triacs | 16 | 600 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| T1610-600G | D ² PAK | 16-Amp Logic Level Triacs | 16 | 600 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| BTB16-600C | TO-220AB | 16-Amp Standard Triacs | 16 | 600 | 160 | 125 | I, II, III, IV | 25, 25, 25, 50 | 7 ⁽²⁾ | 200 |
| BTA16-600C | TO-220AB Ins | 16-Amp Standard Triacs | 16 | 600 | 160 | 125 | I, II, III, IV | 25, 25, 25, 50 | 7 ⁽²⁾ | 200 |
| BTB16-600CW | TO-220AB | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| BTA16-600CW | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| T1635-600G | D ² PAK | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| T1650-600G | D ² PAK | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 50, 50, 50 | 14 | 1000 |
| BTB16-600BW | TO-220AB | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 50, 50, 50 | 14 | 1000 |
| BTA16-600BW | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 600 | 160 | 125 | I, II, III | 50, 50, 50 | 14 | 1000 |
| BTB16-600B | TO-220AB | 16-Amp Standard Triacs | 16 | 600 | 160 | 125 | I, II, III, IV | 50, 50, 50, 100 | 7 ⁽¹⁾ | 400 |
| BTA16-600B | TO-220AB Ins | 16-Amp Standard Triacs | 16 | 600 | 160 | 125 | I, II, III, IV | 50, 50, 50, 100 | 7 ⁽¹⁾ | 400 |
| T1610-800G | D ² PAK | 16-Amp Logic Level Triacs | 16 | 800 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| BTB16-800SW | TO-220AB | 16-Amp Logic Level Triacs | 16 | 800 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| BTA16-800SW | TO-220AB Ins | 16-Amp Logic Level Triacs | 16 | 800 | 160 | 125 | I, II, III | 10, 10, 10 | 3 ⁽¹⁾ | 40 |
| T1635-800G | D ² PAK | 16-Amp Snubberless™ Triacs | 16 | 800 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| BTB16-800CW | TO-220AB | 16-Amp Snubberless™ Triacs | 16 | 800 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| BTA16-800CW | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 800 | 160 | 125 | I, II, III | 35, 35, 35 | 8.5 | 500 |
| BTB16-800BW | TO-220AB | 16-Amp Snubberless™ Triacs | 16 | 800 | 160 | 125 | I, II, III | 50, 50, 50 | 14 | 1000 |
| BTA16-800BW | TO-220AB Ins | 16-Amp Snubberless™ Triacs | 16 | 800 | 160 | 125 | I, II, III | 50, 50, 50 | 14 | 1000 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|--|--------------|----------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T) | | I_{GT} (I, II, III, IV) | (di/dt) _c (@T _j max) | (@T _j max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | max (mA) | min (A/ms) | min (V/μs) |
| BTB16-800B | T0-220AB | 16-Amp Standard Triacs | 16 | 800 | 160 | 125 | I, II, III, IV | 50, 50, 50, 100 | 7 ⁽¹⁾ | 400 |
| BTA16-800B | T0-220AB Ins | 16-Amp Standard Triacs | 16 | 800 | 160 | 125 | I, II, III, IV | 50, 50, 50, 100 | 7 ⁽¹⁾ | 400 |
| 20 A Snubberless™ Triacs | | | | | | | | | | |
| BTA20-600CWRG | T0-220AB Ins | 20-Amp Snubberless™ Triacs | 20 | 600 | 200 | 125 | I, II, III | 35, 35, 35 | 20 ⁽¹⁾ | 250 |
| BTA20-700CWRG | T0-220AB Ins | 20-Amp Snubberless™ Triacs | 20 | 700 | 200 | 125 | I, II, III | 35, 35, 35 | 20 ⁽¹⁾ | 250 |
| BTA20-700BWRG | T0-220AB Ins | 20-Amp Snubberless™ Triacs | 20 | 700 | 200 | 125 | I, II, III | 50, 50, 50 | 20 | 500 |
| 25 A Standard and Snubberless™ Triacs | | | | | | | | | | |
| BTA25-600CWRG | RD-91 | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTB24-600CWRG | T0-220AB | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTA24-600CWRG | T0-220AB Ins | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTA26-600CWRG | TOP 3 ISOL | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTA24-600BWRG | T0-220AB Ins | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 |
| BTA25-600BWRG | RD-91 | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 |
| BTB24-600BWRG | T0-220AB | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 |
| BTA26-600BWRG | TOP 3 ISOL | 25-Amp Snubberless™ Triacs | 25 | 600 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 |
| BTA25-600BRG | RD-91 | 25-Amp Standard Triacs | 25 | 600 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 |
| BTB24-600BRG | T0-220AB | 25-Amp Standard Triacs | 25 | 600 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 |
| BTB26-600BRG | TOP 3 | 25-Amp Standard Triacs | 25 | 600 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 |
| BTA26-600BRG | TOP 3 ISOL | 25-Amp Standard Triacs | 25 | 600 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 |
| T2535-800G | D2PAK | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTA25-800CWRG | RD-91 | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTB24-800CWRG | T0-220AB | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |
| BTA24-800CWRG | T0-220AB Ins | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 |

STANDARD AND SNUBBERLESS™ TRIACS, 4 A - 40 A

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature (T _j) | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current (di/dt) _c (@T _j max) | Rising rate of off voltage dV/dt (@T _j max) | | |
|-----------------------------|--|----------------------------|----------------------|------------------------------------|--|--|----------------------|----------------------------------|---|--|------------|------------|
| | | | I _{T(RMS)} | V _{DRM} /V _{RRM} | I _{TSM} | (°C) | | I _{GT} (I, II, III, IV) | (di/dt) _c (A/ms) | (V/μs) | | |
| | | | max (A) | max (V) | max (A) | max (°C) | | | | max (mA) | min (A/ms) | min (V/μs) |
| BTA26-800CWRG | TOP 3 ISOL | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 35, 35, 35 | 13 | 500 | | |
| BTA25-800BWRG | RD-91 | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 | | |
| BTB24-800BWRG | T0-220AB | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 | | |
| BTA24-800BWRG | T0-220AB Ins | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 | | |
| BTA26-800BWRG | TOP 3 ISOL | 25-Amp Snubberless™ Triacs | 25 | 800 | 250 | 125 | I, II, III | 50, 50, 50 | 22 | 1000 | | |
| BTA25-800BRG | RD-91 | 25-Amp Standard Triacs | 25 | 800 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 | | |
| BTB24-800BRG | T0-220AB | 25-Amp Standard Triacs | 25 | 800 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 | | |
| BTB26-800BRG | TOP 3 | 25-Amp Standard Triacs | 25 | 800 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 | | |
| BTA26-800BRG | TOP 3 ISOL | 25-Amp Standard Triacs | 25 | 800 | 250 | 125 | I, II, III, IV | 50, 50, 50, 100 | 13 ⁽¹⁾ | 500 | | |
| T2550-12 | T0-220AB, D ² PAK, T0-220AB ins | 25-Amp Snubberless™ Triacs | 25 | 1200 | 240 | 125 | I, II, III | 50, 50, 50 | 20 | 2500 | | |
| 40 A Standard Triacs | | | | | | | | | | | | |
| BTA40 | RD-91 | 40-Amp Standard Triacs | 40 | 800 | 400 | 125 | I, II, III, IV | 50, 50, 50, 100 | 20 ⁽¹⁾ | 500 | | |
| BTB41 | TOP 3 | 40-Amp Standard Triacs | 40 | 800 | 400 | 125 | I, II, III, IV | 50, 50, 50, 100 | 20 ⁽¹⁾ | 500 | | |
| BTA41 | TOP 3 ISOL | 40-Amp Standard Triacs | 40 | 800 | 400 | 125 | I, II, III, IV | 50, 50, 50, 100 | 20 ⁽¹⁾ | 500 | | |

Notes: (1) parameter at 5 V/μs, (2) parameter at 10 V/μs

1200 V TRIACS, SNUBBERLESS™ HIGH VOLTAGE TRIACS

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Triggering gate current | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|-----------------|--|----------------------------|----------------------|-----------------------------------|--|----------------------|----------------------|---------------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T_J) | | I_{GT} (I, II, III, IV) | (di/dt) _c (@ T_J max) | dV/dt (@ T_J max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | | | min (V/ μ s) |
| TXDVxx12 | TO-220AB Ins | 12-Amp high voltage Triacs | 12 | 1200 | 120 | 125 | I, II, III | 100,100,100 | 30 | 200 |
| T2550-12 | TO-220AB, D ² PAK, TO-220AB Ins | 25-Amp high voltage Triacs | 25 | 1200 | 240 | 125 | I, II, III | 50, 50, 50 | 20 | 2500 |
| TPDVxx25 | TOP 3 Ins | 25-Amp high voltage Triacs | 25 | 1200 | 230 | 125 | I, II, III | 150,150,150 | 20 | 500 |
| TPDVxx40 | TOP 3 Ins | 40-Amp high voltage Triacs | 40 | 1200 | 350 | 125 | I, II, III | 200,200,200 | 35 | 500 |

AUTOMATIC VOLTAGE SWITCHES

| Part number | Package | General description | RMS on-state current | Repetitive peak off-state voltage | Non repetitive surge peak on-state current | Junction temperature | Triggering quadrants | Rate of decrease of commutating on-state current | Rising rate of off voltage |
|----------------|----------|---|----------------------|-----------------------------------|--|----------------------|----------------------|--|----------------------------|
| | | | $I_{T(RMS)}$ | V_{DRM}/V_{RRM} | I_{TSM} | (T_J) | | (di/dt) _c (@ T_J max) | dV/dt (@ T_J max) |
| | | | max (A) | max (V) | max (A) | max (°C) | | | min (V/ μ s) |
| AVS08CB | TO-220AB | Automatic voltage switch (SMPS < 200 W) | 8 | 500 | 65 | 125 | I, II, III | 100 | - |
| AVS10CB | TO-220AB | Automatic voltage switch (SMPS < 300 W) | 8 | 600 | 80 | 125 | I, II, III | 100 | 50 |
| AVS12CB | TO-220AB | Automatic voltage switch (SMPS < 500 W) | 12 | 600 | 100 | 125 | I, II, III | 100 | 50 |

TRIGGER DIODES

| Part number | Package | Description | Breakover voltage (V _{BO}) | |
|-------------|----------|-------------|--------------------------------------|---------|
| | | | min (V) | max (V) |
| DB3 | DO-35 | DIAC | 28 | 36 |
| DB3TG | DO-35 | DIAC | 30 | 34 |
| DB4 | DO-35 | DIAC | 35 | 45 |
| SMDB3 | SOT-23 | DIAC | 28 | 36 |
| TMMDB3 | MINIMELF | DIAC | 28 | 36 |
| TMMDB3TG | MINIMELF | DIAC | 30 | 34 |



ST is a global leader in the semiconductor market serving customers across the spectrum of sense and power and automotive products and embedded processing solutions. From energy management and savings to trust and data security, from healthcare and wellness to smart consumer devices, in the home, car and office, at work and at play, ST is found everywhere microelectronics make a positive and innovative contribution to people's life.

By getting more from technology
to get more from life, ST stands for

life.augmented

life.augmented



Order code: SGTHYRACS0416

© STMicroelectronics - April 2016 - Printed in United Kingdom - All rights reserved
The STMicroelectronics corporate logo is a registered trademark
of the STMicroelectronics group of companies
All other names are the property of their respective owners

For more information on ST products and solutions, visit www.st.com









Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View T435-600W](#) on WIN SOURCE

 [STMicroelectronics](#) Information

Optimize Your Supply Chain with WIN SOURCE S

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management