




**THE DATASHEET OF  
AN1102W-TR**





**Pb-free  
HEAT**



# □□1102W

Surface Mount IRED/Inner Lens Type

## Features

Package	3015 type, Water clear epoxy
Product features	<ul style="list-style-type: none"> <li>•Outer Dimension 3.0 x 1.5 x 1.5mm ( L x W x H )</li> <li>•Inner Lenz type</li> <li>•Radiant Intensity               <ul style="list-style-type: none"> <li>DNK : 2.2mW/sr TYP. (I<sub>F</sub>=20mA)</li> <li>TAN : 1.4mW/sr TYP. (I<sub>F</sub>=20mA)</li> <li>AN : 0.8mW/sr TYP. (I<sub>F</sub>=20mA)</li> </ul> </li> <li>•Lead-free soldering compatible</li> <li>•RoHS compliant</li> </ul>
Peak Wavelength	DNK : 865nm TAN : 940nm AN : 950nm
Half Intensity Angle	DNK : $\theta_x = 60 \text{ deg.}, \theta_y = 80 \text{ deg.}$ TAN : $\theta_x = 80 \text{ deg.}, \theta_y = 90 \text{ deg.}$ AN : $\theta_x = 60 \text{ deg.}, \theta_y = 90 \text{ deg.}$
Die materials	GaAlAs (DNK) GaAs (TAN,AN)
Rank grouping parameter	Sorted by radiant intensity per rank taping
Assembly method	Auto pick & place machine (Auto Mounter)
Soldering methods	Reflow soldering ※Please refer to Soldering Conditions about soldering.
Taping and reel	2,500pcs per reel in a 8mm width tape. (Standard) Reel diameter: $\phi 180\text{mm}$
ESD-withstand voltage	2kV (HBM)

## Recommended Applications

Car Audio, Electric Household Appliances, OA/FA, PC/Peripheral Equipment, Other General Applications



**□□1102W**

Surface Mount IRED/Inner Lens Type

## Color and Luminous Intensity

(Ta=25°C)

Part No.	Material	Lens Color	Peak Wavelength $\lambda_p$ (nm)		Radiant Intensity $I_E$ (mW/sr)		
			TYP.	$I_F$ (mA)	MIN.	TYP.	$I_F$ (mA)
DNK1102W	GaAlAs	Water Clear	865	20	1.1	2.2	20
TAN1102W	GaAs		940	20	0.7	1.4	20
AN1102W	GaAs		950	20	0.5	0.8	20

## Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Absolute Maximum Ratings			Unit
		DNK	TAN	AN	
Power Dissipation	$P_d$	80	70	75	mW
Forward Current	$I_F$	50	50	50	mA
Pulse Forward Current ※1	$I_{FRM}$	300	300	300	mA
Derating (Ta=25°C or higher)	$\Delta I_F$	0.67	0.67	0.67	mA/°C
	$\Delta I_{FRM}$	4.00	4.00	4.00	mA/°C
Reverse Voltage	$V_R$	5	5	5	V
Operating Temperature	$T_{opr}$	-30~+85			°C
Storage Temperature	$T_{stg}$	-40~+100			°C

 ※1  $I_{FRM}$  Measurement condition : Pulse Width  $\leq 100 \mu s$ , Duty  $\leq 1/100$ 

## Electro-Optical Characteristics

(Ta=25°C)

Item	Conditions	Symbol	Characteristics			Unit	
			DNK	TAN	AN		
Forward Voltage	$I_F=20mA$	$V_F$	TYP.	1.40	1.20	1.22	V
			MAX.	1.65	1.40	1.40	
Reverse Current	$V_R=5V$	$I_R$	MAX.	100	10	10	$\mu A$
Radiant Intensity	$I_F=20mA$	$I_E$	MIN.	1.1	0.7	0.5	mW/sr
			TYP.	2.2	1.4	0.8	
Total Output Power	$I_F=20mA$	$P_o$	TYP.	8.5	5.7	2	mW
Peak Wavelength	$I_F=20mA$	$\lambda_p$	TYP.	865	940	950	nm
Spectral Half-width	$I_F=20mA$	$\Delta \lambda$	TYP.	45	50	45	nm
Half Intensity Angle	$I_F=20mA$	$2\theta_{1/2}$	TYP.	60( $\theta_x$ )	80( $\theta_x$ )	60( $\theta_x$ )	deg.
				80( $\theta_y$ )	90( $\theta_y$ )	90( $\theta_y$ )	
Cut-off Frequency	$I_F=20mA_{DC} \pm 5mA$ , -3db from 0.1MHz	$f_c$	MIN.	-	-	-	MHz
			TYP.	50	-	0.5	
Response Time	$I_F=20mA$	tr/tf	TYP.	7	1000	700	ns

 ※  $\theta_x$ : Product long side axis,  $\theta_y$ : Product short side axis





## Radiant Intensity Rank

(Ta=25°C)





Rank	I <sub>E</sub> (mW/sr)					
	DNK		TAN		AN	
	I <sub>F</sub> =20mA		I <sub>F</sub> =20mA		I <sub>F</sub> =20mA	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
<b>A</b>	<b>1.1</b>	<b>2.2</b>	<b>0.7</b>	<b>1.4</b>	<b>0.5</b>	<b>1.0</b>
<b>B</b>	<b>1.6</b>	<b>3.2</b>	<b>1.0</b>	<b>2.0</b>	<b>0.7</b>	<b>1.4</b>
<b>C</b>	<b>2.2</b>	<b>4.4</b>	<b>1.4</b>	<b>2.8</b>	<b>1.0</b>	<b>2.0</b>
<b>D</b>	<b>3.2</b>	<b>6.4</b>	<b>2.0</b>	<b>4.0</b>	<b>1.4</b>	<b>2.8</b>
<b>E</b>	<b>4.4</b>	<b>8.8</b>	<b>2.8</b>	<b>5.6</b>	<b>2.0</b>	<b>-</b>

※Please contact our sales staff concerning rank designation.




## Technical Data (DNK)







# Technical Data (DNK)







## Technical Data (DNK)






## Technical Data (TAN)







# Technical Data (TAN)







## Technical Data (TAN)






## Technical Data (AN)



## Technical Data (AN)




## Technical Data (AN)



### Package Dimensions


(Unit: mm)

Weight: (7.80)mg



### Recommended Soldering Pattern


(Unit: mm)




### Taping Specification

(Unit: mm)

Quantity: 2,500pcs/ reel (standard)



## Reflow Soldering Conditions



- 1) The above profile temperature gives the maximum temperature of the LED resin surface. Please set the temperature so as to avoid exceeding this range.
- 2) Total times of reflow soldering process shall be no more than 2 times. When the second reflow soldering process is performed, intervals between the first and second reflow should be short as possible (while allowing some time for the component to return to normal temperature after the first reflow) in order to prevent the LED from absorbing moisture.
- 3) Temperature fluctuation to the LED during the pre-heating process shall be minimized.

## Manual Soldering Conditions

Iron tip temp.	350 °C	(MAX.) (30 W Max.)
Soldering time and frequency	3 s	(MAX.)
	1 time	(MAX.)

## Reliability Testing Result

Reliability Testing Result	Applicable Standard	Testing Conditions	Duration	Failure
Room Temp. Operating Life	EIAJ ED-4701/100(101)	Ta = 25°C, If = Maximum Rated Current	1,000 h	0/25
Resistance to Soldering Heat	EIAJ ED-4701/300(301)	(Pretreatment) Individual standard (Reflow Soldering) Pre-heating 150°C~180°C 120s Operating Heating 230°C Min. Peak temperature 260°C	Twice	0/25
Temperature Cycling	EIAJ ED-4701/100(105)	Minimum Rated Storage Temperature(30min) ~Normal Temperature(15min) ~Maximum Rated Storage Temperature(30min) ~Normal Temperature(15min)	5 cycles	0/25
Wet High Temp. Storage Life	EIAJ ED-4701/100(103)	Ta = 60±2°C, RH = 90±5%	1,000 h	0/25
High Temp. Storage Life	EIAJ ED-4701/200(201)	Ta = Maximum Rated Storage Temperature	1,000 h	0/25
Low Temp. Storage Life	EIAJ ED-4701/200(202)	Ta = Minimum Rated Storage Temperature	1,000 h	0/25
Vibration, Variable Frequency	EIAJ ED-4701/400(403)	98.1m/s <sup>2</sup> (10G), 100 ~ 2KHz sweep for 20min., XYZ each direction	2 h	0/10

## Failure Criteria

Items	Symbols	Conditions	Failure criteria
Radiant Intensity	I <sub>E</sub>	If Value of each product Radiant Intensity	Testing Min. Value < Initial Value x 0.5
Forward Voltage	V <sub>F</sub>	If Value of each product Forward Voltage	Testing Max. Value > Spec. Max. Value x 1.2
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = Maximum Rated Reverse Voltage V	Testing Max. Value ≥ Spec. Max. Value x 2.5

## Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).  
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the wrong operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the "Foreign Exchange and Foreign Trade Control Law," it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:  
<http://www.stanley-components.com>

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View AN1102W-TR on WIN SOURCE](#)
- ⊖ [Stanley Electric Co Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management