



THE DATASHEET OF
FQ1045A-3.6864



10 x 4.5mm SMD Crystal

C8AQ (former FQ1045A) DATASHEET

- Tolerances down to 20 PPM
- Stabilities down to 20 PPM
- Temperature ranges as wide as -40°C to +85°C

• STANDARD SPECIFICATIONS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	3.200 ~ 7.000 MHz
Frequency Tolerance @ 25°C	(See options on page 2)
Frequency Stability, ref @ 25°C Over Operating Temp Range	(See options below)
Temperature Range	
Operating (TOPR)	(See options on page 2)
Storage (TSTG)	-40°C ~ +85°C
Shunt Capacitance (Co)	5 pF
Load Capacitance (CL)	(See options on page 2)
Drive Level	0.5 mW
Aging per year	±5 PPM
Termination Finish	Ag
Seal Method	Resin
Lead (Pb) Free	YES
RoHS / REACH Compliant	YES


Frequency Range	Operating Mode	Max ESR Ω
3.200 ~ 7.000	Fundamental	150

• Available Operating Temperatures and Stabilities*

Stability Temperature	±20 PPM	±25 PPM	±30 PPM	±50 PPM
0 ~+70°C	O	O	O	O
-20 ~+70°C	O	O	O	O
-30 ~+85°C	X	X	O	O
-40 ~+85°C	X	X	X	O

Key: O=Available, X=Not Available, Δ=Consult Fox Technical Support

*Does not imply a stocked part.



	Title / Description: C8AQ STANDARD SPECIFICATIONS	
	Drawing Number: 101169	Size: A
	Part Number:	Cage: 61429
	Draftsperson: BEC	Approved: MAJ
© Copyright 2019 Fox Electronics. All rights reserved		Revision Date: 04/16/2019



10 x 4.5mm SMD Crystal


C8AQ

(former FQ1045A)

DATASHEET

• TAPE SPECIFICATIONS (millimeters)						
A	B	C	D	E	F	STD Reel QTY
Ø1.5	4.0	8.0	11.5	24.0	2.0	-T1 =1,000

• REEL SPECIFICATIONS (millimeters)						
G	H	I	J	K	L	M
2.0	Ø13	Ø21	Ø100	Ø330	24.4	2.0



Available Options & Part Identification for SMD Crystal C8AQ¹

F C8AQ C C M C 3.6864

F	C8AQ	C	C	M	C	3.6464
<u>FOX</u>	<u>Model Number</u>	<u>Tolerance</u> B=50ppm C=30ppm D=25ppm E=20ppm	<u>Stability</u> B=50ppm C=30ppm D=25ppm E=20ppm	<u>Load Capacitance²</u> E=10pF K=16pF L=18pF M=20pF	<u>Operating Temperature</u> C=0 to +70C F=-20 to +70C K=-30 to +85C M=-40 to +85C	<u>Frequency (MHz)</u>

¹ Not all frequency, tolerance, stability, load, and operating temperature combinations may be available.

² Listed load capacitances represent the most commonly used. Other load capacitances are available. Contact Fox Technical Support for assistance



Corporate
Headquarters
5570 Enterprise Parkway
Fort Myers, FL 33905
<http://www.FOXONLINE.com>

Sales
1-888-GET-2-FOX (1-888-438-2369) or
1-239-693-0099
<http://www.FOXONLINE.com/repdisty>

Tech Support
<http://www.FOXONLINE.com/email>

PRODUCT USE: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third-party owners.

For datasheet type definitions and a glossary of common terms, visit <http://www.foxonline.com/tgcrystals.html>.



Title / Description: C8AQ STANDARD SPECIFICATIONS	
Drawing Number: 101169	Size: A
Part Number:	Cage: 61429
Draftsperson: BEC	Approved: MAJ
Revision Date: 04/16/2019	

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View FQ1045A-3.6864 on WIN SOURCE](#)

 [Fox Electronics Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management