



**THE DATASHEET OF  
B1635**



# Botron B1605 Technical Data Sheet



## Overview:

Conductive grid tape is a 2 mil thick copolymer with a charge decay of <.014 seconds. Available on 3" cores in widths of 1/2", 3/4", 1" and 2" (118' in length).

## PROPERTIES

## SPECIFICATIONS

**Material:** Three Layer Copolymer  
**Adhesive:** Acrylic-Based  
**Core:** 3"  
**Thickness:** 1.9 - 2 Mil  
**Length:** 118'  
**Static Generation:** <0-50 volts @50%RH  
**Copolymer layer:** <10<sup>12</sup>  
**Adhesive:** <10<sup>9</sup>  
**Grid layer:** <10<sup>5</sup> @50%RH  
**Size:** 1/2", 3/4", 1" & 2"  
**Tensile Strength:** 270N/mm sq.  
**Elongation:** 160%  
**Colors:** Tan with Black Grid Pattern

## AVAILABLE APPLICATIONS

Botron's anti static grid tape can be used in a variety of forms. Its most common usages are for electromagnetic interference (EMI) shielding and covering pins, connectors and plugs on electronic equipment during storage or transportation.



## PART NUMBERS

B1605 1/2" X 3" Core Conductive grid tape  
B1635 3/4" X 3" Core Conductive grid tape  
B1615 1" X 3" Core Conductive grid tape  
B1620 2" X 3" Core Conductive grid tape

Botron Company Inc. | 325 W. Melinda Ln Phoenix AZ 85027 | Ph# 623-582-6700 | Fax# 623-582-6776

**Disclaimer.** All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user.  
The statements herein shall have no force or effect.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View B1635 on WIN SOURCE](#)
- [Botron Company Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management