THE DATASHEET OF

AOWF11S65

ALPHA & OMEGA SEMICONDUCTOR

AOW11S65/AOWF11S65

650V 11A αMOS™ Power Transistor

General Description

The AOW11S65 & AOWF11S65 have been fabricated using the advanced αMOS™ high voltage process that is designed to deliver high levels of performance and robustness in switching applications.
By providing low $R_{DS(on)}$, Q_g and E_{OSS} along with guaranteed avalanche capability these parts can be adopted quickly into new and existing offline power supply designs.

Product Summary

V_{DS} @ $T_{j,max}$	750V
I_{DM}	45A
$R_{DS(ON),max}$	0.399Ω
$Q_{g,typ}$	13.2nC
E_{oss} @ 400V	2.9µJ

100% UIS Tested
100% R_g Tested

Green Product

TO-262 **TO-262F**



AOW11S65 **AOWF11S65**

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOW11S65	AOWF11S65	Units
Drain-Source Voltage		V_{DS}	650		V
Gate-Source Voltage		V_{GS}	±30		V
Continuous Drain Current	T_C=25°C	I_D	11	11*	A
	T_C=100°C		8	8*	
Pulsed Drain Current [C]		I_{DM}	45		
Avalanche Current [C]		I_{AR}	2		A
Repetitive avalanche energy [C]		E_{AR}	60		mJ
Single pulsed avalanche energy [G]		E_{AS}	120		mJ
Power Dissipation [B]	T_C=25°C	P_D	198	28	W
	Derate above 25°C		1.6	0.22	W/ °C
MOSFET dv/dt ruggedness		dv/dt	100		V/ns
Peak diode recovery dv/dt [H]			20		
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150		°C
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds [J]		T_L	300		°C

Thermal Characteristics

Parameter	Symbol	AOW11S65	AOWF11S65	Units
Maximum Junction-to-Ambient [A,D]	$R_{\theta JA}$	65	65	°C/W
Maximum Case-to-sink [A]	$R_{\theta CS}$	0.5	--	°C/W
Maximum Junction-to-Case	$R_{\theta JC}$	0.63	4.5	°C/W

* Drain current limited by maximum junction temperature.

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V, T_J=25°C	650	-	-	V
		I_D=250µA, V_{GS}=0V, T_J=150°C	700	750	-	
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=650V, V_{GS}=0V	-	-	1	µA
		V_{DS}=520V, T_J=150°C	-	10	-	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±30V	-	-	±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=5V,I_D=250µA	2.6	3.3	4	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=5.5A, T_J=25°C	-	0.35	0.399	Ω
		V_{GS}=10V, I_D=5.5A, T_J=150°C	-	0.98	1.11	Ω
V_{SD}	Diode Forward Voltage	I_S=5.5A,V_{GS}=0V, T_J=25°C	-	0.82	-	V
I_S	Maximum Body-Diode Continuous Current		-	-	11	A
I_{SM}	Maximum Body-Diode Pulsed Current[C]		-	-	45	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=100V, f=1MHz	-	646	-	pF
C_{oss}	Output Capacitance		-	42	-	pF
$C_{o(er)}$	Effective output capacitance, energy related[H]	V_{GS}=0V, V_{DS}=0 to 480V, f=1MHz	-	33	-	pF
$C_{o(tr)}$	Effective output capacitance, time related[I]		-	117	-	pF
C_{rss}	Reverse Transfer Capacitance	V_{GS}=0V, V_{DS}=100V, f=1MHz	-	1.1	-	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	-	18	-	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=10V, V_{DS}=480V, I_D=5.5A	-	13.2	-	nC
Q_{gs}	Gate Source Charge		-	3.2	-	nC
Q_{gd}	Gate Drain Charge		-	4.3	-	nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=400V, I_D=5.5A, R_G=25Ω	-	25	-	ns
t_r	Turn-On Rise Time		-	20	-	ns
$t_{D(off)}$	Turn-Off DelayTime		-	77	-	ns
t_f	Turn-Off Fall Time		-	19	-	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=5.5A,dI/dt=100A/µs,V_{DS}=400V	-	278	-	ns
I_{rm}	Peak Reverse Recovery Current	I_F=5.5A,dI/dt=100A/µs,V_{DS}=400V	-	22	-	A
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=5.5A,dI/dt=100A/µs,V_{DS}=400V	-	4.2	-	µC

A. The value of $R_{\theta JA}$ is measured with the device in a still air environment with T_A=25°C.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C, Ratings are based on low frequency and duty cycles to keep initial T_J =25°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 µs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150°C. The SOA curve provides a single pulse ratin g.

G. L=60mH, I_{AS}=2A, V_{DD}=150V, Starting T_J=25°C

H. $C_{o(er)}$ is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.

I. $C_{o(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.

J. Wavesoldering only allowed at leads.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 1: On-Region Characteristics@25℃



Figure 2: On-Region Characteristics@125℃



Figure 3: Transfer Characteristics



Figure 4: On-Resistance vs. Drain Current and Gate Voltage



Figure 5: On-Resistance vs. Junction Temperature



Figure 6: Break Down vs. Junction Temperature

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Body-Diode Characteristics (Note E)



Figure 8: Gate-Charge Characteristics



Figure 9: Capacitance Characteristics



Figure 10: Coss stored Energy



Figure 11: Maximum Forward Biased Safe Operating Area for AOW11S65 (Note F)



Figure 12: Maximum Forward Biased Safe Operating Area for AOWF11S65(Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 13: Avalanche energy



Figure 14: Current De-rating (Note B)



Figure 15: Normalized Maximum Transient Thermal Impedance for AOW11S65 (Note F)



Figure 16: Normalized Maximum Transient Thermal Impedance for AOWF11S65 (Note F)

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View AOWF11S65 on WIN SOURCE
- Alpha & Omega Semiconductor Inc. Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management