THE DATASHEET OF

TLV2254AIPW

- **Output Swing Includes Both Supply Rails**
- **Low Noise . . . 19 nV/√Hz Typ at f = 1 kHz**
- **Low Input Bias Current . . . 1 pA Typ**
- **Fully Specified for Both Single-Supply and Split-Supply Operation**
- **Very Low Power . . . 34 μA Per Channel Typ**
- **Common-Mode Input Voltage Range Includes Negative Rail**
- **Low Input Offset Voltage 850 μV Max at T_A = 25°C**
- **Wide Supply Voltage Range 2.7 V to 8 V**
- **Macromodel Included**
- **Available in Q-Temp Automotive HighRel Automotive Applications Configuration Control / Print Support Qualification to Automotive Standards**

description

The TLV2252 and TLV2254 are dual and quadruple low-voltage operational amplifiers from Texas Instruments. Both devices exhibit rail-to-rail output performance for increased dynamic range in single- or split-supply applications. The TLV225x family consumes only 34 μA of supply current per channel. This micropower operation makes them good choices for battery-powered applications. This family is fully characterized at 3 V and 5 V and is optimized for low-voltage applications. The noise performance has been dramatically improved over previous generations of CMOS amplifiers. The TLV225x has a noise level of 19 nV/√Hz at 1kHz, four times lower than competitive micropower solutions.



Figure 1

The TLV225x, exhibiting high input impedance and low noise, are excellent for small-signal conditioning for high-impedance sources, such as piezoelectric transducers. Because of the micropower dissipation levels combined with 3-V operation, these devices work well in hand-held monitoring and remote-sensing applications. In addition, the rail-to-rail output feature with single or split supplies makes this family a great choice when interfacing with analog-to-digital converters (ADCs). For precision applications, the TLV225xA family is available and has a maximum input offset voltage of 850 μV.

The TLV2252/4 also make great upgrades to the TLV2322/4 in standard designs. They offer increased output dynamic range, lower noise voltage, and lower input offset voltage. This enhanced feature set allows them to be used in a wider range of applications. For applications that require higher output drive and wider input voltage range, see the TLV2432 and TLV2442 devices. If your design requires single amplifiers, please see the TLV2211/21/31 family. These devices are single rail-to-rail operational amplifiers in the SOT-23 package. Their small size and low power consumption, make them ideal for high density, battery-powered equipment.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Advanced LinCMOS is a trademark of Texas Instruments.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1997−2006, Texas Instruments Incorporated
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

TLV2252 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES					
		SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	TSSOP‡ (PW)	CERAMIC FLATPACK (U)
−40°C to 125°C	850 μV	TLV2252AID	—	—	TLV2252AIP	TLV2252AIPWLE	—
	1500 μV	TLV2252ID	—	—	TLV2252IP	—	—
−40°C to 125°C	850 μV	TLV2252AQD	—	—	—	—	—
	1500 μV	TLV2252QD	—	—	—	—	—
−55°C to 125°C	850 μV	—	TLV2252AMFK	TLV2252AMJG	—	—	TLV2252AMU
	1500 μV	—	TLV2252MFK	TLV2252MJG	—	—	TLV2252MU

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLV2252CDR).
‡ The PW package is available only left-end taped and reeled.
§ Chips are tested at 25°C.

TLV2254 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES					
		SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (J)	PLASTIC DIP (N)	TSSOP‡ (PW)	CERAMIC FLATPACK (W)
−40°C to 125°C	850 μV	TLV2254AID	—	—	TLV2254AIN	TLV2254AIPWLE	—
	1500 μV	TLV2254ID	—	—	TLV2254IN	—	—
−40°C to 125°C	850 μV	TLV2254AQD	—	—	—	—	—
	1500 μV	TLV2254QD	—	—	—	—	—
−55°C to 125°C	850 μV	—	TLV2254AMFK	TLV2254AMJ	—	—	TLV2254AMW
	1500 μV	—	TLV2254MFK	TLV2254MJ	—	—	TLV2254MW

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLV2254CDR).
‡ The PW package is available only left-end taped and reeled.
§ Chips are tested at 25°C.

TLV2252I, TLV2252AI
TLV2252Q, TLV2252AQ
D, P, OR PW PACKAGE
(TOP VIEW)



TLV2252M, TLV2252AM . . . JG PACKAGE
(TOP VIEW)



TLV2252M, TLV2252AM . . . U PACKAGE
(TOP VIEW)



TLV2252M, TLV2252AM . . . FK PACKAGE
(TOP VIEW)



TLV2254I, TLV2254AI, TLV2254Q, TLV2254AQ . . . D OR N PACKAGE
TLV2254M, TLV2254AM . . . J OR W PACKAGE
(TOP VIEW)



TLV2254I, TLV2254AI . . . PW PACKAGE
(TOP VIEW)



TLV2254M, TLV2254AM . . . FK PACKAGE
(TOP VIEW)



equivalent schematic (each amplifier)



ACTUAL DEVICE COMPONENT COUNT†		
COMPONENT	TLV2252	TLV2254
Transistors	38	76
Resistors	30	56
Diodes	9	18
Capacitors	3	6

† Includes both amplifiers and all ESD, bias, and trim circuitry

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{DD} (see Note 1) . . . . . 16 V
Differential input voltage, V_{ID} (see Note 2) . . . . . $\pm V_{DD}$
Input voltage range, V_I (any input, see Note 1) . . . . . V_{DD-} −0.3 V to V_{DD+}
Input current, I_I (each input) . . . . . ±5 mA
Output current, I_O . . . . . ±50 mA
Total current into V_{DD+} . . . . . ±50 mA
Total current out of V_{DD-} . . . . . ±50 mA
Duration of short-circuit current (at or below) 25°C (see Note 3) . . . . . unlimited
Continuous total power dissipation . . . . . See Dissipation Rating Table
Operating free-air temperature range, T_A: I Suffix . . . . . −40°C to 125°C
Q Suffix . . . . . −40°C to 125°C
M Suffix . . . . . −55°C to 125°C
Storage temperature range, T_{stg} . . . . . −65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D, N, P, and PW packages . . . . . 260°C
J, JG, U, and W packages . . . . . 300°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential voltages, are with respect to V_{DD-}.
2. Differential voltages are at the noninverting input with respect to the inverting input. Excessive current flows when input is brought below V_{DD-} − 0.3 V.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 85°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D−8	725 mW	5.8 mW/°C	377 mW	145 mW
D−14	950 mW	7.6 mW/°C	494 mW	190 mW
FK	1375 mW	11.0 mW/°C	715 mW	275 mW
J	1375 mW	11.0 mW/°C	715 mW	275 mW
JG	1050 mW	8.4 mW/°C	546 mW	210 mW
N	1150 mW	9.2 mW/°C	598 mW	230 mW
P	1000 mW	8.0 mW/°C	520 mW	200 mW
PW−8	525 mW	4.2 mW/°C	273 mW	105 mW
PW−14	700 mW	5.6 mW/°C	364 mW	140 mW
U	700 mW	5.5 mW/°C	370 mW	150 mW
W	700 mW	5.5 mW/°C	370 mW	150 mW

recommended operating conditions

	TLV225xI		TLV225xQ		TLV225xM		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
Supply voltage, V_{DD} (see Note 1)	2.7	8	2.7	8	2.7	8	V
Input voltage range, V_I	V_{DD-}	V_{DD+} −1.3	V_{DD-}	V_{DD+} −1.3	V_{DD-}	V_{DD+} −1.3	V
Common-mode input voltage, V_{IC}	V_{DD-}	V_{DD+} −1.3	V_{DD-}	V_{DD+} −1.3	V_{DD-}	V_{DD+} −1.3	V
Operating free-air temperature, T_A	−40	125	−40	125	−55	125	°C

NOTE 1: All voltage values, except differential voltages, are with respect to V_{DD-}.

TLV2252I electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2252I			TLV2252AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±1.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω,	$\lvert V_{IO}\rvert \le$ 5 mV	25°C	0 to 2	−0.3 to 2.2		0 to 2	−0.3 to 2.2		V
				Full range	0 to 1.7			0 to 1.7			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		2.98			2.98		V
		I_{OH} = −75 µA		25°C	2.9			2.9			
				Full range	2.8			2.8			
		I_{OH} = −150 µA		25°C	2.8			2.8			
V_{OL}	Low-level output voltage	V_{IC} = 1.5 V,	I_{OL} = 50 µA	25°C		10			10		mV
				Full range			80			80	
		V_{IC} = 1.5 V,	I_{OL} = 500 µA	25°C		100			100		
				Full range			150			150	
		V_{IC} = 1.5 V,	I_{OL} = 1 mA	25°C		200			200		
				Full range			300			300	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V, V_O = 1 V to 2 V	R_L = 100 kΩ‡	25°C	100	250		100	250		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		800			800		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	P package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		220			220		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V, V_O = 1.5 V,	R_S = 50 Ω	25°C	65	75		65	77		dB
				Full range	60			60			

† Full range is − 40°C to 125°C.
‡ Referenced to 1.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2252I electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2252I			TLV2252AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
k_{SVR}	Supply voltage rejection ratio (ΔV_{DD} /ΔV_{IO})	V_{DD} = 2.7 V to 8 V, V_{IC} = V_{DD}/2, No load	25°C	80	95		80	100		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 1.5 V, No load	25°C		68	125		68	125	μA
			Full range			150			150	

† Full range is − 40°C to 125°C.

TLV2252I operating characteristics at specified free-air temperature, V_{DD} = 3 V

PARAMETER		TEST CONDITIONS	T_A†	TLV2252I			TLV2252AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 1.1 V to 1.9 V, R_L = 100 kΩ‡, C_L = 100 pF‡	25°C	0.07	0.1		0.07	0.1		V/μs
			Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		35			35		nV/√Hz
		f = 1 kHz	25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		0.6			0.6		μV
		f = 0.1 Hz to 10 Hz	25°C		1.1			1.1		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 1 kHz, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		0.187			0.187		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 1 V, A_V = 1, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		60			60		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		63°			63°		
	Gain margin		25°C		15			15		dB

† Full range is −40°C to 125°C.
‡ Referenced to 1.5 V

TLV2252I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2252I			TLV2252AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±2.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
V_{ICR}	Common-mode input voltage range	$\|V_{IO}\|$ ≤5 mV,	R_S = 50 Ω	25°C	0 to 4	−0.3 to 4.2		0 to 4	−0.3 to 4.2		V
				Full range	0 to 3.5			0 to 3.5			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		4.98			4.98		V
		I_{OH} = −75 µA		25°C	4.9	4.94		4.9	4.94		
				Full range	4.8			4.8			
		I_{OH} = −150 µA		25°C	4.8	4.88		4.8	4.88		
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA	25°C		0.01			0.01		V
				Full range			0.06			0.06	
		V_{IC} = 2.5 V,	I_{OL} = 500 µA	25°C		0.09	0.15		0.09	0.15	
				Full range			0.15			0.15	
		V_{IC} = 2.5 V,	I_{OL} = 1 mA	25°C		0.2	0.3		0.2	0.3	
				Full range			0.3			0.3	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, V_O = 1 V to 4 V	R_L = 100 kΩ‡	25°C	100	350		100	350		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		1700			1700		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	P package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V, R_S = 50 Ω	V_O = 2.5 V,	25°C	70	83		70	83		dB
				Full range	70			70			

† Full range is − 40°C to 125°C.
‡ Referenced to 2.5 V

NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2252I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2252I			TLV2252AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V, $V_{IC} = V_{DD}/2$, No load	25°C	80	95		80	95		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		70	125		70	125	μA
			Full range			150			150	

† Full range is − 40°C to 125°C.

TLV2252I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS		T_A†	TLV2252I			TLV2252AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 1.5 V to 3.5 V, C_L = 100 pF‡	R_L = 100 kΩ‡,	25°C	0.07	0.12		0.07	0.12		V/μs
				Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz		25°C		36			36		nV/√Hz
		f = 1 kHz		25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz		25°C		0.7			0.7		μV
		f = 0.1 Hz to 10 Hz		25°C		1.1			1.1		
I_n	Equivalent input noise current			25°C		0.6			0.6		fA/√Hz
THD + N	Total harmonic distortion plus noise	V_O = 0.5 V to 2.5 V, f = 20 kHz, R_L = 50 kΩ‡	A_V = 1	25°C		0.2%			0.2%		
			A_V = 10			1%			1%		
	Gain-bandwidth product	f = 50 kHz, C_L = 100 pF‡	R_L = 50 kΩ‡,	25°C		0.2			0.2		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 50 kΩ‡,	A_V = 1, C_L = 100 pF‡	25°C		30			30		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡,	C_L = 100 pF‡	25°C		63°			63°		
	Gain margin			25°C		15			15		dB

† Full range is − 40°C to 125°C.
‡ Referenced to 2.5 V

TLV2254I electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2254I			TLV2254AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±1.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω,	$\lvert V_{IO}\rvert \le$ 5 mV	25°C	0 to 2	−0.3 to 2.2		0 to 2	−0.3 to 2.2		V
				Full range	0 to 1.7			0 to 1.7			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		2.98			2.98		V
		I_{OH} = −75 µA		25°C	2.9			2.9			
				Full range	2.8			2.8			
		I_{OH} = −150 µA		25°C	2.8			2.8			
V_{OL}	Low-level output voltage	V_{IC} = 1.5 V,	I_{OL} = 50 µA	25°C		10			10		mV
				Full range			80			80	
		V_{IC} = 1.5 V,	I_{OL} = 500 µA	25°C		100			100		
				Full range			150			150	
		V_{IC} = 1.5 V,	I_{OL} = 1 mA	25°C		200			200		
				Full range			300			300	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V, V_O = 1 V to 2 V	R_L = 100 kΩ‡	25°C	100	225		100	225		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		800			800		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	N package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		220			220		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V, R_S = 50 Ω	V_O = 1.5 V,	25°C	65	75		65	77		dB
				Full range	60			60			

† Full range is − 40°C to 125°C.
‡ Referenced to 1.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2254I electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2254I			TLV2254AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 2.7 V to 8 V, $V_{IC} = V_{DD}/2$, No load	25°C	80	95		80	100		dB
			Full range	80			80			
I_{DD}	Supply current (four amplifiers)	V_O = 1.5 V, No load	25°C		135	250		135	250	μA
			Full range			300			300	

† Full range is − 40°C to 125°C.

TLV2254I operating characteristics at specified free-air temperature, V_{DD} = 3 V

PARAMETER		TEST CONDITIONS	T_A†	TLV2254I			TLV2254AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.7 V to 1.7 V, R_L = 100 kΩ‡, C_L = 100 pF‡	25°C	0.07	0.1		0.07	0.1		V/μs
			Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		35			35		nV/√Hz
		f = 1 kHz	25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		0.6			0.6		μV
		f = 0.1 Hz to 10 Hz	25°C		1.1			1.1		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 1 kHz, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		0.187			0.187		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 1 V, A_V = 1, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		60			60		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		63°			63°		
	Gain margin		25°C		15			15		dB

† Full range is − 40°C to 85°C.
‡ Referenced to 1.5 V

TLV2254I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2254I			TLV2254AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±2.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				−40°C to 85°C			150			150	
				Full range			1000			1000	
V_{ICR}	Common-mode input voltage range	$\|V_{IO}\|$ ≤5 mV,	R_S = 50 Ω	25°C	0 to 4	−0.3 to 4.2		0 to 4	−0.3 to 4.2		V
				Full range	0 to 3.5			0 to 3.5			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		4.98			4.98		V
		I_{OH} = −75 µA		25°C	4.9	4.94		4.9	4.94		
				Full range	4.8			4.8			
		I_{OH} = −150 µA		25°C	4.8	4.88		4.8	4.88		
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA	25°C		0.01			0.01		V
				Full range			0.06			0.06	
		V_{IC} = 2.5 V,	I_{OL} = 500 µA	25°C		0.09	0.15		0.09	0.15	
				Full range			0.15			0.15	
		V_{IC} = 2.5 V,	I_{OL} = 1 mA	25°C		0.2	0.3		0.2	0.3	
				Full range			0.3			0.3	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, V_O = 1 V to 4 V	R_L = 100 kΩ‡	25°C	100	350		100	350		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		1700			1700		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	N package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V, R_S = 50 Ω	V_O = 2.5 V,	25°C	70	83		70	83		dB
				Full range	70			70			

† Full range is − 40°C to 125°C.
‡ Referenced to 2.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2254I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2254I			TLV2254AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V, V_{IC} = V_{DD}/2, No load	25°C	80	95		80	95		dB
			Full range	80			80			
I_{DD}	Supply current (four amplifiers)	V_O = 2.5 V, No load	25°C		140	250		140	250	μA
			Full range			300			300	

† Full range is − 40°C to 125°C.

TLV2254I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS		T_A†	TLV2254I			TLV2254AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 1.4 V to 2.6 V, C_L = 100 pF‡	R_L = 100 kΩ‡,	25°C	0.07	0.12		0.07	0.12		V/μs
				Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz		25°C		36			36		nV/√Hz
		f = 1 kHz		25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz		25°C		0.7			0.7		μV
		f = 0.1 Hz to 10 Hz		25°C		1.1			1.1		
I_n	Equivalent input noise current			25°C		0.6			0.6		fA/√Hz
THD + N	Total harmonic distortion plus noise	V_O = 0.5 V to 2.5 V, f = 20 kHz, R_L = 50 kΩ‡	A_V = 1	25°C		0.2%			0.2%		
			A_V = 10			1%			1%		
	Gain-bandwidth product	f = 50 kHz, C_L = 100 pF‡	R_L = 50 kΩ‡,	25°C		0.2			0.2		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 50 kΩ‡,	A_V = 1, C_L = 100 pF‡	25°C		30			30		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡,	C_L = 100 pF‡	25°C		63°			63°		
	Gain margin			25°C		15			15		dB

† Full range is − 40°C to 125°C.
‡ Referenced to 2.5 V

TLV2252Q, and TLV2252M electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2252Q, TLV2252M			TLV2252AQ, TLV2252AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±1.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				125°C			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				125°C			1000			1000	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω,	|V_{IO}| ≤5 mV	25°C	0 to 2	−0.3 to 2.2		0 to 2	−0.3 to 2.2		V
				Full range	0 to 1.7			0 to 1.7			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		2.98			2.98		V
		I_{OH} = −75 µA		25°C	2.9			2.9			
				Full range	2.8			2.8			
		I_{OH} = −150 µA		25°C	2.8			2.8			
V_{OL}	Low-level output voltage	V_{IC} = 1.5 V,	I_{OL} = 50 µA	25°C		10			10		mV
		V_{IC} = 1.5 V,	I_{OL} = 500 µA	25°C		100	150		100	150	
				Full range			165			165	
		V_{IC} = 1.5 V,	I_{OL} = 1 mA	25°C		200	300		200	300	
				Full range			300			300	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V, V_O = 1 V to 2 V	R_L = 100 kΩ‡	25°C	100	250		100	250		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		800			800		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	P package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		220			220		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V, R_S = 50 Ω	V_O = 1.5 V,	25°C	65	75		65	77		dB
				Full range	60			60			
k_{SVR}	Supply voltage rejection ratio (ΔV_{DD} /ΔV_{IO})	V_{DD} = 2.7 V to 8 V, V_{IC} = V_{DD}/2,	No load	25°C	80	95		80	100		dB
				Full range	80			80			
I_{DD}	Supply current	V_O = 1.5 V,	No load	25°C		68	125		68	125	µA
				Full range			150			150	

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 1.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2252Q, and TLV2252M operating characteristics at specified free-air temperature, V_{DD} = 3 V

PARAMETER		TEST CONDITIONS	T_A†	TLV2252Q, TLV2252M			TLV2252AQ, TLV2252AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.8 V to 1.4 V, R_L = 100 kΩ‡, C_L = 100 pF‡	25°C	0.07	0.1		0.07	0.1		V/μs
			Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		35			35		nV/√Hz
		f = 1 kHz	25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		0.6			0.6		μV
		f = 0.1 Hz to 10 Hz	25°C		1.1			1.1		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 1 kHz, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		0.187			0.187		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 1 V, A_V = 1, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		60			60		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		63°			63°		
	Gain margin		25°C		15			15		dB

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 1.5 V

TLV2252Q, and TLV2252M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2252Q, TLV2252M			TLV2252AQ, TLV2252AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±2.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 85°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				125°C			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				125°C			1000			1000	
V_{ICR}	Common-mode input voltage range	|V_{IO}| ≤5 mV,	R_S = 50 Ω	25°C	0 to 4	−0.3 to 4.2		0 to 4	−0.3 to 4.2		V
				Full range	0 to 3.5			0 to 3.5			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		4.98			4.98		V
		I_{OH} = −75 µA		25°C	4.9	4.94		4.9	4.94		
				Full range	4.8			4.8			
		I_{OH} = −150 µA		25°C	4.8	4.88		4.8	4.88		
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA	25°C		0.01			0.01		V
		V_{IC} = 2.5 V,	I_{OL} = 500 µA	25°C		0.09	0.15		0.09	0.15	
				Full range			0.15			0.15	
		V_{IC} = 2.5 V,	I_{OL} = 1 mA	25°C		0.2	0.3		0.2	0.3	
				Full range			0.3			0.3	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, V_O = 1 V to 4 V	R_L = 100 kΩ‡	25°C	100	350		100	350		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		1700			1700		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	P package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V, V_O = 2.5 V,	R_S = 50 Ω	25°C	70	83		70	83		dB
				Full range	70			70			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V, V_{IC} = V_{DD}/2,	No load	25°C	80	95		80	95		dB
				Full range	80			80			

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 2.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2252Q, and TLV2252M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2252Q, TLV2252M			TLV2252AQ, TLV2252AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		70	125		70	125	µA
			Full range			150			150	

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.

TLV2252Q, and TLV2252M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS		T_A†	TLV2252Q, TLV2252M			TLV2252AQ, TLV2252AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 1.25 V to 2.75 V, R_L = 100 kΩ‡, C_L = 100 pF‡		25°C	0.07	0.12		0.07	0.12		V/µs
				Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz		25°C		36			36		nV/√Hz
		f = 1 kHz		25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz		25°C		0.7			0.7		µV
		f = 0.1 Hz to 10 Hz		25°C		1.1			1.1		
I_n	Equivalent input noise current			25°C		0.6			0.6		fA/√Hz
THD + N	Total harmonic distortion plus noise	V_O = 0.5 V to 2.5 V, f = 20 kHz, R_L = 50 kΩ‡	A_V = 1	25°C		0.2%			0.2%		
			A_V = 10			1%			1%		
	Gain-bandwidth product	f = 50 kHz, C_L = 100 pF‡	R_L = 50 kΩ‡,	25°C		0.2			0.2		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 50 kΩ‡,	A_V = 1, C_L = 100 pF‡	25°C		30			30		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡,	C_L = 100 pF‡	25°C		63°			63°		
	Gain margin			25°C		15			15		dB

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 2.5 V

TLV2254Q, and TLV2254M electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±1.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	μV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 125°C		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		μV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				125°C			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				125°C			1000			1000	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω,	$\lvert V_{IO}\rvert \le$ 5 mV	25°C	0 to 2	−0.3 to 2.2		0 to 2	−0.3 to 2.2		V
				Full range	0 to 1.7			0 to 1.7			
V_{OH}	High-level output voltage	I_{OH} = −20 μA		25°C		2.98			2.98		V
		I_{OH} = −75 μA		25°C	2.9			2.9			
				Full range	2.8			2.8			
		I_{OH} = −150 μA		25°C	2.8			2.8			
V_{OL}	Low-level output voltage	V_{IC} = 1.5 V,	I_{OL} = 50 μA	25°C		10			10		mV
		V_{IC} = 1.5 V,	I_{OL} = 500 μA	25°C		100	150		100	150	
				Full range			165			165	
		V_{IC} = 1.5 V,	I_{OL} = 1 mA	25°C		200	300		200	300	
				Full range			300			300	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V, V_O = 1 V to 2 V	R_L = 100 kΩ‡	25°C	100	225		100	225		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		800			800		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	N package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		220			220		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V, R_S = 50 Ω	V_O = 1.5 V,	25°C	65	75		65	77		dB
				Full range	60			60			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 2.7 V to 8 V, V_{IC} = V_{DD}/2,	No load	25°C	80	95		80	100		dB
				Full range	80			80			

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 1.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2254Q, and TLV2254M electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
I_{DD}	Supply current (four amplifiers)	V_O = 1.5 V, No load	25°C		135	250		135	250	μA
			Full range			300			300	

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.

TLV2254Q, and TLV2254M operating characteristics at specified free-air temperature, V_{DD} = 3 V

PARAMETER		TEST CONDITIONS	T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 1.7 V, R_L = 100 kΩ‡, C_L = 100 pF‡	25°C	0.07	0.1		0.07	0.1		V/μs
			Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		35			35		nV/√Hz
		f = 1 kHz	25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		0.6			0.6		μV
		f = 0.1 Hz to 10 Hz	25°C		1.1			1.1		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 1 kHz, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		0.187			0.187		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 1 V, A_V = 1, R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		60			60		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡, C_L = 100 pF‡	25°C		63°			63°		
	Gain margin		25°C		15			15		dB

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 1.5 V

TLV2254Q, and TLV2254M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±2.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	25°C		200	1500		200	850	µV
				Full range			1750			1000	
α_{VIO}	Temperature coefficient of input offset voltage			25°C to 125°C		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				125°C			1000			1000	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				125°C			1000			1000	
V_{ICR}	Common-mode input voltage range	$|V_{IO}| \le$5 mV,	R_S = 50 Ω	25°C	0 to 4	−0.3 to 4.2		0 to 4	−0.3 to 4.2		V
				Full range	0 to 3.5			0 to 3.5			
V_{OH}	High-level output voltage	I_{OH} = −20 µA		25°C		4.98			4.98		V
		I_{OH} = −75 µA		25°C	4.9	4.94		4.9	4.94		
				Full range	4.8			4.8			
		I_{OH} = −150 µA		25°C	4.8	4.88		4.8	4.88		
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA	25°C		0.01			0.01		V
		V_{IC} = 2.5 V,	I_{OL} = 500 µA	25°C		0.09	0.15		0.09	0.15	
				Full range			0.15			0.15	
		V_{IC} = 2.5 V,	I_{OL} = 1 mA	25°C		0.2	0.3		0.2	0.3	
				Full range			0.3			0.3	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, V_O = 1 V to 4 V	R_L = 100 kΩ‡	25°C	100	350		100	350		V/mV
				Full range	10			10			
			R_L = 1 MΩ‡	25°C		1700			1700		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,	N package	25°C		8			8		pF
z_o	Closed-loop output impedance	f = 25 kHz,	A_V = 10	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V, R_S = 50 Ω	V_O = 2.5 V,	25°C	70	83		70	83		dB
				Full range	70			70			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V, V_{IC} = V_{DD}/2,	No load	25°C	80	95		80	95		dB
				Full range	80			80			

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 2.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLV2254Q, and TLV2254M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted) (continued)

PARAMETER		TEST CONDITIONS	T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
I_{DD}	Supply current (four amplifiers)	V_O = 2.5 V, No load	25°C		140	250		140	250	μA
			Full range			300			300	

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.

TLV2254Q, and TLV2254M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS		T_A†	TLV2254Q, TLV2254M			TLV2254AQ, TLV2254AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 3.5 V, C_L = 100 pF‡	R_L = 100 kΩ‡,	25°C	0.07	0.12		0.07	0.12		V/μs
				Full range	0.05			0.05			
V_n	Equivalent input noise voltage	f = 10 Hz		25°C		36			36		nV/√Hz
		f = 1 kHz		25°C		19			19		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz		25°C		0.7			0.7		μV
		f = 0.1 Hz to 10 Hz		25°C		1.1			1.1		
I_n	Equivalent input noise current			25°C		0.6			0.6		fA/√Hz
THD + N	Total harmonic distortion plus noise	V_O = 0.5 V to 2.5 V, f = 20 kHz, R_L = 50 kΩ‡	A_V = 1	25°C		0.2%			0.2%		
			A_V = 10			1%			1%		
	Gain-bandwidth product	f = 50 kHz, C_L = 100 pF‡	R_L = 50 kΩ‡,	25°C		0.2			0.2		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 50 kΩ‡,	A_V = 1, C_L = 100 pF‡	25°C		30			30		kHz
ϕ_m	Phase margin at unity gain	R_L = 50 kΩ‡,	C_L = 100 pF‡	25°C		63°			63°		
	Gain margin			25°C		15			15		dB

† Full range is −40°C to 125°C for Q level part, −55°C to 125°C for M level part.
‡ Referenced to 2.5 V

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
V_{IO}	Input offset voltage	Distribution vs Common-mode voltage	2 − 5 6, 7
α_{VIO}	Input offset voltage temperature coefficient	Distribution	8 − 11
I_{IB}/I_{IO}	Input bias and input offset currents	vs Free-air temperature	12
V_I	Input voltage	vs Supply voltage vs Free-air temperature	13 14
V_{OH}	High-level output voltage	vs High-level output current	15, 18
V_{OL}	Low-level output voltage	vs Low-level output current	16, 17, 19
$V_{O(PP)}$	Maximum peak-to-peak output voltage	vs Frequency	20
I_{OS}	Short-circuit output current	vs Supply voltage vs Free-air temperature	21 22
V_{ID}	Differential input voltage	vs Output voltage	23, 24
A_{VD}	Differential voltage amplification	vs Load resistance	25
A_{VD}	Large-signal differential voltage amplification	vs Frequency vs Free-air temperature	26, 27 28, 29
z_o	Output impedance	vs Frequency	30, 31
CMRR	Common-mode rejection ratio	vs Frequency vs Free-air temperature	32 33
k_{SVR}	Supply-voltage rejection ratio	vs Frequency vs Free-air temperature	34, 35 36
I_{DD}	Supply current	vs Supply voltage	37, 38
SR	Slew rate	vs Load capacitance vs Free-air temperature	39 40
V_O	Inverting large-signal pulse response		41, 42
V_O	Voltage-follower large-signal pulse response		43, 44
V_O	Inverting small-signal pulse response		45, 46
V_O	Voltage-follower small-signal pulse response		47, 48
V_n	Equivalent input noise voltage	vs Frequency	49, 50
	Input noise voltage	Over a 10-second period	51
	Integrated noise voltage	vs Frequency	52
THD + N	Total harmonic distortion plus noise	vs Frequency	53
	Gain-bandwidth product	vs Supply voltage vs Free-air temperature	54 55
ϕ_m	Phase margin	vs Frequency vs Load capacitance	26, 27 56
	Gain margin	vs Load capacitance	57
B_1	Unity-gain bandwidth	vs Load capacitance	58
	Overestimation of phase margin	vs Load capacitance	59

TYPICAL CHARACTERISTICS

**DISTRIBUTION OF TLV2252
INPUT OFFSET VOLTAGE**



Figure 2

**DISTRIBUTION OF TLV2252
INPUT OFFSET VOLTAGE**



Figure 3

**DISTRIBUTION OF TLV2254
INPUT OFFSET VOLTAGE**



Figure 4

**DISTRIBUTION OF TLV2254
INPUT OFFSET VOLTAGE**



Figure 5

TYPICAL CHARACTERISTICS

INPUT OFFSET VOLTAGE† vs COMMON-MODE INPUT VOLTAGE



Figure 6

INPUT OFFSET VOLTAGE† vs COMMON-MODE INPUT VOLTAGE



Figure 7

DISTRIBUTION OF TLV2252 INPUT OFFSET VOLTAGE TEMPERATURE COEFFICIENT†



Figure 8

DISTRIBUTION OF TLV2252 INPUT OFFSET VOLTAGE TEMPERATURE COEFFICIENT†



Figure 9

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

DISTRIBUTION OF TLV2254 INPUT OFFSET VOLTAGE TEMPERATURE COEFFICIENT



Figure 10

DISTRIBUTION OF TLV2254 INPUT OFFSET VOLTAGE TEMPERATURE COEFFICIENT



Figure 11

INPUT BIAS AND INPUT OFFSET CURRENTS† vs FREE-AIR TEMPERATURE



Figure 12

INPUT VOLTAGE vs SUPPLY VOLTAGE



Figure 13

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

INPUT VOLTAGE†‡ vs FREE-AIR TEMPERATURE



Figure 14

HIGH-LEVEL OUTPUT VOLTAGE†‡ vs HIGH-LEVEL OUTPUT CURRENT



Figure 15

LOW-LEVEL OUTPUT VOLTAGE‡ vs LOW-LEVEL OUTPUT CURRENT



Figure 16

LOW-LEVEL OUTPUT VOLTAGE†‡ vs LOW-LEVEL OUTPUT CURRENT



Figure 17

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

HIGH-LEVEL OUTPUT VOLTAGE†‡ vs HIGH-LEVEL OUTPUT CURRENT



Figure 18

LOW-LEVEL OUTPUT VOLTAGE†‡ vs LOW-LEVEL OUTPUT CURRENT



Figure 19

MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE‡ vs FREQUENCY



Figure 20

SHORT-CIRCUIT OUTPUT CURRENT vs SUPPLY VOLTAGE



Figure 21

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

SHORT-CIRCUIT OUTPUT CURRENT† vs FREE-AIR TEMPERATURE



Figure 22

DIFFERENTIAL INPUT VOLTAGE‡ vs OUTPUT VOLTAGE



Figure 23

DIFFERENTIAL INPUT VOLTAGE‡ vs OUTPUT VOLTAGE



Figure 24

DIFFERENTIAL VOLTAGE AMPLIFICATION†‡ vs LOAD RESISTANCE



Figure 25

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL VOLTAGE† AMPLIFICATION AND PHASE MARGIN vs FREQUENCY



Figure 26

LARGE-SIGNAL DIFFERENTIAL VOLTAGE† AMPLIFICATION AND PHASE MARGIN vs FREQUENCY



Figure 27

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL†‡ VOLTAGE AMPLIFICATION vs FREE-AIR TEMPERATURE



Figure 28

LARGE-SIGNAL DIFFERENTIAL†‡ VOLTAGE AMPLIFICATION vs FREE-AIR TEMPERATURE



Figure 29

OUTPUT IMPEDANCE‡ vs FREQUENCY



Figure 30

OUTPUT IMPEDANCE‡ vs FREQUENCY



Figure 31

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

COMMON-MODE REJECTION RATIO† vs FREQUENCY



Figure 32

COMMON-MODE REJECTION RATIO†‡ vs FREE-AIR TEMPERATURE



Figure 33

SUPPLY-VOLTAGE REJECTION RATIO† vs FREQUENCY



Figure 34

SUPPLY-VOLTAGE REJECTION RATIO† vs FREQUENCY



Figure 35

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.
‡ Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

SUPPLY-VOLTAGE REJECTION RATIO† vs FREE-AIR TEMPERATURE



Figure 36

TLV2252 SUPPLY CURRENT† vs SUPPLY VOLTAGE



Figure 37

TLV2254 SUPPLY CURRENT† vs SUPPLY VOLTAGE



Figure 38

SLEW RATE‡ vs LOAD CAPACITANCE



Figure 39

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

SLEW RATE†‡ vs FREE-AIR TEMPERATURE



Figure 40

INVERTING LARGE-SIGNAL PULSE RESPONSE†



Figure 41

INVERTING LARGE-SIGNAL PULSE RESPONSE†



Figure 42

VOLTAGE-FOLLOWER LARGE-SIGNAL PULSE RESPONSE†



Figure 43

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

VOLTAGE-FOLLOWER LARGE-SIGNAL PULSE RESPONSE†



Figure 44

INVERTING SMALL-SIGNAL PULSE RESPONSE†



Figure 45

INVERTING SMALL-SIGNAL PULSE RESPONSE†



Figure 46

VOLTAGE-FOLLOWER SMALL-SIGNAL PULSE RESPONSE†



Figure 47

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

VOLTAGE-FOLLOWER SMALL-SIGNAL PULSE RESPONSE†



Figure 48

EQUIVALENT INPUT NOISE VOLTAGE† vs FREQUENCY



Figure 49

EQUIVALENT INPUT NOISE VOLTAGE† vs FREQUENCY



Figure 50

INPUT NOISE VOLTAGE OVER A 10-SECOND PERIOD†



Figure 51

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

INTEGRATED NOISE VOLTAGE† vs FREQUENCY



Figure 52

TOTAL HARMONIC DISTORTION PLUS NOISE† vs FREQUENCY



Figure 53

GAIN-BANDWIDTH PRODUCT vs SUPPLY VOLTAGE



Figure 54

GAIN-BANDWIDTH PRODUCT†‡ vs FREE-AIR TEMPERATURE



Figure 55

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

PHASE MARGIN vs LOAD CAPACITANCE



Figure 56

GAIN MARGIN vs LOAD CAPACITANCE



Figure 57

UNITY-GAIN BANDWIDTH vs LOAD CAPACITANCE



Figure 58

OVERESTIMATION OF PHASE MARGIN† vs LOAD CAPACITANCE



† See application information

Figure 59

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.
‡ Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

APPLICATION INFORMATION

driving large capacitive loads

The TLV2252 is designed to drive larger capacitive loads than most CMOS operational amplifiers. Figure 56 and Figure 57 illustrate its ability to drive loads up to 1000 pF while maintaining good gain and phase margins (R_{null} = 0).

A smaller series resistor (R_{null}) at the output of the device (see Figure 60) improves the gain and phase margins when driving large capacitive loads. Figure 55 and Figure 56 show the effects of adding series resistances of 10 Ω, 50 Ω, 100 Ω, 200 Ω, and 500 Ω. The addition of this series resistor has two effects: the first adds a zero to the transfer function and the second reduces the frequency of the pole associated with the output load in the transfer function.

The zero introduced to the transfer function is equal to the series resistance times the load capacitance. To calculate the improvement in phase margin, equation 1 can be used.

$$\Delta\phi_{m1} = \tan^{-1}\left(2 \times \pi \times \text{UGBW} \times R_{null} \times C_L\right) \quad (1)$$

Where :

$\Delta\phi_{m1}$ = improvement in phase margin
UGBW = unity-gain bandwidth frequency
R_{null} = output series resistance
C_L = load capacitance

The unity-gain bandwidth (UGBW) frequency decreases as the capacitive load increases (see Figure 58). To use equation 1, UGBW must be approximated from Figure 58.

Using equation 1 alone overestimates the improvement in phase margin as illustrated in Figure 59. The overestimation is caused by the decrease in the frequency of the pole associated with the load, providing additional phase shift and reducing the overall improvement in phase margin.

Using Figure 60, with equation 1 enables the designer to choose the appropriate output series resistance to optimize the design of circuits driving large capacitance loads.



Figure 60. Series-Resistance Circuit

APPLICATION INFORMATION

macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 5) and subcircuit in Figure 61 are generated using the TLV2252 typical electrical and operating characteristics at T_A = 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 5: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, “Macromodeling of Integrated Circuit Operational Amplifiers,” *IEEE Journal of Solid-State Circuits,* SC-9, 353 (1974).




```
.SUBCKT TLV225x 1 2 3 4 5
C1      11      12      6.369E−12
C2      6       7       25.00E−12
DC      5       53      DX
DE      54      5       DX
DLP     90      91      DX
DLN     92      90      DX
DP      4       3       DX
EGND    99      0       POLY (2) (3,0) (4,0) 0 .5 .5
FB      7       99      POLY (5) VB VC VE VLP
+ VLN 0 57.62E6 −60E6 60E6 60E6 −60E6
GA      6       0       11      12 26.86E−6
GCM     0       6       10      99 2.686E−9
ISS     3       10      DC 3.1E−6
HLIM    90      0       VLIM 1K
J1      11      2       10 JX
J2      12      1       10 JX
R2      6       9       100.0E3
RD1     60      11      37.23E3
RD2     60      12      37.23E3
R01     8       5       84
R02     7       99      84
RP      3       4       71.43E3
RSS     10      99      64.52E6
VAD     60      4       −.5
VB      9       0       DC 0
VC      3       53      DC .605
VE      54      4       DC .605
VLIM    7       8       DC 0
VLP     91      0       DC −0.235
VLN     0       92      DC 7.5
.MODEL DX D (IS=800.0E−18)
.MODEL JX PJF (IS=500.0E−15 BETA=139E−6
+ VTO=−.05)
.ENDS
```

Figure 61. Boyle Macromodel and Subcircuit

PSpice and *Parts* are trademarks of MicroSim Corporation.

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
5962-9550401QPA	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550401QPA TLV2262M	Samples
5962-9550403QHA	ACTIVE	CFP	U	10	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550403QHA TLV2262AM	Samples
5962-9550403QPA	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550403QPA TLV2262AM	Samples
5962-9566601QPA	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9566601QPA TLV2252M	Samples
5962-9566603QPA	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9566603QPA TLV2252AM	Samples
TLV2252AID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252A	Samples
TLV2252AIDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252A	Samples
TLV2252AIDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252A	Samples
TLV2252AIDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252A	Samples
TLV2252AIP	ACTIVE	PDIP	P	8	50	Green (RoHS & no Sb/Br)	CU NIPDAU	N / A for Pkg Type	-40 to 125	TLV2252AI	Samples
TLV2252AIPW	ACTIVE	TSSOP	PW	8	150	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY252A	Samples
TLV2252AIPWG4	ACTIVE	TSSOP	PW	8	150	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY252A	Samples
TLV2252AIPWR	ACTIVE	TSSOP	PW	8	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY252A	Samples
TLV2252AMJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9566603QPA TLV2252AM	Samples
TLV2252AQDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		V2252A	Samples
TLV2252ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252I	Samples
TLV2252IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252I	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TLV2252IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2252I	Samples
TLV2252IP	ACTIVE	PDIP	P	8	50	Green (RoHS & no Sb/Br)	CU NIPDAU	N / A for Pkg Type	-40 to 125	TLV2252IP	Samples
TLV2252MJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9566601QPA TLV2252M	Samples
TLV2254AID	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2254AI	Samples
TLV2254AIDR	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	V2254AI	Samples
TLV2254AIN	ACTIVE	PDIP	N	14	25	Green (RoHS & no Sb/Br)	CU NIPDAU	N / A for Pkg Type	-40 to 125	TLV2254AIN	Samples
TLV2254AIPW	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY2254A	Samples
TLV2254AIPWR	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY2254A	Samples
TLV2254AIPWRG4	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TY2254A	Samples
TLV2254AQD	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TLV2254A	Samples
TLV2254ID	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TLV2254I	Samples
TLV2254IDG4	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TLV2254I	Samples
TLV2254IDR	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	TLV2254I	Samples
TLV2254IN	ACTIVE	PDIP	N	14	25	Green (RoHS & no Sb/Br)	CU NIPDAU	N / A for Pkg Type	-40 to 125	TLV2254IN	Samples
TLV2262AMJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550403QPA TLV2262AM	Samples
TLV2262AMUB	ACTIVE	CFP	U	10	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550403QHA TLV2262AM	Samples
TLV2262MJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9550401QPA TLV2262M	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLV2252, TLV2252A, TLV2252AM, TLV2252M, TLV2254A, TLV2262AM, TLV2262M :

- Catalog: TLV2252A, TLV2252, TLV2262A, TLV2262
- Automotive: TLV2252-Q1, TLV2252A-Q1, TLV2252A-Q1, TLV2252-Q1, TLV2254A-Q1, TLV2262A-Q1
- Enhanced Product: TLV2252A-EP, TLV2252A-EP, TLV2254A-EP
- Military: TLV2252M, TLV2252AM

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLV2252AIDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLV2252AIPWR	TSSOP	PW	8	2000	330.0	12.4	7.0	3.6	1.6	8.0	12.0	Q1
TLV2252IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLV2254AIDR	SOIC	D	14	2500	330.0	16.4	6.5	9.0	2.1	8.0	16.0	Q1
TLV2254AIPWR	TSSOP	PW	14	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
TLV2254IDR	SOIC	D	14	2500	330.0	16.4	6.5	9.0	2.1	8.0	16.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLV2252AIDR	SOIC	D	8	2500	340.5	338.1	20.6
TLV2252AIPWR	TSSOP	PW	8	2000	367.0	367.0	35.0
TLV2252IDR	SOIC	D	8	2500	340.5	338.1	20.6
TLV2254AIDR	SOIC	D	14	2500	350.0	350.0	43.0
TLV2254AIPWR	TSSOP	PW	14	2000	367.0	367.0	35.0
TLV2254IDR	SOIC	D	14	2500	350.0	350.0	43.0

U (S–GDFP–F10) CERAMIC DUAL FLATPACK



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only.
E. Falls within MIL STD 1835 GDFP1–F10 and JEDEC MO–092AA

MCER001A – JANUARY 1995 – REVISED JANUARY 1997

JG (R-GDIP-T8) **CERAMIC DUAL-IN-LINE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification.
E. Falls within MIL STD 1835 GDIP1-T8

P (R–PDIP–T8) PLASTIC DUAL–IN–LINE PACKAGE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001 variation BA.

N (R–PDIP–T**)

PLASTIC DUAL–IN–LINE PACKAGE

16 PINS SHOWN



DIM \ PINS **	14	16	18	20
A MAX	0.775 (19,69)	0.775 (19,69)	0.920 (23,37)	1.060 (26,92)
A MIN	0.745 (18,92)	0.745 (18,92)	0.850 (21,59)	0.940 (23,88)
MS–001 VARIATION (C)	AA	BB	AC	AD



4040049/E 12/2002

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001, except 18 and 20 pin minimum body length (Dim A).
D. The 20 pin end lead shoulder width is a vendor option, either half or full width.

PACKAGE OUTLINE

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153, variation AA.



LAND PATTERN EXAMPLE
SCALE:10X



SOLDER MASK DETAILS
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

D (R–PDSO–G14) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
E. Reference JEDEC MS–012 variation AB.

D (R–PDSO–G14) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R–PDSO–G14) PLASTIC SMALL OUTLINE



4040064–3/G 02/11

NOTES:
A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M–1994.
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
E. Falls within JEDEC MO–153



PACKAGE OUTLINE

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



NOTES:

1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE
BASED ON .005 INCH [0.125 MM] THICK STENCIL
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View TLV2254AIPW on WIN SOURCE
- Texas Instruments Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management